AppViewX



Copyright © 2017 AppViewX, Inc. All Rights Reserved.

This document may not be copied, disclosed, transferred, or modified without the prior written consent of AppViewX, Inc. While all content is believed to be correct at the time of publication, it is provided as general purpose information. The content is subject to change without notice and is provided "as is" and with no expressed or implied warranties whatsoever, including, but not limited to, a warranty for accuracy made by AppViewX. The software described in this document is provided under written license only, contains valuable trade secrets and proprietary information, and is protected by the copyright laws of the United States and other countries. Unauthorized use of software or its documentation can result in civil damages and criminal prosecution.

Trademarks

The trademarks, logos, and service marks displayed in this manual are the property of AppViewX or other third parties. Users are not permitted to use these marks without the prior written consent of AppViewX or such third party which may own the mark.

This product includes software developed by the CentOS Project (www.centos.org).

This product includes software developed by Red Hat, Inc. (www.redhat.com).

This product includes software developed by the VMware (www.vmware.com).

All other trademarks mentioned in this document are the property of their respective owners.

Contact Information

Seattle, WA 98109

AppViewX, Inc. 500 Yale Avenue North, Suite 100

Tel: +1 (206) 207 7541
Email: info@appviewx.com
Web: www.appviewx.com

Document Information

Software Version: 12.2.0 Document Version: 1.0

Last updated on: December 18, 2017


Contents

Description	
Prerequisites	
Compatible Software Versions	
Limitations	
Log In to AppViewX	
Add an ADC Device: F5 LTM	2
Import Visual Workflows	3
Import Helper Scripts	Z
Enable a Workflow	
Delete Expired Certificates from F5 workflow	<u>5</u>
WorkOrder flow	6
Request Inventory	8
Schedule a Workflow	8
View Scheduled workflows	
Add a Credential	
Troubleshooting	10

Description

The Delete Expired Certificates from F5 workflow is used to delete the expired certificates and its associated SSL profiles and keys from an F5 device. The configuration to delete the expired certificate and key from an F5 device are reviewed and approved at AppViewX. After the approval is granted, the workflow will delete the expired certificate from an F5 device. If an expired certificate is associated to any SSL profile, it is deleted from the F5 device only after the certificate and the key of that particular profile are replaced with the default certificate and key.

The Delete Expired Certificates from F5 flow diagram is shown in the image below:



Prerequisites

To run this automation workflow in your environment, ensure that the following pre-requisites are met:

- Free AppViewX or AppViewX version 12.1.0 and 12.2.0 has been downloaded and installed.
- The ADC devices has been added in the AppViewX inventory with a Data center name.
- Each ADC device is a managed entity in AppViewX.
- You have administrator permissions to add a device to the AppViewX inventory.

Compatible Software Versions

The workflow has been tested and validated on the following software versions:

- AppViewX Free AppViewX, AVX 12.1.0, and AVX 12.2.0
- F5 (both LTM and GTM) version10.x, 11.x, or 12.x

Limitations

Not applicable

Log In to AppViewX

Log in to the AppViewX web interface. The standard format for a login URL is:


https://hostname:portnumber.

The hostname and port number are configured during deployment, with the default port number set to 5004 and the default web credentials set to admin/AppViewX@123.

Note: It is recommended that you access AppViewX using Internet Explorer, Firefox, or Google Chrome.

Add an ADC Device: F5 LTM

- 1. Click the (Menu) button on the left-hand side of the AppViewX screen.
- 2. Navigate to **Inventory** > **Device**.
- 3. The Device screen opens with the ADC device inventory displayed by default.
- 4. Click the + (Add) button in the Command bar.
- 5. On the Add screen that opens, click to select **F5** as the ADC vendor.




- 6. Select the module to be managed on the ADC device.
- Click the vCMP Host check box, if you want to add and manage the vCMP guest devices.
- 8. In the **Device name** field, enter a name for the devices to help the users identify it.
- 9. In the **IP address** field, enter the management IP address of the device.
- 10. Enter the default or custom defined **SSH port** number for the device.
- 11. (Optional) Specify a **Data center** name in which the device resides and you will have the option later to filter devices based on their location.
- 12. In the **Cert sync** field, select the radio button for the kind of synchronization relationship you want to establish between SSL certificates on the ADC device and AppViewX: **Managed**, **Monitored**, or **Ignored**.

Note: Ensure that the Cert sync option is in a managed state.

13. (Optional) Select the **AppViewX group sync** check box if you need AppViewX to sync the configuration changes from an active to standby ADC device.

Note: This is required only in older versions, as the latest versions sync automatically.

- 14. From the **Credential type** dropdown list, select how to want to provide the credentials:
 - Select Manual entry, if you want to manually enter the credential details (user name and the associated password) every time the device is accessed. Select the Access type as API to help AppViewX to establish communication and to fetch the configuration after the device is in a manage state.
 - Select Credential list, if you want to retrieve the login details created in the credential template. For more details on how to add a credential to a device, refer to the Add a Credential section of this guide.
 - When you select the credential name from the dropdown list, the user name and password fields will be auto-filled with the values provided in the credential template.
- 15. In the **Secondary/Alternate** device field, select how you want to fetch the details of a backup device when the primary device becomes unavailable due to failure or scheduled down time:
 - a. Select **Auto detect** if you want AppViewX to automatically detect and retrieve the configuration of the secondary/alternate device, then click Save to add the device to AppViewX.
 - b. Select **Manual Entry** if you want to manually provide the details of the secondary device. At a minimum, fill in all fields that contain a red asterisk beside their names.
- 16. Click **Add** to add the secondary device to the list at the bottom of the screen.
 - **Note:** You can add more than one secondary devices. The **Update** and **Delete** buttons are enabled only when you try to modify the existing secondary device.
- 17. Click **Save** to add the new WAF device. The device is then displayed in the table on the WAF tab.



The device will display one of the following statuses:

- o **In Progress** Device configuration fetch is in progress.
- Managed Device configurations are fetched and parsed successfully. This is the status a successfully added ADC device should have.
- Unresolved Unable to communicate with device, due to invalid login credentials.
- Failed Device configuration fetch failed, due to unsupported version.

Import Visual Workflows

Note: Free AppViewX comes preloaded with visual workflows. You will only need to use the following import instructions when newer versions of the workflows are available.


- 1. Click the (Menu) button.
- 2. Navigate to Workflow > Configurator.

3. Click the (Import) button in the Command bar.



- 4. To import a workflow, complete the following sub-steps:
 - Click the Browse button.
 - b. Select the zip file containing one or more workflows, then click **Upload**.
 - c. In the table at the bottom of the *Import* page, select the check box beside the unzipped workflow file.
 - d. Click **Submit** to deploy the workflow into your AppViewX environment.


The Delete Expired Certificate from F5 workflow is shown in the image below:



Import Helper Scripts

Note: Free AppViewX comes preloaded with helper scripts. You will only need to use the following import instructions when newer versions of the helper scripts are available.

- 1. Click the (Menu) button.
- 2. Navigate to **Provisioning > Templates**.
- 3. Click the (Import) button in the Command bar.
- 4. On the *Import* screen that opens, complete the following steps:
 - a. Select the **Helper script** radio button.
 - b. Click **Browse** and select the helper script zip file you want to import.
 - c. Click **Upload** to import the file and view its contents.




- d. In the table at the bottom of the *Import* screen, select the check boxes beside each of the helper scripts.
- e. Click **Submit** to deploy them into your AppViewX environment.

Enable a Workflow

To enable the Delete Expired Certificates from F5 workflow, complete the following steps:

- 1. Click the (Menu) button.
- 2. Navigate to **Workflow** > **Configurator**. The *Workflow* screen opens.
- 3. Click the ☐ (**Select**) button on the Delete Expired Certificates from F5 workflow to enable. If the workflow is already selected, a ✓ (**Deselect**) button appears.
- 4. Click the (Enable) button in the Command bar.

Note: You can also enable the Delete Expired Certificates from F5 workflow from the Card view by clicking the (**Disable**) button.



5. On the Confirmation screen that appears, click Yes.


Delete Expired Certificates from F5 workflow

To submit the Delete Expired Certificates from F5 workflow, complete the following steps:

- 1. Click the (Menu) button.
- 2. Navigate to Workflow > Request.

The *Request* screen opens with **My catalog** tab displayed by default. This screen displays all enabled workflows assigned to a specific user role.

3. Click the (Run workflow) button for deleting expired certificates. The Form Builder screen opens.




- 4. Click the **Get F5 Device** button to retrieve the list of F5 devices.
- 5. From the **F5 Device** dropdown list, select the device from which you want to delete the expired certificates.
- 6. Click the **Get Expired Cert** button to retrieve the list of expired certificates available on the selected F5 device.
- 7. From the **Expired Cert** dropdown filed, select the expired certificates you want to delete from the device.
- 8. Click **Get Profile with Expired Cert** to retrieve the list of client or server profiles to which the certificate and key are associated.
- 9. In the **Cert and Associated Profile** box, the profiles associated with the certificate and key are displayed.
- 10. Click Submit.

A new **Request ID** is created. To view all requests refer to the <u>Request Inventory</u> section of this guide.


WorkOrder flow

The following are the workorder tasks of Delete Expired Certificates from F5 workflow.

Note: You can click each task to view its details. Wherever applicable, all logs related to the selected task are displayed in the **Logs** pane at the bottom of the screen.



- Generate Implementation The configuration commands are generated in order to delete the expired certificates after associating their SSL profile with the default certificate and key. You can delete those SSL profiles and keys only if they are not associated with any other SSL certificate other than the default certificate.
- 2. Approval 1 Approval of a work order is based on the role assigned to the user (who has an access to approve and implement). After you submit the request form, the configuration changes are reviewed and approved at AppViewX. The configuration changes are implemented on the device only when the approval is received.



- a. On the screen that opens, select **Manual** or **Auto** radio button depending on how you want to set the implementation process.
- b. If you have selected the **Auto** radio button, fill in all the fields, which are designated by red asterisk (*) beside their names.
- c. Enter any comments you have related to the implementation request and then, click **Implement**.

3. **Implementation** — The expired certificates and its dependent profiles will be deleted from an F5 device.

Request Inventory

To go to Request inventory, complete the following steps:

- 1. Click the (Menu) button.
- 2. Navigate to **Workflow** > **Request**.

The Request screen opens with My catalog tab displayed by default.

3. Click the Request Inventory tab.

This displays all workflows that have been triggered. On the **Request Inventory** screen, you can perform the following tasks: Search for a request using the **Search** field. Click the (Filter) button to select the options you want to use to sort the requests.



- Click the Request ID created for Delete Expired Certificates from F5 to view the tasks or phases of a request in a tree-view. For more details, refer to the (<u>WorkOrder flow</u>) section of this guide.
- 5. You can also view the following details of the request that are created: request creator, request time, last updated time, status, and activity log.
- 6. Click View in the Activity log column to display the request in a stage-view. In the Summary tab, click the (Expand) icon to view the details of each task. Click the Details tab to view log messages and other particulars of a request.



Schedule a Workflow

To schedule a workflow, complete the following steps:

- 1. Click the (Menu) button.
- 2. Navigate to **Workflow** > **Request**.

The Request screen opens with My catalog tab displayed by default.

- 3. Click the (Schedule workflow) button on the Delete Expired Certificates from F5 workflow.
- 4. On the *Delete Expired Certificates from F5* window that opens, select the frequency of the policy migration process: once, hourly, daily, weekly, monthly, or yearly. The remaining fields in the Scheduler region update depending on what you select.
- 5. Click Save.

View Scheduled workflows

To go to the scheduled workflow screen, complete the following steps:

- 1. Click the (Menu) button.
- 2. Navigate to Workflow > Request.
- 3. The Request screen opens with My catalog tab displayed by default.
- 4. Click the **Scheduled workflows** tab.
- 5. On the Scheduled workflow screen that appears, you can perform the following tasks:
 - a. In the View log column, click View to display the details of a scheduled workflow.
 - b. Click the (Pause) or (Resume) button to temporarily stop or continue the execution of a workflow.

Add a Credential

To add a credential to a device, complete the following steps:

- 1. Click the (Menu) button.
- 2. Navigate to Inventory > Device.

The Device screen opens with the ADC tab selected by default.

- 3. Click the **ADC** tab.
- 4. Click the check box beside the device name, then click the (Credential) button in the Command bar.
- 5. On the *Add credential* screen that appears, enter the name of the credential you want to add to the device.
- 6. Enter the **username** and **password** associated with the credential.
- 7. (Optional) If a secondary credential password was created by a vendor in order to communicate with the device, thus allowing different levels of control over the credential, enter this password in the **Secondary password** field.
- 8. Click Save.

The credential is then added to the table at the bottom of the screen. You can delete a credential or modify its name, user name, or password by selecting the check box beside the credential name in the table at the bottom of the screen and then clicking either the **Modify credential** or **Delete** button in the Command bar.

Troubleshooting

I cannot find the Delete Expired Certificates from F5 workflow in the Request Catalog

You must enable the workflow from the Configurator section. For more details on how to enable a workflow, refer to the Enable a Workflow section of this guide.

Why is the ASM policy not migrated to the target device?

You must have an Admin user privileges in order to add an F5 device in the AppViewX inventory. For more details on how to add an ADC device, refer to the <u>Add an ADC Device: F5 LTM</u> device section of this guide.