(IPL)User Story 6 – IPL Sends ACK (Accept/Reject) for Mission to Adapter

Story ID:US-IPL-P2P-006
Actor: IPL (Receiver System responding to mission)
Goal: To send a clear Accept or Reject acknowledgement for each mission received from UCRM via the Adapter.
Business Value: Closes the loop for reverse-flow missions, ensuring UCRM receives explicit feedback on whether IPL has accepted or rejected the mission, supporting reliable P2P interactions.

User Story

As an *IPL receiving system*, I want to send an Accept or Reject acknowledgement for each mission I receive so that UCRM (via the Adapter) knows whether the mission has been successfully accepted and processed by IPL or rejected due to issues.

Key Behaviours

- Decide Accept vs Reject based on IPL's validation and business rules.
- Construct ACK payload (Accept/Reject) with mission identifiers and reasons for rejection when applicable.
- Send ACK to Adapter, which forwards it to UCRM using P2P mechanisms.

Acceptance Criteria

- Given IPL receives and successfully validates a mission, when IPL decides to accept it, then IPL sends an "Accept" ACK to the Adapter containing at least mission ID, correlation ID, and acceptance timestamp.
- Given IPL receives a mission that fails validation or violates IPL business rules, when IPL decides to reject it, then IPL sends a "Reject" ACK to the Adapter containing mission ID, correlation ID, and a rejection reason if possible.
- Given a mission ACK (Accept or Reject) is sent, when Adapter receives it successfully, then IPL logs the ACK transmission with status and timestamp for traceability.
- Given a communication failure when sending the mission ACK to Adapter, when IPL attempts to send it, then IPL applies a retry policy or marks the ACK as "failed to deliver" and logs the issue for operational follow-up.