(ADAPTER)User Story 1 – Receive Business (Tenant Payload) from IPL

Story ID:US-ADAPTER-P2P-001
Actor: Adapter Integration
Goal: Accept and process incoming business payload from IPL
Business Value: Enables standardized intake, validation, and orchestration of UCRI 2.0 P2P messages, ensuring only compliant requests proceed to authentication and forwarding toward UCRM.
Jira Ticket: IPL-26508: (ADAPTER) Receive Business-Payload (EinsatzTransfer with Patientdata) from IPL CLOSED

User Story:

As an Adapter Integration system,
I want to receive and validate a business payload submitted by the IPL system,
So that only valid messages are accepted for further processing (authentication and forwarding) in accordance with UCRI 2.0 P2P rules.

Key Scenarios & Variations:

- Valid payload structure and required headers present
- Invalid payload (schema violation / missing fields)
- Invalid headers (missing authorization / incorrect format)
- Technical request issues (unsupported HTTP method, invalid content type)

Acceptance Criteria:

- Given a well-formed business payload from IPL
  When the payload is submitted to the Adapter endpoint
  Then the Adapter must accept the request and trigger validation logic.
- Given a payload missing mandatory fields or violating schema
  When the payload is submitted to the Adapter
  Then the Adapter must respond immediately with a validation error indicating the reason (e.g., missing field, invalid format).
- Given a request using an unsupported HTTP method or invalid content type
  When the request reaches the Adapter
  Then the Adapter must reject the request with a clear technical error response
- Given a valid payload
  When the Adapter accepts the request

Then the Adapter must return an immediate acknowledgment (e.g., “accepted for processing”) distinct from the final UCRM processing result.

