(ADAPTER)User Story 3 – Authenticate Adapter to UCRM via P2P /token

Story ID:US-ADAPTER-P2P-003
Actor: Adapter Integration
Goal: Obtain P2P authentication token from UCRM before sending messages.
Business Value: Ensures secure and authorized communication between Adapter and UCRM, complying with P2P security requirements at the integration layer.
Referenced Diagram:UCRI 2.0 – P2P FlowDiagram (segment: “For valid requests, the Adapter authenticates against the target UCRM using the P2P /token endpoint”).
Jira Ticket: IPL-26517: (ADAPTER) Authenticate Adapter <> UCRM via P2P /token IN PROGRESS

User Story:

> As the Adapter Integration, I want to authenticate against the target UCRM using the P2P /token endpoint so that I can securely send validated messages to UCRM.

Key Scenarios & Variations:

- Successful token retrieval.
- Authentication failure (invalid credentials, expired client secrets, etc.).
- Token expiry and renewal during ongoing message processing.

Acceptance Criteria:

- Given a validated message ready to be sent to UCRM
  When the Adapter does not have a valid token
  Then the Adapter must call the P2P /token endpoint to obtain a token before calling /messaging/send.
- Given valid Adapter credentials
  When the Adapter calls /token
  Then UCRM must return a token that can be used for subsequent /messaging/send calls within its validity period.

- Given invalid or expired Adapter credentials
  When the Adapter calls /token
  Then UCRM must return an authentication error, and the Adapter must not attempt to send the message to /messaging/send.
- Given a token that has expired
  When the Adapter attempts to send a message and receives an authentication error from UCRM
  Then the Adapter must attempt to refresh or re-acquire a token via /token and retry sending, according to defined retry policies.
- Given repeated authentication failures beyond a configured threshold
  When the Adapter cannot obtain a token
  Then the Adapter must log the incident and return an appropriate error status to IPL for affected messages.

