(ADAPTER)User Story 5 – Handle UCRM Acceptance/Rejection Response at Adapter

Story ID:US-(ADAPTER)-P2P-005

Actor: Adapter Integration

Goal: Receive and interpret the acceptance/rejection response from UCRM after a message is sent, and prepare it for propagation back to IPL.

Business Value: Ensures that the integration layer correctly understands UCRM's outcome and can reliably inform IPL about whether the message was accepted or rejected, without implementing any UCRM internal business processing.

Referenced Diagram:UCRI 2.0 – P2P FlowDiagram (segment: "The target UCRM processes the message and responds with acceptance or rejection based on UCRI-2.0 rules" – this story covers only the Adapter's handling of that response).

Jira Ticket: IPL-26519: (ADAPTER) Handle UCRM Acceptance/Rejection Response at Adapter OPEN

User Story:

> As the Adapter Integration, I want to receive and interpret the acceptance or rejection response returned by UCRM for a previously sent message so that I can correctly map and store this outcome and make it available to IPL.

What This Story Covers (Integration Scope Only):

- Receiving the HTTP response from UCRM's /messaging/send call.
- Parsing the response payload and status (acceptance or rejection).
- Mapping UCRM-specific response codes/structure to a standardized status model used by the Adapter and IPL.
- Persisting or buffering the outcome so it can be propagated to IPL (covered in US-IPL-P2P-006).

Key Scenarios & Variations:

- UCRM returns a successful acceptance response (business accepted).
- UCRM returns a business rejection response (business rejected).

- UCRM returns a technical error response (technical rejected).
- UCRM returns an unexpected or malformed response.

Acceptance Criteria:

- Given the Adapter has sent a message to UCRM via /messaging/send
  When UCRM returns an HTTP response with a well-formed acceptance payload
  Then the Adapter must parse the response, identify it as an ACCEPTED outcome, and map it to the internal standardized status model (e.g., status = ACCEPTED, with UCRM message ID and correlation ID).
- Given the Adapter has sent a message to UCRM via /messaging/send
  When UCRM returns an HTTP response indicating a business rejection (e.g., business rule violation, unsupported operation)
  Then the Adapter must parse the response, identify it as a BUSINESS REJECTION, and map it to the standardized status model (e.g., status = REJECTED_BUSINESS, with UCRM error code and description).
- Given the Adapter has sent a message to UCRM via /messaging/send
  When UCRM returns an HTTP response indicating a technical error (e.g., internal server error, temporary failure)
  Then the Adapter must parse the response, identify it as a TECHNICAL REJECTION, and map it to the standardized status model (e.g., status = REJECTED_TECHNICAL, with technical error details where available).
- Given the Adapter receives an unexpected or malformed response from UCRM (e.g., missing mandatory fields, unknown status)
  When the Adapter attempts to parse the response
  Then the Adapter must classify the outcome as UNKNOWN/UNPARSABLE, log the incident, and treat it as a technical failure for the purpose of notifying IPL.
- Given any of the above outcomes (accepted, business rejected, technical rejected, unknown)
  When the Adapter has mapped the UCRM response to the standardized status model
  Then the Adapter must store or buffer this outcome together with the original correlation ID so that it can be propagated to IPL as part of US-IPL-P2P-006.

