(ADAPTER)User Story 7 – Support Reverse Flow UCRM → IPL via /messaging/send

Story ID:US-ADAPTER-P2P-007

Actor:UCRM (as Sender), Adapter Integration, IPL (as Target)

Goal: Enable UCRM to send messages to IPL using the same P2P /messaging/send endpoint, with the Adapter handling validation, authentication (if needed), and forwarding in the reverse direction.

Business Value: Provides full bidirectional P2P communication, allowing UCRM to initiate events or responses towards IPL using a consistent interface, with the Adapter acting as the integration layer.

Referenced Diagram:UCRI 2.0 – P2P FlowDiagram (segment: “Reverse Flow UCRI→IPL”) and note:“In the P2P flow, the same endpoint (POST /messaging/send) is used for sending and receiving messages.”

Jira ticket: IPL-26521: (ADAPTER) Receive UCRI Payload → IPL via /messaging/send

IN PROGRESS

User Story:

> As the UCRM system, I want to send messages to IPL via the Adapter using the same /messaging/send endpoint so that I can initiate UCRI 2.0-compliant communications towards IPL in a peer-to-peer manner.

Key Scenarios & Variations:

- UCRM sends a message to IPL via Adapter using /messaging/send.
- Adapter validates UCRM-originated messages and forwards them to IPL.
- IPL processes incoming messages and returns acceptance/rejection to Adapter/UCRM (IPL internal processing is out of scope; only integration handling is in scope).

Acceptance Criteria:

- Given UCRM needs to send a message to IPL
  When UCRM calls /messaging/send (P2P) towards the Adapter
  Then the Adapter must validate the incoming request similarly to IPL-originated messages (schema, mandatory fields, basic integration-level business rules).

- Given a valid UCRM-originated message
  When the Adapter validates it successfully
  Then the Adapter must forward the message to IPL using the agreed interface, preserving correlation and message identifiers.
- Given an invalid UCRM-originated message
  When the Adapter validates it
  Then the Adapter must return a validation error to UCRM without forwarding to IPL.
- Given IPL receives a message from the Adapter
  When IPL processes the message (outside this project's scope)
  Then IPL must return an acceptance or rejection status to the Adapter, which in turn must propagate this outcome back to UCRM using a standardized status mapping similar to IPL→UCRM flow.
- Given the same /messaging/send endpoint is used for both directions
  When the Adapter receives a message
  Then the Adapter must correctly determine the direction (IPL→UCRM or UCRM→IPL) based on configuration, routing rules, or message metadata, and process it accordingly.

