(IPL)User Story 1 – IPL Sends Event to Adapter

Story ID:US-IPL-P2P-001
Actor: IPL (Sender System)
Goal: To send a UCRI 2.0-compliant event payload to the Adapter.
Business Value: Allows IPL to publish events into the UCRI P2P ecosystem so adapter can receive, validate, and process them.

User Story

As an *IPL sending system*, I want to send a IPL event payload to the Adapter so that the target UCRM can receive and process the event according to UCRI 2.0 P2P rules.

Key Behaviors

- Construct event payload according to agreed schema (UCRI 2.0 + Adapter contract).
- Include correlation ID, timestamps, sender/receiver identifiers.
- Invoke the Adapter's endpoint/interface for event submission.

Acceptance Criteria

- Given a valid event in IPL, when IPL builds the payload, then all mandatory fields (e.g., event type, correlation ID, timestamps, sender ID, target UCRM ID) are present and follow the agreed schema.
- Given a supported event type, when IPL sends the event to the Adapter, then the Adapter receives the payload without schema validation errors at the transport level (e.g., JSON/XML well-formed, correct field types).
- Given a transient communication failure between IPL and Adapter, when IPL sends an event, then IPL applies a configured retry policy or surfaces a clear error status without losing the event payload. (optional)
- Given IPL successfully sends the event to Adapter, when the request is accepted at the transport level, then IPL accept the response as per defined in the contract.