(IPL)User Story 3 – IPL Processes “Accept” ACK from Adapter (UCRM Accepted)

Story ID:US-IPL-P2P-003

Actor:IPL (Sender System)

Goal: To update IPL state when Adapter indicates that UCRM has accepted and processed the message according to UCRI 2.0 rules.

Business Value: Provides end-to-end confirmation that IPL events have been successfully processed by UCRM, enabling reliable business tracking and SLA reporting.

User Story

As an *IPL sending system*, I want to process the final “Accept/EMPFANG” acknowledgement from the Adapter so that I can mark the corresponding event as successfully processed by UCRM.

Key Behaviours

- Receive asynchronous/synchronous final outcome from Adapter indicating UCRM acceptance.
- Correlate the ACK with the original event via correlation ID.
- Update IPL’s internal status and audit trail. (if there are any)

Acceptance Criteria

- Given an event was previously accepted by Adapter for processing, when Adapter sends a final “Accept” ACK (UCRM accepted), then IPL updates the event status to “Accepted by UCRM” with the final timestamp.
- Given multiple events are in-flight, when IPL receives an “Accept” ACK, then the ACK is correctly matched to the originating event using correlation ID (or agreed key) and no mis-association occurs.
- Given a final “Accept” ACK is stored, when IPL users or systems query the event history, then they can see the full lifecycle: “Sent to Adapter” → “Accepted by Adapter” → “Accepted by UCRM”.
- Given an “Accept” ACK is received with incomplete or inconsistent identifiers, when IPL processes it, then IPL logs the inconsistency, does not update any unrelated event, and flags the ACK as “unmatched”.
- Given a final “Accept” ACK is received multiple times for the same event, when IPL processes the duplicate ACK, then IPL applies idempotent handling (no duplicate status change, only a logged note of duplication).

