(IPL)User Story 4 – IPL Processes “Reject” ACK from Adapter (UCRM Rejected)

Story ID:US-IPL-P2P-004

Actor:IPL (Sender System)

Goal: To handle and record UCRM-level rejections propagated by Adapter.

Business Value: Ensures that IPL can detect and react to UCRM rejections (e.g., business rule violations), enabling corrective actions and accurate reporting.

User Story

As an *IPL sending system*, I want to process the final “Reject” acknowledgement from the Adapter so that I can mark the corresponding event as rejected by UCRM and act accordingly.

Key Behaviours

- Receive final rejection outcome from Adapter (UCRM rejection).
- Correlate rejection with original event.
- Store rejection reason and make it visible to operators or upstream systems.

Acceptance Criteria

- Given an event was previously accepted by Adapter for processing, when Adapter sends a final “Reject” ACK (UCRM rejected), then IPL updates the event status to “Rejected by UCRM” and stores the rejection reason (code, message, category if provided).
- Given multiple events are in-flight, when IPL receives a “Reject” ACK, then the ACK is correctly matched to the originating event using correlation ID or equivalent key.
- Given a “Reject” ACK is received, when IPL updates the event, then IPL makes the rejection reason available for monitoring, reporting, or potential automated corrective flows (e.g., re-submission after fix, notification to upstream systems).
- Given a “Reject” ACK is received with missing or invalid correlation ID, when IPL processes it, then IPL logs the issue, does not incorrectly update any event, and marks the ACK as “unmatched rejection”.
- Given IPL receives multiple identical “Reject” ACKs for the same event, when IPL processes them, then IPL applies idempotent handling (single recorded rejection, duplicates logged only).