Mapping (UCRI)

Patient Data

IGNIS → UCRI (`TransferPatientendaten` → `incident.patients[]`

UCRI field (target JSONPath)	IGNIS field (source)	Mapping rule	Comment
patients[].name	nachname	Copy 1:1	
patients[].surname	vorname	Copy 1:1	
patients[].phone	telefonNummer	Copy 1:1	
patients[].address.street	wohnAdresse	Parse street name from free text	Best-effort parsing: split into street + house number.
patients[].address.houseNumber	wohnAdresse	Parse house number from free text	Populate if a house number token exists (e.g., 12a).
patients[].address.postalCode	wohnPlzOrt	Extract digits only	Example: "12345 Berlin" → "12345".
patients[].address.city	wohnPlzOrt	Extract non-digit text	Example: "12345 Berlin" → "Berlin" (trim).
patients[].gender	geschlecht	Map enum to Male/Female/Diverse	If unmappable/unknown: omit or default to Diverse (decision).

patients[].dateOfBirth	geburtsdatum		ISO date (no time).
patients[].age	alterInJahren	Copy as number	Ensure non-negative.
patients[].initialAssessment.rmi	rmi1 or rmi2	Use rmi1 if present else rmi2; left-pad to 3 digits	UCRI requires exactly 3 digits.
patients[].initialAssessment.pzc	zuweisungsCode	Keep digits; left-pad to 6 digits	UCRI requires exactly 6 digits.
patients[].transportNumber	patientennummer	Copy 1:1	Transport number as string.
patients[].additionalInformation	see below		

UCRI ➜ IGNIS (`incident.patients[]` ➜ `TransferPatientendaten`)

IGNIS field (target)	**UCRI field (source JSONPath)**	**Mapping rule**	**Comment**
nachname	patients[].name	Copy 1:1	Required in UCRI; must be non-empty.
vorname	patients[].surname	Copy 1:1	Optional in UCRI.
telefonNummer	patients[].phone	Copy 1:1	Keep formatting.
wohnAdresse	patients[].address.street, patients[].address.houseNumber	Compose "street houseNumber"	If houseNumber missing, use street only.



wohnPlzOrt	patients[].address.postalCode, patients[].address.city	Compose "postalCode city"	If one part missing, use the other.
geschlecht	patients[].gender	Map Male/Female/Diverse to IGNIS enum	If unknown: leave null.
geburtsdatum	patients[].dateOfBirth	Parse date	Store as Date (as defined).
alterInJahren	patients[].age	Convert to integer	If decimal, round or floor (decision).
rmi1 (preferred)	patients[].initialAssessment.rmi	Parse 3-digit string to int	Store in rmi1; keep rmi2 null unless needed.
zuweisungsCode	patients[].initialAssessment.pzc	Copy string	Validate 6-digit numeric string.
patientennummer	patients[].transportNumber	Copy 1:1	—
*	patients[].additionalInformation	see below	

Incident Data

IGNIS ➜ UCRI (`TransferEinsatz` ➜ `incident`)

UCRI field (target JSONPath)	**IGNIS field (source)**	**Mapping rule**	**Comment**
sharedIncidentId	einsatzTransferId	Copy as UUID string	



internalId	nummer	Copy as string	Sender internal ID.
sentByDispatcherAt	angelegt	Format as ISO-8601 date-time	
startTimestamp	ersteMeldungAm	Format as ISO-8601 date-time	Optional
classifications[]	einsatzStichwort	Create array from string	mapping needed
issue	wasIstPassiert	Copy 1:1	Tactical description / situation.
flashingLights	sonderrechte	Copy boolean 1:1	
missionLocation	einsatzort	Map address/coordinate into UCRI location	
informers[0].name	meldender	Copy full string into name	UCRI name is required within a person. If you can parse first/last name, split into name/surname.
informers[0].phone	rueckrufnummer	Copy 1:1	Use callback number (more reliable than parsing from name).
patients[]	transferPatientendaten[]	see below	UCRI requires ≥1 patient.
additionalInformation		see below	



UCRI ➜ IGNIS (`incident` ➜ `TransferEinsatz`)

IGNIS field (target)	**UCRI field (source JSONPath)**	**Mapping rule**	**Comment**
einsatzTransferId	sharedIncidentId	Copy 1:1	Should remain stable (identifier).
nummer	internalId	Copy 1:1	mapping needed
angelegt	sentByDispatcherAt	Parse ISO date-time into Date	Preserve timezone/instant.
ersteMeldungAm	startTimestamp	Parse ISO date-time into Date	Optional.
einsatzStichwort	classifications[]	Join array to single string	mapping needed
wasIstPassiert	issue	Copy 1:1	—
sonderrechte	flashingLights	Copy boolean 1:1	—
einsatzort	missionLocation	Map UCRI location back into TransferAddresse	
meldender	informers[0].name, informers[0].surname	Compose display name	Example: surname + " " + name or keep name only.
rueckrufnummer	informers[0].phone	Copy 1:1	
transferPatientendaten[]	patients[]	see below	



*	additionalInformation	see below	

non-mapping fields

Incident

Base rule: Write remaining relevant non-mapped fields as text entries in the format [Label]: value. Skip null/empty. Join entries with comma or newline

`incident.additionalInformation` (IGNIS ➔ UCRI)

IGNIS field (source)	Label format	Comment
proqaHinweis	[ProQA-Hinweis]: {value}	—
betroffener	[Betroffene Person]: {value}	—
hinweise (List)	[Einsatzhinweise]: {v1, v2, ...}	Join list items with comma+space.

Patient

`patients[].additionalInformation` (IGNIS ➔ UCRI)

IGNIS field (source)	Label format	Comment
hinweis	[Patientenhinweise]: {value}	Keep as-is.
bemerkungen (List)	[Bemerkungen]: {v1, v2, ...}	Join list items with comma+space.
alterInMonaten	[Alter in Monaten]: {value}	Numeric string recommended.
unbekannt == true	[Identitaet unbekannt]: true	Only write if true.



storniert == true	[Transport storniert]: true	Only write if true.
stornierungsgrund	[Stornierungsgrund]: {value}	Only if not empty (even if storniert=true).

