(IPL)User Story 2 – IPL Handles Validation Response from Adapter

Story ID:US-IPL-P2P-002
Actor: IPL (Sender System)
Goal: To interpret and act on the Adapter's immediate validation response (acceptance vs validation error).
Business Value: Provides quick feedback to IPL, enabling early correction of invalid requests and preventing useless traffic to UCRM.

User Story

As an *IPL sending system*, I want to handle the Adapter's immediate validation response so that I can know whether my request was accepted for further processing or rejected due to validation errors.

Key Behaviours

- Receive synchronous response from Adapter after sending event.
- Differentiate between "accepted for processing" and "validation error".
- Store validation status for each event.

Acceptance Criteria

- Given IPL sends an event, when Adapter responds with a successful validation (e.g., HTTP 2xx with "accepted" status), then IPL records the event as "Accepted by Adapter for processing" and retains correlation ID.
- Given IPL sends an invalid event (missing mandatory field, incorrect format), when Adapter responds with a validation error, then IPL records the event as "Rejected by Adapter – Validation Error", stores the error details (code, message), and makes them available for monitoring/support.
- Given a validation error is returned, when IPL processes the response, then IPL does not consider the event as sent to UCRM and does not expect a further UCRM-level outcome for this event.
- Given Adapter returns an unexpected or malformed response, when IPL receives it, then IPL logs the anomaly, marks the event status as "Validation response error/unknown", and retains the original payload for investigation.
- Given the validation response is not received within a configured timeout, when IPL monitors the request, then IPL marks the status as "Validation response timeout" and logs the incident.