

# Home Access Plus+ Access your school from Home

**Version 9 Manual** 



Version 9 Documentation

Updated 19/04/2013 19:43:00

For best results, follow the video

http://hap.codeplex.com/wikipage?title=Installation%20Video&referringTitle=Documentation

Home Access Plus+ needs to be installed onto a Website with SSL enabled, i.e. a HTTPS website.

You can get a free SSL Certificate from http://www.startssl.com

#### **Installation Instructions IIS 6**

- 1. Remote Desktop and/or log on to your primary domain controller (it can run on a member server)
- 2. Go to http://www.microsoft.com/net
- 3. Download .net framework version 4.
- 4. Install .net framework 4
- 5. Restart the server
- 6. Load IIS Manager
- 7. Expand the server
- 8. Click on web service extensions
- 9. Select ASP.net v4.xxx
- 10. Click Allow
- 11. Right Click on Application Pools
- 12. Select Add New Pool
- 13. Enter a Pool ID (e.g. "HAP")
- 14. Right Click on HAP (Pool ID) and Click Properties
- 15. Deselect Recycle worker process in minutes
- 16. Click on Performance
- 17. Deselect Idle shutdown timer
- 18. Install an SSL Certificate onto the Default Website:
  - a. Right click on the Website you want to put HAP+ into and click Properties
  - b. Under Web Site Identification click Advanced
  - c. In the Advanced Web site identification box, under Multiple identities for this Web site, verify that the Web site IP address is assigned to port 443, the default port for secure communications, and then click OK. Optionally, to configure more SSL ports for this Web site, click Add under Multiple identities of this Web site, and then click OK.
  - d. On the Directory Security or File Security tab, under Secure communications, click Edit.
  - e. To enable SSL client certificate authentication and mapping features, select the Enable client certificate mapping check box, click Edit, add the 1-to-1 or many-to-1 mappings you need, and then click OK three times.
- 19. Browse to <a href="http://hap.codeplex.com">http://hap.codeplex.com</a>
- 20. Download the latest version
- 21. Browse to
  - a. RM CC: D:\RMNetwork\RMManage\Web Components
  - b. All other: Your IIS wwwroot for the website you wish to use
- 22. Create a new folder called "HAP"
- 23. Extract the contents of the HAP Download to this folder
- 24. Right click HAP and select properties
- 25. Deselect readonly and click ok.

  Allow it to reset every readonly attribute






Version 9 Documentation

Updated 19/04/2013 19:43:00

#### 26. Add the permission:

- a. IIS\_WPG and Network Service. Set them to Read & Execute permissions
- b. App Data Folder: Set to Read & Write
- 27. Go back to IIS Manager
- 28. Expand Web Sites
- 29. Select the website you want to use
- 30. Right Click on HAP and click properties
- 31. Click the create button next to Application name:
- 32. Select "HAP" (App Pool from 13) as the application pool
- 33. Click the ASP.net Tab
- 34. Change ASP.net Version to v4.x.x
- 35. Click Apply
- 36. Click Yes on the Confirm Box
- 37. Wait...
- 38. Click on Directory
- 39. Click the Configuration Button
- 40. Double Click on the .ascx Application Extension
- 41. Copy the Executable path
- 42. Click OK
- 43. Click Insert... under wildcard application maps
- 44. Paste the Path from 41
- 45. Deselect Verify that file exists
- 46. Click OK
- 47. Click OK
- 48. Under Documents
- 49. Remove all from the default documents
- 50. Add "Default.aspx"
- 51. Click the Directory Security Tab
- 52. Click Edit
- 53. Tick Enable Anonymous Access
- 54. Untick Basic Authentication
- 55. Click OK
- 56. Close IIS Manager





Version 9 Documentation

Updated 19/04/2013 19:43:00

#### **Installation Instructions IIS 7**

- 1. Remote Desktop and/or log on to your primary domain controller (it can run on a member server)
- 2. Go to <a href="http://www.microsoft.com/net">http://www.microsoft.com/net</a>
- 3. Download .net framework version 4 (Full not Client).
- 4. Install .net framework 4
- 5. Restart the server
- 6. Load IIS Manager
- 7. Expand the server
- 8. Click on Application Pools
- 9. Select Add Application Pool...
- 10. Enter a Pool ID (e.g. "HAP")
- 11. Select .NET Framework v4
- 12. Integrated Managed Pipeline Mode
- 13. Click OK
- 14. Select your server in the tree on the left
- 15. Double click on the Server Certificates in the main section
- 16. Import or Create an SSL Certificate
- 17. Select a site in the tree view and click Bindings... in the Actions pane.
- 18. Click Add... to add your new SSL binding to the site.

  (if HTTPS already exists check that it has the correct certificate assigned to it)
- 19. Click Add... to add your new SSL binding to the site.
- 20. Select https as the Type, and assign the SSL Certificate added to IIS from above
- 21. Click OK
- 22. Click Close
- For more information visit <a href="http://learn.iis.net/page.aspx/144/how-to-set-up-ssl-on-iis/">http://learn.iis.net/page.aspx/144/how-to-set-up-ssl-on-iis/</a>
- 23. Browse to http://hap.codeplex.com
- 24. Download the latest version of the HAP+ Web ZIP
- 25. Browse to Your IIS wwwroot for the website you wish to use (C:\inetpub\wwwroot)
- 26. Create a new folder called "HAP"
- 27. Extract the contents of the HAP Download to this folder
- 28. Right click HAP and select properties
- 29. Deselect readonly and click ok.

Allow it to reset every readonly attribute

- 30. Add the permission:
  - a. IIS AppPool\HAP (Findable from the Local Machine). Set them to Read & Execute permissions
  - b. App\_Data Folder: Set to Read & Write
- 31. Go back to IIS Manager
- 32. Expand Web Sites
- 33. Select the website you want to use
- 34. Right Click on HAP and select Convert to Application...
- 35. Tell IIS to use the HAP Application Pool
- 36. Select "HAP"
- 37. Double Click on IIS Authentication
- 38. Confirm Anonymous and Forms Authentication is Enabled, and the rest are disabled
- 39. Click on Anonymous Authentication
- 40. Click on Edit...



Version 9 Documentation

Updated 19/04/2013 19:43:00

- 41. Select Application pool identity
- 42. Go Back
- 43. Close IIS Manager

## **Configuration**

1. Browse to your website and the setup should run



#### **Kerberos Internal SSO**

To enable this, please follow the video at

http://hap.codeplex.com/wikipage?title=Kerberos%20Setup&referringTitle=Videos

## Exchange 2007/2010/2013/Office 365 LiveTiles

If you are using Kerberos SSO or Windows Authentication, please set (Under the Proxy/SMTP Tab of the HAP+ Settings) the EWS Url as well a user to use for base impersonation, please this Technet Article: http://technet.microsoft.com/en-us/library/ff793352%28v=office.14%29.aspx

## **Layout Integration/Branding**

- 1. Browse to ~/master.masterpage
- 2. Edit the content of this file to suit your site's layout

#### **User Card Setup**

- 1. Download the HAP+ User Card Installer from the HAP+ Site
- 2. Extract the ZIP file
- 3. Edit HAP User Card.config in notepad
- 4. Change:
  - a. The Endpoint Address to your HAP+ URL
  - b. Change the OU for controlled assessment users (BLANK = DISABLED FEATURE)
  - c. Enable/Disable the Help Desk Tab
- 5. Deploy HAP User Card Setup.msi

#### **Logon Tracker Setup**

- 1. Download the HAP+ Logon Tracker Installer from the HAP+ Site
- 2. Deploy HAP User Card Setup.msi
- 3. In a Group Policy Object add Startup/Logon/Logoff/Shutdown Scripts:
  - a. Startup: "%windir%\system32\hap logon tracker.exe" https://%yourdomain%/hap
  - b. Logon: "%windir%\system32\hap logon tracker.exe" logon <a href="https://wyourdomain%/hap">https://wyourdomain%/hap</a>
  - c. Logoff: "%windir%\system32\hap logon tracker.exe" https://%yourdomain%/hap
  - d. Shutdown: "%windir%\system32\hap logon tracker.exe" https://%yourdomain%/hap
- Note the Parameter(s), this tells the logon tracker where HAP+ is installed



Version 9 Documentation

Updated 19/04/2013 19:43:00

## **Logon Tracker SQL Provider**

New in HAP+ v6 is the ability to offload the Logon Tracker to a SQL Provider

- 1. Open SQL Server Management Console (SQLEXPRESS or SQL FULL)
- 2. Create a new Database
- 3. IIS 7.5: Add IIS APPPOOL\\$apppool\$ where \$apppool\$ is the apppool identity of the application pool to the databases users
- 4. Execute ~/app data/hap.sql to create the tables
- 5. Close SQL Server Management Console
- 6. Open ~/web.config
- 7. Find the connectionStrings entry
- 8. You should find a SQLConnectionString, edit this to be your SQL Server's ConString
- 9. Find the hapConfig tracker entry
- 10. Change provider="XML" to provider=" SQLConnectionString" (or whatever you have called your SQL Connection String Provider
- 11. Save
- 12. Run HAP+
- 13. Browse to the Tracker Page
- 14. Run the Migration from the XML files
- 15. Enjoy the speed boost

## **Booking System Rooms Drop Down**

There's a hidden feature of the HAP+ Booking System, for Equipment and Laptops, which shows a list of rooms to use rather than a text box to enter. You can define a global list of use a local list.

This is a sample Xml excerpt for this, you can add this code either at the Booking System level and/or at the Resource Level.

On each resource you need to use the drop down list you need to, at least, have the inherit option set in the rooms element in the resource:

```
<resource...>
<rooms inherit="True" />
</resource>
```

For more info, please open a thread of the HAP+ Edugeek Forum.



Version 9 Documentation

Updated 19/04/2013 19:43:00

#### The Live Tiles

## **Uptime Live Tiles**

The Uptime Live Tiles are an advanced feature and are added directly in the HAPConfig.xml

<Link name="%a name, usually server name%" showto="Inherit" description="Uptime"
url="#" icon="" target="" type="uptime:%servername%" />

Notes:

Uptime Live Tiles only work on Active Directory connected servers.

#### **Calendar Live Tiles**

The Calendar Live Tiles allow you to place a live tile that accesses another mailbox's calendar, are an advanced feature and are added directly in the HAPConfig.xmlLive Tiles

<Link name="%a name%" showto="Inherit" description="%a description%" url="%url to
calendar%" icon="~/images/icons/metro/applications/calendar.png" target=""
type="exchange.calendar:%mailbox smtp address%" />

#### **The Other Tiles**

The Live Tiles are:

- Uptime Show a server's Uptime See above
- Exchange Calendar Shows the next 48 hours of calendar appointments in Exchange
   Add: type="exchange.appointments" to the Live Tile in ~/App\_Data/HAPConfig.xml
- Exchange Unread Emails Shows an unread mail count from Exchange
   Add: type="exchange.unread" to the Live Tile in ~/App\_Data/HAPConfig.xml
- My Files Shows the Drive Space indicators
   Add: type="myfiles" to the Live Tile in the ~/App\_Data/HAPConfig.xml
- Help Desk Shows the Open Help Desk Tickets
   Add: type="helpdesk" to the Live Tile in the ~/App\_Data/HAPConfig.xml
- Booking System Shows your bookings from the booking system for the next week
   Add: type="bookings" to the Live Tile in the ~/App\_Data/HAPConfig.xml