

## Problem B. Random Interactive MST Bot

Input file: *standard input*  
Output file: *standard output*  
Time limit: 1 second  
Memory limit: 256 mebibytes

How do setters come up with problems? Sometimes they just take a couple of buzzwords and smash them together. But we are in 2024, so this totally can be outsourced to AI. Introducing our creation based on ChatGPT: RICH B! And its second official problem:

*Prompt:* Minimum Spanning Tree

*Problem:* A complete graph with  $n$  nodes and  $\frac{n \cdot (n-1)}{2}$  edges is chosen. Each edge is randomly assigned a real-valued weight within the range of  $[0, 1]$ . Your task is to find its minimum spanning tree. But you are not given the edges. Instead, you can make queries of the form “?  $v_1$   $u_1$   $v_2$   $u_2$ ”, and the jury program will respond to you with 1 if the weight of edge  $(v_1, u_1)$  is less than the weight of edge  $(v_2, u_2)$ , and it will respond with 0 if it's not.

When you think that you know the minimum spanning tree, print it as “!  $v_1$   $u_1$   $v_2$   $u_2$  ...  $v_{n-1}$   $u_{n-1}$ ”, where edges  $(v_i, u_i)$  form the minimum spanning tree. Constraints:  $2 \leq n \leq 100$ , and you can make at most 6000 queries.

### Interaction Protocol

First, read a line that contains a single  $n$  ( $2 \leq n \leq 100$ ): the size of the graph.

To compare two edges, print a single line in the following format: “?  $v_1$   $u_1$   $v_2$   $u_2$ ”. You will then have to read a line with the result of the comparison: 1 if the weight of the first edge is less than the weight of the second edge, or 0 otherwise.

To output the answer, print a single line in the following format: “!  $v_1$   $u_1$   $v_2$   $u_2$  ...  $v_{n-1}$   $u_{n-1}$ ”. Your program has to immediately terminate after printing this line, otherwise, you may get unpredictable verdicts.

In every line you print,  $(v_i, u_i)$  should be pairs of integers where  $1 \leq v < u \leq n$ , otherwise, you may get unpredictable verdicts.

Your program should not make more than 6000 comparisons.

### Example

<i>standard input</i>	<i>standard output</i>
3	? 1 2 1 3
1	? 1 3 2 3
1	! 1 2 1 3

### Note

The Minimum Spanning Tree (MST) of a graph is defined as the graph's spanning tree having the minimum possible total weight.

A spanning tree is a connected subgraph of the given graph that contains all of the graph's vertices and does not contain cycles.

The interactor is **not adaptive**.

Remember to end the line and flush the output after every line you print. To flush the output, you can use `fflush(stdout)` in C/C++, `System.out.flush()` in Java, or `sys.stdout.flush()` in Python.