

Antivirus

Input file: **standard input**
Output file: **standard output**
Time limit: 2 seconds
Memory limit: 1024 megabytes

In the introduction to network flow, the teacher had barely begun explaining when their pet chicken figured out how to solve the problem. The teacher exclaimed: Our avian flu is amazing!

—Roasted-chicken

Hyrule is entering the flu season.

Hyrule consists of n cities, which are connected by m **directed** roads. The capital (city numbered 1) can be reached from all cities through these roads.

The flu season will last for q days. On the i -th day at noon, the flu virus will start spreading from city a_i . The virus will spread along the roads to other cities. The virus spreads very quickly, so it can be assumed that all cities reachable from a_i will be infected immediately. As the capital city of Hyrule, city 1 is crucial for the whole country. If the virus that starts spreading on the i -th day reaches the capital, there will be an economic loss cost of b_i .

To prevent the virus from spreading, Auru can deploy a virus filter in a city each night (including the night before the first day). Deploying a virus filter in city i has a deployment cost of c_i . The virus cannot spread through the city equipped with a virus filter, and that city will also remain uninfected. If the virus were to start spreading from a city equipped with a virus filter, the virus would simply disappear without infecting any cities. The deployed virus filter remains effective until Auru deploys a new filter in another city. (In other words, there can be at most one virus filter at a time.)

Auru wants to know: for each $i = 1, 2, \dots, q$, considering only the viruses in the first i days, what is the minimum value of “economic loss cost + deployment cost”.

Input

Each test file contains multiple test cases. The first line contains the number of test cases T ($1 \leq T \leq 10^4$). The description of the test cases follows.

The first line contains three integers n , m , and q ($2 \leq n \leq 10^5$, $n - 1 \leq m \leq 2 \times 10^5$, $1 \leq q \leq 10^5$), representing the number of cities, the number of roads, and the duration of the flu season in days, respectively.

In the next m lines, each contains two integers u_i and v_i ($1 \leq u_i, v_i \leq n$), representing a **directed** road from city u_i to city v_i . It is guaranteed that there are no self-loops, but **there may be multiple edges** between cities. The capital can be reached from all cities.

The next line contains n integers c_1, c_2, \dots, c_n ($1 \leq c_i \leq 10^9$), representing the deployment cost of the virus filter in each city.

In the following q lines, the i -th one contains two integers a_i and b_i ($2 \leq a_i \leq n$, $1 \leq b_i \leq 10^9$), indicating the city where the virus starts to spread on the i -th day and the economic loss cost if the virus reaches the capital.

For each test file, it is guaranteed that the sum of n over all test cases does not exceed 10^5 , the sum of m over all test cases does not exceed 2×10^5 , and the sum of q over all test cases does not exceed 10^5 .

Output

For each test case, output a line containing n integers, where the i -th integer represents the minimum value of the “economic loss cost + deployment cost” when only considering the viruses in the first i days.


Example

standard input	standard output
3	2 3 4 4
7 6 4	5 100 102 202
2 1	10
3 1	
4 2	
5 2	
6 3	
7 3	
4 3 5 2 2 1 1	
4 2	
5 2	
6 2	
7 2	
5 6 4	
1 3	
3 2	
2 1	
4 2	
5 4	
2 5	
10000 10000 2 100 5	
5 1000	
4 1000	
3 1000	
4 1000	
4 4 1	
2 1	
3 1	
4 2	
4 3	
100 1 1 100	
4 10	

Note

In the first test case:


- The minimum cost after day 1 is 2: on night 0, deploy a virus filter in city 4 with a deployment cost of 2.
- The minimum cost after day 2 is 3: on night 0, deploy a virus filter in city 2 with a deployment cost of 3.
- The minimum cost after day 3 is 4: on night 0, deploy a virus filter in city 2 with a deployment cost of 3; on night 2, deploy a virus filter in city 6 with a deployment cost of 1.
- The minimum cost after day 4 is 4: on night 0, deploy a virus filter in city 1 with a deployment cost of 4.



Example 1 Illustration


In the second test case:

- The minimum cost after day 1 is 5: on night 0, deploy a virus filter in city 5 with a deployment cost of 5.
- The minimum cost after day 2 is 100: on night 0, deploy a virus filter in city 4 with a deployment cost of 100.
- The minimum cost after day 3 is 102: on night 0, deploy a virus filter in city 4 with a deployment cost of 100; on night 2, deploy a virus filter in city 3 with a deployment cost of 2.
- The minimum cost after day 4 is 202: on night 0, deploy a virus filter in city 4 with a deployment cost of 100; on night 2, deploy a virus filter in city 3 with a deployment cost of 2; on night 3, deploy a virus filter in city 4 again with a deployment cost of 100.



Example 2 Illustration

In the third test case, since only one virus filter can exist at a time, it is not possible to stop the virus from spreading by deploying virus filters in both cities 2 and 3. The deployment costs for cities 1 and 4 are higher than the economic loss cost caused by the virus, so no virus filter is deployed, and the minimum cost is 10 (economic loss cost).



Example 3 Illustration