Dynamic Reachability

Input file: standard input
Output file: standard output

Time limit: 12 seconds Memory limit: 512 megabytes

You are given a directed graph with n vertices and m edges, the vertices of which are labeled by $1, 2, \ldots, n$. The color of each edge is either black or white. Initially, all the m edges are colored black.

You need to perform q operations. Each operation is one of the following:

- "1 k" $(1 \le k \le m)$: Change the color of the k-th edge in the input from black to white and vice versa.
- "2 u v" $(1 \le u, v \le n, u \ne v)$: You need to answer whether vertex u can reach vertex v without passing any white edge.

Input

The input contains only a single case.

The first line contains three integers n, m and q ($2 \le n \le 50\,000, 1 \le m, q \le 100\,000$), denoting the number of vertices, the number of edges, and the number of operations.

Each of the following m lines contains two integers u_i and v_i $(1 \le u_i, v_i \le n, u_i \ne v_i, 1 \le i \le m)$, denoting a directed edge from vertex u_i to vertex v_i .

Each of the next q lines describes an operation in formats described in the statement above.

Output

For each query, print a single line. If vertex u can reach vertex v without passing any white edge, print "YES". Otherwise, print "NO".

Example

standard input	standard output
5 6 7	YES
1 2	NO
1 3	NO
2 4	YES
3 4	
3 5	
4 5	
2 1 5	
2 2 3	
1 3	
1 4	
2 1 4	
1 3	
2 1 5	