

Engineering Ceramic Rigid+

SDS Quick Glance



PRODUCT

Name: Engineering Ceramic Rigid+
Description: Commercial 3D Print Resin
Manufacturer: Applied Molecules LLC
Type: Acrylics

HAZARDS

Signal Word: Danger



DETAILS

Physical State: Liquid
Viscosity: 750 cP
Flashpoint: >93°C
Jurisdiction: United States of America
Language: English
Created By: Nick Gripp
(ngripp@appliedmolecules.com)
Created Date: 2026-08-20



This SDS was automatically generated by Albert
in 6.4 seconds.

At Albert, our mission is to accelerate the
innovation of sustainable products.

<https://www.albertinvent.com/>

TRANSPORTATION

Based on US Department of Transportation Ground (49 CFR)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Diacrylate ester; Acrylic ester)
Hazard class or division: 9
Identification number: UN3082
Packing group: III

REGULATION

This section calls out a few of the major regulations. For full regulatory details, please see section 15 of the SDS.

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

SUSTAINABILITY METRICS

International Living Future Institute



100.00% of this product is free from any "worst in class" materials



Red List

100% of this product is known to be **Red List Free**
0% of this product is on the **Red List**



Priority List

100% of this product is known to be **Priority List Free**
0% of this product is on the **Priority List**



Watch List

100% of this product is known to be **Watch List Free**
0% of this product is on the **Watch List**

For more information, visit: <https://living-future.org/lbc/red-list/>



01. Product and Company Identification

Engineering Ceramic Rigid+

Product name

- Description: Commercial 3D Print Resin
- Albert ID: AM296-001
- Product type/use: Acrylics
- Jurisdiction: United States of America

Chemtrec - 800.424.9300 (Toll Free)

Applied Molecules LLC,
11230 Lemen Industrial Drive, 48189, Whitmore Lake, MI,
USA TelePhone : 810-355-1475
www.appliedmolecules.com
info@appliedmolecules.com

02. Hazards Identification

DANGER

Signal Word



GHS CLASSIFICATION

Hazard Class	Hazard Statement	Hazard Category
Skin Irritation	Causes skin irritation (H315)	2
Skin Sensitization	May cause an allergic skin reaction (H317)	1A
Serious Eye Damage	Causes serious eye damage (H318)	1
STOT RE	May cause damage to organs through prolonged or repeated exposure (H373)	2

Precautionary Statements



Prevention: (P260) Do not breathe vapors, mist, or spray. (P264) Wash affected area thoroughly after handling. (P264+P265) Wash hands thoroughly after handling. Do not touch eyes. (P272) Contaminated work clothing should not be allowed out of the workplace. (P280) Wear protective gloves, clothing, eye and face protection.



Response: (P302+P352) IF ON SKIN: Wash with plenty of water. (P305+P354+P338) IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. (P317) Get emergency medical help. (P319) Get medical help if you feel unwell. (P321) Specific treatment (see additional information on this label). (P332+P317) If skin irritation occurs: Get medical help. (P333+P313) If skin irritation or rash occurs: Get medical attention. (P362+P364) Take off contaminated clothing and wash it before reuse.



Storage: Not available.

