

Battle Bond 328

SDS Quick Glance



PRODUCT

Name: Battle Bond 328
Description: Solvent Based Adhesive
Manufacturer: Applied Molecules LLC
Type: Solvent based adhesive

HAZARDS

Signal Word: Danger



DETAILS

Physical State: Liquid
Viscosity: 1200 cP
Flashpoint: <23°C
Jurisdiction: United States of America
Language: English
Created By: Nick Gripp
(ngripp@appliedmolecules.com)
Created Date: 2026-08-21



This SDS was automatically generated by Albert
in 6.1 seconds.

At Albert, our mission is to accelerate the
innovation of sustainable products.

<https://www.albertinvent.com/>

TRANSPORTATION

Based on US Department of Transportation Ground (49 CFR)

Proper shipping name: FLAMMABLE LIQUID, N.O.S. (001 | Acetone (legal classification))
Hazard class or division: 3
Identification number: UN1993
Packing group: I

REGULATION

This section calls out a few of the major regulations. For full regulatory details, please see section 15 of the SDS.

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

SUSTAINABILITY METRICS

International Living Future Institute



100.00% of this product is free from any "worst in class" materials

Red List

100% of this product is known to be **Red List Free**
0% of this product is on the **Red List**

Priority List

100% of this product is known to be **Priority List Free**
0% of this product is on the **Priority List**

Watch List

100% of this product is known to be **Watch List Free**
0% of this product is on the **Watch List**

For more information, visit: <https://living-future.org/lbc/red-list/>



01. Product and Company Identification

Battle Bond 328

Product name

- Description: Solvent Based Adhesive
- Albert ID: AM328-001
- Product type/use: Solvent based adhesive
- Jurisdiction: United States of America

Chemtrec - 800.424.9300 (Toll Free)

Applied Molecules LLC,
11230 Lemen Industrial Drive, 48189, Whitmore Lake, MI,
USA TelePhone : 810-355-1475
www.appliedmolecules.com
info@appliedmolecules.com

02. Hazards Identification

DANGER

Signal Word



GHS CLASSIFICATION

Hazard Class	Hazard Statement	Hazard Category
Flammable Liquid	Extremely flammable liquid and vapour (H224)	1
Eye Irritation	Causes serious eye irritation (H319)	2A
STOT SE	May cause drowsiness or dizziness (H336)	3

Precautionary Statements



Prevention: (P210) Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P233) Keep container tightly closed. (P240) Ground and bond container and receiving equipment. (P241) Use explosion-proof equipment. (P242) Use non-sparking tools. (P243) Take action to prevent static discharges. (P261) Avoid breathing vapors, mist, or spray. (P264+P265) Wash hands thoroughly after handling. Do not touch eyes. (P271) Use only outdoors or in a well-ventilated area. (P280) Wear protective gloves, clothing, eye and face protection.



Response: (P303+P361+P353) IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. (P304+P340) IF INHALED: Remove person to fresh air and keep comfortable for breathing. (P305+P351+P338) IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P319) Get medical help if you feel unwell. (P337+P317) If eye irritation persists: Get medical help. (P370+P378) In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.



Storage: (P403+P233) Store in a well-ventilated place. Keep container tightly closed. (P403+P235) Store in a well-ventilated place. Keep cool. (P405) Store locked up.



Disposal: (P501) Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

