

What does  $O(< expr >)$  mean?

1

What does  $\Theta(< expr >)$  mean?

2

What does  $\Omega(< expr >)$  mean?

3

What are the best, average and worst case complexities of  
**Bubble Sort**?

4

What are the best, average and worst case complexities of  
**Merge Sort**?

5

Give pseudo code for merging 2 sorted lists, as part of merge  
sort.

6

Give pseudo code for MergeSort(L).

7

What are the best, average and worst case complexities of  
**Quick Sort**?

8

The complexity (i.e. space/running time) has the complexity proportional to  $\langle \text{expr} \rangle$ .

The complexity (i.e. running time/space) is bounded by the  $\langle \text{expr} \rangle$ .

2

1

Best:  $O(n)$ ,  
Average:  $O(n^2)$ ,  
Worst:  $O(n^2)$

The complexity (i.e. running time/space) is at least by the  $\langle \text{expr} \rangle$ .

4

3

```
Merge( $L_1$ ,  $L_2$ )
  if  $L_1 = []$  return  $L_2$ 
  if  $L_2 = []$  return  $L_1$ 
   $x_1 = L_1[0]$ 
   $x_2 = L_2[0]$ 
   $L'_1 = L_1[1 : |L_1| - 1]$ 
   $L'_2 = L_2[1 : |L_2| - 1]$ 
  if  $x_1 \leq x_2$ 
    return  $[x_1] + \text{Merge}(L'_1, L_2)$ 
  return  $[x_2] + \text{Merge}(L_1, L'_2)$ 
```

Best:  $O(n \log \log_2 n)$ ,  
Average:  $O(n \log \log_2 n)$ ,  
Worst:  $O(n \log \log_2 n)$

Merge two sorted lists

6

5

Best:  $O(n \log \log_2 n)$ ,  
Average:  $O(n \log \log_2 n)$ ,  
Worst:  $O(n^2)$

```
MergeSort( $L$ )
  if  $|L| \leq 1$ 
    return  $L$ 
  Split  $L$  into roughly equal halves,  $L_l$  and  $L_r$ 
  return Merge(MergeSort( $L_l$ ), MergeSort( $L_r$ ))
```

MergeSort( $L$ )

8

7

*What would the pseudo code be for Quick Sort?*

9

*Say that the input represents a positive integer,  $x$ , what is the size of  $n$ ?*

10

*What does it mean by  $O(1)$ ?*

11

*What is the minimum time for any sorting algorithm that uses only number comparisons?*

12

*What would the pseudo code be for Euclid's algorithm?*

13

*What would the pseudo code be for Fast Modular Exponentiation?*

14

*Give pseudo code for calculating the Discrete Logarithm?*

15

*Consider the equation  $a^x = y \bmod p$ . If  $a$  is a primitive root modulo  $p$ , then for every  $y(1 \leq y < p)$ , such an  $x(1 \leq x < p)$  exists. What is  $x$ ?*

16

$\lfloor \log_b x \rfloor + 1$  Where  $b$  is the number representation, usually binary (so 2).

```
quicksort(L)
  if length of L ≤ 1
    return L
  remove the first element, x, from L
  L≤ := elements of L less than or equal to x
  L> := elements of L greater than x
  Ll := quicksort(L≤)
  Lr := quicksort(L>)
  return Ll + [x] + Lr
```

Quick Sort

10

9

$n \log_2 n$

It takes a constant time, no matter the amount of data, to perform the operation.

12

11

```
fme(a,b,k)
  d = a
  e = b
  s = 1
  While e > 0
    if e is odd
      s = (s.d)modk
    d = d2modk
    e = ⌊e/2⌋
  return s
```

Fast Modular Exponentiation

```
// Assume a ≥ b
hcf(a,b)
  if b = 0
    return a
  r = a mod b
  return hcf(b,r)
```

Euclid's algorithm

14

13

$X$  is the **discrete logarithm** of  $y$  with base  $a$ , modulo  $p$ .

```
discreteLog(p,g,b)
  x := 1
  While x is less than p
    y = gxmodp
    if x = b
      return x
  x ++
```

Calculates Discrete Logarithm

16

15

The  is the inverse of exponentiation.

17

Why can the private key not, in practice, be recovered from the public key when  $p$  is large?

18

What is one way you can argue correctness of Euclid's algorithm?

19

What would half the correctness proof be for Euclid's algorithm?

20

$$(a.b) \bmod k = \text{$$

21

Let  $p$  be a prime number. What is meant by a primitive root modulo  $p$ ?

22

What does saying that algorithm  $A$  runs in time  $g$  mean?

23

To calculate a public key,  $y$ , a private key,  $x$  is needed. The equation for modular exponentiation can be used:  $y = g^x \text{ mod } p$ . It is considered a one-way function - easy to compute, hard to invert. For a large  $p$ , the only way to figure out the private key would be to use brute force, which would take a large amount of time.

The discrete logarithm is the inverse of exponentiation.

18

17

As  $r = a \text{ mod } b$ ,  $\exists q$  such that  $a = bq + r$ ,  $\therefore r = a - bq$ .  
 Suppose  $x$  is a factor of  $a$  and  $b$ , then  $\exists y$  and  $z$  such that  
 $a = xy$ ,  $b = xz$ .  
 Hence:  $r = xy - xzq$ ,  $r = x(y - zq)$ .  
 $\therefore x$  is a factor of  $r$  (and also of  $b$  and  $r$ ).

Let  $r = a \text{ mod } b$ .  $\text{hcf}(a, b) = \text{hcf}(b, r)$  because all factors of  $a$  and  $b$  are also factors of  $b$  and  $r$  and vice versa. If they have the same factors, they have the same highest common factor.

20

19

The numbers  $r_x$  between 1 and  $p - 1$  that, when raised by the numbers between 1 and  $p - 1$  compute all the numbers between 1 and  $p - 1$  in some order with no repetitions.

$$(a.b) \text{ mod } k = (a \text{ mod } k.b \text{ mod } k) \text{ mod } k$$

22

21

Given an input of size  $n$ , the number of operations executed by  $A$  is bounded above by  $g(n)$ .

23