

Python
for everybody



Session 3

4. String

4. String

4.1. String vs List

String vs List

A **string** is a sequence of characters.

```
1 fruit = "banana"
```

Strings are **not** lists, but they share many features:

```
1 letter = fruit[1]
2 print(letter)
3
4 print('b' in fruit)
5
6 sliced_word = fruit[0:3]
7
8 for char in fruit:
9     print(char)
```

String vs List

Strings are **immutable**, which means you can't change an existing string :

```
1 fruit = "banana"
2 fruit[0] = 'v' #Error
```

The best you can do is create a **new string** that is a variation on the original:

```
1 fruit = "banana"
2 new_fruit = 'v' + fruit[1:]
3 print(new_fruit)
```

4. String

4.2. String Methods

String methods

```
1 fruit = "banana"
2
3 index = fruit.find('b')           # Returns index of 'b' which is 0
4
5 characters = list(fruit)          # ['b', 'a', 'n', 'a', 'n', 'a']
6
7 full_name = "Mohamed Ali Mahmoud"
8 names = full_name.split(" ")      # ['Mohamed', 'Ali', 'Mahmoud']
9
10 words = ['look', 'for', 'a', 'job']
11 sentence = " ".join(words)        # 'look for a job'
```


5. Functions in Python

5. Functions in Python

5.1. Definition

Definition

A function is a named sequence of statements that performs a specific task.

In other words, it allows you to group several instructions under one name and execute (or “call”) them whenever needed.

5. Functions in Python

5.2. Built-in functions

Built-in functions

We have already used several functions such as `print()`, `len()`, etc. These are called built-in functions, meaning they are predefined by Python.

Examples:

```
1 print("Hello, World!")      # Output: Hello, World!
2
3 length = len("AppsClub")    # length = 8
4
5 sys.exit()                  # Exits the program
6
7 value = random.random()     # Returns a random float between 0 and 1
```

5. Functions in Python

5.3. Why do we use functions?

Why do we use functions?

We create our own functions for several reasons:

- They make the code **easier to read** by naming what the block does.
- They **eliminate repetitive** code blocks
- They help us **debug faster** and more efficiently
- They allow us to **reuse** code across different programs

5. Functions in Python

5.4. Defining your own functions

Defining your own functions

Syntax:

```
1 def function_name(parameter1, parameter2, ...):  
2     # Function body (instructions)
```

To call a function:

```
1 function_name(argument1, argument2, ...)
```

Defining your own functions

Example 1:

```
1 def welcome_user(name):  
2     print("Welcome, Mr.", name)  
3  
4 welcome_user("Ahmed")
```

Example 2:

```
1 def sum_numbers(x, y, z):  
2     print(x + y + z)  
3  
4 sum_numbers(6, 2, 3)
```

Notes:

- Function with default parameters

```
1 def welcome_user(name="X"):  
2     print("Welcome, Mr.", name)  
3  
4 welcome_user("Ahmed")    # Welcome, Mr. Ahmed  
5 welcome_user()           # Welcome, Mr. X
```

- Function with no arguments

```
1 import random  
2 def random_message():  
3     value = random.random()  
4     if value > 0.5:  
5         print("You win!")  
6     else:  
7         print("You lose!")  
8  
9 random_message()
```

Defining your own functions

Return statement

In previous examples, the functions printed results.

But functions can also return a value, which can be stored and reused.

Example 1:

```
1 def sum_numbers(x, y, z):  
2     return x + y + z  
3  
4 S = sum_numbers(10, 20, 30)  
5 print(S)    # 60
```

Example 2:

```
1 def split_link(link):  
2     return link.split('/')  
3  
4 splitted_link = split_link("www.school.com/Bac/Math/Exercices")  
5 # ['www.school.com', 'Bac', 'Math', 'Exercices']
```

5. Functions in Python

5.5. Variable scope in Python

Variable scope in Python

Example:

```
1 a = 10
2
3 def change_value():
4     a = 20
5
6 change_value()
7 print(a)
```

What do you expect the value of a to be? *It is still 10.*

Why? Because assigning a value to a inside the function makes Python treat it as a new local variable inside the function's scope. It does not modify the variable a from the global scope.

Variable scope in Python

Solution: If you want to modify the global variable from inside the function, you must explicitly tell Python by using the keyword **global**.

```
1 a = 10
2
3 def change_value():
4     global a
5     a = 20
6
7 change_value()
8 print(a)    # Now prints 20
```

