ESP32 Formats and Communication

Updates

Software versions listed in Table 1-10.

The latest Arduino IDE software is version 2.2.1. www.arduino.cc/en/software

The latest *esp32* Boards Manager is version v2.0.14. github.com/espressif/arduino-esp32/releases

Chapter 2 I2S Audio

When playing internet radio (Listing 2-6) or MP3 files (Listing 2-9) with the *M5Core2 0.1.3* and the *Audio* libraries, the sound quality is fine. However, with the *M5Core2 0.1.4* or *M5Core2 0.1.5* libraries, the audio plays at a "slow speed".

The "slow speed" problem, for the *M5Core2 0.1.7* library, is resolved by replacing the instructions:

```
M5.begin(true, true, true, true) in Listing 2-6 with
M5.begin(true, true, true, true, kMBusModeOutput, false) or replacing
M5.begin() in Listing 2-9 with
M5.begin(true, true, true, false, kMBusModeOutput, false).
```

The impact of the changes is to set the *SpeakerEnable* variable to *false*, as the default M5.begin parameters are:

with the power option equal to 0 or 1 when the M5Stack Core2 is powered by USB/battery or by outside input, respectively.

Chapter 9 MQTT

Cayenne (developers.mydevices.com) announced that Cayenne MQTT broker will be discontinued in September 2023 (community.mydevices.com/t/end-of-life-announcement-for-cayenne/18926). Chapter 9 *MQTT* has been updated with the Blynk, Arduino IoT Cloud and Adafruit IO MQTT broker services. The updated Chapter and accompanying sketches are included in the **Chapter** 9_NEW_V2 folder on GitHub (github.com/Apress/ESP32-Formats-and-Communication/tree/main/Chapter9_NEW_V2).

Corrections

Despite repeatedly checking the page proofs, some typos may have persisted.

If you find typos, then please either email esp32ndc@gmail.com or use GitHub Issues to log the typo or other issues.

Page 88 last -5 line Change expression to (A > B) ? C : D by inserting a ?

Page 367 Line 10 Change SCTpin = 37 to SCTpin = 36 (as in Figure 9-7)

Page 395 Line 9 Change comment to "Clear LCD screen"

Neil Cameron

November 2023