Electronics Projects with the ESP8266 and ESP32

Updates

Listing5-3 is based on version 2.8.0 of the *IRremote* library for the ESP32 microcontroller. **Listing5-3_NEW** is based on version 3.0.2 of the *IRremote* library.

Library version 3.0.2 instruction <code>IrReceiver.begin(IRpin)</code> replaces library 2.8.0 instructions <code>IRrecv irrecv(IRpin)</code>, <code>decode_results reading</code> and <code>irrecv.enableIRIn()</code>. The library version 3.0.2 instruction <code>if(IrReceiver.decode())</code> replaces the instruction <code>if(irrecv.decode(&reading))</code>.

Received data is accessed in library version 3.0.2 from IrReceiver.decodedIRData (protocol, command and numberOfBits), rather than from reading (decode_type, value and bits) in library version 2.8.0.

ESP-MESH protocol could have been included in Chapter 14: *ESP-NOW and LoRa communication*, but the book already covered many topics and a line had to be drawn somewhere.

Details of ESP-MESH with sketches are included in the folder ESP-MESH.

Corrections

Despite repeatedly checking the page proofs, some typos persevered. If you find other typos, then please use *GitHub Issues* to log the typo.

Page 172 text line 7 change R'' (=== and ===) " to R''=== (and) ==="

Page 207 text line 1 delete "or app"

Page 233 line 11 change servoFb.write(N) to servoFB.write(N)

Page 588 listing line 3 in the comment, change Wi-FI to Wi-Fi

Neil Cameron

March 2021