

# Key concepts on Deep Neural Networks

10/10 points (100%)

Quiz, 10 questions

✓ **Congratulations! You passed!**

Next Item



1 / 1  
points

1.

What is the "cache" used for in our implementation of forward propagation and backward propagation?

- ☐ It is used to cache the intermediate values of the cost function during training.
- ☐ It is used to keep track of the hyperparameters that we are searching over, to speed up computation.
- ☒ We use it to pass variables computed during forward propagation to the corresponding backward propagation step. It contains useful values for backward propagation to compute derivatives.



**Correct**

Correct, the "cache" records values from the forward propagation units and sends it to the backward propagation units because it is needed to compute the chain rule derivatives.

- ☐ We use it to pass variables computed during backward propagation to the corresponding forward propagation step. It contains useful values for forward propagation to compute activations.



1 / 1  
points

2.

Among the following, which ones are "hyperparameters"? (Check all that apply.)



size of the hidden layers  $n^{[l]}$



**Correct**



number of iterations



Correct

## Key concepts on Deep Neural Networks

10/10 points (100%)

Quiz, 10 questions ☒ activation values  $a^{[l]}$

Un-selected is correct

☐ number of layers  $L$  in the neural network

Correct

☐ bias vectors  $b^{[l]}$

Un-selected is correct

☐ weight matrices  $W^{[l]}$

Un-selected is correct

☐ learning rate  $\alpha$

Correct



1 / 1  
points

3.

Which of the following statements is true?



The deeper layers of a neural network are typically computing more complex features of the input than the earlier layers.



Correct



The earlier layers of a neural network are typically computing more complex features of the input than the deeper layers.



1 / 1  
points

4.

Vectorization allows you to compute forward propagation in an  $L$ -layer neural network without an explicit for-loop (or any other explicit iterative loop) over the layers  $l=1, 2, \dots, L$ . True/False?



## Key concepts on Deep Neural Networks

10/10 points (100%)

Quiz, 10 questions

Correct

Forward propagation propagates the input through the layers, although for shallow networks we may just write all the lines ( $a^{[2]} = g^{[2]}(z^{[2]})$ ,  $z^{[2]} = W^{[2]}a^{[1]} + b^{[2]}$ , ...) in a deeper network, we cannot avoid a for loop iterating over the layers: ( $a^{[l]} = g^{[l]}(z^{[l]})$ ,  $z^{[l]} = W^{[l]}a^{[l-1]} + b^{[l]}$ , ...).



1 / 1  
points

5.

Assume we store the values for  $n^{[l]}$  in an array called layers, as follows: layer\_dims = [ $n_x$ , 4,3,2,1]. So layer 1 has four hidden units, layer 2 has 3 hidden units and so on. Which of the following for-loops will allow you to initialize the parameters for the model?



```
1 for(i in range(1, len(layer_dims)/2)):
2     parameter['W' + str(i)] = np.random.randn(layers[i], layers[i-1]
3     )) * 0.01
3     parameter['b' + str(i)] = np.random.randn(layers[i], 1) * 0.01
```



```
1 for(i in range(1, len(layer_dims)/2)):
2     parameter['W' + str(i)] = np.random.randn(layers[i], layers[i-1]
3     )) * 0.01
3     parameter['b' + str(i)] = np.random.randn(layers[i-1], 1) * 0.01
```



```
1 for(i in range(1, len(layer_dims))):
2     parameter['W' + str(i)] = np.random.randn(layers[i-1], layers[i]
3     )) * 0.01
3     parameter['b' + str(i)] = np.random.randn(layers[i], 1) * 0.01
```



```
1 for(i in range(1, len(layer_dims))):
2     parameter['W' + str(i)] = np.random.randn(layers[i], layers[i-1]
3     )) * 0.01
3     parameter['b' + str(i)] = np.random.randn(layers[i], 1) * 0.01
```



Correct



1 / 1  
points


6.

Consider the following neural network.

## Key concepts on Deep Neural Networks

10/10 points (100%)

Quiz, 10 question



How many layers does this network have?

☒ The number of layers  $L$  is 4. The number of hidden layers is 3.

**Correct**

Yes. As seen in lecture, the number of layers is counted as the number of hidden layers + 1. The input and output layers are not counted as hidden layers.

☐ The number of layers  $L$  is 3. The number of hidden layers is 3.

☐ The number of layers  $L$  is 4. The number of hidden layers is 4.

☐ The number of layers  $L$  is 5. The number of hidden layers is 4.



1 / 1  
points

7.

During forward propagation, in the forward function for a layer  $l$  you need to know what is the activation function in a layer (Sigmoid, tanh, ReLU, etc.). During backpropagation, the corresponding backward function also needs to know what is the activation function for layer  $l$ , since the gradient depends on it. True/False?

☒ True

**Correct**

Yes, as you've seen in the week 3 each activation has a different derivative. Thus, during backpropagation you need to know which activation was used in the forward propagation to be able to compute the correct derivative.

☐ False



1 / 1  
points

8.

There are certain functions with the following properties:

## Key concepts on Deep Neural Networks

For computing a function using a shallow network circuit, you will need a large network (where we measure size by the number of logic gates in the network), but (ii) To compute it using a deep network circuit, you need only an exponentially smaller network. True/False?

☒ True

Correct


☐ False



1 / 1  
points

9.

Consider the following 2 hidden layer neural network:



Which of the following statements are True? (Check all that apply).

☒  $W^{[1]}$  will have shape (4, 4)

Correct

Yes. More generally, the shape of  $W^{[l]}$  is  $(n^{[l]}, n^{[l-1]})$ .

☒  $b^{[1]}$  will have shape (4, 1)

Correct

Yes. More generally, the shape of  $b^{[l]}$  is  $(n^{[l]}, 1)$ .

☐  $W^{[1]}$  will have shape (3, 4)

## Key concepts on Deep Neural Networks

10/10 points (100%)

Un-selected is correct  
Quiz, 10 questions

☐  $b^{[1]}$  will have shape (3, 1)

Un-selected is correct

☐  $W^{[2]}$  will have shape (3, 4)

Correct

Yes. More generally, the shape of  $W^{[l]}$  is  $(n^{[l]}, n^{[l-1]})$ .

☐  $b^{[2]}$  will have shape (1, 1)

Un-selected is correct

☐  $W^{[2]}$  will have shape (3, 1)

Un-selected is correct

☐  $b^{[2]}$  will have shape (3, 1)

Correct

Yes. More generally, the shape of  $b^{[l]}$  is  $(n^{[l]}, 1)$ .

☐  $W^{[3]}$  will have shape (3, 1)

Un-selected is correct

☐  $b^{[3]}$  will have shape (1, 1)

Correct

Yes. More generally, the shape of  $b^{[l]}$  is  $(n^{[l]}, 1)$ .

☐  $W^{[3]}$  will have shape (1, 3)

Correct

Yes. More generally, the shape of  $W^{[l]}$  is  $(n^{[l]}, n^{[l-1]})$ .

☐  $b^{[3]}$  will have shape (3, 1)

## Key concepts on Deep Neural Networks

10/10 points (100%)

Quiz, 10 questions

---

1 / 1  
points

10.

Whereas the previous question used a specific network, in the general case what is the dimension of  $W^{[l]}$ , the weight matrix associated with layer  $l$ ?

☐  $W^{[l]}$  has shape  $(n^{[l-1]}, n^{[l]})$ ☐  $W^{[l]}$  has shape  $(n^{[l]}, n^{[l+1]})$ ☐  $W^{[l]}$  has shape  $(n^{[l+1]}, n^{[l]})$ ☒  $W^{[l]}$  has shape  $(n^{[l]}, n^{[l-1]})$ **Correct**True

---

