Skills Network

HTML and HTML5 Elements Cheat Sheet

Element	Description	Example
<!DOCTYPE html>	All HTML documents must start with this declaration. It tells the browser what document type to expect. Note that this element has no ending tag.	1 2 3 4 5 6 7 8 9 10 11 1 2 3. <!DOCTYPE html> 4. <html> 5. <head> 6. <title>Document Title</title> 7. </head> 8. <body> 9. Document body here 10. </body> 11. </html> Copied!
<a href= "path">	This tag, called an "anchor tag" creates hyperlinks using the href attribute. In place of **path** enter the URL or path name to the page you want to link to.	<a href="https://www.ibm.com">IBM</a>
<article>	Identifies a self-contained piece of content that could be distributed to other websites and platforms as a stand-alone unit. Similar to tag in that it does not render as anything special in the browser unless it is styled with CSS.	1 2 3 4 5 6 1. <article class="CSS-Style-Reference"> 2. <h2>HTML</h2> 3. HTML stands for Hypertext Markup Language. 4. It is a standardized system for tagging text files to display specific 5. font, color, graphics, and hyperlinks on World Wide Web pages. 6. </article> Copied!
<aside>	Defines some content aside from the content it is placed in. Similar to tag in that it does not render as anything special in the browser unless it is	1 2 3 4 1. <aside> 2. Use the aside tag to represent a section of a page that consists 3. of content tangentially related to the content. 4. </aside> Copied!

	styled with CSS.	

<body>	Contains the contents of the HTML document. It should contain all other tags besides the <head> element to display the body of the document.	1 2 3 4 5 6 7 8 9
		`<!DOCTYPE html>`
		`<html>`
		`<head>`
		`<title>Document Title</title>`
		`</head>`
		`<body>`
		`Document body here`
		`</body>`
		`</html>`
		Copied!

** **	Often used to separate sections in the body of a document in order to style that content with CSS.	1 2 3 4
		`<div>`
		`This element has no particular semantic meaning but is often used`
		`in conjunction with CSS for styling purposes.`
		`</div>`
		Copied!

<fieldset>	Groups related elements in a form and puts a box around them.	1 2 3 4 5 6 7 8 9 10 `<form action= "/script.php">` `<fieldset>` `<legend>User:</legend>` `<label for="fname">First name:</label>` `<input type="text" id="fname" name="fname">  ` `<label for="lname">Last name:</label>` `<input type="text" id="lname" name="lname">  ` `<input type="submit" value="Submit">` `</fieldset>` `</form>` Copied!

<figcaption>	Used in conjunction with the <figure> tag to mark up an image.	1 2 3 4 5
		`<figure>`
		`<img src="durham.jpg">`
		`<figcaption>Fig.1 - Durham, NC</figcaption>`
		`</figure>`
		
		Copied!

<figure>	Used to mark up an image in conjunction with the <figcaption> tag.	1 2 3 4 5
		`<figure>`
		`<img src="durham.jpg">`
		`<figcaption>Fig.1 - Durham, NC</figcaption>`
		`</figure>`
		
		Copied!

<footer>	Contains a footer of a document and often contains information such as authoring, copyright info, contact info, sitemap, and related documents.	1 2 3 4
		`<footer>`
		`<p>Author: Christopher Moore</p>`
		`</footer>`
		`<form action="/script.php">`
		Copied!

<form>	Creates an HTML form for user input.	1 2 3 4 5 6 7 8 9 10 `<form action="/script.php">` `<fieldset>` `<legend>User:</legend>` `<label for= "fname">First name:</label>` `<input type="text" id="fname" name="fname">  ` `<label for= "lname">Last name:</label>` `<input type="text" id="lname" name="lname">  ` `<input type="submit" value="Submit">` `</fieldset>` `</form>` Copied!
<h1>	Adds a level 1 heading to the HTML document.	`<h1>Thomas J. Watson</h1>`

<head>	Contains metadata and should be placed after the <html> tag and before the <body> tag.	1
		2
		3
		4
		5
		6
		7
		8
		9
		
		`<!DOCTYPE html>`
		`<html>`
		`<head>`
		`<title>Document Title</title>`
		`</head>`
		`<body>`
		Document body here
		`</body>`
		`</html>`
		
		Copied!

<header>	A container for introductory content such as heading elements, logo, or authoring information.	1
		2
		3
		4
		5
		
		`<header>`
		`<h1>Header tag example</h1>`
		`<p>It works as a container for introductory content such as heading elements, logo, or authoring information.</`
		`<p>Author: Christopher Moore</p>`
		`</header>`
		
		Copied!

<html>	The root element of an HTML document. All other tags in the document should be contained in this tag.	1
		2
		3
		4
		5
		6
		7
		8
		9
		
		`<!DOCTYPE html>`
		`<html>`
		`<head>`
		`<title>Document Title</title>`
		`</head>`
		`<body>`
		Document body here
		`</body>`
		`</html>`
		
		Copied!

<img src="path" width="dim1" height="dim2">	This tag is used to place an img. In place of path insert a URL or a relative file path to the image location. Other optional attributes include width	1
		2
		3
		4
		
		`<img`
		`src="https://upload.wikimedia.org/wikipedia/commons/7/7e/Thomas_J_Watson_Sr.jpg"`
		`width="300"`
		`height="300">`
		
		Copied!

	and height of the image in pixels.	
<input type="?">	Specifies an input field on a form with the type attribute. Common input types include: "color," "date," "datetime-local," "email," "number," "range," "search," "url," "tel," "datalist," "select," "text," "option," and "placeholder."	1. 1 2. 2 3. 3 4. 4 5. 5 6. 6 7. 7 8. 8 9. 9 10. 10 1. <form action="/script.php"> 2. <fieldset> 3. <legend>User:</legend> 4. <label for="fname">First name:</label> 5. <input type="text" id="fname" name="fname"> 6. <label for="lname">Last name:</label> 7. <input type="text" id="lname" name="lname"> 8. <input type="submit" value="Submit">> 9. </fieldset> 10. </form> Copied!
<li>	Element that creates bulleted line items in an ordered or unordered list. Should be used in conjunction with the <ul> or <ol> tags.	1. 1 2. 2 3. 3 4. 4 5. 5 1. <ul> 2. <li>Bullet point 1</li> 3. <li>Bullet point 2</li> 4. </ul> 5. Copied!
<link>	Used to link a CSS document to an HTML document.	1. 1 2. 2 3. 3 4. 4 1. <head> 2. <link rel="stylesheet" href="styles.css"> 3. </head> 4. Copied!
<meta>	Used to provide metadata about the HTML document.	1. 1 2. 2 3. 3 4. 4 1. <head> 2. <meta name="author" content="Christopher Moore"> 3. </head> 4. Copied!
<nav>	Used to define a set of navigational elements.	1. 1 2. 2 3. 3 4. 4 5. 5 6. 6 1. <nav> 2. <a href="home.html">Home</a> 3. <a href="page1.html">Page 1</a> 4. <a href="page2.html">Page 2</a> 5. </nav> 6. Copied!
<ol>	Element that creates an ordered list using numbers. Should be used in conjunction with the <li> tag.	1. 1 2. 2 3. 3 4. 4 1. <ol> 2. <li>Numbered bullet point 1</li> 3. <li>Numbered bullet point 2</li> 4. </ol> Copied!

<p>

This tag is used to identify a paragraph. It places a line break after the text it is enclosed in.

```
1
2
3
4
```

```
<p>Thomas J. Watson, Sr. is the American
industrialist, who built the International Business
Machines Corporation (IBM) into the largest
manufacturer of electric typewriters and data processing equipment in the world. </p>
```

Copied!

<script>

Used to embed Javascript in an HTML document.

```
1
2
3
```

```
<script>
alert("Hello World");
</script>
```

Copied!

<section>

Defines an important section of a document. Can be used within headers and footers as well.

```
1
2
3
4
5
6
```

```
<section>
 <h2>Introduction</h2>
 <p>This document provides some examples of how to
 use a variety of HTML elements</p>
</section>

```

Copied!

<style>

Used to apply simple CSS to an HTML document.

```
1
2
3
4
5
6
7
8
9
```

```
<head>
<style>
p {color:red}
</style>
</head>
<body>
<p>This paragraph will be red because I've styled
the paragraph tag with CSS.</p>
</body>
```

Copied!

<table>

This tag is used to denote a table. Should be used with <tr> (defines a table row) and <td> (defines a table cell within a row) tags. The <th> tag can also be used to define the table header row.

```
1
2
3
4
5
6
7
8
9
10
11
12
13
```

```
<table>
<tr>
<th>Header cell 1</th>
<th>Header cell 2</th></tr>
<tr>
<td>First row first cell</td>
<td>First row second cell</td>
</tr>
<tr>
<td>Second row first cell</td>
<td>Second row second cell</td>
</tr>
</table>
```

Copied!

<td>

Denotes a cell within a row, within a table.

```
1
2
3
4
5
6
7
8
9
10
11
12
13
14
```

```
<table>
<tr>
```

```
<th>Header cell 1</th>
<th>Header cell 2</th>
</tr>
<tr>
<td>First row first cell</td>
<td>First row second cell</td>
</tr>
<tr>
<td>Second row first cell</td>
<td>Second row second cell</td>
</tr>
</table>
```

Copied!

<th>	Denotes the header cells within a row within a table.	1 2 3 4 5 6 7 8 9 10 11 12 13 14 <table> <tr> <th>Header cell 1</th> <th>Header cell 2</th> </tr> <tr> <td>First row first cell</td> <td>First row second cell</td> </tr> <tr> <td>Second row first cell</td> <td>Second row second cell</td> </tr> </table> Copied!
<title>	Defines the title of the HTML document displayed in the browser's title bar and tabs. It is required in all HTML documents. It should be contained in the <head> tag.	1 2 3 4 5 6 7 8 9 <!DOCTYPE html> <html> <head> <title>Document Title</title> </head> <body> Document body here </body> </html> Copied!
<tr>	Denotes a row within a table.	1 2 3 4 5 6 7 8 9 10 11 12 13 14 <table> <tr> <th>Header cell 1</th> <th>Header cell 2</th> </tr> <tr> <td>First row first cell</td> <td>First row second cell</td> </tr> <tr> <td>Second row first cell</td> <td>Second row second cell</td> </tr> </table> Copied!
<ul>	Element that creates an unordered list using	1 2 3 4 5

bullets. Should be used in conjunction with the <li> tag.

```
<ul>
<li>Bullet point 1</li>
<li>Bullet point 2</li>
</ul>
```

Copied!

Changelog

Date	Version	Changed by	Change Description
21-10-2022	1.0	Samaah	Initial version created
24-10-2022	1.1	Michelle Saltoun	Minor edits

© IBM Corporation 2022. All rights reserved.