Skills Network

Module 2 Cheatsheet: HTML5 Overview

Element	Description	Example
<!-- -->	This tag denotes a comment in HTML, which is not displayed by a browser but can be useful to hide and document code.	1 `<!-- This is a comment -->` Copied!

<!DOCTYPE html>	All HTML documents must start with this declaration. It tells the browser what document type to expect. Note that this element has no ending tag.	1
		2
		3
		4
		5
		6
		7
		8
		9
		`<!DOCTYPE html>`
		`<html>`
		`  <head>`
		`  <!-- Metadata Here -->`
		`  </head>`
		`  <body>`
		`  <!-- Document Body Here -->`
		`  </body>`
		`</html>`
		Copied!

<a href= "path" >link name</a>	This tag, called an "anchor tag" creates hyperlinks using the href attribute. In place of path enter the URL or path name to the page you want to link to.	1 `<a href="https://www.ibm.com">IBM</a>` Copied!

<body>	Contains the contents of the HTML document. It should contain all other tags besides the <head> element to display the body of the document.	1
		2
		3
		4
		5
		6
		7
		8
		9
		`<!DOCTYPE html>`
		`<html>`
		`  <head>`
		`  <!-- Metadata Here -->`
		`  </head>`
		`  <body>`
		`  <!-- Document Body Here -->`
		`  </body>`
		`</html>`
		Copied!

	Often used to separate sections in the body of a document in order to style that content with CSS.	1
		2
		3
		`<div>`
		`This element has no particular semantic meaning but is often used in conjunction with CSS for styling purpose`
		`</div>`
		Copied!

<h1>	Adds a level 1 heading to the HTML document.	1 `<h1>Thomas J. Watson</h1>` Copied!

<head>	Contains metadata and should be placed after the <html> tag and before the <body> tag.	1 2 3 4 5 6 7 8 9 1 <!DOCTYPE html> 2 <html> 3 <head> 4 <!-- Metadata Here --> 5 </head> 6 <body> 7 <!-- Document Body Here --> 8 </body> 9 </html> Copied!
<html>	The root element of an HTML document. All other tags in the document should be contained in this tag.	1 2 3 4 5 6 7 8 9 1 <!DOCTYPE html> 2 <html> 3 <head> 4 <!-- Metadata Here --> 5 </head> 6 <body> 7 <!-- Document Body Here --> 8 </body> 9 </html> Copied!
<img src= “path” width= “dim1” height= “dim2” >	This tag is used to place an img. In place of path insert a URL or a relative file path to the image location. Other optional attributes include width and height of the image in pixels.	1 1 <img src= “https://upload.wikimedia.org/wikipedia/commons/7/7e/Thomas_J_Watson_Sr.jpg” width= “300” height= “ Copied!
<li>	Element that creates bulleted line items in an ordered or unordered list. Should be used in conjunction with the <ul> or <ol> tags.	1 2 3 4 1 <ul> 2 <l1>Bullet point 1<l1> 3 <l1>Bullet point 2<l1> 4 </ul> Copied!
<link>	Used to link an external document, such as a CSS file, to an HTML document.	1 2 3 1 <head> 2 <link rel= “stylesheet” href= “styles.css” > 3 </head> Copied!
<meta>	Used to provide metadata about the HTML document.	1 2 3 1 <head> 2 <meta name= “author” content= “Christopher Moore” > 3 </head> Copied!
<ol>	Element that creates an ordered list	1 2 3 4

using numbers. Should be used in conjunction with the <li> tag.

```
<ol>
    <li>Numbered bullet point 1<li>
    <li>Numbered bullet point 2<li>
</ol>
```

Copied!

<p>

This tag is used to identify a paragraph. It places a line break after the text it is enclosed in.

```
1
```

```
<p>This is a paragraph of text. It can be as short or as long as needed.</p>
```

Copied!

<script>

Used to embed JavaScript in an HTML document.

```
1
2
3
```

```
<script>
    alert(“Hello World”);
</script>
```

Copied!

<table>

This tag is used to denote a table. Should be used with <tr> (defines a table row) and <td> (defines a table cell within a row) tags. The <th> tag can also be used to define the table header row.

```
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
```

```
<table>
  <tr>
    <th>Header cell 1</th>
    <th>Header cell 2</th>
  </tr>
  <tr>
    <td>First row first cell</td>
    <td>First row second cell</td>
  </tr>
  <tr>
    <td>Second row first cell</td>
    <td>Second row second cell</td>
  </tr>
</table>

</td>
```

Copied!

<td>

Denotes a cell within a row, within a table.

```
1
```

```
<td>Cell Content</td>
```

Copied!

<th>

Denotes the header cells within a row within a table.

```
1
2
3
4
5
6
7
8
9
10
11
12
13
14
```

```
<table>
  <tr>
    <th>Header cell 1</th>
    <th>Header cell 2</th>
  </tr>
  <tr>
    <td>First row first cell</td>
    <td>First row second cell</td>
  </tr>
  <tr>
    <td>Second row first cell</td>
    <td>Second row second cell</td>
  </tr>
</table>
```

Copied!

`<title>`	Defines the title of the HTML document displayed in the browser’s title bar and tabs. It is required in all HTML documents. It should be contained in the <head> tag.	1
		2
		3
		4
		5
		6
		7
		8
		9
		
		`<!DOCTYPE html>`
		`<html>`
		`  <head>`
		`  <title>Document Title</title>`
		`  </head>`
		`  <body>`
		`  <!-- Document Body Here -->`
		`  </body>`
		`</html>`
		
		Copied!

<tr>	Denotes a row within a table.	1
		2
		3
		4
		5
		6
		7
		8
		9
		10
		11
		12
		13
		14
		
		`<table>`
		`  <tr>`
		`  <th>Header cell 1</th>`
		`  <th>Header cell 2</th>`
		`  </tr>`
		`  <tr>`
		`  <td>First row first cell</td>`
		`  <td>First row second cell</td>`
		`  </tr>`
		`  <tr>`
		`  <td>Second row first cell</td>`
		`  <td>Second row second cell</td>`
		`  </tr>`
		`</table>`
		
		Copied!

<ul>	Element that creates an unordered list using bullets. Should be used in conjunction with the • tag.	1
		2
		3
		4
		
		`<ul>`
		`  <li>Bullet point 1<li>`
		`  <li>Bullet point 2<li>`
		`</ul>`
		
		Copied!

Changelog

Date	Version	Changed by	Change Description
18-10-2022	1.0	Michelle Saltoun	Initial version created
20-03-2023	1.1	Sneha R Baddi	Instructions Updated

© IBM Corporation 2022. All rights reserved.