



RS-1 Complete Dijkstra Algorithm 分数 6

作者 杨子祺 单位 浙江大学

Find the shortest path in a weighted graph. The function `dijkstra` implements the Dijkstra algorithm where given the source node `from` and the destination node `to`, it returns the shortest path between the two nodes.

```
#define SIZE 110
#define INF 99999

int map[SIZE][SIZE]; // The graph, initialized to be INF
int len[SIZE];
int visit[SIZE];
int n; // Number of vertices
int m; // Number of edges

int dijkstra(int from, int to){
    int i;
    for(i = 1; i <= n; i++){
        visit[i] = 0;
        len[i] = map[from][i];
    }
    int j;
    for(i = 1; i < n; ++i){
        int min = INF;
        int pos;
        for(j = 1; j <= n; ++j){
            if(!visit[j] && min > len[j]){
                pos = j;
                min = len[j];
            }
        }
        visit[pos] = 1;
        for(j = 1; j <= n; ++j){
            if(!visit[j] && len[pos] + map[pos][j] < len[j]){
                len[j] = len[pos] + map[pos][j];
            }
        }
    }
    return len[to];
}
```

< 上一题

□ 单题作答

下一题 >

```
for(j = 1; j <= n; ++j){
    if( len[pos] + map[pos][j] < len[j] ) {
        len[j] = len[pos] + map[pos][j];
    }
}
return len[to];
}
```

答案正确: 6 分

RS-2 Hash Table with Linear Probing 分数 6

作者 冯雁 单位 浙江大学

Find Key from a hash table H with linear probing. The function `Find` should return the position of the Key in hash table. If Key value is not in hash table, the function should return `-1`. (When testing, the values of elements of array `TheCells` in `Hashtbl` will be initialized to `-1`, which represents empty.)

```
int Hash(const int Key, int TableSize);
typedef int ElementType;
typedef unsigned int Position;

struct Hashtbl{
    int TableSize;
    ElementType *TheCells;
};
typedef struct Hashtbl *HashTable;

Position Find(ElementType Key, HashTable H){
    Position CurrentPos = Hash(Key, H->TableSize);
    while( H->TheCells[CurrentPos] != Key ) {
        if(H->TheCells[CurrentPos] == -1) return -1;
        CurrentPos++;
        if(CurrentPos >= H->TableSize) CurrentPos -= H->TableSize;
    }
    return CurrentPos;
}
```

答案正确: 6 分