```
- MODULE hashmap -
```

This module describes a hashmap to be used for testing with Shalev et al.'s split-ordered list implementation of the data structure

EXTENDS Integers, Bags

CONSTANTS NULL, PossibleKeys, PossibleValues

VARIABLES keys, Hashmap

Initial state has empty map and all possible values

$$\begin{array}{ll} Init \stackrel{\triangle}{=} & \wedge keys = EmptyBag \\ & \wedge Hashmap = [k \in PossibleKeys \mapsto NULL] \end{array}$$

Insert changes exactly one mapping of the hashmap

```
Insert \triangleq \exists k \in PossibleKeys: \\ \exists v \in PossibleValues: \\ \land keys' = \text{if } BagIn(k, keys) \text{ then } keys \text{ else } keys \oplus SetToBag(\{k\}) \\ \land Hashmap' = [Hashmap \text{ except } ![k] = v]
```

Remove sets exactly one mapping to the emtpy set

```
Remove \triangleq \exists k \in BagToSet(keys) :

\land keys' = keys \ominus SetToBag(\{k\})

\land Hashmap' = [Hashmap \ EXCEPT \ ![k] = NULL]
```

Next is either an insert or a remove

$$Next \triangleq \bigvee Insert \\ \lor Remove$$

TypeOK asserts all keys are of the right type

$$TypeOK \stackrel{\triangle}{=} \forall k \in BagToSet(keys) : \\ \land k \in PossibleKeys \\ \land Hashmap[k] \in PossibleValues$$

KeyUnique asserts there are no duplicate keys

```
KeyUnique \stackrel{\triangle}{=} \forall k \in BagToSet(keys) : CopiesIn(k, keys) = 1
```

KeyHasValue asserts that every key is mapped to a value

```
KeyHasValue \stackrel{\triangle}{=} \forall k \in BagToSet(keys) : \neg(Hashmap[k] = NULL)
```

- \* Last modified Sat Mar 07 16:11:23 CET 2020 by agissiag
- \\* Created Sat Mar 07 15:14:36 CET 2020 by a qissiaq