Tugas Mobile Week 7
Gesture Apps

R.Iqbal Maulana Ibrahim

```
You, 30 seconds ago | 2 authors (Aqshal Nur Ikhsan and one other)
import 'package:flutter/material.dart';
import 'home_page.dart';

Run | Debug | Profile
void main() {
  runApp(GestureApp());
}

You, 30 seconds ago | 2 authors (Aqshal Nur Ikhsan and one other)
class GestureApp extends StatelessWidget {    Constructors for public widgets should have a named 'key' p
  @override
  Widget build(BuildContext context) {
    return MaterialApp(
      title: 'Gesture Lab',
      debugShowCheckedModeBanner: true,
      // theme: ThemeData(useMaterial3: true, colorSchemeSeed: const Color.fromARGB(255, 178, 44, 44)),
      home: HomePage(),
    ); // MaterialApp
  }
}
```

main.dart

File Tersebut adalah main.dart yang fungsinya hanyalah pendefinisian awal ketika flutter di run

```
body: Padding(
  padding: EdgeInsets.all(16),
  child: GridView.builder(
    itemCount: menus.length,
    gridDelegate: SliverGridDelegateWithFixedCrossAxisCount(
      crossAxisCount: 2,
      crossAxisSpacing: 16,
      mainAxisSpacing: 106,
    ), // SliverGridDelegateWithFixedCrossAxisCount
    itemBuilder: (_, i) {
      return GestureDetector(
        onTap: () {
          Navigator.push(
            context,
            MaterialPageRoute(builder: (_) => menus[i]["page"] as Widget),
          );
        },
        child: AnimatedContainer(
          duration: Duration(milliseconds: 300),
          decoration: BoxDecoration(
            borderRadius: BorderRadius.circular(20),
            gradient: LinearGradient(
```

home_page.dart

File ini adalah file yang di panggil pada file main.dart seblumnya, file ini bertugas untuk mengatur isi content

```dart
class _TapPageState extends State<TapPage> {
  double size = 150;
  Color color = Colors.blue;

  void randomize() {
    setState(() {
      size = size == 150 ? 220 : 150;
      color = color == Colors.blue ? Colors.red : Colors.blue;
    });
  }

  @override
  Widget build(BuildContext context) {
    return Scaffold(
      appBar: AppBar(title: Text("Tap Interaction")),
      body: Center(
        child: GestureDetector(
          onTap: randomize,
          onDoubleTap: () => setState(() => color = Colors.green),
          onLongPress: () => setState(() => size = 250),
          child: AnimatedContainer(
            duration: Duration(milliseconds: 300),
            width: size,
            height: size,
            decoration: BoxDecoration(
              color: color,
              borderRadius: BorderRadius.circular(30),
```

Aqshal Nur Ikhsan, 4 days ago • Initial commit

tap_page.dart

File ini adalah file yang di panggil pada file home_page seblumnya, file ini bertugas untuk mengatur logika tentang gesture tap

```dart
class _TapPageState extends State<TapPage> {
  double size = 150;
  Color color = Colors.blue;

  void randomize() {
    setState(() {
      size = size == 150 ? 220 : 150;
      color = color == Colors.blue ? Colors.red : Colors.blue;
    });
  }

  @override
  Widget build(BuildContext context) {
    return Scaffold(
      appBar: AppBar(title: Text("Tap Interaction")),
      body: Center(        Aqshal Nur Ikhsan, 4 days ago • Initial commit
        child: GestureDetector(
          onTap: randomize,
          onDoubleTap: () => setState(() => color = Colors.green),
          onLongPress: () => setState(() => size = 250),
          child: AnimatedContainer(
            duration: Duration(milliseconds: 300),
            width: size,
            height: size,
            decoration: BoxDecoration(
              color: color,
              borderRadius: BorderRadius.circular(30),
```

drag_page.dart

File ini adalah file yang di panggil pada file home_page seblumnya, file ini bertugas untuk mengatur logika tentang gesture drag

```dart
class _TapPageState extends State<TapPage> {
  double size = 150;
  Color color = Colors.blue;

  void randomize() {
    setState(() {
      size = size == 150 ? 220 : 150;
      color = color == Colors.blue ? Colors.red : Colors.blue;
    });
  }

  @override
  Widget build(BuildContext context) {
    return Scaffold(
      appBar: AppBar(title: Text("Tap Interaction")),
      body: Center(        Aqshal Nur Ikhsan, 4 days ago • Initial commit
        child: GestureDetector(
          onTap: randomize,
          onDoubleTap: () => setState(() => color = Colors.green),
          onLongPress: () => setState(() => size = 250),
          child: AnimatedContainer(
            duration: Duration(milliseconds: 300),
            width: size,
            height: size,
            decoration: BoxDecoration(
              color: color,
              borderRadius: BorderRadius.circular(30),
```

scale_page.dart

File ini adalah file yang di panggil pada file home_page seblumnya, file ini bertugas untuk mengatur logika tentang gesture scale

```dart
class _TapPageState extends State<TapPage> {
  double size = 150;
  Color color = Colors.blue;

  void randomize() {
    setState(() {
      size = size == 150 ? 220 : 150;
      color = color == Colors.blue ? Colors.red : Colors.blue;
    });
  }

  @override
  Widget build(BuildContext context) {
    return Scaffold(
      appBar: AppBar(title: Text("Tap Interaction")),
      body: Center(
        child: GestureDetector(
          onTap: randomize,
          onDoubleTap: () => setState(() => color = Colors.green),
          onLongPress: () => setState(() => size = 250),
          child: AnimatedContainer(
            duration: Duration(milliseconds: 300),
            width: size,
            height: size,
            decoration: BoxDecoration(
              color: color,
              borderRadius: BorderRadius.circular(30),
```

Aqshal Nur Ikhsan, 4 days ago • Initial commit

playground_page.dart

File ini adalah file yang di panggil pada file home_page seblumnya, file ini bertugas untuk mengatur logika tentang gesture playground

Terima Kasih
dan Sampai Jumpa