

dbhydroR: An R package to access the DBHYDRO Environmental Database

Joseph Stachelek

June 16, 2016

1 Introduction

This document introduces the `dbhydroR` package and its associated functions. These functions are aimed at improving programmatic workflows that query the DBHYDRO Environmental Database. HTTP requests are facilitated by the `httr` (Wickham 2015) package.

2 Package installation

The R package `dbhydroR` is distributed via a `.tar.gz` (analagous to `.zip`) package archive file. This package contains the source code for package functions. In RStudio, it can be installed by navigating to **Tools -> Install Packages... -> Install from: -> Package Archive File**. Computers running the Windows operating system can only install binary `.zip` package archive files unless they have additional `compiler software` installed. The `dbhydroR` binary package can be installed by running the following commands from the R console:

```
install.packages(c("httr", "RCurl", "reshape2", "XML"))
install.packages(paste("\\\\ad.sfwmd.gov\\DFSRoot\\data\\restoration_sciences",
"\\projects\\joe_stachelek\\R\\dbhydroR_0.1-6.zip", sep = ""))
, type = "win.binary", repos = NULL)
```

Once installed, the package can be loaded using the following command:

```
library(dbhydroR)
```

3 Composing database queries

3.1 Water quality data

Water quality data can be retrieved using the `getwq` function which takes four required arguments. The user must specify a station ID, a test name, and a date range. Station IDs can be located on the [SFWMD Google Earth portal](#). An abbreviated list of available test names can be found in the [Appendix](#) to this document while a full listing can be found at the [DBHYDRO metadata page](#). Dates must be specified in YYYY-MM-DD format (e.g. 2015-02-26). The following set of examples retrieve measurements between March 2011 and May 2012. They can be run from the R console by issuing the command:

```
example(getwq)
```

- One variable at one station

```
getwq(station_id = "FLAB08", date_min = "2011-03-01",  
      date_max = "2012-05-01", test_name = "CHLOROPHYLLA-SALINE")
```

- One variable at multiple stations

```
getwq(station_id = c("FLAB08","FLAB09"), date_min = "2011-03-01",  
      date_max = "2012-05-01", test_name = "CHLOROPHYLLA-SALINE")
```

- One variable at a wildcard station

```
getwq(station_id = c("FLAB0%"), date_min = "2011-03-01",  
      date_max = "2012-05-01", test_name = "CHLOROPHYLLA-SALINE")
```

- Multiple variables at multiple stations

```
getwq(station_id = c("FLAB08","FLAB09"), date_min = "2011-03-01",  
      date_max = "2012-05-01", test_name = c("CHLOROPHYLLA-SALINE",  
      "SALINITY"))
```

By default, `getwq` returns a *cleaned output*. First, the cleaning function `cleanwq` converts the raw output from native DBHYDRO *long* format (each piece of data on its own row) to *wide* format (each site x variable combination in its own column) using the `reshape2` package ([Wickham 2007](#)). Next, the extra columns associated with QA flags, LIMS, and District receiving are removed. Finally, row entries associated with QA *blanks* are removed. Setting the `raw` flag to `TRUE` will force `getwq` to retain this information. An example query that retains this information and the original *long* formatting is shown below.

```
getwq(station_id = "FLAB08", date_min = "2011-03-01",
      date_max = "2011-05-01", test_name = "CHLOROPHYLLA-SALINE",
      raw = TRUE)
```

3.2 Hydrologic data

Hydrologic time series data can be retrieved using the `gethydro` function. The first task to accomplish prior to running `gethydro` is to identify one or more dbkeys. This can be done before-hand using the `getdbkey` function or the [DBHYDRO Browser](#). One useful strategy for finding desired dbkeys is to run the `getdbkey` function interactively using progressively narrower search terms. For example, suppose we are interested in daily average wind data at Joe Bay but we have no alphanumeric dbkey. Initially we could run `getdbkey` with the `detail.level` set to "summary".

```
getdbkey(stationid = "JBTS", category = "WEATHER", param = "WNDS",
      detail.level = "summary")
```

Our search returns two results but only one of them has a daily average (DA) measurement frequency. We can verify the remaining attributes of our likely dbkey by setting the `freq` parameter to "DA" and the `detail.level` parameter to "full".

```
getdbkey(stationid = "JBTS", category = "WEATHER", param = "WNDS",
      freq = "DA", detail.level = "full")
```

This exact dbkey can only be returned reliably by specifying all of the `getdbkey` parameters applicable to the "WEATHER" category.

```
getdbkey(stationid = "JBTS", category = "WEATHER", param = "WNDS",
      freq = "DA", stat = "MEAN", recorder = "CR10", agency = "WMD",
      detail.level = "dbkey")
```

Now that we have our dbkey in hand, we can use it as input to `gethydro`. In addition to a dbkey, we must specify a date range. Dates must be entered in YYYY-MM-DD format (e.g. 2015-02-26).

```
gethydro(dbkey = "15081",
      date_min = "2013-01-01", date_max = "2013-02-02")
```

Alternatively, we can specify a set of arguments in our call to `gethydro` that will be passed to `getdbkey` on-the-fly. Use caution when using this strategy as complex stationid/category/parameter combinations can easily cause errors or return unexpected results. It is good practice to pre-screen your parameter values using `getdbkey`.

```
gethydro(date_min = "2013-01-01", date_max = "2013-02-02",  
         stationid = "JBTS", category = "WEATHER", param = "WNDS",  
         freq = "DA", stat = "MEAN", recorder = "CR10", agency = "WMD")
```

The contents of multiple data streams can be returned by specifying multiple dbkeys or entering on-the-fly getdbkey queries that return multiple dbkeys.

```
gethydro(dbkey = c("15081", "15069"), date_min = "2013-01-01",  
         date_max = "2013-02-02")
```

```
gethydro(date_min = "2013-01-01", date_max = "2013-02-02",  
         category = "WEATHER", stationid = c("JBTS", "MBTS"),  
         param = "WNDS", freq = "DA", stat = "MEAN")
```

More `gethydro` examples including queries of other `category` values ("SW", "GW", and "WQ") can be viewed by issuing the following commands from the R console:

```
example(getdbkey)  
example(gethydro)
```

4 Appendix

4.1 Test names

There are many test names available in DBHYDRO. A subset of these are detailed in the following table.

Code
AMMONIA-N
CARBON, TOTAL ORGANIC
CHLOROPHYLL-A(LC)
CHLOROPHYLL-B(LC)
CHLOROPHYLLA-SALINE
DISSOLVED OXYGEN
KJELDAHL NITROGEN,TOTAL
NITRATE+NITRITE-N
NITRITE-N
PHEOPHYTIN-A(LC)
PHOSPHATE,ORTHO AS P
PHOSPHATE,TOTAL AS P
SALINITY
SILICA
SP CONDUCTIVITY, FIELD
TEMP
TOTAL NITROGEN
TURBIDITY

4.2 Further reading

See section on URL-based data access in the [DBHYDRO Browser User's Guide](#)

References

Hadley Wickham. Reshaping data with the reshape package. *Journal of Statistical Software*, 21(12):1–20, 2007. URL <http://www.jstatsoft.org/v21/i12/>.

Hadley Wickham. *httr: Tools for Working with URLs and HTTP*, 2015. URL <http://CRAN.R-project.org/package=httr>. R package version 0.6.1.