

TECHNICAL DATASHEET

VE-AWG-6000

Industrial Atmospheric Water Generator

A location-engineered system that converts

ambient moisture into treated water through integrated air handling, condensation, water treatment, storage, control, and delivery.

UP TO 6,000 L/DAY

Nominal target at the agreed project design point.



PRODUCTION TARGET

Up to 6,000 L/day

SYSTEM ARCHITECTURE

4 modular sections

EQUIPMENT ENVELOPE

3000 x 1500 x 1800 mm

INTEGRATED PROCESS ARCHITECTURE

01

AIR INTAKE

High-volume intake and pre-filtration

02

CONDENSATION

Four modular moisture-recovery sections

03

WATER TREATMENT

Multi-stage filtration, UV and mineralization

04

STORAGE + DELIVERY

Raw/treated storage and outlet pumping

DESIGN INTENT

Commercial, industrial, agricultural, infrastructure, remote-site and emergency water applications.

Made for location: final performance and configuration are engineered against site climate, utilities, water-quality target and duty profile.

01 / CORE SYSTEM

Product configuration

Model	VE-AWG-6000
System type	Industrial atmospheric water generator
Nominal production target	Up to 6,000 L/day at the agreed project design point
Moisture-recovery system	Four modular condensation sections
Air-side configuration	Large X-frame intake with integrated air filtration
Overall dimensions (L x W x H)	3000 x 1500 x 1800 mm
Installation environment	Outdoor or semi-outdoor; final weather protection subject to project specification

02 / WATER + CONTROLS

Treatment, monitoring and delivery

Water-treatment train	Sediment, activated carbon, UV sterilization, mineralization and polishing filtration
Water storage	Integrated raw-water and treated-water storage architecture
Water delivery	Outlet pump / pressure-delivery system
Local controls	Industrial HMI touchscreen with system status, alarms and diagnostics
Monitored parameters	Production status, tank level, alerts, diagnostics and configured water-quality indicators
Connectivity	IoT-ready for remote monitoring and predictive-maintenance integration

SITE INTERFACES

Electrical supply	Three-phase industrial supply
Voltage / frequency	Project-specific
Drainage	Service and overflow drainage required
Clearance	Maintain intake, discharge and service access

ENGINEERING STATUS

Rated input power	To be confirmed after site design review
Operating envelope	To be defined for project climate
Dry / operating weight	To be confirmed at final design
Sound level / IP rating	To be confirmed at final design

IMPORTANT ENGINEERING NOTES

- Water output varies with ambient temperature, relative humidity, altitude, air quality and operating schedule.
- Final electrical load, component selection and production guarantee require a project-specific design point and site survey.
- Potability depends on treatment configuration, commissioning, maintenance and verification against applicable local standards.
- Specifications are preliminary and may change as engineering, compliance and supplier selections are finalized.