
Emergent Cognition Under 64-Bit Constraints


The DCSI Multi-Module Cognitive Swarm Architecture




```
SYSTEM ENVELOPE
Max Node Memory: 64 Bytes
Max Comm: 64 Bits/Cycle
Global State: ZERO
```

NotebookLM

Traditional Hash Consensus



Distributed Semantic Field Dynamics




Strict cryptographic hash equivalence is blind to latent semantic drift. Distributed cognition requires continuous geometric alignment.

NotebookLM

Memory Constraint:
64 Bytes Total
(Split into Core A/B/C layers)

Bandwidth Constraint:
Exactly 64 bits per cycle
(1 packet emitted, max 8 received)



Energy Budget:
≤ 1 unit per cycle
(failure if exceeded)

State Space:
Fixed 23 dimensions per node
(minimal defensible state)


Arithmetic:
Only add/sub, fixed-point scalar, bitwise XOR, circular-convolution

Constraints are not aesthetic; they are the pressure cooker that forces swarm emergence over local computation.


NotebookLM

From Biological Primitive to Silicon Architecture

Biology



Silicon




NotebookLM

INTRA-NODE DETERMINISTIC MICRO-CYCLE

$$A(t+1) = 0.92 \cdot A(t) + 0.08 \cdot \mathrm{clip}(B_{\mathrm{error}} + C_{\mathrm{gate}}, -1, 1)$$

$$B(t+1) = \tanh\left(\mathrm{mean}(A) + \sum_{hj}^{m} h_j\right), \quad E = \|\hat{s} - s\|_1$$



$$C(t+1) = \mathrm{kWTA}_3(\lambda E + \mu \mathrm{salience} + \nu \mathrm{atp})$$

The node forms a closed-loop internal attractor. Identity stabilization drives **prediction**, which drives **regulation**, which scales communication.

NotebookLM

The 64-Bit Digital Vesicle

Bits 0–15:
Anomaly Signature
(16-bit compressed slice)

Bits 16–27:
Location Bucket
(12-bit Morton code)

Bits 28–35:
Salience
(8-bit localized importance)

Bits 36–43:
Confidence
(8-bit prediction confidence)

Bits 44–51:
Checksum
(8-bit CRC)


Bits 52–63:
Reserved
(12-bit)



Biological Translation


Bits: 00, 01, 11 → A → 10, 10 → 11 → U RNA Letters


RNA Mapping Rule: 00→A, 01→C, 10→G, 11→U = 32-nt RNA Payload



NotebookLM

The HTLA Binding Operator





Superposition Mechanism: Bitwise majority vote applied to max 8 incoming packets gracefully handles collision and noise without shared memory.

NotebookLM


Distributed Semantic Field Dynamics

Kuramoto Coupling Equation:

$$\frac{d}{dt}\mathrm{SCF}_i(t) = V_{\theta_i}(\mathrm{SCF}_i(t)) + \frac{K}{N}\sum_{ij} A_{ij}\Gamma(\mathrm{SCF}_i, \mathrm{SCF}_j)$$

Riemannian Center of Mass:

$$\mathrm{SCF}_{\mathrm{global}}(t) = \arg\min_S \sum_S w_i d^2_{\mathrm{HTLA}}(S, \mathrm{SCF}_i(t))$$



Semantic Momentum Diffusion: Momentum propagates rapidly across highly salient conceptual labels and dissipates across noise, akin to anisotropic heat diffusion.

NotebookLM


Cognitive Topology Architectures

Architecture	Viz	Stability	Latency	Semantic Coherence Risk
Full Mesh		High	Low	Low (Thermodynamically impossible at scale)
Leader-Follower		Moderate	Very Low	High (Deterministic tracking risk)
Sharded Zones		Variable	High	Medium (Boundary fracture risk)
Hierarchical Clusters		High	Variable	Medium (Phase lag vulnerability)
Federated Low-Trust		Variable	High	High (Gradient boundaries)

Conclusion: The architecture forces a fluid, emergent small-world topology based on preferential attachment to high-salience nodes.

NotebookLM


Zero-Knowledge Federated Trust



Replaces continuous raw payload sharing with probabilistic verification, ensuring adaptive semantic alignment while preserving partial state exposure limits.

NotebookLM

Thermodynamics & Phase Transitions



$$E_{cog} = \lambda_1 U + \lambda_2 C + \lambda_3 \dot{\Sigma} - \lambda_4 \kappa_{align}$$

$$T_i(t) = T_{base} \cdot e^{-\lambda t} + \gamma \int \rho dt - \beta \, \text{Penalty}$$


The Intervention

When energy dissipation approaches the Landauer limit, the swarm triggers Lyapunov stability controls: it aggressively scales up internal sparsity, forcing the system back into the asin at the cost of temporary processing depth.


NotebookLM

Resilience by Design: Surviving 30% Necrosis


T0: Steady State



T_{Lesion}: 30% Deletion



$T_{Recovery}$: Stabilization



The swarm does not compute recovery; recovery emerges from local nodes reacting to suddenlly empty space and high error margins.
$\lambda_{recover}$ = rewire boundary nodes + redistribute h_i via random walk + increase α

NotebookLM

Formulating the Phi-Proxy (System Coherence)

Algebraic connectivity (spectral gap) showing graph resilience.

The hypervector recoverability index (HRI).

$$\Phi_{\text{proxy}} = \frac{\lambda_2(G) \cdot \text{mean recoverability}}{\text{entropy of salience distribution}}$$

Measures meaningful gradients versus flat background noise.

Target Metric: System survival is rigorously defined as $\Phi_{\text{iproxy}} > 0.5$ post-lesion recovery (within 120 cycles).

NotebookLM

The Multi-Scale Consensus Stack



Macro: Swarm-Level Consensus

Global Riemannian Center of Mass stabilizing 10,000 nodes

Meso: Local Neighborhood Consensus

HTLA Superposition voting on shared anomaly states

Micro: Intra-Node Consensus

Identity aligning with prediction (Core A <-> Core B <-> Core C)

The exact feedback loops stabilizing the 64-byte node are the identical mathematical mechanics stabilizing the 10,000-node global swarm.

NotebookLM

Simulation Architecture Blueprint

The Execution Stack

- Paradigm: Hybrid agent-based + graph-dynamical
- Scale: N=10,000 nodes, simulated at ~40 Hz
- Hardware: Single RTX 4090
- Stack: Python 3.12 + Numba + NetworkX + h5py

The Litmus Test: Minimal viable subsystem is a 3-node triangle. Removing one node must collapse the organism.

Phase 1 Readiness

Component	Status
Tri-cell node	90% Implemented
64-bit HTLA	95% Implemented
Lesion + Lyapunov	85% Implemented
Executable Sim	100% Implemented

All hand-waves eliminated. This specification is immediately compilable into a working simulator. The swarm lives.

NotebookLM