Cognitive Regime Class	Primary Functional Role	Sensory Anchor (Inferred)	Associative Radius (Inferred)	Critical Scrutiny (Inferred)	Active Candidate Budget	Subsystem Mechanics	Source
Critical / Analytic	Rigorous deduction, verification, contradiction testing, and code execution. High-precision evaluation of candidates and constitutional/admissibility enforcement.	0.80 - 0.95	0.10 - 0.20	0.95	0.20 (Dense selection); strictly limited (likely < 30%)	HTLA exact-inverse checks and epistemic discipline; HIGC strict invariant gating and contradiction detection (IMPOSSIBLE status); narrow beam search in HTCE; high provenance sensitivity via Cyrae.	1, 2, 3, 4
Creative / Divergent	Hypothesis generation, artistic synthesis, and out-of-distribution discovery. Expansion of search geometry to explore hypothetical or unlikely candidate states and semantic search.	0.30 - 0.40	0.80 - 0.90	0.20 - 0.30	0.60 (Broad selection); expanded (approaching or exceeding 30%)	High softmax temperature and recursive-field semantics in HTCE; exploratory candidate branching in ephemeral HVDs; weaker prior filtering; exploration-biased modulation vector.	1, 2, 3, 4

Abstract / Structural	Higher-order relational reasoning, cross-domain mapping, category theory, and structural analogy extraction.	0.30 - 0.50	0.40 - 0.70	0.60 - 0.70	0.30 (Moderate selection)	Block-diagonal projection in HTLA; relational distance comparison across label direct sums; utilizes THDE temporal-evolution semantics and HTCE active-field mechanisms; focused on HTLA/HTNLA transforms.	1, 2, 3
Daydream / Wandering	Spontaneous internal generation, memory linking, associative indexing, and episodic recombination with reduced external sensory coupling.	0.10 - 0.20	0.60 - 0.80	0.20 - 0.40	0.40 (Fluid selection); high internal population	Internal prediction loop driven by latent noise; low-salience candidate traversal across TMS engrams; utilizes HTCE for episodic recombination; historical Perturbed State Engine ancestry.	1, 2, 3

Offline Dream-Like	Memory consolidation, counterfactual reorganization, attractor cleanup, and synaptic homeostasis renormalization.	0.00	0.50 - 0.90	0.10 - 0.50	0.30 (Fixed budget); maximum (unconstrained by sensory input)	Sensory inputs fully severed/attenuated (Hobson-Hong-Friston); generative replay from TMS episodic trace log; Synaptic Homeostasis (SHY) renormalization via Cyrae; HVD/HDF5 memory refinery.	1, 2, 3