



2026. "Año del Humanismo Mexicano en el Estado de México"

Tecnológico de estudios Superiores de Villa Guerrero.

Ingeniería en Sistemas Computacionales

UNIDAD DE APRENDIZAJE:

SISTEMAS OPERATIVOS

PRÁCTICA:

PRACTICA 3. Explorando el Hardware de tu Sistema con lspci

PRESENTA:

GARCIA ALBARRAN ARACELI ADRIANA

GRUPO:

3501

DOCENTE:

ISC. REYNOSO ELIAS JUAN

LA FINCA, VILLA GUERRERO, ESTADO DE MÉXICO.

OCTUBRE DE 2026





2026. "Año del Humanismo Mexicano en el Estado de México"

INDICE

INDICE.....	2
INDICE IMÁGENES	3
INTRODUCCION.....	4
OBJETIVO	4
REQUISITOS	4
DESARROLLO.....	5
Paso 1: Ver que hay en tu sistema.....	5
Comando utilizado: lspci.....	5
Paso 2: La lista básica es útil, pero a menudo se requiere saber qué controlador (módulo del kernel) está usando un dispositivo.	6
Comando utilizado: lspci -v.....	6
PREGUNTAS.....	8
Pregunta 1:	9
Pregunta 2:	9
CONCLUSION	10





2026. "Año del Humanismo Mexicano en el Estado de México"

INDICE IMÁGENES

Ilustración 1 comando lspci.....	5
Ilustración 2 comando lspci -v	6
Ilustración 3 tarjeta de red	9
Ilustración 4 tarjeta grafica.....	9





2026. "Año del Humanismo Mexicano en el Estado de México"

INTRODUCCION

En esta práctica trabajamos con el comando `lspci` en un sistema Linux, con el propósito de conocer e identificar los diferentes dispositivos de hardware que se encuentran conectados al equipo mediante el bus PCI. Esto nos permite observar qué componentes son reconocidos por el sistema y obtener información relacionada con ellos.

Durante la práctica utilizamos primero el comando `lspci` para visualizar de manera general los dispositivos detectados. Después empleamos `lspci -v` para obtener información más detallada y poder identificar el controlador o módulo del kernel que utiliza cada dispositivo. De esta manera, pudimos analizar específicamente la tarjeta de red Wi-Fi y la tarjeta gráfica de nuestro equipo.

Con esta práctica buscamos familiarizarnos con las herramientas que proporciona Linux para consultar información del hardware desde la terminal y comprender mejor la relación entre los dispositivos físicos del equipo y los controladores que permiten su funcionamiento.

OBJETIVO

Familiarizarse con el comando `lspci` para identificar y entender los dispositivos de hardware (periféricos) conectados a tu sistema a través del bus PCI (Peripheral Component Interconnect).

REQUISITOS

- Un sistema Linux con acceso a la terminal.
- Acceso a terminal
- Usuario estándar o root





2026. "Año del Humanismo Mexicano en el Estado de México"

DESARROLLO

Para realizar esta práctica trabajamos con el comando `lspci` en un sistema Linux, con el propósito de identificar los diferentes dispositivos de hardware que se encuentran conectados al sistema mediante el bus PCI. Con esto pudimos conocer una parte de los componentes que reconoce el sistema operativo y obtener información más detallada sobre ellos.

Paso 1: Ver que hay en tu sistema.

Ejecutar el comando `lspci` sin opciones y observar los resultados.

Primero, ejecutamos el comando `lspci` sin agregar ninguna opción. Al utilizarlo, se muestra una lista de los dispositivos que el sistema reconoce a través del bus PCI. Esta primera consulta nos permitió observar de manera general qué dispositivos de hardware se encuentran presentes en el equipo.

Comando utilizado: `lspci`

Ilustración 1 comando `lspci`

```
user@debian:~$ lspci
00:00.0 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Root Complex
00:00.2 IOMMU: Advanced Micro Devices, Inc. [AMD] Phoenix IOMMU
00:01.0 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Dummy Host Bridge
00:01.2 PCI bridge: Advanced Micro Devices, Inc. [AMD] Phoenix GPP Bridge
00:02.0 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Dummy Host Bridge
00:02.2 PCI bridge: Advanced Micro Devices, Inc. [AMD] Phoenix GPP Bridge
00:02.4 PCI bridge: Advanced Micro Devices, Inc. [AMD] Phoenix GPP Bridge
00:03.0 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Dummy Host Bridge
00:04.0 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Dummy Host Bridge
00:08.0 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Dummy Host Bridge
00:08.1 PCI bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Internal GPP Bridge to Bus [C:A]
00:08.2 PCI bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Internal GPP Bridge to Bus [C:A]
00:08.3 PCI bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Internal GPP Bridge to Bus [C:A]
00:14.0 SMBus: Advanced Micro Devices, Inc. [AMD] FCH SMBus Controller (rev 71)
00:14.3 ISA bridge: Advanced Micro Devices, Inc. [AMD] FCH LPC Bridge (rev 51)
00:18.0 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Data Fabric; Function 0
00:18.1 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Data Fabric; Function 1
00:18.2 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Data Fabric; Function 2
00:18.3 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Data Fabric; Function 3
00:18.4 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Data Fabric; Function 4
00:18.5 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Data Fabric; Function 5
00:18.6 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Data Fabric; Function 6
00:18.7 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Data Fabric; Function 7
01:00.0 Non-Volatile memory controller: MAXIO Technology (Hangzhou) Ltd. NVMe SSD Controller MAP1202 (DRAM-less) (rev 01)
02:00.0 Network controller: Realtek Semiconductor Co., Ltd. RTL8852BE PCIe 802.11ax Wireless Network Controller
03:00.0 Non-Volatile memory controller: MAXIO Technology (Hangzhou) Ltd. NVMe SSD Controller MAP1202 (DRAM-less) (rev 01)
04:00.0 VGA compatible controller: Advanced Micro Devices, Inc. [AMD/ATI] Phoenix1 (rev c2)
04:00.1 Audio device: Advanced Micro Devices, Inc. [AMD/ATI] Radeon High Definition Audio Controller [Rembrandt/Strix]
04:00.2 Encryption controller: Advanced Micro Devices, Inc. [AMD] Phoenix CCP/PSP 3.0 Device
04:00.3 USB controller: Advanced Micro Devices, Inc. [AMD] Device 15b9
04:00.4 USB controller: Advanced Micro Devices, Inc. [AMD] Device 15ba
04:00.6 Audio device: Advanced Micro Devices, Inc. [AMD] Family 17h/19h/1ah HD Audio Controller
05:00.0 Non-Essential Instrumentation [1300]: Advanced Micro Devices, Inc. [AMD] Phoenix Dummy Function
05:00.1 Signal processing controller: Advanced Micro Devices, Inc. [AMD] AMD IPU Device
06:00.0 Non-Essential Instrumentation [1300]: Advanced Micro Devices, Inc. [AMD] Phoenix Dummy Function
06:00.3 USB controller: Advanced Micro Devices, Inc. [AMD] Device 15c0
06:00.4 USB controller: Advanced Micro Devices, Inc. [AMD] Device 15c1
user@debian:~$
```



2026. "Año del Humanismo Mexicano en el Estado de México"

Paso 2: La lista básica es útil, pero a menudo se requiere saber qué controlador (módulo del kernel) está usando un dispositivo.

Ejecutar el comando `lspci -v` y observar los resultados.

Después, utilizamos el comando `lspci -v`. Esta opción permite obtener información más detallada de los dispositivos que aparecen en la lista. Al revisar los resultados, pudimos encontrar información adicional, incluyendo el controlador o módulo del kernel que está utilizando cada dispositivo.

Comando utilizado: `lspci -v`

Con esta información fue posible localizar específicamente los dispositivos relacionados con la conexión inalámbrica y con los gráficos del equipo, para posteriormente identificar qué controlador está utilizando cada uno.

Ilustración 2 comando `lspci -v`

```
user@debian:~$ lspci -v
00:00.0 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Root Complex
Subsystem: Advanced Micro Devices, Inc. [AMD] Phoenix Root Complex
Flags: fast devsel

00:00.2 IOMMU: Advanced Micro Devices, Inc. [AMD] Phoenix IOMMU
Subsystem: Advanced Micro Devices, Inc. [AMD] Phoenix IOMMU
Flags: bus master, fast devsel, latency 0, IRQ 29
Capabilities: <access denied>

00:01.0 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Dummy Host Bridge
Flags: fast devsel, IOMMU group 0

00:01.2 PCI bridge: Advanced Micro Devices, Inc. [AMD] Phoenix GPP Bridge (prog-if 00 [Normal decode])
Subsystem: Advanced Micro Devices, Inc. [AMD] Device 1453
Flags: bus master, fast devsel, latency 0, IRQ 36, IOMMU group 1
Bus: primary=00, secondary=01, subordinate=01, sec-latency=0
I/O behind bridge: [disabled] [32-bit]
Memory behind bridge: fcf00000-fcffffff [size=1M] [32-bit]
Prefetchable memory behind bridge: [disabled] [64-bit]
Capabilities: <access denied>
Kernel driver in use: pcieport

00:02.0 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Dummy Host Bridge
Flags: fast devsel, IOMMU group 2

00:02.2 PCI bridge: Advanced Micro Devices, Inc. [AMD] Phoenix GPP Bridge (prog-if 00 [Normal decode])
Subsystem: Advanced Micro Devices, Inc. [AMD] Device 1453
Flags: bus master, fast devsel, latency 0, IRQ 37, IOMMU group 3
Bus: primary=00, secondary=02, subordinate=02, sec-latency=0
I/O behind bridge: f000-ffff [size=4K] [16-bit]
Memory behind bridge: fce00000-fcefffff [size=1M] [32-bit]
Prefetchable memory behind bridge: [disabled] [64-bit]
Capabilities: <access denied>
Kernel driver in use: pcieport

00:02.4 PCI bridge: Advanced Micro Devices, Inc. [AMD] Phoenix GPP Bridge (prog-if 00 [Normal decode])
Subsystem: Advanced Micro Devices, Inc. [AMD] Device 1453
Flags: bus master, fast devsel, latency 0, IRQ 38, IOMMU group 4
Bus: primary=00, secondary=03, subordinate=03, sec-latency=0
I/O behind bridge: [disabled] [32-bit]
Memory behind bridge: fcd00000-fcdfffff [size=1M] [32-bit]
Prefetchable memory behind bridge: [disabled] [64-bit]
Capabilities: <access denied>
Kernel driver in use: pcieport

00:03.0 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Dummy Host Bridge
Flags: fast devsel, IOMMU group 5

00:04.0 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Dummy Host Bridge
Flags: fast devsel, IOMMU group 6

00:08.0 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Dummy Host Bridge
Flags: fast devsel, IOMMU group 7

00:08.1 PCI bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Internal GPP Bridge to Bus [C:A] (prog-if 00 [Normal decode])
Subsystem: Advanced Micro Devices, Inc. [AMD] Phoenix Internal GPP Bridge to Bus [C:A]
Flags: bus master, fast devsel, latency 0, IRQ 39, IOMMU group 8
Bus: primary=00, secondary=04, subordinate=04, sec-latency=0
I/O behind bridge: e000-efff [size=4K] [16-bit]
Memory behind bridge: fc400000-fc9fffff [size=6M] [32-bit]
Prefetchable memory behind bridge: 7fa000000-7faffffff [size=756M] [32-bit]
```



2026. "Año del Humanismo Mexicano en el Estado de México"

```
Oct 4 11:36 PM
user@debian:~

Memory behind bridge: fca00000-fcbfffff [size=8M] [32-bit]
Prefetchable memory behind bridge: 7fe000000-7feffffff [size=256M] [32-bit]
Capabilities: <access denied>
Kernel driver in use: pcieport

00:08.2 PCI bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Internal GPP Bridge to Bus [C:A] (prog-if 00 [Normal decode])
Subsystem: Advanced Micro Devices, Inc. [AMD] Phoenix Internal GPP Bridge to Bus [C:A]
Flags: bus master, fast devsel, latency 0, IRQ 40, IOMMU group 9
Bus: primary=00, secondary=05, subordinate=05, sec-latency=0
I/O behind bridge: [disabled] [32-bit]
Memory behind bridge: fcc00000-fccfffff [size=1M] [32-bit]
Prefetchable memory behind bridge: 7ff000000-7ff00fffff [size=1M] [32-bit]
Capabilities: <access denied>
Kernel driver in use: pcieport

00:08.3 PCI bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Internal GPP Bridge to Bus [C:A] (prog-if 00 [Normal decode])
pci1b: Error reading /sys/bus/pci/devices/0000:00:08.3/label: Operation not permitted
Subsystem: Advanced Micro Devices, Inc. [AMD] Phoenix Internal GPP Bridge to Bus [C:A]
Flags: bus master, fast devsel, latency 0, IRQ 41, IOMMU group 10
Bus: primary=00, secondary=06, subordinate=06, sec-latency=0
I/O behind bridge: [disabled] [32-bit]
Memory behind bridge: fca00000-fcbfffff [size=2M] [32-bit]
Prefetchable memory behind bridge: [disabled] [64-bit]
Capabilities: <access denied>
Kernel driver in use: pcieport

00:14.0 SMBus: Advanced Micro Devices, Inc. [AMD] FCH SMBus Controller (rev 71)
Subsystem: Advanced Micro Devices, Inc. [AMD] FCH SMBus Controller
Flags: 66MHz, medium devsel, IOMMU group 11
Kernel driver in use: piix4_smbus
Kernel modules: i2c_piix4, sp5100_tco

00:14.3 ISA bridge: Advanced Micro Devices, Inc. [AMD] FCH LPC Bridge (rev 51)
Subsystem: Advanced Micro Devices, Inc. [AMD] FCH LPC Bridge
Flags: bus master, 66MHz, medium devsel, latency 0, IOMMU group 11

00:18.0 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Data Fabric; Function 0
Flags: fast devsel, IOMMU group 12

00:18.1 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Data Fabric; Function 1
Flags: fast devsel, IOMMU group 12

00:18.2 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Data Fabric; Function 2
Flags: fast devsel, IOMMU group 12

00:18.3 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Data Fabric; Function 3
Flags: fast devsel, IOMMU group 12
Kernel driver in use: k10temp
Kernel modules: k10temp

00:18.4 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Data Fabric; Function 4
Flags: fast devsel, IOMMU group 12

00:18.5 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Data Fabric; Function 5
Flags: fast devsel, IOMMU group 12

00:18.6 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Data Fabric; Function 6
Flags: fast devsel, IOMMU group 12

00:18.7 Host bridge: Advanced Micro Devices, Inc. [AMD] Phoenix Data Fabric; Function 7
Flags: fast devsel, IOMMU group 12
```

```
Oct 4 11:36 PM
user@debian:~

Flags: fast devsel, IOMMU group 12

01:00.0 Non-Volatile memory controller: MAXIO Technology (Hangzhou) Ltd. NVMe SSD Controller MAP1202 (DRAM-less) (rev 01) (prog-if 02 [NVM Express])
Subsystem: MAXIO Technology (Hangzhou) Ltd. NVMe SSD Controller MAP1202 (DRAM-less)
Flags: bus master, fast devsel, latency 0, IRQ 44, IOMMU group 13
Memory at fcf00000 (64-bit, non-prefetchable) [size=16K]
Capabilities: <access denied>
Kernel driver in use: nvme
Kernel modules: nvme

02:00.0 Network controller: Realtek Semiconductor Co., Ltd. RTL8852BE PCIe 802.11ax Wireless Network Controller
Subsystem: Realtek Semiconductor Co., Ltd. RTL8852BE PCIe 802.11ax Wireless Network Controller
Flags: bus master, fast devsel, latency 0, IRQ 80, IOMMU group 14
I/O ports at f000 [size=256]
Memory at fce00000 (64-bit, non-prefetchable) [size=1M]
Capabilities: <access denied>
Kernel driver in use: rtlw89_8852be
Kernel modules: rtlw89_8852be

03:00.0 Non-Volatile memory controller: MAXIO Technology (Hangzhou) Ltd. NVMe SSD Controller MAP1202 (DRAM-less) (rev 01) (prog-if 02 [NVM Express])
Subsystem: MAXIO Technology (Hangzhou) Ltd. NVMe SSD Controller MAP1202 (DRAM-less)
Flags: bus master, fast devsel, latency 0, IRQ 42, IOMMU group 15
Memory at fcd00000 (64-bit, non-prefetchable) [size=16K]
Capabilities: <access denied>
Kernel driver in use: nvme
Kernel modules: nvme

04:00.0 VGA compatible controller: Advanced Micro Devices, Inc. [AMD/ATI] Phoenix1 (rev c2) (prog-if 00 [VGA controller])
Subsystem: Device 2014:8001
Flags: bus master, fast devsel, latency 0, IRQ 65, IOMMU group 16
Memory at 7fe000000 (64-bit, prefetchable) [size=256M]
Memory at fca00000 (64-bit, prefetchable) [size=2M]
I/O ports at e000 [size=256]
Memory at fc900000 (32-bit, non-prefetchable) [size=512K]
Capabilities: <access denied>
Kernel driver in use: amdgpu
Kernel modules: amdgpu

04:00.1 Audio device: Advanced Micro Devices, Inc. [AMD/ATI] Radeon High Definition Audio Controller [Rembrandt/Strix] (prog-if 00 [HDA compatible])
Subsystem: Advanced Micro Devices, Inc. [AMD/ATI] Radeon High Definition Audio Controller [Rembrandt/Strix]
Flags: bus master, fast devsel, latency 0, IRQ 77, IOMMU group 17
Memory at fc980000 (32-bit, non-prefetchable) [size=16K]
Capabilities: <access denied>
Kernel driver in use: snd_hda_intel
Kernel modules: snd_hda_intel

04:00.2 Encryption controller: Advanced Micro Devices, Inc. [AMD] Phoenix CCP/PSP 3.0 Device
Subsystem: Advanced Micro Devices, Inc. [AMD] Phoenix CCP/PSP 3.0 Device
Flags: bus master, fast devsel, latency 0, IRQ 73, IOMMU group 18
Memory at fcb00000 (32-bit, non-prefetchable) [size=1M]
Memory at fc98c000 (32-bit, non-prefetchable) [size=8K]
Capabilities: <access denied>
Kernel driver in use: ccp
Kernel modules: ccp

04:00.3 USB controller: Advanced Micro Devices, Inc. [AMD] Device 15b9 (prog-if 30 [XHCI])
Subsystem: Advanced Micro Devices, Inc. [AMD] Device 15b9
Flags: bus master, fast devsel, latency 0, IRQ 63, IOMMU group 19
Memory at fc700000 (64-bit, non-prefetchable) [size=1M]
Capabilities: <access denied>
Kernel driver in use: xhci_hcd
Kernel modules: xhci_pci
```





2026. "Año del Humanismo Mexicano en el Estado de México"

```
Oct 4 11:37 PM
user@debian: ~

04:00.3 USB controller: Advanced Micro Devices, Inc. [AMD] Device 15b9 (prog-if 30 [XHCI])
Subsystem: Advanced Micro Devices, Inc. [AMD] Device 15b9
Flags: bus master, fast devsel, latency 0, IRQ 63, IOMMU group 19
Memory at fc700000 (64-bit, non-prefetchable) [size=1M]
Capabilities: <access denied>
Kernel driver in use: xhci_hcd
Kernel modules: xhci_pci

04:00.4 USB controller: Advanced Micro Devices, Inc. [AMD] Device 15ba (prog-if 30 [XHCI])
Subsystem: Advanced Micro Devices, Inc. [AMD] Device 15b9
Flags: bus master, fast devsel, latency 0, IRQ 65, IOMMU group 20
Memory at fc600000 (64-bit, non-prefetchable) [size=1M]
Capabilities: <access denied>
Kernel driver in use: xhci_hcd
Kernel modules: xhci_pci

04:00.6 Audio device: Advanced Micro Devices, Inc. [AMD] Family 17h/19h/1ah HD Audio Controller (prog-if 00 [HDA compatible])
DeviceName: OnBoard Audio
Subsystem: Device 2014:7034
Flags: bus master, fast devsel, latency 0, IRQ 78, IOMMU group 21
Memory at fc900000 (32-bit, non-prefetchable) [size=32K]
Capabilities: <access denied>
Kernel driver in use: snd_hda_intel
Kernel modules: snd_hda_intel

05:00.0 Non-Essential Instrumentation [1300]: Advanced Micro Devices, Inc. [AMD] Phoenix Dummy Function
Subsystem: Advanced Micro Devices, Inc. [AMD] Phoenix Dummy Function
Flags: fast devsel, IOMMU group 22
Capabilities: <access denied>

05:00.1 Signal processing controller: Advanced Micro Devices, Inc. [AMD] AMD IPU Device
Subsystem: Device 2014:8001
Flags: fast devsel, IRQ 255, IOMMU group 23
Memory at fcc00000 (32-bit, non-prefetchable) [disabled] [size=512K]
Memory at fccc0000 (32-bit, non-prefetchable) [disabled] [size=8K]
Memory at 7ff0000000 (64-bit, prefetchable) [disabled] [size=256K]
Memory at fcc80000 (32-bit, non-prefetchable) [disabled] [size=256K]
Capabilities: <access denied>

06:00.0 Non-Essential Instrumentation [1300]: Advanced Micro Devices, Inc. [AMD] Phoenix Dummy Function
Subsystem: Advanced Micro Devices, Inc. [AMD] Phoenix Dummy Function
Flags: fast devsel, IOMMU group 24
Capabilities: <access denied>

06:00.3 USB controller: Advanced Micro Devices, Inc. [AMD] Device 15c0 (prog-if 30 [XHCI])
Subsystem: Advanced Micro Devices, Inc. [AMD] Device 15c0
Flags: bus master, fast devsel, latency 0, IRQ 67, IOMMU group 25
Memory at fcb00000 (64-bit, non-prefetchable) [size=1M]
Capabilities: <access denied>
Kernel driver in use: xhci_hcd
Kernel modules: xhci_pci

06:00.4 USB controller: Advanced Micro Devices, Inc. [AMD] Device 15c1 (prog-if 30 [XHCI])
Subsystem: Advanced Micro Devices, Inc. [AMD] Device 15c1
Flags: bus master, fast devsel, latency 0, IRQ 69, IOMMU group 26
Memory at fca00000 (64-bit, non-prefetchable) [size=1M]
Capabilities: <access denied>
Kernel driver in use: xhci_hcd
Kernel modules: xhci_pci

user@debian:~$
```



2026. "Año del Humanismo Mexicano en el Estado de México"

PREGUNTAS

Pregunta 1: ¿Qué driver está usando tu tarjeta de red Wi-Fi (Wireless)?

Al revisar la información obtenida mediante `lspci -v`, buscamos el apartado correspondiente a la tarjeta de red inalámbrica (Wireless). Dentro de la información del dispositivo se puede identificar el controlador que está utilizando.

Rtw89_8852be

Ilustración 3 tarjeta de red

```
02:00.0 Network controller: Realtek Semiconductor Co., Ltd. RTL8852BE PCIe 802.11ax Wireless Network Controller
Subsystem: Realtek Semiconductor Co., Ltd. RTL8852BE PCIe 802.11ax Wireless Network Controller
Flags: bus master, fast devsel, latency 0, IRQ 80, IOMMU group 14
I/O ports at f000 [size=256]
Memory at fce00000 (64-bit, non-prefetchable) [size=1M]
Capabilities: <access denied>
Kernel driver in use: rtw89_8852be
Kernel modules: rtw89_8852be
```

Pregunta 2: ¿Qué driver está usando tu tarjeta gráfica?

Posteriormente, revisamos la información correspondiente a la tarjeta gráfica. De la misma manera, buscamos dentro de los resultados de `lspci -v` el controlador asociado con este dispositivo.

amdgpu

Ilustración 4 tarjeta grafica

```
04:00.0 VGA compatible controller: Advanced Micro Devices, Inc. [AMD/ATI] Phoenix1 (rev c2) (prog-if 00 [VGA controller])
Subsystem: Device 2014:8001
Flags: bus master, fast devsel, latency 0, IRQ 65, IOMMU group 16
Memory at 7fe0000000 (64-bit, prefetchable) [size=256M]
Memory at fc400000 (64-bit, prefetchable) [size=2M]
I/O ports at e000 [size=256]
Memory at fc900000 (32-bit, non-prefetchable) [size=512K]
Capabilities: <access denied>
Kernel driver in use: amdgpu
Kernel modules: amdgpu
```





2026. "Año del Humanismo Mexicano en el Estado de México"

CONCLUSION

Con esta práctica pudimos conocer una forma de identificar los dispositivos de hardware que reconoce un sistema Linux mediante la terminal. También aprendimos que el comando `lspci` permite obtener información básica de los dispositivos y que, utilizando la opción `-v`, podemos consultar información más detallada, como el controlador utilizado por cada componente. Esto nos ayudó a relacionar los dispositivos físicos del equipo con la información que el sistema operativo utiliza para reconocerlos y trabajar con ellos.

