

NAME : MOHAMED ARAFATH K

REG NO: 241801161

BASIC C PROGRAMMING-PRACTICE

PROGRAM 1:

Question 1 | Correct | Mark 1.00 out of 1.00 | [Flag question](#)

Given two numbers, write a C program to swap the given numbers.

For example:

| Input | Result |
|-------|--------|
| 10 20 | 20 10 |

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c;
5     scanf("%d %d",&a,&b);
6     c=a;
7     a=b;
8     b=c;
9     printf("%d %d",a,b);
10 }
```

| | Input | Expected | Got | |
|---|-------|----------|-------|---|
| ✓ | 10 20 | 20 10 | 20 10 | ✓ |

Passed all tests! ✓

PROGRAM 2:

Question 2 | Correct | Mark 1.00 out of 1.00 | [Flag question](#)

Write a C program to find the eligibility of admission for a professional course based on the following criteria:

- Marks in Maths >= 65
- Marks in Physics >= 55
- Marks in Chemistry >= 50
- Or
- Total in all three subjects >= 180

Sample Test Cases

Test Case 1

Input
70 60 80

Output

The candidate is eligible

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c,t;
5     scanf("%d %d %d",&a,&b,&c);
6     t=a+b+c;
7     if((a>=65&&b>=55&&c>=50)|| (t>=180))
8     {
9         printf("The candidate is eligible");
10    }
11    else
12    {
13        printf("The candidate is not eligible");
14    }
15 }
```

| | Input | Expected | Got | |
|---|----------|---------------------------|---------------------------|---|
| ✓ | 70 60 80 | The candidate is eligible | The candidate is eligible | ✓ |
| ✓ | 50 80 80 | The candidate is eligible | The candidate is eligible | ✓ |

Passed all tests! ✓

PROGRAM 3:

Question 3 | Correct | Mark 1.00 out of 1.00 | [Flag question](#)

Malini goes to BestSave hyper market to buy grocery items. BestSave hyper market provides 10% discount on the bill amount B when ever the bill amount B is more than Rs.2000.

The bill amount B is passed as the input to the program. The program must print the final amount A payable by Malini.

Input Format:

The first line denotes the value of B.

Output Format:

The first line contains the value of the final payable amount A.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,r;
5     scanf("%d",&a);
6     if(a<=2000)
7     {
8         r=a;
9     }
10    if(a>2000)
11    {
12        r=a-(a*0.1);
13    }
14    printf("%d",r);
15 }
```

| | Input | Expected | Got | |
|---|-------|----------|------|---|
| ✓ | 1900 | 1900 | 1900 | ✓ |
| ✓ | 3000 | 2700 | 2700 | ✓ |

Passed all tests! ✓

Correct

PROGRAM 4:

Question 4 | Correct | Mark 1.00 out of 1.00 | [Flag question](#)

Baba is very kind to beggars and every day Baba donates half of the amount he has when ever a beggar requests him. The money M left in Baba's hand is passed as the input and the number of beggars B who received the alms are passed as the input. The program must print the money Baba had in the beginning of the day.

Input Format:

The first line denotes the value of M.

The second line denotes the value of B.

Output Format:

The first line denotes the value of money with Baba in the beginning of the day.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int b,p,r;
5     scanf("%d %d",&b,&p);
6     r=b*(2*p);
7     printf("%d",r);
8 }
```

| | Input | Expected | Got | |
|---|-------|----------|-----|---|
| ✓ | 100 | 400 | 400 | ✓ |
| | 2 | | | |

Passed all tests! ✓

PROGRAM 5:

Question 5 | Correct | Mark 1.00 out of 1.00 | [Flag question](#)

The CEO of company ABC Inc wanted to encourage the employees coming on time to the office. So he announced that for every consecutive day an employee comes on time in a week (starting from Monday to Saturday), he will be awarded Rs.200 more than the previous day as "Punctuality Incentive". The incentive I for the starting day (ie on Monday) is passed as the input to the program. The number of days N an employee came on time consecutively starting from Monday is also passed as the input. The program must calculate and print the "Punctuality Incentive" P of the employee.

Input Format:

The first line denotes the value of I.
The second line denotes the value of N.

Output Format:

The first line denotes the value of P.

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,r=0;
5     scanf("%d %d",&a,&b);
6     for(int i=0;i<b;i++)
7     {
8         r+=a+(200*i);
9     }
10    printf("%d",r);
11 }
```

| | Input | Expected | Got | |
|---|----------|----------|------|---|
| ✓ | 500 3 | 2100 | 2100 | ✓ |
| ✓ | 100 3 | 900 | 900 | ✓ |

Passed all tests! ✓

PROGRAM 6:

Question 6 | Correct | Mark 1.00 out of 1.00 | Flag question

Two numbers M and N are passed as the input. A number X is also passed as the input. The program must print the numbers divisible by X from N to M (inclusive of M and N).

Input Format:

The first line denotes the value of M
The second line denotes the value of N
The third line denotes the value of X

Output Format:

Numbers divisible by X from N to M, with each number separated by a space.

Boundary Conditions:

1 <= M <= 99999999
M < N <= 99999999
1 <= X <= 9999

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int m,n,x;
5     scanf("%d %d %d",&m,&n,&x);
6     for(int i=n;i>=m;i--)
7     {
8         if(i%x==0)
9         {
10             printf("%d ",i);
11         }
12     }
13 }
```

| | Input | Expected | Got | |
|---|--------------|---------------|---------------|---|
| ✓ | 2 40 7 | 35 28 21 14 7 | 35 28 21 14 7 | ✓ |

Passed all tests! ✓

PROGRAM 7:

Write a C program to find the quotient and remainder of given integers.

For example:

| Input | Result |
|-------|--------|
| 12 | 4 |
| 3 | 0 |

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,q,r;
5     scanf("%d %d",&a,&b);
6     q=a/b;
7     r=a%b;
8     printf("%d\n%d",q,r);
9 }
```

| | Input | Expected | Got | |
|---|-------|----------|-----|---|
| ✓ | 12 | 4 | 4 | ✓ |
| | 3 | 0 | 0 | |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

PROGRAM 8:

Write a C program to find the biggest among the given 3 integers?

For example:

| Input | Result |
|----------|--------|
| 10 20 30 | 30 |

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c,r;
5     scanf("%d %d %d",&a,&b,&c);
6     if(a>b&&a>c)
7     {
8         r=a;
9     }
10    else if(b>a&&b>c)
11    {
12        r=b;
13    }
14    else
15    {
16        r=c;
17    }
18    printf("%d",r);
19 }
```

| | Input | Expected | Got | |
|---|----------|----------|-----|---|
| ✓ | 10 20 30 | 30 | 30 | ✓ |

Passed all tests! ✓

PROGRAM 9:

Write a C program to find whether the given integer is odd or even?

For example:

| Input | Result |
|-------|--------|
| 12 | Even |
| 11 | Odd |

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a;
5     scanf("%d",&a);
6     if(a%2==0)
7     {
8         printf("Even");
9     }
10    else
11    {
12        printf("Odd");
13    }
14 }
```

| | Input | Expected | Got | |
|---|-------|----------|------|---|
| ✓ | 12 | Even | Even | ✓ |
| ✓ | 11 | Odd | Odd | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

PROGRAM 10:

Write a C program to find the factorial of given n.

For example:

| Input | Result |
|-------|--------|
| 5 | 120 |

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int factorial(int n)
3  {
4      if(n==0||n==1)
5      {
6          return 1;
7      }
8      return n*factorial(n-1);
9  }
10 int main()
11 {
12     int a,fact=0;
13     scanf("%d",&a);
14     fact+=factorial(a);
15     printf("%d",fact);
16 }
17
```

| | Input | Expected | Got | |
|---|-------|----------|-----|---|
| ✓ | 5 | 120 | 120 | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

PROGRAM 11:

Write a C program to find the sum first N natural numbers.

For example:

| Input | Result |
|-------|--------|
| 3 | 6 |

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int a,sum=0;
5      scanf("%d",&a);
6      for(int i=1;i<=a;i++)
7      {
8          sum+=i;
9      }
10     printf("%d",sum);
11 }
```

| | Input | Expected | Got | |
|---|-------|----------|-----|---|
| ✓ | 3 | 6 | 6 | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

PROGRAM 12:

Question 12 | Correct | Mark 1.00 out of 1.00 | [Flag question](#)

Write a C program to find the Nth term in the fibonacci series.

For example:

| Input | Result |
|-------|--------|
| 0 | 0 |
| 1 | 1 |
| 4 | 3 |

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n;
5     scanf("%d",&n);
6     int a=0,b=1,c;
7     for(int i=2;i<=n;i++)
8     {
9         c=a+b;
10        a=b;
11        b=c;
12    }
13    if(n==0)
14    {
15        c=a;
16    }
17    if(n==1)
18    {
19        c=b;
20    }
21    printf("%d",c);
22 }
```

| | Input | Expected | Got | |
|---|-------|----------|-----|---|
| ✓ | 0 | 0 | 0 | ✓ |
| ✓ | 1 | 1 | 1 | ✓ |
| ✓ | 4 | 3 | 3 | ✓ |

Passed all tests! ✓

PROGRAM 13:

Question 13 | Correct Mark 1.00 out of 1.00 [Flag question](#)

Write a C program to find the power of integers.

input:

a b

output:

a^b value

For example:

| Input | Result |
|-------|--------|
| 2 5 | 32 |

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 #include<math.h>
3 int main()
4 {
5     int a,b,r;
6     scanf("%d %d",&a,&b);
7     r=pow(a,b);
8     printf("%d",r);
9 }
```

| | Input | Expected | Got | |
|---|-------|----------|-----|---|
| ✓ | 2 5 | 32 | 32 | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

PROGRAM 14:

Question 14 | Correct | Mark 1.00 out of 1.00 | [Flag question](#)

Write a C program to find Whether the given integer is prime or not.

For example:

| Input | Result |
|-------|----------|
| 7 | Prime |
| 9 | No Prime |

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int prime(int n,int d)
3  {
4      if(n<=1)
5      {
6          return 0;
7      }
8      if(d==1)
9      {
10         return 1;
11     }
12     if(n%d==0)
13     {
14         return 0;
15     }
16     return prime(n,d-1);
17 }
18 int main()
19 {
20     int n;
21     scanf("%d",&n);
22     if(prime(n,n/2))
23     {
24         printf("Prime");
25     }
26     else
27     {
28         printf("No Prime");
29     }
30 }
```

| | Input | Expected | Got | |
|---|-------|----------|----------|---|
| ✓ | 7 | Prime | Prime | ✓ |
| ✓ | 9 | No Prime | No Prime | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

PROGRAM 15:

Question 15 | Correct Mark 1.00 out of 1.00 [Flag question](#)

Write a C program to find the reverse of the given integer?

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a;
5     scanf("%d",&a);
6     int digit,rev=0;
7     while(a!=0)
8     {
9         digit=a%10;
10        rev=(rev*10)+digit;
11        a/=10;
12    }
13    printf("%d",rev);
14 }
```

| | Input | Expected | Got | |
|---|-------|----------|-----|---|
| ✓ | 123 | 321 | 321 | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.