A Structural Threshold in Decision Capacity Governs Collapse in Self-Play Reinforcement Learning

Arahan Kujur
Independent Researcher
kujurarahan@gmail.com

Abstract

We show that a threshold in decision capacity determines whether self-play reinforcement learning agents collapse under asymmetric rule perturbations. Across poker variants (Kuhn, Leduc, Leduc-4), matrix games (Matching Pennies), a dice game (Liar's Dice; 24,576 info sets), and six learning algorithms (Q-Learning, SARSA, REINFORCE, PPO, DQN, NFSP), eliminating all *strategically meaningful* decisions causes rapid convergence to a deterministic exploitation attractor (DEA)—a fixed point at near-maximal loss. Preserving even a single contingent decision point prevents this collapse. A frozen baseline and fixed-opponent control confirm the mechanism is co-adaptation under constraint, not the perturbation itself. The phenomenon is timing-invariant, fully reversible upon action restoration, and intensifies under function approximation. These results establish an empirically sharp threshold between zero and minimal decision capacity—theoretically continuous via reach-weighted CAC (Proposition 2) but exhibiting high contrast in all tested domains.

1 Introduction

Multi-agent reinforcement learning (MARL) agents trained through self-play have achieved superhuman performance in complex games [Silver et al., 2018, Brown and Sandholm, 2019, Vinyals et al., 2019], yet their robustness to structural changes in the environment remains poorly understood. Prior work has focused primarily on adversarial perturbations to observations or rewards [Gleave et al., 2020], opponent modelling under distribution shift [Foerster et al., 2018], or training stability in population-based methods [Balduzzi et al., 2019]. Structural changes to the *action space*—where an agent permanently loses access to certain actions—remain largely unexplored.

Such perturbations arise naturally in practice. In robotics, hardware failures may disable actuators, eliminating actions from an agent's repertoire mid-deployment. In financial trading, regulatory changes can restrict previously available strategies. In multi-agent software systems, API deprecations may remove action endpoints. Understanding how self-play agents respond to these asymmetric capability losses is essential for deploying RL systems in environments where the action space is not guaranteed to remain static.

We study this question in imperfect-information games by removing one player's ability to bet or raise at subsets of decision nodes. This creates a controlled perturbation that reduces the agent's *contingent action capacity* (CAC)—the number of information sets at which it retains more than one legal action.

Our central finding is a pronounced threshold effect. When CAC drops to zero (every decision is forced), adaptive self-play agents converge to a *deterministic exploitation attractor* (DEA)—the unique optimal policy of the single-agent MDP induced by the forced player's policy σ_0^f, characterised by near-maximal loss, near-zero reward variance, and ε-greedy perturbations bounding deviation from the theoretical minimum. When even a single decision point is preserved (CAC ≥ 1,

with positive reach), agents stabilise near Nash equilibrium. A frozen baseline and fixed-opponent control isolate continued co-adaptation as the mechanism. Our contributions:

- We identify a pronounced CAC threshold governing collapse in self-play RL and provide formal propositions characterising the zero-contingency fixed point.
- We isolate co-adaptation under constraint as the mechanism via frozen baseline and fixed-opponent comparisons.
- We demonstrate that collapse persists and intensifies under function approximation (DQN).
- We replicate across five games (1–24,576 info sets), four algorithms, multiple perturbation schedules, and show full reversibility. Boundary conditions (IPD, Liar's Dice) sharpen the threshold definition.

2 Related Work

Solving imperfect-information games. Counterfactual regret minimisation (CFR) [Zinkevich et al., 2007] and its variants have solved increasingly large poker games, from heads-up limit hold'em [Bowling et al., 2015] to no-limit variants via DeepStack [Moravcík et al., 2017], Libratus [Brown and Sandholm, 2018], and Pluribus [Brown and Sandholm, 2019]. These systems assume a fixed game structure. We study what happens when the game structure changes asymmetrically after training.

Self-play reinforcement learning. Self-play has driven advances from TD-Gammon [Tesauro, 1994] through AlphaZero [Silver et al., 2018] and AlphaStar [Vinyals et al., 2019]. Neural Fictitious Self-Play (NFSP) [Heinrich and Silver, 2016] combines RL with average-strategy tracking. Policy-Space Response Oracles (PSRO) [Lanctot et al., 2017] maintain diverse strategy populations. However, self-play dynamics can be unstable—agents may cycle, overfit to their own weaknesses, or exhibit non-transitive behaviour [Balduzzi et al., 2019, Lanctot et al., 2019]. Our work identifies a distinct failure mode: co-adaptation-driven collapse under asymmetric action-space constraints.

Robustness in multi-agent RL. The MARL robustness literature encompasses adversarial policies [Gleave et al., 2020], opponent-learning awareness [Foerster et al., 2018], and distributional robustness [Zhang et al., 2021]. These typically perturb observations, rewards, or opponent behaviour. We perturb the *action space* itself—a structural change that eliminates decision points rather than adding noise. This reveals a qualitative threshold effect that continuous perturbations cannot produce.

Action masking and constrained RL. Invalid action masking is standard practice in game AI [Huang and Ontañón, 2022], and constrained MDPs formalise action restrictions [Altman, 1999]. Robust MDPs address uncertain transitions [Iyengar, 2005, Nilim and El Ghaoui, 2005], and stochastic action-set MDPs model settings where available actions vary [Boutilier et al., 2018]. However, the dynamic consequences of *mid-training* action removal under self-play have not been studied.

Self-play stabilisation. Opponent-shaping methods such as LOLA [Foerster et al., 2018] and SOS [Letcher et al., 2019] stabilise self-play by accounting for the opponent's learning dynamics. Population-based methods including PSRO [Lanctot et al., 2017] and α-PSRO [Muller et al., 2020] maintain diverse strategy populations to avoid cycling. We test PSRO empirically and find it *mitigates* but does not eliminate collapse (§6.3).

Exploitability and game-theoretic evaluation. Exploitability—the gap between an agent's value and the Nash equilibrium value—is the standard evaluation metric in computational game theory [Johanson and Bowling, 2007, Timbers et al., 2022]. We connect our threshold effect to the best-response structure of reduced games via formal propositions (Section 5).

3 Background

Kuhn Poker. Three cards ($J < Q < K$), two actions (pass, bet), ante 1. Nash value for P0: $-1/18 \approx -0.056$. 12 information sets.

Leduc Poker. Six cards ($J, Q, K \times 2$ suits), three actions (fold, check/call, raise), two rounds, fixed-limit betting. Nash P0 value: ≈ -0.087. 288 information sets. Our CFR implementation converges to -0.0866.

Leduc-4 Poker. A Leduc variant with four ranks (J, Q, K, A) and three suits (12 cards). Same rules as Leduc. 504 information sets. Nash P0 value ≈ -0.096.

Liar's Dice (1 die). Two players each roll one six-sided die (private). Players alternate claiming a minimum count of a face value across both dice; claims must strictly increase. A player may challenge instead of claiming. On challenge, the claim is verified—if true the challenger loses, otherwise the claimer loses (± 1). 13 actions (12 claims + challenge). 24,576 information sets. Our CFR implementation yields Nash P0 value ≈ -0.076.

Coordination Game. Two agents simultaneously choose among 3 actions to match a randomly revealed target. Payoff +1 if both match, 0 otherwise. 10 rounds/episode. *Cooperative*, not competitive—the first non-zero-sum domain tested.

Matching Pennies. Two players, two actions (heads, tails), simultaneous single-shot. Nash: 50/50 mixed, value 0. 1 information set per player.

Agents. **CFR**: Nash equilibrium via full-tree CFR, frozen post-training. **Q-Learning**: Tabular, ε-greedy ($\varepsilon = 0.15$), MC terminal updates. **QL-Frozen**: Q-Learning frozen at perturbation (Q-table and ε fixed). **DQN**: 2-layer MLP (64 hidden), experience replay, target network. **SARSA/REINFORCE**: On-policy tabular variants.

4 Methodology

Each experiment runs 20 seeds of 20,000 episodes (50,000 for DQN). Perturbation applied to Player 0 at the midpoint.

Contingent action capacity (CAC). The number of reachable information sets at which the perturbed agent retains > 1 legal action. All CAC-based experiments use the unweighted count as a proxy; CAC_w (reach-weighted, Section 5) is the governing theoretical quantity.

Self-play setup. A single agent plays both roles, with Q-values indexed by player-specific information states. This is equivalent to independent self-play in our zero-sum setting because each player's policy is implicitly determined by separate information-state entries. We verify this empirically: separate-agent experiments produce identical results (Appendix B).

Statistical analysis. Paired t-tests across seeds, bootstrap 95% CIs (10,000 resamples), Cohen's d. Due to low across-seed variance under paired evaluation, effect sizes are large and should be interpreted as indicating direction and reliability.

Normalization. Cross-game comparison uses $(r - r_{\min})/(r_{\max} - r_{\min}) \in [0, 1]$. This normalization aids comparison across reward scales but obscures absolute exploitability; we report exact exploitability where computable (Kuhn, Leduc) to complement normalized rewards.

5 Theory

We formalise the threshold effect in two-player zero-sum extensive-form games. The propositions below apply to the zero-sum case; Section 6.5 presents empirical evidence that cooperative and mixed-motive settings produce a qualitatively different (bounded degradation) response. Extending

the formal treatment to general-sum games is left to future work. Let $G = (H, P, A, \mathcal{I}, u)$ be a two-player zero-sum game with history set H, player function P, action sets A, information partition $\mathcal{I}$, and utility u.

Reach-weighted contingent action capacity. For a strategy profile σ, the *reach probability* of information set h is $\rho^\sigma(h) = \prod_{h' \sqsubset h} \sigma_{P(h')}(h')$, the product of action probabilities on the path to h. We define the *reach-weighted CAC*:

$$\text{CAC}_w(P_0) = \sum_{h \in \mathcal{I}_0} \rho^\sigma(h) \cdot \mathbf{1}[|A(h)| \geq 2] \tag{1}$$

This refines the unweighted count by discounting information sets that are rarely reached. The unweighted CAC used in experiments is an upper bound: $\text{CAC} \geq \text{CAC}_w$.

Proposition 1 (Zero-contingency exploitation)**.** *Let G' be the reduced game with CAC$(P_0) = 0$ (equivalently CAC$_w(P_0) = 0$). Then P_0's value in G' is:*

$$v_0(G') = -\max_{\pi_1 \in \Pi_1} \sum_{z \in Z} u_1(z) \cdot \rho^{\sigma_0^f, \pi_1}(z)$$

where σ_0^f is P_0's forced (deterministic) strategy. Moreover, P_1's best response is pure and computable in $O(|Z|)$ time.

Proof. Under zero contingency, σ_0^f is the unique strategy for P_0. The game reduces to a single-player MDP for P_1 with a deterministic environment. The optimal policy is a pure best response computable by backward induction over P_1's decision nodes, with complexity linear in the number of terminal histories reachable under σ_0^f. □

Proposition 2 (Residual contingency bound)**.** *Suppose P_0 retains at least one information set $h^* \in \mathcal{I}_0$ with $|A(h^*)| \geq 2$ and reach $\rho^\sigma(h^*) > 0$. Let v_0^* be P_0's minimax value in the subgame rooted at h^*, and let v_0^{forced} be the value under the forced policy at all other nodes. Then:*

$$v_0(G') \geq \rho^\sigma(h^*) \cdot v_0^* + (1 - \rho^\sigma(h^*)) \cdot v_0^{forced}$$

In particular, $v_0(G') > v_0^{zero\text{-}cont}$ whenever $v_0^* > v_0^{forced}$ and $\rho^\sigma(h^*) > 0$. The improvement is proportional to the reach of the retained node:

$$\delta(h^*) = \rho^\sigma(h^*) \cdot (v_0^* - v_0^{forced})$$

Proof. By linearity of expectation over reach probabilities, P_0's value decomposes into the contribution from histories passing through h^* (where P_0 plays optimally) and those not passing through h^* (where P_0 is forced). The bound follows directly. When h^* is reached with probability 1 (as in Kuhn root-only removal where all games pass through the "pb" node), $\delta(h^*) = v_0^* - v_0^{\text{forced}}$ and the full minimax value is recovered. □

Corollary 1. *The transition from CAC$_w > 0$ to CAC$_w = 0$ qualitatively changes the best-response structure: from a game with strategic interaction (requiring mixed or adaptive responses, with value bounded by $\delta(h^*)$) to one with a trivially computable pure best response. A single retained decision point with positive reach is sufficient to prevent collapse; a retained decision with zero reach provides no protection.*

Proposition 3 (DEA as a fixed point of self-play dynamics)**.** *Consider tabular Q-learning self-play under zero contingency (CAC$_w = 0$). Let $Q_1(s, a)$ denote P_1's Q-values. Under standard assumptions ($\varepsilon > 0$, $\alpha_t \to 0$, $\sum \alpha_t = \infty$), P_1's Q-values converge to the unique fixed point $Q_1^* = Q^{BR(\sigma_0^f)}$—the optimal Q-function for a single-agent MDP defined by P_0's forced policy σ_0^f. The resulting joint policy profile (σ_0^f, π_1^*) is a Nash equilibrium of the reduced game G' and constitutes the DEA.*

Proof. Under CAC$_w = 0$, P_0's policy is fixed and deterministic at every reachable information set. From P_1's perspective, the environment is a stationary MDP with deterministic transitions (conditioned on the card deal). Standard Q-learning convergence guarantees [Tesauro, 1994] apply:

with decaying learning rate and persistent exploration, $Q_1 \to Q_1^*$ almost surely. Since P_0 cannot deviate from σ_0^f, the profile (σ_0^f, π_1^*) satisfies the Nash equilibrium conditions of G'. The fixed point is unique because the reduced MDP has a unique optimal Q-function. The ε-greedy policy induced by Q_1^* places probability $\geq 1 - \varepsilon$ on the best response at each information set, yielding $v_0 \geq V_{\min} + \varepsilon_{\text{floor}}$ where $\varepsilon_{\text{floor}} = O(\varepsilon)$. □

6 Experiments

Results are organised as: phenomenon (§6.1), threshold (§6.2), mechanism (§6.3), generalisation (§6.4), boundary conditions (§6.5), and dynamics (§6.6). Additional experiments appear in the Appendix.

6.1 The Phenomenon

Zero contingency (CAC $= 0$). Bet removed from P0 at all nodes in Kuhn. P0 is forced to check then fold.

Table 1: Kuhn, zero contingency. Player 0 reward (20 seeds, 95% CIs).

Agent	Pre	Post	p	d
CFR	-0.060 $[-0.067, -0.054]$	-0.221 $[-0.225, -0.216]$	<0.0001	-6.9
Q-Learning	-0.041 $[-0.050, -0.032]$	$\mathbf{-0.926}$ $[-0.928, -0.924]$	<0.0001	-42.0

Q-Learning converges to the DEA at -0.926 (normalized: 0.27; $d = -42.0$) within a mean of four episodes. CFR drops to -0.22, bounded by its static opponent.

Figure 1: Zero contingency (Kuhn): Q-Learning converges to the DEA within four episodes, illustrating the transition to deterministic exploitation.

Residual contingency (CAC $= 1$). Bet removed at root only; P0 retains call/fold. Q-Learning drops modestly ($\Delta = -0.024$, $d = -0.8$) then stabilises near Nash (Table 2).

Table 2: Kuhn, residual contingency (CAC $= 1$). 20 seeds.

Agent	Pre	Post	p	d
CFR	-0.060	-0.053	0.20	$+0.3$
Q-Learning	-0.041	-0.065	0.002	-0.8

6.2 The Threshold

The jump from CAC $= 0$ to 1 is $\Delta = 0.86$ ($+0.21$ normalized). The jump from 1 to 2 is marginal ($\Delta = 0.03$). Figure 2 shows the discontinuity on a normalized scale.

Table 3: CAC sweep (Kuhn): the discontinuity at CAC $= 0 \rightarrow 1$.

CAC	Description	CFR	QL	QL Norm.
0	Zero-contingency	-0.221	$\mathbf{-0.926}$	0.27
1	Residual contingency	-0.053	-0.065	0.48
2	Full (control)	-0.053	-0.034	0.49



Figure 2: The CAC threshold (normalized). The discontinuity at 0→1 confirms a structural threshold.

6.3 The Mechanism

Frozen baseline. QL-Frozen avoids the DEA (-0.141 vs -0.927; $\Delta = -0.787$, $p = 0.004$, $d = -2.6$; 5 seeds). Co-adaptation—not the constraint—drives collapse.

Fixed opponent. Against a static Nash opponent (5 seeds), Q-Learning drops only to -0.228 (identical to CFR). Under self-play the same condition produces -0.926 (20 seeds). Co-adaptation is necessary for catastrophic collapse.

Population-based training (PSRO). Under PSRO with a 5-policy population, P0's post-perturbation reward improves to -0.418 ± 0.062 (3 seeds)—substantially better than self-play (-0.927) but still degraded from pre-perturbation (≈ -0.05). The diverse population prevents the opponent from fully specialising against P0's forced policy, but cannot recover the strategic loss from zero contingency. PSRO *mitigates* but does not *eliminate* collapse: the structural vulnerability remains, but its exploitation is bounded by population diversity. With larger populations, P0's post-perturbation reward improves monotonically (-0.275 at pop. 3; -0.598 at pop. 15; all vs. -0.927 under self-play). Population diversity bounds the degree of exploitation but cannot restore lost strategic degrees of freedom: the structural vulnerability at CAC $= 0$ persists regardless of opponent diversity, though its severity is modulated.



Figure 3: QL-Frozen avoids the DEA, isolating co-adaptation as the mechanism.

6.4 Generalisation

Table 4: Algorithm invariance under zero contingency (Kuhn, 5 seeds).

Algorithm	Type	Post	d
Q-Learning	Tabular	$\mathbf{-0.927}$	-66.1
SARSA	Tabular	$\mathbf{-0.927}$	-66.1
REINFORCE	Tabular	$\mathbf{-0.500}$	-39.6
DQN	Neural	$\mathbf{-0.994}$	-24.4
PPO	Tabular	$\mathbf{-0.500}$	-39.6
NFSP	Tabular	$\mathbf{-0.505}$	–

Algorithm invariance. All algorithms collapse. DQN reaches -0.994—*more* severe than tabular agents. PPO and REINFORCE both reach -0.500, partially protected by their softmax policy parameterisation. Notably, NFSP—which maintains an explicit average strategy via supervised learning, designed specifically for imperfect-information games—also collapses to -0.505. This occurs because NFSP's best-response component still learns to exploit the forced opponent, and the average strategy cannot compensate when the action space itself has collapsed: there is no historical action diversity to average over when P0's every decision is forced. To isolate the ε-schedule effect, we ran DQN with fixed $\varepsilon = 0.15$ (no decay): post-perturbation reward improved modestly to -0.923, confirming that the deeper collapse under decaying ε is driven by reduced exploration ($\varepsilon \to 0.01$), but the structural vulnerability persists regardless. Figure 5 provides mechanistic insight: after perturbation, DQN's policy entropy drops to near zero and Q-value gaps spike, confirming rapid convergence to a deterministic policy.



Figure 4: All four algorithms converge toward the DEA. DQN collapses deepest.



Figure 5: DQN neural analysis under zero contingency (Kuhn). Left: policy entropy drops to near zero post-perturbation, confirming deterministic policy convergence. Right: Q-value gap ($|Q(a_0) - Q(a_1)|$) spikes, reflecting the network's growing certainty in the forced-fold action.

Table 5: Cross-game normalized collapse severity.

Game	QL Post	Info sets	Normalized
Matching Pennies	-0.851	1	0.07
Kuhn Poker	-0.926	12	0.27
Leduc Poker	-0.252	288	0.49
Leduc-4 Poker	-0.185	504	0.49
Liar's Dice (1d)	-0.032	24,576	$0.48^{\dagger}$
Liar's Dice (1d, true zero)	$\mathbf{-0.524}$	24,576	0.24
Coordination	$+1.44^{\ddagger}$	–	–
Liar's Dice (2d)	$+0.008$	200,000+	$0.50^{\dagger}$

†Challenge-only retains strategic value (§6.5). ‡Cooperative game; forced single action reduces coordination but reward remains positive ($p = 0.001$).

Cross-game replication. Collapse holds across poker and matrix games (1–504 info sets). Liar's Dice at both scales (24,576 and 200,000+ info sets) shows no collapse because challenge-only play retains strategic flexibility—a boundary condition consistent with Proposition 2. Severity scales inversely with residual action options: Matching Pennies (most severe, 0.07) has zero residual options; Leduc variants (least severe, 0.49) retain fold/check-call. Under residual contingency, no game collapses.

6.5 Boundary Conditions

IPD: when perturbation aligns with equilibrium. Removing "cooperate" in the Iterated Prisoner's Dilemma produces no collapse (post $= +1.12$). IPD Nash is always-defect; removing cooperate pushes P0 *toward* equilibrium. The threshold operates only when the perturbation forces the agent into a dominated regime where the opponent can extract surplus.

Liar's Dice: strategic flexibility vs. action type. Removing all claims from P0 in Liar's Dice forces challenge-only play. Neither tabular Q-Learning (1-die; post $= -0.032$) nor DQN (2-dice; post $= +0.008$) collapses, because challenging at different points is a strategically contingent decision. However, when we force P0 to play *deterministically* (always the lowest legal action, eliminating timing choices), Q-Learning collapses to -0.524 (normalized: 0.24; $p < 0.0001$)—demonstrating collapse at 24,576 information sets. This confirms that the threshold depends on the reach-weighted CAC (Eq. 1), not the action-type count: challenge-only play retains high CAC_w because challenge decisions are contingent on private information, whereas deterministic-lowest play sets $\text{CAC}_w = 0$.

Non-zero-sum domains: degradation without collapse. In the cooperative Coordination game (match-the-target), forcing P0 to a single action (CAC $= 0$) degrades team performance ($+1.57 \rightarrow$

$+1.44$, $p = 0.001$, $d = -3.8$) but does not produce convergence to the DEA. In the Negotiation game (ultimatum, 11 offer actions), forcing P0 to a single offer (CAC $= 0$) degrades outcomes; crucially, P1's policy shifts toward rejection because it can condition on P0's inability to adapt its offer, but this rejection is bounded—P1 does not converge to unconditional rejection as it would under zero-sum exploitation pressure. Retaining partial flexibility (offers 0–2, CAC $= 3$) reverses the degradation entirely. In contrast to competitive settings where zero contingency produces collapse to the DEA, cooperative and mixed-motive environments exhibit bounded degradation, suggesting that the threshold interacts with the underlying interaction structure: zero-sum dynamics amplify the constraint into catastrophic exploitation, while cooperative dynamics produce performance loss without attractor convergence.

Timing invariance. Perturbation at episodes 3k, 10k, 17k yields identical collapse (-0.926, -0.927, -0.925). The DEA is a structural attractor independent of training stage.

6.6 Dynamics

Recovery. Restoring actions at episode 15k produces full recovery ($\Delta = +0.90$) within four episodes—symmetric with collapse speed. The DEA is a maintained attractor, not a corrupted representation. (See Figure 6 and Table 6.)

Table 6: Recovery (Kuhn, 5 seeds): three-phase Q-Learning reward.

Phase	Mean	95% CI
Pre (0–10k)	-0.035	$[-0.05, -0.03]$
Collapsed (10–15k)	-0.927	$[-0.93, -0.92]$
Recovered (15–25k)	-0.025	$[-0.06, -0.01]$



Figure 6: Collapse and recovery are symmetric. The DEA is maintained only by the constraint.

Exploitability trajectory. Figure 7 plots exact exploitability (computed via best-response tree walk) over training in Kuhn. Pre-perturbation, exploitability converges toward zero as the agent approaches Nash. Post-perturbation, exploitability spikes. For Leduc Poker, exact exploitability (120 deals, full tree walk) increases from 1.63 pre-perturbation to 1.93 post-perturbation ($\Delta = +0.30$), corroborating the reward-based findings with a game-theoretic metric. Reward degradation aligns with increased exploitability where computable (Kuhn, Leduc), supporting generalisation of the DEA characterisation to games where only reward is available.

Variance decomposition. Post-collapse reward variance is 5×10^{-6}, confirming the DEA is a deterministic fixed point.



Figure 7: Exploitability over time (Kuhn, full removal). Post-perturbation exploitability spikes as the agent's policy becomes deterministically exploitable.

7 Conclusion

We have identified a pronounced threshold in contingent action capacity that governs whether self-play RL agents collapse under asymmetric action-space perturbations. The severity of the transition depends on the reach-weighted CAC of the retained decision points (Proposition 2): higher reach yields stronger protection. The finding is, within the tested class of imperfect-information and matrix games, algorithm-invariant (Q-Learning, SARSA, REINFORCE, PPO, NFSP, DQN), co-adaptation-driven, timing-invariant, and fully reversible. A single retained decision point prevents catastrophic exploitation by maintaining strategic coupling between players.

Limitations. Games studied range from 1 to $200{,}000+$ information sets, with confirmed collapse at 24,576 info sets under true zero contingency (Liar's Dice). CAC is unweighted by reach probability. Reversibility may not hold under deeper networks where gradient-based collapse could corrupt representations.

Future work. Scaling to larger games; cooperative and general-sum settings; formal exploitability bounds beyond Kuhn (approximate BR for Leduc/Liar's Dice); testing regret-minimisation self-play (NFSP) as a dynamic opponent; formalising degradation attractors in non-zero-sum settings.

References

Eitan Altman. *Constrained Markov decision processes: Stochastic modeling*. CRC Press, 1999.

David Balduzzi, Marta Garnelo, Yoram Bachrach, Wojciech Czarnecki, Julien Pérolat, Max Jaderberg, and Thore Graepel. Open-ended learning in symmetric zero-sum games. In *International Conference on Machine Learning*, pages 434–443, 2019.

Craig Boutilier, Chih-Wei Hsu, Branislav Kveton, Ofer Meshi, and Zheng Qin. Planning and acting in stochastic action sets. In *International Joint Conference on Artificial Intelligence*, pages 4674–4682, 2018.

Michael Bowling, Neil Burch, Michael Johanson, and Oskari Tammelin. Heads-up limit hold'em poker is solved. *Science*, 347(6218):145–149, 2015.

Noam Brown and Tuomas Sandholm. Superhuman AI for heads-up no-limit poker: Libratus beats top professionals. *Science*, 359(6374):418–424, 2018.

Noam Brown and Tuomas Sandholm. Superhuman AI for multiplayer poker. *Science*, 365(6456): 885–890, 2019.

Jakob Foerster, Richard Y Chen, Maruan Al-Shedivat, Shimon Whiteson, Pieter Abbeel, and Igor Mordatch. Learning with opponent-learning awareness. In *International Conference on Autonomous Agents and Multiagent Systems*, pages 122–130, 2018.

Adam Gleave, Michael Dennis, Cody Wild, Neel Kant, Sergey Levine, and Stuart Russell. Adversarial policies: Attacking deep reinforcement learning. In *International Conference on Learning Representations*, 2020.

Johannes Heinrich and David Silver. Deep reinforcement learning from self-play in imperfect-information games. In *International Conference on Learning Representations*, 2016.

Shengyi Huang and Santiago Ontañón. A closer look at invalid action masking in policy gradient algorithms. In *International FLAIRS Conference*, 2022.

Garud N Iyengar. Robust dynamic programming. *Mathematics of Operations Research*, 30(2): 257–280, 2005.

Michael Johanson and Michael Bowling. Computing robust counter-strategies. In *Advances in Neural Information Processing Systems*, volume 20, 2007.

Marc Lanctot, Vinicius Zambaldi, Audrunas Gruslys, Angeliki Lazaridou, Karl Tuyls, Julien Pérolat, David Silver, and Thore Graepel. A unified game-theoretic approach to multiagent reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 30, 2017.

Marc Lanctot, Edward Lockhart, Jean-Baptiste Lespiau, Vinicius Zambaldi, Satyaki Upadhyay, Julien Pérolat, Sriram Srinivasan, Finbarr Timbers, Karl Tuyls, Shayegan Omidshafiei, et al. OpenSpiel: A framework for reinforcement learning in games. *arXiv preprint arXiv:1908.09453*, 2019.

Alistair Letcher, Jakob Foerster, David Balduzzi, Tim Rocktäschel, and Shimon Whiteson. Stable opponent shaping in differentiable games. In *International Conference on Learning Representations*, 2019.

Matej Moravcík, Martin Schmid, Neil Burch, Viliam Lisý, Dustin Morrill, Nolan Bard, Trevor Davis, Kevin Waugh, Michael Johanson, and Michael Bowling. DeepStack: Expert-level artificial intelligence in heads-up no-limit poker. *Science*, 356(6337):508–513, 2017.

Paul Muller, Shayegan Omidshafiei, Mark Rowland, Karl Tuyls, Julien Perolat, Siqi Liu, Daniel Hennes, Luke Marris, Marc Lanctot, Edward Hughes, et al. A generalized training approach for multiagent learning. In *International Conference on Learning Representations*, 2020.

Arnab Nilim and Laurent El Ghaoui. Robust control of Markov decision processes with uncertain transition matrices. *Operations Research*, 53(5):780–798, 2005.

David Silver, Thomas Hubert, Julian Schrittwieser, Ioannis Antonoglou, Matthew Lai, Arthur Guez, Marc Lanctot, Laurent Sifre, Dharshan Kumaran, Thore Graepel, et al. A general reinforcement learning algorithm that masters chess, shogi, and Go through self-play. *Science*, 362(6419):1140–1144, 2018.

Gerald Tesauro. TD-Gammon, a self-teaching backgammon program, achieves master-level play. *Neural Computation*, 6(2):215–219, 1994.

Finbarr Timbers, Neil Burch, Martin Schmid, Michael Bowling, and Marc Lanctot. Approximate exploitability: Learning a best response. In *Advances in Neural Information Processing Systems*, 2022.

Oriol Vinyals, Igor Babuschkin, Wojciech M Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David H Choi, Richard Powell, Timo Ewalds, Petko Georgiev, et al. Grandmaster level in StarCraft II using multi-agent reinforcement learning. *Nature*, 575(7782):350–354, 2019.

Kaiqing Zhang, Zhuoran Yang, and Tamer Başar. Multi-agent reinforcement learning: A selective overview of theories and algorithms. *Handbook of Reinforcement Learning and Control*, pages 321–384, 2021.

Martin Zinkevich, Michael Johanson, Michael Bowling, and Carmelo Piccione. Regret minimization in games with incomplete information. In *Advances in Neural Information Processing Systems*, volume 20, 2007.

A Hyperparameter Sensitivity

Collapse persists across all 9 tested hyperparameter combinations under zero contingency in Kuhn Poker. Learning rate (α) has negligible effect; exploration rate (ε) shifts only the floor (lower ε = deeper collapse, as expected from reduced residual stochasticity).

	$\alpha = 0.01$	$\alpha = 0.1$	$\alpha = 0.3$
$\varepsilon = 0.05$	-0.974	-0.976	-0.976
$\varepsilon = 0.15$	-0.924	-0.927	-0.927
$\varepsilon = 0.30$	-0.849	-0.853	-0.851

The DEA is robust to hyperparameter choice. The only variation is the ε-floor effect predicted by Proposition 1.

B Separate Self-Play Verification

Experiments with independent P0/P1 Q-tables produce identical collapse dynamics (separate: -0.926 ± 0.003; shared: -0.927; difference: $+0.0008$), confirming that shared-table self-play is equivalent in our zero-sum setting.

C Tabular PPO Details

Our "tabular PPO" maintains a softmax policy over a preference table $\theta(s, a)$ indexed by information state. Action probabilities: $\pi(a|s) = \text{softmax}(\theta(s, \cdot))$. Updates use the clipped surrogate objective $L = \min(r_t A_t, \text{clip}(r_t, 1 - \epsilon, 1 + \epsilon)A_t)$ where $r_t = \pi_{\text{new}}/\pi_{\text{old}}$, $A_t = R - b$ (advantage with running baseline), and $\epsilon = 0.2$. An entropy bonus $-0.01 \cdot H(\pi)$ is added. Learning rate: 0.01. The softmax parameterisation explains the partial protection: unlike ε-greedy, softmax policies cannot fully collapse to deterministic play under finite θ updates, bounding post-perturbation loss at ≈ -0.50 rather than -0.93.

D Fixed-Opponent Calibration

Under forced check-fold (Kuhn, CAC $= 0$), P_1's best response is to always bet: P_0 checks, P_1 bets, P_0 folds, yielding $+1$ for P_1 (-1 for P_0) on every hand. The ε-floor prevents exact convergence, so the theoretical DEA bound is $v_0 \approx -1 + \varepsilon_{\text{floor}}$—consistent with the observed self-play collapse at -0.926.

Under a *fixed Nash opponent* (which does *not* best-respond to σ_0^f), P_0 drops only to -0.228. This is far from the BR value of -1 because the Nash opponent was trained before perturbation and does not adapt. The gap between -0.228 (fixed Nash) and -0.926 (self-play) directly quantifies the contribution of co-adaptation: without an adapting opponent, P_0 loses only what the Nash strategy extracts from forced check-fold; with co-adaptation, P_1 converges toward the BR and extracts nearly the maximum.

E Additional Experiments

Severity sweep. Perturbation timing ($\times$ severity) under Kuhn Poker. Collapse severity is invariant to timing.

Timing	Episode	Severe (CAC 0)	Mild (CAC 1)
Early	3,000	-0.926	-0.063
Mid	10,000	-0.927	-0.073
Late	17,000	-0.925	-0.061

Stochastic masking. Root-only perturbation applied with 50% probability per episode (Kuhn): QL post $= -0.049$ ($p = 0.06$). Intermittent perturbation does not trigger collapse.

Variance decomposition. Post-collapse Q-Learning reward variance: $V_{\text{total}} = 5 \times 10^{-6}$, $V_{\text{env}} = 7 \times 10^{-6}$, $V_{\text{policy}} = 6 \times 10^{-6}$. Near-zero total variance confirms the DEA is a deterministic fixed point.

F Reach-Weighted CAC Values

Perturbation	CAC	CAC_w	Collapse?
Full removal (Kuhn)	0	0.000	Yes (-0.926)
Root-only (Kuhn)	1	0.473	No (-0.065)
No perturbation	2	1.473	No (-0.034)

The "pb" node has average reach $\rho = 0.473$ under Nash play (P0 passes at root, P1 bets). This positive reach confirms Proposition 2: the retained node has sufficient strategic weight to prevent collapse. The improvement $\delta(h^*) \propto \rho(h^*)$ is directly observable in the data.

G DQN Hyperparameters and Normalization

Parameter	Value
Network	2-layer MLP, 64 hidden units, ReLU
Optimizer	Adam, lr $= 10^{-3}$
Replay buffer	10,000 transitions
Batch size	32
Target network update	Every 500 episodes
ε schedule	$0.15 \to 0.01$ linear over 50,000 steps

Normalization bounds per game.

Game	$r_{\min}$	$r_{\max}$	Nash v_0
Kuhn Poker	-2	$+2$	-0.056
Leduc Poker	-13	$+13$	-0.087
Leduc-4	-13	$+13$	-0.096
Matching Pennies	-1	$+1$	0
Liar's Dice (1d)	-1	$+1$	-0.076
Liar's Dice (2d)	-1	$+1$	≈ 0

Exploitability computation. Exact exploitability is computed for Kuhn Poker via full best-response tree walk over all 6 deals: $\text{Exploit}(\pi) = (\text{BR}_{P_0}(\pi) + \text{BR}_{P_1}(\pi))/2$, where BR_{P_i} is the best-response value for player i against π playing as the opponent. This is exact (no approximation) for Kuhn's 12 information sets.

H Entropy Regularisation

We test whether entropy regularisation ($Q(s,a) \leftarrow Q(s,a) + \alpha(r + \tau H(\pi_s) - Q(s,a))$) can prevent collapse. Under zero contingency in Kuhn:

τ	QL Post
0.00 (baseline)	-0.927
0.05	-0.925
0.10	-0.923
0.20	-0.926

Entropy regularisation has no measurable effect on collapse severity. The DEA is robust to diversity-encouraging bonuses because the zero-contingency constraint eliminates the agent's ability to act on

any maintained diversity. The structural nature of the threshold—not insufficient exploration—is what drives collapse.

I Reach Sensitivity

We vary ε (exploration rate) to change the empirical reach of the retained "pb" node under root-only perturbation in Kuhn:

ε	reach(pb)	QL Post
0.05	0.464	-0.065
0.15	0.469	-0.049
0.30	0.486	-0.088
0.50	0.517	-0.092

Post-perturbation reward remains stable near -0.06 to -0.09 across all reach values, confirming that the retained node provides effective protection once $\text{CAC}_w > 0$, with only modest sensitivity to the exact reach probability.