

# MapReduce

**Tushar B. Kute,**  
<http://tusharkute.com>

# What is MapReduce?

- MapReduce is a framework using which we can write applications to process huge amounts of data, in parallel, on large clusters of commodity hardware in a reliable manner.
- MapReduce is a processing technique and a program model for distributed computing based on java.
- The MapReduce algorithm contains two important tasks, namely Map and Reduce.

# Map and Reduce

- Map takes a set of data and converts it into another set of data, where individual elements are broken down into tuples (key/value pairs).
- Secondly, reduce task, which takes the output from a map as an input and combines those data tuples into a smaller set of tuples. As the sequence of the name MapReduce implies, the reduce task is always performed after the map job.


# Map and Reduce

- The major advantage of MapReduce is that it is easy to scale data processing over multiple computing nodes.
- Under the MapReduce model, the data processing primitives are called mappers and reducers.
- Decomposing a data processing application into mappers and reducers is sometimes nontrivial. But, once we write an application in the MapReduce form, scaling the application to run over hundreds, thousands, or even tens of thousands of machines in a cluster is merely a configuration change.
- This simple scalability is what has attracted many programmers to use the MapReduce model.

# The Algorithm

- MapReduce program executes in three stages, namely map stage, shuffle stage, and reduce stage.
- **Map stage:** The map or mapper's job is to process the input data. Generally the input data is in the form of file or directory and is stored in the Hadoop file system (HDFS). The input file is passed to the mapper function line by line. The mapper processes the data and creates several small chunks of data.
- **Reduce stage:** This stage is the combination of the Shuffle stage and the Reduce stage. The Reducer's job is to process the data that comes from the mapper. After processing, it produces a new set of output, which will be stored in the HDFS.

# The MapReduce



# Inserting Data into HDFS


- The MapReduce framework operates on  $\langle \text{key}, \text{value} \rangle$  pairs, that is, the framework views the input to the job as a set of  $\langle \text{key}, \text{value} \rangle$  pairs and produces a set of  $\langle \text{key}, \text{value} \rangle$  pairs as the output of the job, conceivably of different types.
- The key and the value classes should be in serialized manner by the framework and hence, need to implement the Writable interface. Additionally, the key classes have to implement the Writable-Comparable interface to facilitate sorting by the framework.
- Input and Output types of a MapReduce job: (Input)  $\langle k_1, v_1 \rangle \rightarrow \text{map} \rightarrow \langle k_2, v_2 \rangle \rightarrow \text{reduce} \rightarrow \langle k_3, v_3 \rangle$  (Output).

# Input and output


	Input	Output
<b>Map</b>	$\langle k1, v1 \rangle$	list ( $\langle k2, v2 \rangle$ )
<b>Reduce</b>	$\langle k2, \text{list}(v2) \rangle$	list ( $\langle k3, v3 \rangle$ )




# Wordcount Example



# Matrix Multiplication Example



# Matrix Multiplication Example



# Thank you

*This presentation is created using LibreOffice Impress 5.1.6.2, can be used freely as per GNU General Public License*



@mitu\_skillologies



/mITuSkillologies



@mitu\_group



/company/mitu-  
skillologies



MITUSkillologies

## Web Resources

<https://mitu.co.in>  
<http://tusharkute.com>

[contact@mitu.co.in](mailto:contact@mitu.co.in)  
[tushar@tusharkute.com](mailto:tushar@tusharkute.com)