

User management

Types

- 1) **System User** : Create when service are installed in system.
- 2) **Standard User** : Local user is standard user.it has limited access.
- 3) **Root user** : Super user is root user . it has full access.

Add New user :

Syntax : `useradd username` : create new user.

ex. `useradd ram`

```
[root@ip-172-31-31-108 ec2-user]# ls
new newdir
[root@ip-172-31-31-108 ec2-user]# ls /home
ec2-user ram
[root@ip-172-31-31-108 ec2-user]# |
```

Files are affected after adding new user :

- 1) **/etc/passwd** : Store new profile related information.

```

[ec2-user@ip-172-31-31-108 ~]$ ls /home
[ec2-user@ip-172-31-31-108 ~]$ cat /etc/passwd
root:x:0:0:root:/root:/bin/bash
bin:x:1:1:bin:/bin:/sbin/nologin
daemon:x:2:2:daemon:/sbin:/sbin/nologin
adm:x:3:4:adm:/var/adm:/sbin/nologin
lp:x:4:7:lp:/var/spool/lpd:/sbin/nologin
sync:x:5:0:sync:/sbin:/bin/sync
shutdown:x:6:0:shutdown:/sbin:/sbin/shutdown
halt:x:7:0:halt:/sbin:/sbin/halt
mail:x:8:12:mail:/var/spool/mail:/sbin/nologin
operator:x:11:0:operator:/root:/sbin/nologin
games:x:12:100:games:/usr/games:/sbin/nologin
ftp:x:14:50:FTP User:/var/ftp:/sbin/nologin
nobody:x:65534:65534:Kernel Overflow User:/sbin/nologin
dbus:x:81:81:System message bus:/sbin/nologin
systemd-network:x:192:192:systemd Network Management:/usr/sbin/nologin
systemd-oom:x:999:999:systemd Userspace OOM Killer:/usr/sbin/nologin
systemd-resolve:x:193:193:systemd Resolver:/usr/sbin/nologin
sshd:x:74:74:Privilege-separated SSH:/usr/share/empty.sshd:/sbin/nologin
rpc:x:32:32:Rpcbind Daemon:/var/lib/rpcbind:/sbin/nologin
libstoragemgmt:x:997:997:daemon account for libstoragemgmt:/usr/sbin/nologin
systemd-coredump:x:996:996:systemd Core Dumper:/usr/sbin/nologin
systemd-timesync:x:995:995:systemd Time Synchronization:/usr/sbin/nologin
chrony:x:994:994:chrony system user:/var/lib/chrony:/sbin/nologin
ec2-instance-connect:x:993:993:/home/ec2-instance-connect:/sbin/nologin
staprunpriv:x:159:159:systemtap unprivileged user:/var/lib/staprunpriv:/sbin/nologin
rpcuser:x:29:29:RPC Service User:/var/lib/nfs:/sbin/nologin
tcpdump:x:72:72:/sbin/nologin
ec2-user:x:1000:1000:EC2 Default User:/home/ec2-user:/bin/bash
ram:x:1001:1001:/home/ram:/bin/bash
[ec2-user@ip-172-31-31-108 ~]$

```

2) **/etc/shadow** : Store user password policy.

```
[root@ip-172-31-31-108 ec2-user]# cat /etc/shadow
root:*LOCK*:14600:::::::::
bin:*:19387:0:99999:7:::
daemon:*:19387:0:99999:7:::
adm:*:19387:0:99999:7:::
lp:*:19387:0:99999:7:::
sync:*:19387:0:99999:7:::
shutdown:*:19387:0:99999:7:::
halt:*:19387:0:99999:7:::
mail:*:19387:0:99999:7:::
operator:*:19387:0:99999:7:::
games:*:19387:0:99999:7:::
ftp:*:19387:0:99999:7:::
nobody:*:19387:0:99999:7:::
dbus:!!:20313:::::::::
systemd-network:!*:20313:::::::::
systemd-oom:!*:20313:::::::::
systemd-resolve:!*:20313:::::::::
sshd:!!:20313:::::::::
rpc:!!:20313:0:99999:7:::
libstoragemgmt:!*:20313:::::::::
systemd-coredump:!*:20313:::::::::
systemd-timesync:!*:20313:::::::::
chrony:!!:20313:::::::::
ec2-instance-connect:!!:20313:::::::::
staprunpriv:!*:20313:::::::::
rpcuser:!!:20313:::::::::
tcpdump:!!:20313:::::::::
ec2-user:!!:20335:0:99999:7:::
ram:!!:20353:0:99999:7:::
[root@ip-172-31-31-108 ec2-user]# |
```

3) **/etc/group** : Store group information.

```
14m11112000101999911111
[root@ip-172-31-31-108 ec2-user]# cat /etc/group
root:x:0:
bin:x:1:
daemon:x:2:
sys:x:3:
adm:x:4:ec2-user
tty:x:5:
disk:x:6:
lp:x:7:
mem:x:8:
kmem:x:9:
wheel:x:10:ec2-user
cdrom:x:11:
mail:x:12:
man:x:15:
dialout:x:18:
floppy:x:19:
games:x:20:
tape:x:33:
video:x:39:
ftp:x:50:
lock:x:54:
audio:x:63:
users:x:100:
nobody:x:65534:
utmp:x:22:
utempter:x:35:
dbus:x:81:
input:x:104:
kvm:x:36:
render:x:105:
sgx:x:106:
systemd-journal:x:190:ec2-user
systemd-network:x:192:
```

```
systemd-journal:x:190:ec2-user
systemd-network:x:192:
systemd-oom:x:999:
systemd-resolve:x:193:
ssh_keys:x:998:
sshd:x:74:
rpc:x:32:
libstoragemgmt:x:997:
systemd-coredump:x:996:
systemd-timesync:x:995:
chrony:x:994:
ec2-instance-connect:x:993:
stapusr:x:156:
stapsys:x:157:
stapdev:x:158:
stapunpriv:x:159:stapunpriv
rpcuser:x:29:
tcpdump:x:72:
screen:x:84:
ec2-user:x:1000:
ram:x:1001:
[root@ip-172-31-31-108 ec2-user]#
```

4) **/etc/gshadow** : Store group password and members list.

```
14m7x120017  
[root@ip-172-31-31-108 ec2-user]# cat /etc/gshadow  
root:::  
bin:::  
daemon:::  
sys:::  
adm:::ec2-user  
tty:::  
disk:::  
lp:::  
mem:::  
kmem:::  
wheel:::ec2-user  
cdrom:::  
mail:::  
man:::  
dialout:::  
floppy:::  
games:::  
tape:::  
video:::  
ftp:::  
lock:::  
audio:::  
users:::  
nobody:::  
utmp:!:::  
utempter:!:::  
dbus:!:::  
input:!*::  
kvm:!*::  
render:!*::  
sgx:!*::  
systemd-journal:!*::ec2-user  
systemd-network:!*::  
systemd-oom:!*::  
systemd-resolve:!*::  
ssh_keys:!:::  
sshd:!:::  
rpc:!:::  
libstoragemgmt:!*:::
```

```
libstoragegmt:*::
systemd-coredump:*::
systemd-timesync:*::
chrony:::
ec2-instance-connect:::
stapusr:*::
stapsys:*::
stapdev:*::
stapunpriv:*::stapunpriv
rpcuser:::
tcpdump:::
screen:::
ec2-user:::
ram:::
[root@ip-172-31-31-108 ec2-user]# cat /etc/gshadow
```

To modify User :

Syntax : usermod username

```
[root@ip-172-31-31-108 ec2-user]# usermod ram
usermod: no options
Usage: usermod [options] LOGIN

Options:
  -b, --badnames          allow bad names
  -c, --comment COMMENT   new value of the GECOS field
  -d, --home HOME_DIR     new home directory for the user account
  -e, --expiredate EXPIRE_DATE set account expiration date to EXPIRE_DATE
  -f, --inactive INACTIVE  set password inactive after expiration
                           to INACTIVE
  -g, --gid GROUP          force use GROUP as new primary group
  -G, --groups GROUPS      new list of supplementary GROUPS
  -a, --append             append the user to the supplemental GROUPS
                           mentioned by the -G option without removing
                           the user from other groups
  -h, --help              display this help message and exit
  -l, --login NEW_LOGIN    new value of the login name
  -L, --lock              lock the user account
  -m, --move-home         move contents of the home directory to the
                           new location (use only with -d)
  -o, --non-unique         allow using duplicate (non-unique) UID
  -p, --password PASSWORD  use encrypted password for the new password
  -R, --root CHROOT_DIR    directory to chroot into
  -P, --prefix PREFIX_DIR  prefix directory where are located the /etc/* files
  -s, --shell SHELL        new login shell for the user account
  -u, --uid UID            new UID for the user account
  -U, --unlock            unlock the user account
  -v, --add-subuids FIRST-LAST add range of subordinate uids
  -V, --del-subuids FIRST-LAST remove range of subordinate uids
  -w, --add-subgids FIRST-LAST add range of subordinate gids
  -W, --del-subgids FIRST-LAST remove range of subordinate gids
  -Z, --selinux-user SEUSER new SELinux user mapping for the user account
```

options :

-u : user id

Syntax : usermod -u new userid username

```
tcpdump:x:72:72:/:/sbin/nologin
ec2-user:x:1000:1000:EC2 Default User:/home/ec2-user:/bin/bash
ram:x:1001:1001:/:/home/ram:/bin/bash
[root@ip-172-31-31-108 ec2-user]# usermod -u 1111 ram
```

```
tcpdump:x:72:72:/:/sbin/nologin
ec2-user:x:1000:1000:EC2 Default User:/home/ec2-user:/bin/bash
ram:x:1111:1001:/:/home/ram:/bin/bash
[root@ip-172-31-31-108 ec2-user]#
```

-g : primary group

Syntax : usermod -g new groupid username


```
ec2-user:x:1000:1000:EC2 Default User:/home/ec2-user:/bin/bash
ram:x:1111:1001::/home/ram:/bin/bash
[root@ip-172-31-31-108 ec2-user]#
```

```
ec2-user:x:1000:1000:EC2 Default User:/home/ec2-user:/bin/bash
ram:x:1111:1000::/home/ram:/bin/bash
[root@ip-172-31-31-108 ec2-user]#
```

-c : comment

Syntax : usermod -c new "Discription(comment)" username

```
tcpdump:x:72:72:::/sbin/nologin
ec2-user:x:1000:1000:EC2 Default User:/home/ec2-user:/bin/bash
ram:x:1111:1000:This is standard user:/home/ram:/bin/bash
[root@ip-172-31-31-108 ec2-user]#
```

-s :shell type

```
ec2-user:x:1000:1000:EC2 Default User:/home/ec2-user:/bin/bash
ram:x:1111:1000:This is standard user:/home/ram:/bin/bash
[root@ip-172-31-31-108 ec2-user]#
```

```
ec2-user:x:1000:1000:EC2 Default User:/home/ec2-user:/bin/bash
ram:x:1111:1000:This is standard user:/home/ram:/bin/sh
[root@ip-172-31-31-108 ec2-user]#
```

- G : secondary group

-l : login name or rename username

Syntax : usermod -l newname username

```
ec2-user:x:1000:1000:EC2 Default User:/home/ec2-user:/bin/bash
ram:x:1111:1000:This is standard user:/home/ram:/bin/sh
[root@ip-172-31-31-108 ec2-user]#
```

```
ec2-user:x:1000:1000:EC2 Default User:/home/ec2-user:/bin/bash
sham:x:1111:1000:This is standard user:/home/ram:/bin/sh
[root@ip-172-31-31-108 ec2-user]#
```

-L : lock user password

-U : Unlock user password

To Remove user :

syntax : `userdel username`

`userdel -r username` : to remove the user and their directory.