

# Permission

## ❖ Types :

1. **Read** : To open and view
2. **Write** : To update, modify, delete the files.
3. **Execute** : To run all files accordingly.

## ❖ Set permission in four categories :

1. **Owner (u)** : The users who owns the files or directory.
2. **Group (g)** : The users who are the members of the group.
3. **Others(o)** : The users who are not the part of the group and file.
4. **All (a)** : For all.

## ❖ Represented by Symbols :

1. **r** : Indicates read permission.
2. **w** : Indicates write permission.
3. **x** : Indicates write permission.
4. **\_** : Indicates no permission.

## ❖ Types Of the files :

### 1) Ordinary File /Regular File:

- It Start with **\_**.
- It contains data.
- Store data like text or images.

### 2) Directory File :

- Contains Files and folders.
- It can store the location of another file.

### 3) Link file :

- **Hard Link** : It is the mirror image of the original file.  
if we delete the original file the mirror image remains.
- **Soft Link** : It is opposite to the hard link.

**It contains no data.**

**4) Named pipe file :**

- **It start with the p.**
- **It is used to establish communication between two unrelated files.**
- **It present in a /run folder.**

**5) Socket file:**

- **It start with the s.**
- **Communication between two process.**
- **Present in /run folder.**

**6) Character file :**

- **It start with the c.**
- **Store data character by character.**
- **It present in /dev folder.**

**7) Block device file :**

- **It start with the b.**
- **Access to blocks.**
- **It present in /dev folder.**