



Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than $\lfloor n / 2 \rfloor$ times. You may assume that the majority element always exists in the array.

Example 1:

Input: `nums = [3,2,3]`

Output: 3

Example 2:

Input: `nums = [2,2,1,1,1,2,2]`

Output: 2

Constraints:

- `n == nums.length`
- `1 <= n <= 5 * 104`
- `-231 <= nums[i] <= 231 - 1`

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 #include <stdlib.h>
3
4 int main() {
5     int n;
6
7     if (scanf("%d", &n) != 1) {
8         return 0;
9     }
10
11     int count = 0;
12     int candidate = 0;
13     int current_num;
14
15     for (int i = 0; i < n; i++) {
16         if (scanf("%d", &current_num) != 1) {
17             break;
18         }
19
20         if (count == 0) {
21             candidate = current_num;
22         }
23
24         if (current_num == candidate) {
25             count++;
26         } else {
27             count--;
28         }
29     }
30     printf("%d\n", candidate);
31     return 0;
32 }
33
```

Check

	Input	Expected	Got	
✓	3	3	3	✓
	3 2 3			

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)

