



Given two arrays `array_One[]` and `array_Two[]` of same size `N`. We need to first rearrange the arrays such that the sum of the product of pairs (1 element from each) is minimum. That is $\text{SUM}(A[i] * B[i])$ for all `i` is minimum.

For example:

Input	Result
3	28
1	
2	
3	
4	
5	
6	

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2  #include <stdlib.h>
3
4  int compare_asc(const void *a, const void *b) {
5      long long x = *(long long*)a;
6      long long y = *(long long*)b;
7      if (x > y) return 1;
8      if (x < y) return -1;
9      return 0;
10 }
11
12 int compare_desc(const void *a, const void *b) {
13     long long x = *(long long*)a;
14     long long y = *(long long*)b;
15     if (x < y) return 1;
16     if (x > y) return -1;
17     return 0;
18 }
19
20 int main() {
21     int n;
22     scanf("%d", &n);
23
24     long long a[n], b[n];
25     for (int i = 0; i < n; i++) {
26         scanf("%lld", &a[i]);
27     }
28     for (int i = 0; i < n; i++) {
29         scanf("%lld", &b[i]);
30     }
31
32     qsort(a, n, sizeof(long long), compare_asc);
33     qsort(b, n, sizeof(long long), compare_desc);
34
35     long long min_product_sum = 0;
36     for (int i = 0; i < n; i++) {
37         min_product_sum += a[i] * b[i];
38     }
39
40     printf("%lld\n", min_product_sum);
41     return 0;
42 }
```

Check

	Input	Expected	Got	
✓	3 1 2 3 4 5 6	28	28	✓
✓	4 7 5 1 2 1 3 4 1	22	22	✓
✓	5 20 10 30 10 40 8 9 4 3 10	590	590	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)