



Assume you are an awesome parent and want to give your children some cookies. But, you should give each child at most one cookie.

Each child i has a greed factor $g[i]$, which is the minimum size of a cookie that the child will be content with; and each cookie j has a size $s[j]$. If $s[j] \geq g[i]$, we can assign the cookie j to the child i , and the child i will be content. Your goal is to maximize the number of your content children and output the maximum number.

Example 1:

Input:

```
3
1 2 3
2
1 1
```

Output:

```
1
```

Explanation: You have 3 children and 2 cookies. The greed factors of 3 children are 1, 2, 3.

And even though you have 2 cookies, since their size is both 1, you could only make the child whose greed factor is 1 content.

You need to output 1.

Constraints:

$1 \leq g.length \leq 3 \cdot 10^4$

$0 \leq s.length \leq 3 \cdot 10^4$

$1 \leq g[i], s[j] \leq 2^{31} - 1$

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 #include <stdlib.h>
3
4 int compare(const void *a, const void *b) {
5     long long diff = (long long)*(int*)a - (long long)*(int*)b;
6     return (diff > 0) - (diff < 0);
7 }
8
9 int main() {
10     int n, m;
11     scanf("%d", &n);
12     int g[n];
13     for (int i = 0; i < n; i++) {
14         scanf("%d", &g[i]);
15     }
16     scanf("%d", &m);
17     int s[m];
18     for (int i = 0; i < m; i++) {
19         scanf("%d", &s[i]);
20     }
21
22     qsort(g, n, sizeof(int), compare);
23     qsort(s, m, sizeof(int), compare);
24
25     int child_i = 0, cookie_j = 0;
26     while (child_i < n && cookie_j < m) {
27         if (s[cookie_j] >= g[child_i]) {
28             child_i++;
29         }
30         cookie_j++;
31     }
32
33     printf("%d\n", child_i);
34     return 0;
35 }
```

Check

	Input	Expected	Got	
✓	2	2	2	✓
	1 2			
	3			
	1 2 3			

Passed all tests! ✓

[Back to Course](#)