

# POE Secondary Belt Cleaner

## Reliable Secondary Belt Cleaner

The Flexco P-Type® Secondary Belt Cleaner is compact and designed to be positioned just off the head pulley to remove carryback from the belt. Stand alone, or when used in conjunction with a precleaner, the P-Type cleaner is a reliable choice for maintaining a highly efficient cleaning system.



### Features and Benefits

- Cleaning efficiency of metal blades.
- Works with Flexco mechanical splices.
- A complete cleaning system.
- Fits most conveyor structures.

### Specifications and Guidelines

- **Maximum Belt Speed**  
1000 FPM (5 m/s)
- **Temperature Rating**  
-30° F to 180° F (-35° C to 82° C)
- **Usable Blade Wear Length**  
3/8" (9 mm)
- **Available for Belt Widths**  
18" to 72" (450 to 1800mm)
- **Horizontal Clearance Required**  
4" (100mm)
- **Vertical Clearance Required**  
8" (200mm)
- **Blade Material**  
Impact resistant, long-lasting tungsten carbide (C-Tip for mechanical fasteners)

### Ordering Information

<i>P-Type OE Secondary with C-Tips*</i>		
Belt Width	Item code	Ordering Number
600	90924	POE-600
800	90925	POE-800
1000	90926	POE-1000
1200	90927	POE-1200
1350	90928	POE-1400
1500	90929	POE-1500
1800	90930	POE-1800

<i>Replacement Tips</i>	
Ordering Number	Item Code
ICT6	74535

\* For higher sizes contact Flexco representative/distributor

240 Macpherson Road • #02-01 • Singapore 348574  
Tel: +65-6484-1533 • Fax: +65-6484-1531 • E-mail: [asiasales@flexco.com](mailto:asiasales@flexco.com)

Visit [www.flexco.com](http://www.flexco.com) for other Flexco locations and products.

©2019 Flexible Steel Lacing Company. 01/23/20

[www.flexco.com](http://www.flexco.com)

