

MHS HD Secondary Belt Cleaner

Installation, Operation and Maintenance Manual



MHS with SST Tensioners



MHS with MST Tensioners



MHS with SAT2 Tensioners

MHS HD Secondary Cleaner

Serial Number: _____

Purchase Date: _____

Purchased From: _____

Installation Date: _____

Serial number information can be found on the Serial Number Label included in the Information Packet found in the cleaner carton.

This information will be helpful for any future inquiries or questions about belt cleaner replacement parts, specifications or troubleshooting.

Table of Contents

Section 1 - Important Information	4
1.1 General Introduction	4
1.2 User Benefits	4
1.3 Service Option	4
Section 2 - Safety Considerations and Precautions	5
2.1 Stationary Conveyors.....	5
2.2 Operating Conveyors.....	5
Section 3 - Pre-Installation Checks and Options.....	6
3.1 Checklist	6
3.2 Optional Installation Accessories.....	7
Section 4 - Installation Instructions.....	8
4.1 Installation Instructions - MHS with SST Tensioner	8
4.2 Push-up Tensioning Instructions (SST).....	10
4.3 Installation Instructions - MHS with MST Tensioner.....	11
4.4 Installation Instructions - MHS with SAT2 Tensioner.....	14
4.5 Push-up Tensioning Instructions for SAT2	16
Section 5 - Pre-Operation Checklist and Testing.....	17
5.1 Pre-Op Checklist	17
5.2 Test Run the Conveyor	17
Section 6 - Maintenance.....	18
6.1 New Installation Inspection.....	18
6.2 Routine Visual Inspection.....	18
6.3 Routine Physical Inspection	18
6.4 Maintenance Log.....	19
6.5 Cleaner Maintenance Checklist.....	20
Section 7 - Troubleshooting	21
Section 8 - Specs and CAD Drawings.....	22
8.1 Specs and Guidelines	22
8.2 CAD Drawing - MHS Cleaners with SST Tensioners	23
8.3 CAD Drawing - MHS Cleaners with MST Tensioners	24
8.4 CAD Drawing - MHS Cleaners with SAT2 Tensioners	25
Section 9 - Replacement Parts	26
9.1 Replacement Parts - MHS.....	26
9.2 Replacement Parts - Optional MST and SAT2 Tensioners.....	27
9.3 Replacement Parts - MHS Stainless Steel.....	28
Section 10 - Other Flexco Conveyor Products.....	31

Section 1 - Important Information

1.1 General Introduction

We at Flexco are very pleased that you have selected an MHS HD Secondary Cleaner for your conveyor system.

This manual will help you to understand the operation of this product and assist you in making it work up to its maximum efficiency over its lifetime of service.

It is essential for safe and efficient operation that the information and guidelines presented be properly understood and implemented. This manual will provide safety precautions, installation instructions, maintenance procedures and troubleshooting tips.

If, however, you have any questions or problems that are not covered, please contact your field representative or our Customer Service Department:

Customer Service: +65-6484-1533

Visit www.flexco.com for other Flexco locations and products.

Please read this manual thoroughly and pass it on to any others who will be directly responsible for installation, operation and maintenance of this cleaner. While we have tried to make the installation and service tasks as easy and simple as possible, **it does however require correct installation and regular inspections and adjustments to maintain top working condition.**

1.2 User Benefits

Correct installation and regular maintenance will provide the following benefits for your operation:

- Reduced conveyor downtime
- Reduced man-hour labor
- Lower maintenance budget costs
- Increased service life for the belt cleaner and other conveyor components

1.3 Service Option

The MHS HD Secondary Cleaner is designed to be easily installed and serviced by your on-site personnel. However, if you would prefer complete turn-key factory service, please contact your local Flexco Field Representative.

Section 2 - Safety Considerations and Precautions

Before installing and operating the MHS HD Secondary Cleaner, it is important to review and understand the following safety information.

There are set-up, maintenance and operational activities involving both **stationary** and **operating** conveyors. Each case has a safety protocol.

2.1 Stationary Conveyors

The following activities are performed on stationary conveyors:

- Installation
- Blade replacement
- Repairs
- Tension adjustments
- Cleaning

DANGER

It is imperative that OSHA/MSHA Lockout/Tagout (LOTO) regulations, 29 CFR 1910.147, be followed before undertaking the preceding activities. Failure to use LOTO exposes workers to uncontrolled behavior of the belt cleaner caused by movement of the conveyor belt. Severe injury or death can result.

Before working:

- Lockout/Tagout the conveyor power source
- Disengage any takeups
- Clear the conveyor belt or clamp securely in place

WARNING

Use Personal Protective Equipment (PPE):

- Safety eyewear
- Hardhats
- Safety footwear

Close quarters, springs and heavy components create a worksite that compromises a worker's eyes, feet and skull.

PPE must be worn to control the foreseeable hazards associated with conveyor belt cleaners. Serious injuries can be avoided.

2.2 Operating Conveyors

There are two routine tasks that must be performed while the conveyor is running:

- Inspection of the cleaning performance
- Dynamic troubleshooting

DANGER

Every belt cleaner is an in-running nip hazard. Never touch or prod an operating cleaner. Cleaner hazards cause instantaneous amputation and entrapment.

WARNING

Belt cleaners can become projectile hazards. Stay as far from the cleaner as practical and use safety eyewear and headgear. Missiles can inflict serious injury.

WARNING

Never adjust anything on an operating cleaner. Unforseeable belt projections and tears can catch on cleaners and cause violent movements of the cleaner structure. Flailing hardware can cause serious injury or death.

Section 3 - Pre-installation Checks and Options


3.1 Checklist

- Check that the cleaner size is correct for the beltline width
- Check the belt cleaner carton and make sure all the parts are included
- Review the “Tools Needed” list on the top of the installation instructions
- Check the conveyor site:
 - Will the cleaner be installed on a chute
 - Is the install on an open head pulley requiring mounting structure (see 3.2 - Optional Installation Accessories)

Section 3 - Pre-installation Checks and Options


3.2 Optional Installation Accessories

Versatile, adjustable brackets that can be mounted on the conveyor structure so the MHS HD Secondary Cleaner can be quickly and easily bolted into place. Pole extenders are also available for wide, non-standard conveyor structures.




76071
SST Standard
Mounting Bracket Kit
(for SST Tensioner)

- For most secondary cleaner installs.
- 325mm W x 388mm L
(13" W x 15 1/2" L)



76072
SST Long
Mounting Bracket Kit
(for SST Tensioner)

- For installations that require extra length legs.
- 325mm W x 538mm L
(13" W x 21 1/2" L)




76073
SST Optional Top Angle Kit
(for SST Tensioner)

- Used with both standard and long mounting bracket kits for additional mounting options.
- 325mm (13") L

76024

Pole Extender Kit (includes 2 pole extenders)


- For cleaner sizes 1800mm (72") and larger
- Provides 750mm (30") of extended pole length



Optional Mounting Kits (includes 2 brackets/bars)			
Description	Ordering Number	Item Code	Wt. Kg.
Standard Mounting Bracket Kit*	SSTSMB	76071	15.6
Long Mounting Bracket Kit*	SSTLMB	76072	19.7
Optional Top Angle Kit*	SSTOTA	76073	4.8
Pole Extender Kit	MAPEK	76024	9.0
MST Drop Bracket Kit	MSTDDB	79434	12.0

*Hardware Included

Lead time: 1 working day




79434


MST Drop Bracket Kit (includes 2 brackets)
(for MST Tensioner only)

Section 4.1 - Installation Instructions

MHS HD with SST Standard & Reversing Secondary Cleaners








Physically lock out and tag the conveyor at the power source before you begin cleaner installation.






1. **Install the spring tensioner mounting bases.** (For push-up tensioning refer to additional instructions on Page 10.) Clamp the mounting base into position so the top flange of the base is aligned with the belt (Fig. 1a). Bolt or weld the mounting base in place. Locate and install the mounting base on the opposite side. Adjust the tension nuts on each side so the center of the torsion pole mount is 225mm (9") below the belt line.

NOTE: For chute mounting, a belt location line must be drawn on the chute wall so the mounting base can be aligned with the belt (Fig. 1b). Cut access holes as needed (Fig. 1c).





2. **Install the pole.** Slide the pole into one torsion pole mount as far as needed and locate the other end into the opposite mount (Fig. 2a). If there is not enough space, remove one of the torsion pole mounts from the mounting base, slide the pole through the mounting base and reassemble (Fig. 2b).



3. **Set the blade angle.** Center the pole/blades on the belt. **For MHS Standard:** Rotate the pole until the tips align with the white “MHS Standard” side of the tip setup gauge provided (Fig. 3a). **For MHS Reversing:** Rotate the pole until the tips are perpendicular to the belt, using the black “MHS Reversing” side of the tip setup gauge provided (Fig. 3b). Tighten the two locking bolts on each torsion pole mount to lock the pole in place (Fig. 3c). There should be no blade-to-belt contact while locking the pole in the correct position. If contact occurs, double check the dimension from Step 1.
4. **Set the blade tension.** Loosen the top tension jam nuts on both sides. Turn the tension nuts until the correct spring compression is reached (Fig. 4). Spring compression is determined by spring length. See the chart at right for the correct spring length for your belt width.




Fig. 4

Shading indicates preferred spring option. Measure from the top of the flat washer to the mounting base to determine spring length.

SST Tensioner Spring Length Chart

Blade Width		White Spring		Silver Spring		Black Spring		Gold Spring	
mm	in.	mm	in.	mm	in.	mm	in.	mm	in.
450	18	86	3 3/8	102	4	N/A	N/A	N/A	N/A
600	24	79	3 1/8	98	3 7/8	N/A	N/A	N/A	N/A
750	30	73	2 7/8	95	3 3/4	N/A	N/A	N/A	N/A
900	36	N/A	N/A	95	3 3/4	98	3 7/8	N/A	N/A
1050	42	N/A	N/A	92	3 5/8	95	3 3/4	N/A	N/A
1200	48	N/A	N/A	89	3 1/2	92	3 5/8	N/A	N/A
1350	54	N/A	N/A	86	3 3/8	92	3 5/8	95	3 3/4
1500	60	N/A	N/A	83	3 1/4	89	3 1/2	95	3 3/4
1800	72	N/A	N/A	N/A	N/A	86	3 3/8	92	3 5/8
2100	84	N/A	N/A	N/A	N/A	79	3 1/8	89	3 1/2
2400	96	N/A	N/A	N/A	N/A	N/A	N/A	89	3 1/2
2700	108	N/A	N/A	N/A	N/A	N/A	N/A	86	3 3/8
3000	120	N/A	N/A	N/A	N/A	N/A	N/A	86	3 3/8





Fig. 5

5. **Set adjusting rod sleeve.** After setting the blade tension, screw the adjusting rod sleeve into the UHMW bushing until 38mm (1-1/2") is showing (Fig. 5). Tighten the adjusting rod sleeve jam nut.
6. **Test run the cleaner and inspect the cleaning performance.** If vibration occurs or more cleaning efficiency is desired, increase the blade tension by making 3mm (1/8") compression adjustments on the tension springs.

Section 4.2 - Push-up Tensioning Instructions

MHS HD Secondary Cleaner



1. **Reconfigure the standard pull-up tensioner to the push-up style.** Remove the 3 tension nuts, the flat washer, 2 bushings, the spring, the sleeve and the hat bracket; reassemble (Fig. 1) with 2 tension nuts, the flat washer, 2 bushings, the spring and the hat bracket on the upper end of the adjusting rod. Add washer (from instruction packet) and 3rd tension nut to bottom of adjusting rod.

2. **Install the tensioner mounting bases.** Mount the bases to the structure or chute so that the tops of the base legs are 83mm (3-1/4\") below the belt (Fig. 1).

3. **Install the cleaner pole and set the blade angle.** Follow the installation steps from the cleaner instructions on Page 8. **Note:** be sure the lock bolts on the torsion pole mount have been securely tightened to lock the pole in place before moving to Step 4.



4. **Set the blade tension.** Remove the bottom tension nut and washer from the adjusting rod. Turn the 2 upper tension nuts until the spring is compressed to the length shown on the Spring Length Chart below. Tighten the 2 tension nuts together to prevent loosening.

SST Tensioner Spring Length Chart

Blade Width		White Spring		Silver Spring		Black Spring		Gold Spring	
mm	in.	mm	in.	mm	in.	mm	in.	mm	in.
450	18	86	3 3/8	102	4	N/A	N/A	N/A	N/A
600	24	79	3 1/8	98	3 7/8	N/A	N/A	N/A	N/A
750	30	73	2 7/8	95	3 3/4	N/A	N/A	N/A	N/A
900	36	N/A	N/A	95	3 3/4	98	3 7/8	N/A	N/A
1050	42	N/A	N/A	92	3 5/8	95	3 3/4	N/A	N/A
1200	48	N/A	N/A	89	3 1/2	92	3 5/8	N/A	N/A
1350	54	N/A	N/A	86	3 3/8	92	3 5/8	95	3 3/4
1500	60	N/A	N/A	83	3 1/4	89	3 1/2	95	3 3/4
1800	72	N/A	N/A	N/A	N/A	86	3 3/8	92	3 5/8
2100	84	N/A	N/A	N/A	N/A	79	3 1/8	89	3 1/2
2400	96	N/A	N/A	N/A	N/A	N/A	N/A	89	3 1/2
2700	108	N/A	N/A	N/A	N/A	N/A	N/A	86	3 3/8
3000	120	N/A	N/A	N/A	N/A	N/A	N/A	86	3 3/8

Shading indicates preferred spring option.


NOTE: Measure from the top of the flat washer to the mounting base to determine spring length.




5. **Replace the sleeve.** Position the sleeve over the adjusting rod and turn it until it is in the middle of the bushing. Replace the bottom tension nut and tighten until it locks the sleeve in place (Fig. 5).

Section 4.3 - Installation Instructions

MHS HD with MST Standard & Reversing Secondary Cleaners for belts 450-1800mm (18" - 72")






Physically lock out and tag the conveyor at the power source before you begin cleaner installation.



- 1. Install the spring tensioner mounting bases.** The preferred mounting orientation relative to belt direction is shown in Fig. 1a; if necessary the tensioners may be mounted with the opposite belt direction. Clamp the mounting base into position so the top flange is 95mm (3-3/4") below the bottom of the belt. Bolt or weld the mounting base in place. Locate and install the mounting base on the opposite side. Remove the tensioner lock pins and turn the adjustment nuts to fully lower the pole mount.

Note: For chute mounting, a belt location line must be drawn on the chute wall so the mounting base can be aligned 95mm (3-3/4") below the belt (Fig. 1b). Cut access holes as needed.



Section 4.3 - Installation Instructions

MHS HD with MST Standard & Reversing Secondary Cleaners

2. Install the pole.

Remove pole clamp bolt and lift or remove top half of pole clamp from the tensioner on the near side of the conveyor, and loosen pole clamp bolt on the opposite side. Slide the pole across the conveyor and through the loosened pole clamp, then place the near end of pole in remaining pole clamp (Fig. 2). Replace top half of pole clamp, reinstall the bolt and tighten both bolts finger tight.




Fig. 2

3. **Set the blade angle.** Center the pole/blades on the belt. **For MHS Standard:** Rotate the pole until the tips align with the white “MHS Standard” side of the tip setup gauge provided (Fig. 3a). **For MHS Reversing:** Rotate the pole until the tips are perpendicular to the belt, using the black “MHS Reversing” side of the tip setup gauge provided (Fig. 3b). Tighten the pole clamp bolt on each pole mount to lock the pole in place. There should be no blade-to-belt contact while locking the pole in the correct position. If contact occurs, double check the dimension from Step 1.




Fig. 3a - MHS Standard




Fig. 3b - MHS Reversing




Fig. 4

4. **Ensure the tensioner travels freely.** Pull up and push down on each pole end to ensure the pole mount travels freely on the guide pole. If there is any sign of binding, loosen the bolts on the mounting base and pivot until the tensioner moves freely (Fig. 4). Retighten bolts.
5. **Set the blade tension.** Turn the adjustment nuts until the correct spring compression is reached (Fig. 5). Spring compression is determined by the spring length. See the chart below for the correct spring length for your belt width. Replace locking pins.




Fig. 5

MST Tensioner Spring Length Chart


Blade Width		2 White Springs		2 Silver Springs		2 Black Springs	
mm	in.	mm	in.	mm	in.	mm	in.
450	18	73	2 7/8	86	3 3/8	89	3 1/2
600	24	67	2 5/8	86	3 3/8	86	3 3/8
750	30	60	2 3/8	83	3 1/4	86	3 3/8
900	36	54	2 1/8	79	3 1/8	83	3 1/4
1050	42	48	1 7/8	76	3	79	3 1/8
1200	48	N/A	N/A	73	2 7/8	79	3 1/8
1350	54	N/A	N/A	73	2 7/8	76	3
1500	60	N/A	N/A	70	2 3/4	73	2 7/8
1800	72	N/A	N/A	64	2 1/2	70	2 3/4

Shading indicates preferred spring option.

Section 4.3 - Installation Instructions


MHS HD with MST Standard & Reversing Secondary Cleaners

6. **Secure guide poles.** Ensure the ends of the guide pole extend at least 12mm (1/2") outside top and bottom guide bearings. If adjustment is necessary, loosen guide pole set screws and lock nuts, then tap guide pole up or down. Tighten guide pole set screws and lock nuts (Fig. 6).
7. **Check movement of each tensioner** to ensure they do not bind up. If there are binding concerns, refer to Step 4.
8. **Test run the cleaner and inspect the cleaning performance.** If vibration occurs or more cleaning efficiency is desired, increase the blade tension by making 3mm (1/8") compression adjustments on the tension springs.





Section 4.3 - Installation Instructions

MHS with SAT2 Tensioner




Physically lock out and tag the conveyor at the power source before you begin cleaner installation.



- 1. Install the air/water tensioner mounting bases.** Clamp the mounting base into position so the flange is even with the belt (Fig. 1a). Bolt the mounting base in place and adjust threaded rod nuts 38mm (1-1/2") down from the top of the threaded rod. Locate and install the mounting base on the opposite side and adjust the threaded rod nuts down on that side as well.


NOTE: For chute mounting, a belt location line must be drawn on the chute wall so the mounting base can be aligned with the belt (Fig. 1b). Cut access holes as needed.

NOTE: If push-up tensioning is needed because of space restriction or obstruction, follow steps on Page 16 to reconfigure the tensioners.



Section 4.3 - Installation Instructions

Fig. 2



2. **Install the pole.** Slide the pole into one torsion pole mount as far as needed and locate the other end into the opposite mount (Fig. 2). If there is not enough space, remove one of the mounting bases, slide the pole through the torsion pole mount, and remount the base.

Fig. 3a





Fig. 3b



3. **Set the blade angle.** Center the pole/blades on the belt. **For MHS Standard:** Rotate the pole until the tips align with the white "MHS Standard" side of the tip setup gauge provided (Fig. 3a). **For MHS Reversing:** Rotate the pole until the tips are perpendicular to the belt, using the black "MHS Reversing" side of the tip setup gauge provided (Fig. 3b). Tighten the two locking bolts on each torsion pole mount to lock the pole in place (Fig. 3c). There should be no blade-to-belt contact while locking the pole in the correct position. If contact occurs, double check the dimension from Step 1.

4. **Connect the supply lines and set tension pressure.** With the parts supplied, attach a line to each air bag and run the lines to the outlet side of the control box (Fig. 4). **NOTE:** Be sure lines are safely away from the belt. Connect the line from the inlet side of the box to the site's supply or air tank. Test the connections for leaks and set the pressure per the chart below. Pressure may be reduced to suit application.




Fig. 4

SAT2 Tensioner Pressure Chart


Blade Width		Blades	Pressure	
mm	in.		psi	kPa
450	18"	3	15#	103
600	24"	4	19#	131
750	30"	5	23#	159
900	36"	6	27#	186
1050	42"	7	31#	214
1200	48"	8	35#	241
1350	54"	9	39#	269
1500	60"	10	43#	296
1800	72"	12	51#	352
2100	84"	14	59#	407
2400	96"	16	67#	462

5. **Test run the cleaner and inspect the cleaning performance.** If vibration occurs, increase tip layback by a small amount (approx. 3 degrees).


Section 4.4 - Push-up Tensioning Instructions

MHS with SAT2 Tensioner

1. **Disassemble guide kit.** Remove nuts and washers from both sides of tensioner (Fig. 1).
2. **Disassemble upper mounting plate and air bag.** Remove and save bushing nut. Remove and discard upper mounting plate. Remove (unscrew) and save air bag, threaded insert and support plate (Fig. 2). **Optional:** Remove guide bushings. It will not affect the tensioner if these are left in place.
3. **Remove and save top hat bracket and its hardware** (Fig. 3).
4. **Flip over PAT mounting bracket assembly.** The two flanges are now at the bottom.



5. **Reassemble the SAT2 Tensioner.** Remove three screws from air bag support plate (Fig. 4a). Turn the threaded insert into the support plate. Also turn part of the threaded insert into the hole on pole mount. (Fig. 4b). Ensure 6mm 1/4" of threaded insert is still exposed, then turn the air bag onto the threaded insert and tighten (Fig. 5).
6. **Reassemble top hat bracket.** Ensure bracket is resting on flanges of mounting bracket (Fig. 6).
7. **Slide pole mount/threaded rods/air bag assembly down** with hose barb through hole in top hat bracket and reinstall bushing nut (Fig. 6).
8. **Complete installation** by following the steps on page 15.



Section 5 - Pre-Operation Checklist and Testing

5.1 Pre-Op Checklist

- Recheck that all fasteners are tightened properly
- Add pole caps
- Apply all supplied labels to the cleaner
- Check the blade location on the belt
- Be sure that all installation materials and tools have been removed from the belt and the conveyor area

5.2 Test Run the Conveyor

- Run the conveyor for at least 15 minutes and inspect the cleaning performance
- Check the tensioner spring for recommended length (proper tensioning)
- Make adjustments as necessary

NOTE: Observing the cleaner when it is running and performing properly will help to detect problems or when adjustments are needed later.

Section 6 - Maintenance

Flexco belt cleaners are designed to operate with minimum maintenance. However, to maintain superior performance some service is required. When the cleaner is installed a regular maintenance program should be set up. This program will ensure that the cleaner operates at optimal efficiency and problems can be identified and fixed before the cleaner stops working.

All safety procedures for inspection of equipment (stationary or operating) must be observed. The MHS Belt Cleaner operates at the discharge end of the conveyor and is in direct contact with the moving belt. Only visual observations can be made while the belt is running. Service tasks can be done only with the conveyor stopped and by observing the correct lockout/tagout procedures.

6.1 New Installation Inspection

After the new cleaner has run for a few days a visual inspection should be made to ensure the cleaner is performing properly. Make adjustments as needed.

6.2 Routine Visual Inspection (every 2-4 weeks)

A visual inspection of the cleaner and belt should look for:

- If spring length is the correct length for optimal tensioning
- If belt looks clean or if there are areas that are dirty
- If blade is worn out and needs to be replaced
- If there is damage to the blade or other cleaner components
- If fugitive material is built up on cleaner or in the transfer area
- If there is cover damage to the belt
- If there is vibration or bouncing of the cleaner on the belt
- If a snub pulley is used, a check should be made for material buildup on the pulley
- Significant signs of carryback

If any of the above conditions exist, a determination should be made on when the conveyor can be stopped for cleaner maintenance.

6.3 Routine Physical Inspection (every 6-8 weeks)

When the conveyor is not in operation and properly locked and tagged out, a physical inspection of the cleaner to perform the following tasks:

- Clean material buildup off of the cleaner blade and pole
- Closely inspect the blade for wear and any damage. Replace if needed.
- Ensure full blade to belt contact
- Inspect the cleaner pole for damage
- Inspect all fasteners for tightness and wear. Tighten or replace as needed.
- Replace any worn or damaged components
- Check the tension of the cleaner blade to the belt. Adjust the tension if necessary using the chart on the cleaner or the one on Page 8 (SST spring tensioner), Page 11 (MST spring tensioner or Page 14 (SAT2 air tensioner).
- When maintenance tasks are completed, test run the conveyor to ensure the cleaner is performing properly

Section 6 - Maintenance

6.4 Maintenance Log

Conveyor Name/No. _____

Date: _____ Work done by: _____ Service Quote # _____

Activity: _____

Date: _____ Work done by: _____ Service Quote # _____

Activity: _____

Date: _____ Work done by: _____ Service Quote # _____

Activity: _____

Date: _____ Work done by: _____ Service Quote # _____

Activity: _____

Date: _____ Work done by: _____ Service Quote # _____

Activity: _____

Date: _____ Work done by: _____ Service Quote # _____

Activity: _____

Date: _____ Work done by: _____ Service Quote # _____

Activity: _____

Section 6 - Maintenance

6.5 Cleaner Maintenance Checklist

Belt Cleaner: _____ Serial Number: _____

Beltline Information:

Beltline Number: _____ Belt Condition: _____

Belt Width: 18"☐ 24"☐ 30"☐ 36"☐ 42"☐ 48"☐ 54"☐ 60"☐ 72"☐ 84"☐ 96"☐
(450mm) (600mm) (750mm) (900mm) (1050mm) (1200mm) (1350mm) (1500mm) (1800mm) (2100mm) (2400mm)

Belt Speed: _____ fpm Belt Thickness: _____

Belt Splice _____ Condition of Splice _____ Number of splices _____ ☐ Skived ☐ Unskived

Material conveyed _____

Days per week run _____ Hours per day run _____

Blade Life:

Date blades installed: _____ Date blades inspected: _____ Estimated blade life: _____

Are blades making complete contact with belt? ☐ Yes ☐ No

Blade wear: LEFT _____ MIDDLE _____ RIGHT _____

Blade condition: ☐ Good ☐ Grooved ☐ Smiled ☐ Not contacting belt ☐ Damaged

Measurement of spring: Required _____ Currently _____

For SAT2 Tensioner only: Air/Nitrogen Pressure Required _____ Currently _____
Inspect SAT2 bags and lines

Was Cleaner Adjusted: ☐ Yes ☐ No

Pole Condition: ☐ Good ☐ Bent ☐ Worn

Lagging: ☐ Slide lag ☐ Ceramic ☐ Rubber ☐ Other ☐ None

Condition of lagging: ☐ Good ☐ Bad ☐ Other _____

Cleaner's Overall Performance:

(Rate the following 1 - 5, 1 = very poor - 5 = very good)

Appearance: ☐ Comments: _____

Location: ☐ Comments: _____

Maintenance: ☐ Comments: _____

Performance: ☐ Comments: _____

Other Comments: _____

Section 7 - Troubleshooting

Problem	Possible Cause	Possible Solutions
Vibration	Cleaner secure bolts not set	Ensure all locking nuts are tight (Loctite)
	Cleaner not set up correctly	Ensure cleaner set up properly (check tip angle with gauge) MHS Standard 1°-3° into belt; MHS Reversing and SAT2 perpendicular
	Belt tension too high	Ensure cleaner can conform to belt, or replace with alternate Flexco secondary cleaner
	Belt flap	Introduce hold-down roller to flatten belt
	Cleaner over-tensioned	Ensure cleaner is correctly tensioned
	Cleaner under-tensioned	Ensure cleaner is correctly tensioned
	Nylon bearing worn out or missing	Replace nylon bearing
Material buildup on cleaner	Cleaner not set up correctly	Ensure cleaner set up properly (1°-3° into belt)
	Buildup on chute	Ensure cleaner is not located too close to back of chute, allowing buildup
	Cleaner being overburdened	Introduce Flexco precleaner
	Excessive sticky material	Frequently clean unit of buildup
Damaged belt cover	Cleaner over-tensioned	Ensure cleaner is correctly tensioned
	Cleaner blade damage	Check blade for wear, damage and chips, replace where necessary
	Attack angle not correct	Ensure cleaner set up properly (check tip angle with gauge) MHS Standard 1°-3° into belt; MHS Reversing and SAT2 perpendicular
	Material buildup in chute	Frequently clean unit of buildup
Cleaner not conforming to belt	Cleaner not set up correctly	Ensure cleaner set up properly (check tip angle with gauge) MHS Standard 1°-3° into belt; MHS Reversing and SAT2 perpendicular
	Belt tension too high	Ensure cleaner can conform to belt (introduce hold-down roller), or replace with alternate Flexco secondary cleaner
	Belt flap	Introduce hold-down roller to flatten belt
	Cleaner cannot conform	Ensure cleaner can conform to belt (introduce hold-down roller), or replace with alternate Flexco secondary cleaner
Material passing cleaner	Cleaner not set up correctly	Ensure cleaner set up properly (check tip angle with gauge) MHS Standard 1°-3° into belt; MHS Reversing and SAT2 perpendicular
	Cleaner tension too low	Ensure cleaner is correctly tensioned
	Cleaner blade worn/damaged	Check blade for wear, damage and chips, replace where necessary
	Cleaner being overburdened	Introduce Flexco precleaner
	Belt flap	Introduce hold-down roller to flatten belt
	Belt worn or grooved	Introduce water spray pole
	Cleaner cannot conform	Ensure cleaner can conform to belt (introduce hold-down roller), or replace with alternate Flexco secondary cleaner
	Blade in backwards	Install blade correctly and set correct tension
Damage to mechanical fastener	Incorrect cleaner blade selection	Change blade type to accommodate fastener style (UC or UF)
	Belt not skived correctly	Spot and redo splice correctly, lowering the profile flush or below belt surface
	Blade angle incorrect	Reset with gauge
Missing material in belt center only	Cupped Belt	Install hold-down roller and reset blade angle with gauge
	Cleaner blade worn/damaged	Check blade for wear, damage and chips, replace where necessary
Missing material on outer edges only	Cupped Belt	Install hold-down roller and reset blade angle with gauge
	Cleaner blade worn/damaged	Check blade for wear, damage and chips, replace where necessary
MST Tensioners binding	Tensioners not aligned properly	Adjust mounting bases until tensioners travel without binding
	Material buildup on tensioner guide pole	Clean off guide pole



Section 8 - Specs and CAD Drawings

8.1 Specs and Guidelines

Pole Length Specifications*

CLEANER SIZE		BLADE WIDTH		POLE LENGTH		MAXIMUM CONVEYOR SPAN	
mm	in.	mm	in.	mm	in.	mm	in.
450	18	450	18	1800	72	1550	62
600	24	600	24	1950	78	1700	68
750	30	750	30	2100	84	1850	74
900	36	900	36	2250	90	2000	80
1050	42	1050	42	2400	96	2150	86
1200	48	1200	48	2550	102	2300	92
1350	54	1350	54	2700	108	2450	98
1500	60	1500	60	2850	114	2600	104
1800	72	1800	72	3150	126	2900	116
2100	84	2100	84	3450	138	3200	128
2400	96	2400	96	3750	150	3500	140

*For special extra long pole length requirements a Pole Extender Kit (#76024) is available that provides 30" (750mm) of extended pole length. See Page 7.
Pole Diameter - 73mm (2-7/8")



Clearance Guidelines for Installation

HORIZONTAL CLEARANCE REQUIRED		VERTICAL CLEARANCE REQUIRED	
mm	in.	mm	in.
100	4	245	10


SST Tensioner Spring Length Chart

Blade Width		White Spring		Silver Spring		Black Spring		Gold Spring	
mm	in.	mm	in.	mm	in.	mm	in.	mm	in.
450	18	86	3 3/8	102	4	N/A	N/A	N/A	N/A
600	24	79	3 1/8	98	3 7/8	N/A	N/A	N/A	N/A
750	30	73	2 7/8	95	3 3/4	N/A	N/A	N/A	N/A
900	36	N/A	N/A	95	3 3/4	98	3 7/8	N/A	N/A
1050	42	N/A	N/A	92	3 5/8	95	3 3/4	N/A	N/A
1200	48	N/A	N/A	89	3 1/2	92	3 5/8	N/A	N/A
1350	54	N/A	N/A	86	3 3/8	92	3 5/8	95	3 3/4
1500	60	N/A	N/A	83	3 1/4	89	3 1/2	95	3 3/4
1800	72	N/A	N/A	N/A	N/A	86	3 3/8	92	3 5/8
2100	84	N/A	N/A	N/A	N/A	79	3 1/8	89	3 1/2
2400	96	N/A	N/A	N/A	N/A	N/A	N/A	89	3 1/2
2700	108	N/A	N/A	N/A	N/A	N/A	N/A	86	3 3/8
3000	120	N/A	N/A	N/A	N/A	N/A	N/A	86	3 3/8

Shading indicates preferred spring option. Measure spring as shown below.

SST


Top of Washer to Mounting Base



MST Tensioner Spring Length Chart

Blade Width		2 White Springs		2 Silver Springs		2 Black Springs	
mm	in.	mm	in.	mm	in.	mm	in.
450	18	73	2 7/8	86	3 3/8	89	3 1/2
600	24	67	2 5/8	86	3 3/8	86	3 3/8
750	30	60	2 3/8	83	3 1/4	86	3 3/8
900	36	54	2 1/8	79	3 1/8	83	3 1/4
1050	42	48	1 7/8	76	3	79	3 1/8
1200	48	N/A	N/A	73	2 7/8	79	3 1/8
1350	54	N/A	N/A	73	2 7/8	76	3
1500	60	N/A	N/A	70	2 3/4	73	2 7/8
1800	72	N/A	N/A	64	2 1/2	70	2 3/4

Shading indicates preferred spring option. Measure spring as shown below.



MST

Bottom of Pole Mount to Bottom of Spring Support Plate


SAT2 Tensioner Pressure Chart

Blade Width		Blades	Pressure	
mm	in.		psi	kPa
450	18"	3	15#	103
600	24"	4	19#	131
750	30"	5	23#	159
900	36"	6	27#	186
1050	42"	7	31#	214
1200	48"	8	35#	241
1350	54"	9	39#	269
1500	60"	10	43#	296
1800	72"	12	51#	352
2100	84"	14	59#	407
2400	96"	16	67#	462

- Maximum Belt Speed SST/SAT2 Tensioner - 6M/sec (1200 FPM)
- Maximum Belt Speed MST Tensioner - 5M/sec (1000 FPM)
- Temperature Rating -35°C to 82°C (-30°F to 180°F)
- Usable Blade Wear Length 9mm(3/8")
- Blade Materials C-Tip: Impact Resistant Tungsten Carbide (works with mechanical fasteners)
V-Tip: Long Life Tungsten Carbide (for vulcanized belts only)
- Available for Belt Widths SST/SAT2 Tensioners - 450 to 2400 mm (18" to 96"). Other sizes available upon request.
- Available for Belt Widths MST Tensioners - 450 to 1800mm (18" to 72"). Other sizes available upon request.
- CEMA Cleaner Rating Class 5

Section 8 - Specs and CAD Drawings

8.2 CAD Drawing - MHS with SST Tensioners





PART NO.	75910	75911	75912	75913	
BELT WIDTH	24" [600mm]	30" [750mm]	36" [900mm]	42" [1050mm]	
LENGTH "A"	66.48" [1689mm]	72.36" [1838mm]	78.24" [1987mm]	84.12" [2137mm]	
LENGTH "B"	23-5/8" [600mm]	29-1/2" [751mm]	35-1/2" [902mm]	41-3/8" [1051mm]	
NO. OF BLADES	4	5	6	7	

PART NO.	75914	75915	75916	75917	76803
BELT WIDTH	48" [1219mm]	54" [1372mm]	60" [1542mm]	72" [1829mm]	84" [2134mm]
LENGTH "A"	90" [2286mm]	95.88" [2435mm]	101.76" [2585mm]	113.52" [2882mm]	125.28" [3182mm]
LENGTH "B"	47-1/4" [1200mm]	53-1/4" [1353mm]	59-1/8" [1500mm]	70-7/8" [1800mm]	82-5/8" [2100mm]
NO. OF BLADES	8	9	10	12	14

Section 8 - Specs and CAD Drawings


8.3 CAD Drawing - MHS with MST Tensioners

SPECIFICATIONS					MHS V CLEANER		ITEM 1 MHS POLE	
BELT WIDTH 'A'		POLE LENGTH 'B'		# OF TIPS	ORDER NUMBER	ITEM CODE	ORDER NUMBER	ITEM CODE
(in.)	(mm)	(in.)	(mm)					
18	450	72	1828	3	MHS-18V-MST	79442	MHSP-18	76178
24	600	78	2133	4	MHS-24V-MST	79443	MHSP-24	75918
30	700	84	2286	5	MHS-30V-MST	79444	MHSP-30	75919
36	900	90	2438	6	MHS-36V-MST	79445	MHSP-36	75920
42	1050	96	2590	7	MHS-42V-MST	79446	MHSP-42	75921
48	1200	102	2743	8	MHS-48V-MST	79447	MHSP-48	75922
54	1350	108	2895	9	MHS-54V-MST	79448	MHSP-54	75923
60	1500	114	3200	10	MHS-60V-MST	79449	MHSP-60	75924
72	1800	126	3750	12	MHS-72V-MST	79450	MHSP-72	75925



Section 8 - Specs and CAD Drawings



8.4 CAD Drawing - MHS with SAT2 Tensioners



Specifications			MHS SEC Cleaner W/PAT	
Belt Width "A"		Pole Length "B"	Order Number	Item Code
in.	mm	in.	mm	
24	600	78	1980	MHS-24P 78736
30	750	84	2133	MHS-30P 78737
36	900	90	2286	MHS-36P 78738
42	1050	96	2438	MHS-42P 78739
48	1200	102	2590	MHS-48P 78740
54	1350	108	2743	MHS-54P 78741
60	1500	114	2895	MHS-60P 78742
72	1800	126	3200	MHS-72P 78743
84	2100	138	3505	MHS-84P 78744
96	2400	150	3750	MHS-96P 79047

Section 9 - Replacement Parts

9.1 Replacement Parts List - MHS HD Secondary Cleaners (SST Tensioners)



Replacement Parts


REF	DESCRIPTION	ORDERING NUMBER	ITEM CODE	WT. LBS.
1	450mm (18") Pole	MHSP-18	76178	46.2
	600mm (24") Pole	MHSP-24	75918	51.7
	750mm (30") Pole	MHSP-30	75919	57.2
	900mm (36") Pole	MHSP-36	75920	62.8
	1050mm (42") Pole	MHSP-42	75921	68.3
	1200mm (48") Pole	MHSP-48	75922	73.9
	1350mm (54") Pole	MHSP-54	75923	79.4
	1500mm (60") Pole	MHSP-60	75924	85.0
	1800mm (72") Pole	MHSP-72	75925	96.1
	2100mm (84") Pole	MHSP-84	76814	112.1
	2400mm (96") Pole	MHSP-96	79052	128.1
2	C-Tip*	ICT6	74535	0.7
2a	V-Tip* (for vulcanized belts only)	RSA150	73628	1.3
3	PowerFlex™ Cushion* (complete)	PFC	75927	4.2
3a	PowerFlex Cushion* SS (complete)	PFC-SS	76560	4.2
4a	Tension Spring - White (1 ea.) for belts 450-750mm (18" - 30")	STS-W	75846	0.5
4b	Tension Spring - Silver (1 ea.) for belts 900-1200mm (36" - 48")	STS-S	75843	0.8
4c	Tension Spring - Black (1 ea.) for belts 1350-2100mm (54" - 84")	STS-B	75844	1.0
4d	Tension Spring - Gold (1 ea.) for belts 2400mm (96")	STS-G	78142	1.3
5	HD Torsion Pole Mount* (1 ea.) (includes HD adjusting rod, nuts & sleeve) (See 9 & 9a for bushings)	SSTHDP	77868	15.0
6	HD Mounting Base Kit* (includes 1 mounting base, 2 slide guides, top hat bracket & bottom bushing)	SSTHDMK	77870	10.2
7	SST Hat Bracket (pair)	SSTHB	79582	3.0
8	Slide Guide Kit* (incl. 2 slide guides)	STGK2	77867	1.1
9a	SST Bushing Kit - White/Silver (includes 2 bushings)	SSTBK-W	76636	0.1
9b	SST Bushing Kit - Black/Gold (includes 2 bushings)	SSTBK-B	76637	0.1
10	SST Lower Bushing Kit (pair)	SSTLBK	79493	.2
11	P Stainless Steel Shield	PSSS	74773	0.5
12	PowerFlex™ Reverse Shield	PFRS	76622	0.4
—	HD Spring Tensioner* - White (includes 2 each items 4, 5, 6, & 9) for belts 450-750mm (18" - 30")	SST2HD-W	77879	60.6
—	HD Spring Tensioner* - Silver (includes 2 each items 4a, 5, 6, & 9a) for belts 900-1200mm (36" - 48")	SST2HD-S	77880	61.4
—	HD Spring Tensioner* - Black (includes 2 each items 4b, 5, 6, & 9a) for belts 1350-2100mm (54" - 84")	SST2HD-B	77881	62.0
—	HD Spring Tensioner* - Gold (includes 2 each items 4c, 5, 6, & 9a) for belts 2400mm (96")	SST2HD-G	79041	62.6

*Hardware Included
Lead time: 1 working day

Legacy Replacement Parts for Tensioners shipped prior to Dec. 31, 2014*

L1	Adjusting Rod Kit (includes 1 rod, 2 nuts, 1 bushing, 1 washer) for belts 600-1500mm (24" - 60")	STAK	75847	2.9
L2	HD Adjusting Rod Kit (includes 1 rod, 2 nuts, 1 HD bushing, 1 washer) for belts 1800-2100mm (72"-84")	STAKHD	75892	3.0
L3	Legacy SST Hat Channel Kit	SSTHK	79070	1.5
L4	SAT2 Adjusting Rod Kit (2 ea.)	SAT2AK	78733	5.0
—	SST Tensioner Bushing Update Kit (includes 2 lower bushings, 2 sleeves, 2 nuts)	SST-BUK	76943	0.3

*Verify if legacy parts are needed by looking at threaded rod. If it has standard threads, use legacy parts. If it has flat/acme threads, choose from regular replacement parts.




Spring Tensioner Selection Chart

CLEANER SIZE	77879 SST2HD-W	77880 SST2HD-S	77881 SST2HD-B	79041 SST2HD-G
MHS 450 - 750mm (18" - 30")	X			
MHS 900 - 1200mm (36" - 48")		X		
MHS 1350 - 2100mm (54" - 84")			X	
MHS 2400 mm (96")				X

Section 9 - Replacement Parts

9.2 Replacement Parts List - MST and SAT2 Tensioners



MST Tensioner Replacement Parts


REF	DESCRIPTION	ORDERING NUMBER	ITEM CODE	WT. LBS.
13a	Tension Spring - White (1 ea.) for belts 450-750mm (18" - 30")	STS-W	75846	0.5
13b	Tension Spring - Silver (1 ea.) for belts 900-1350mm (36" - 54")	STS-S	75843	0.8
13c	Tension Spring - Black (1 ea.) for belts 1500-1800mm (60" - 72")	STS-B	75844	1.0
14	MST Adjusting Mechanism	MSTAM	79435	2.8
15	MST Mounting Bracket LH (incl. bushings)	MST-MBL	79436	5.7
16	MST Mounting Bracket RH (incl. bushings)	MST-MBR	79437	5.7
17	MST HD Clamp*	MSTCHD	79439	2.5
18	MST Bushing Kit (incl. 4 bushings)	MSTBK	79440	.2
19	MST Guide Pole	MSTGT	79441	1.5
20	MST HD Pole Mount*	MSTPMHD	79451	7.3
21	MST Drop Brackets (2)	MSTDDB	79434	27.7
-	MST HD Tensioner w/White Spring (incl. 1 ea. items 15, 16; 2 ea. items 13a, 14, 17, 19, 20)	MSTHD-W	79431	36.8
-	MST HD Tensioner w/Silver Spring (incl. 1 ea. items 15, 16; 2 ea. items 13b, 14, 17, 19, 20)	MSTHD-S	79432	37.5
-	MST HD Tensioner w/Black Spring (incl. 1 ea. items 15, 16; 2 ea. items 13c, 14, 17, 19, 20)	MSTHD-B	79433	38.1

*Hardware included

Lead time: 1 working day

MST Spring Tensioner Selection Chart

CLEANER SIZE	79431 MSTHD-W	79432 MSTHD-S	79433 MSTHD-B
MHS 450 - 750mm (18" - 30")	X		
MHS 900 - 1350mm (36" - 54")		X	
MHS 1500 - 1800 (mm60" - 72")			X





SAT2 (Secondary Air Tensioner 2) Replacement Parts

REF	DESCRIPTION	ORDERING NUMBER	ITEM CODE	WT. LBS.
22	SAT2 w/PAT Control Box	SAT2PAT	78735	43.5
23	SAT2 w/o Control Box	SAT2NCB	78703	41.0
24	SAT Air/Water Bag Kit	SATB	76083	5.1
25	SAT 1/8" Hose Barb Kit	SATHB	76084	0.1
26	SAT2 Mounting Base Kit	SAT2MK	78704	11.6
27	ST Slide Guide Kit	STGK2	77867	1.1
28	SAT2 Torsion Pole Mount	SAT2PM	78732	11.1
29	SAT2 Adjusting Rod Kit	SAT2AK	78733	5.0
30	PAT Control Box 100psi	PACB100	78683	11.0

Lead time: 1 working day

Section 9 - Replacement Parts

9.3 Replacement Parts List - Stainless Steel MHS Cleaners



Replacement Parts

REF	DESCRIPTION	ORDERING NUMBER	ITEM CODE
1	600mm (24") SS Pole	MHSP24-S/S	77620
	750mm (30") SS Pole	MHSP30-S/S	77621
	900mm (36") SS Pole	MHSP36-S/S	77622
	1050mm (42") SS Pole	MHSP42-S/S	77623
	1200mm (48") SS Pole	MHSP48-S/S	77624
	1350mm (54") SS Pole	MHSP54-S/S	77625
	1500mm (60") SS Pole	MHSP60-S/S	77626
	1800mm (72") SS Pole	MHSP72-S/S	77627
	2100mm (84") SS Pole	MHSP84-S/S	77628
	2400mm (96") SS Pole	MHSP96-S/S	79053
2	C-Tip*	ICT6	74535
2a	SS C-Tip	ICT6-S/S	78700
2b	V-Tip* (for vulcanized belts only)	RSA150	73628
2c	S/S V-Tip* (for vulcanized belts only)	RV76-S/S	76205
3	PowerFlex Cushion* (complete)	PFC-SS	76560
4a	Tension Spring - White (1 ea.) for belts 450-750mm (18" - 30")	STS-W-S/S	77630
4b	Tension Spring - Silver (1 ea.) for belts 900-1200mm (36" - 48")	STS-S-S/S	77631
4c	Tension Spring - Black (1 ea.) for belts 1350-2100mm (54" - 84")	STS-B-S/S	77632
4d	Tension Spring - Gold (1 ea.) for belts 2400mm (96")	STS-G-S/S	79057
5	SS HD Torsion Mounting Kit* (1 ea.) (includes adjusting rod, 3 nuts & sleeve) (See 9 & 9a for bushings)	STHDPM2-S/S	77633
6	SS Mounting Base Kit* (includes 1 mounting base, 2 slide guides, top hat bracket & bottom bushing)	STHDMK2-S/S	77634
7	SS Base Mounting Kit* (includes 2 slide guides)	STGK2-S/S	77635
8	SST Hat Bracket S/S (pair)	SSTHB-S/S	79586
9a	SST Bushing Kit - White/Silver (includes 2 bushings)	SSTBK-W	76636
9b	SST Bushing Kit - Black/Gold (includes 2 bushings)	SSTBK-B	76637
10	SST Lower Bushing Kit (pair)	SSTLBK	79493
11	P Stainless Steel Shield	PSSS	74773
12	PowerFlex™ Reverse Shield	PFRS	76622
—	SS Spring Tensioner* - White (includes 2 each items 4, 5, 6 & 9) for belts 450-750mm (18" - 30")	SST2HD-W-S/S	77637
—	SS Spring Tensioner* - Silver (includes 2 each items 4a, 5, 6 & 9) for belts 900-1200mm (36" - 48")	SST2HD-S-S/S	77638
—	SS Spring Tensioner* - Black (includes 2 each items 4b, 5, 6 & 9a) for belts 1350-2100mm (54" - 84")	SST2HD-B-S/S	77639
—	SS Spring Tensioner* - Gold (includes 2 each items 4c, 5, 6 & 9a) for belts 2400mm (96")	SST2HD-G-S/S	79042

*Hardware Included
Lead time: 1 working day

Shaded items are made to order.
Lead time: 3 weeks

Legacy Replacement Parts for Tensioners shipped prior to changeover Dec. 31, 2014*

REF	DESCRIPTION	ORDERING NUMBER	ITEM CODE
L1	Adjusting Rod Kit* (includes 1 rod, 2 nuts, 1 bushing, 1 washer) for belts 450-1500mm (18" - 60")	STAK	75847
L2	HD Adjusting Rod Kit* (includes 1 rod, 2 nuts, 1 HD bushing, 1 washer) for belts 1800-2400mm (72" - 96")	STAKHD	75892
L3	SST Hat Channel Kit S/S	SSTHK-S/S	79071
—	SS Bushing Update Kit (includes 2 ea. lower bushings, sleeves, nuts)	SST-BUK-S/S	77636

*Verify if legacy parts are needed by looking at threaded rod. If it has standard threads, use legacy parts. If it has flat/acme threads, choose from regular replacement parts.

Standard thread profile

Acme/trapezoidal thread profile

Spring Tensioner Selection Chart

CLEANER SIZE	77637 SSTHD-W-S/S	77638 SSTHD-S-S/S	77639 SSTHD-B-S/S	79042 SST2HD-G-S/S
MHS S/S 450 - 750mm (18" - 30")	X			
MHS S/S 900 - 1200mm (36" - 48")		X		
MHS S/S 1350 - 2100mm (54" - 84")			X	
MHS S/S 2400 mm (96")				X

Section 10 - Other Flexco Conveyor Products

Flexco provides many conveyor products that help your conveyors to run more efficiently and safely. These components solve typical conveyor problems and improve productivity. Here is a quick overview on just a few of them:

MMP Precleaner



- Extra cleaning power right on the head pulley
- A 250mm (10") TuffShear™ blade provides increased blade tension on the belt to peel off abrasive materials
- The unique Visual Tension Check™ ensures optimal blade tensioning and quick, accurate retensioning
- Easy to install and simple to service

DRX Impact Beds



- Exclusive Velocity Reduction Technology™ in order to better protect the belt
- Slide-Out Service™ gives direct access to all impact bars for change-out
- Impact bar supports for longer bar life
- 4 models to custom fit to the application

MDWS DryWipe Secondary Cleaner



- Wipes the belt dry as final cleaner in system
- Automatic blade tensioning to the belt
- Easy, visual blade tension check
- Simple, one-pin blade replacement

PT Max™ Belt Trainer



- Patented “pivot & tilt” design for superior training action
- Dual sensor rollers on each side to minimize belt damage
- Pivot point guaranteed not to freeze up
- Available for topside and return side belts

Flexco Specialty Belt Cleaners



- “Limited space” cleaners for tight conveyor applications
- High Temp cleaners for severe, high heat applications
- A rubber fingered cleaner for chevron and raised rib belts
- Multiple cleaner styles in stainless steel for corrosive applications

Belt Plows



- A belt cleaner for the tail pulley
- Exclusive blade design quickly spirals debris off the belt
- Economical and easy to service
- Available in vee or diagonal models

The Flexco Vision

To become the leader in maximising
belt conveyor productivity for our customers worldwide
through superior service and innovation.

2 Woodlands Sector 1 • #01-21 • Woodlands Spectrum I • Singapore 738068
Tel: +65-6484-1533 • Fax: +65-6484-1531 • E-mail: asiasales@flexco.com

Visit www.flexco.com for other Flexco locations and products.

©2017 Flexible Steel Lacing Company. 09/21/17. For reorder: X4171

