Rajalakshmi Engineering College

Name: Aravinth Sankaran.N

Email: 240801028@rajalakshmi.edu.in

Roll no: 240801028 Phone: 8939452242

Branch: REC

Department: I ECE FA

Batch: 2028

Degree: B.E - ECE



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 3_COD_Question 4

Attempt : 1 Total Mark : 10 Marks Obtained : 10

Section 1: Coding

1. Problem Statement

You are a software developer tasked with building a module for a scientific calculator application. The primary function of this module is to convert infix mathematical expressions, which are easier for users to read and write, into postfix notation (also known as Reverse Polish Notation). Postfix notation is more straightforward for the application to evaluate because it removes the need for parentheses and operator precedence rules.

The scientific calculator needs to handle various mathematical expressions with different operators and ensure the conversion is correct. Your task is to implement this infix-to-postfix conversion algorithm using a stack-based approach.

Example

Input: noa+b Output: ab+ **Explanation:** The postfix representation of (a+b) is ab+. **Input Format** The input is a string, representing the infix expression. The output displays the postfix representation of the given infix expression. Refer to the sample output for formatting specifications. Sample Test Case Input: a+(b*e) Output: abe*+ **Answer** #include <stdio.h> #include <stdlib.h> #include <string.h> struct Stack { int top; unsigned capacity; char* array; **}**; struct Stack* createStack(unsigned capacity) { struct Stack* stack = (struct Stack*)malloc(sizeof(struct Stack)); if (!stack)

```
return NULL;
                                                                                240801028
     stack->capacity = capacity;
     stack->array = (char*)malloc(stack->capacity * sizeof(char));
     return stack:
   }
   int isEmpty(struct Stack* stack) {
     return stack->top == -1;
   }
   char peek(struct Stack* stack) {
   return stack->array[stack->top];
   char pop(struct Stack* stack) {
     if (!isEmpty(stack))
        return stack->array[stack->top--];
     return '$';
   }
   void push(struct Stack* stack, char op) {
     stack->array[++stack->top] = op;
   // You are using GCC
  int isOperand(char ch)
     return(ch>='a'&&ch<='z')||(ch>='A'&&ch<='Z')||(ch>='0'&&ch<='9');
   int Prec(char ch)
     switch(ch)
       case '+':
       case '-':
                                                                                240801028
        return 1;
      case '*':
       case '/':
         return 2;
```

```
240801028
                                                   240801028
    case '^':
     return 3;
 return -1;
void infixToPostfix(char* exp)
  int i,k=0;
  int l=strlen(exp);
  struct Stack* stack=createStack(I);
  if(!stack)
                                                                                240801028
  char *output=(char*)malloc((l+1)*sizeof(char));
if(!output)
{
    printf("* '
    printf("Memory allocation for output failed!\n");
    free(stack->array);
    free(stack);
    return;
  for(i=0;exp[i];i++)
                                                                                240801028
    if(isOperand(exp[i]))
    output[k++]=exp[i];
    push(stack,exp[i]);
else if(exp[i]-
       while(!isEmpty(stack)&&peek(stack)!='(')
       output[k++]=pop(stack);
       if(!isEmpty(stack)&&peek(stack)=='(')
       pop(stack);
       else
         printf("Invalid Expression (mismatched parentheses)\n");
                                                                                240801028
                                                   240801028
         free(stack->array);
         free(stack);
         free(output);
```

```
240801028
                                                            240807028
                return;
           else
             while(!isEmpty(stack)&&Prec(exp[i])<=Prec(peek(stack)))
             {
                if(exp[i]=='^'\&peek(stack)=='^')
                break;
                else
push(stack,exp[i]);
                output[k++]=pop(stack);
                                                                                         240801028
        while(!isEmpty(stack))
output[k++]=pop(s+0
output[k]='\0'
        printf("%s\n",output);
        free(stack->array);
        free(stack);
        free(output);
      }
      int main() {
...ar exp[100];
scanf("%s", exp);
infi∨<sup>+</sup>
                                                                                         240801028
                                                            240801028
        , ~^μ);
infixToPostfix(exp);
return 0;
```

Status: Correct Marks: 10/10

240801028

240801028

240801028

240801028