

RC Chakraborty 03/03 to 08/3, 2007, Lecture 15 to 22 (8 hrs) Slides 1 to 79

myreaders , <http://myreaders.wordpress.com/> , rcchak@gmail.com (***Revised – Feb. 02, 2008***)

Artificial Intelligence

Knowledge Representation Issues, Predicate Logic, Rules

Topics
(Lectures 15, 16, 17, 18, 19, 20, 21, 22 8 hours)

Slides

1. Knowledge Representation

03-26

Introduction – KR model, typology, relationship, framework, mapping, forward & backward representation, system requirements; KR schemes - relational, inheritable, inferential, declarative, procedural; KR issues - attributes, relationship, granularity.

2. KR Using Predicate Logic

27-47

Logic representation, Propositional logic - statements, variables, symbols, connective, truth value, contingencies, tautologies, contradictions, antecedent, consequent, argument; Predicate logic - expressions, quantifiers, formula; Representing “IsA” and “Instance” relationships, computable functions and predicates; Resolution.

3. KR Using Rules

48-77

Types of Rules - declarative, procedural, meta rules; Procedural verses declarative knowledge & language; Logic programming – characteristics, Statement, language, syntax & terminology, simple & structured data objects, Program Components - clause, predicate, sentence, subject; Programming paradigms - models of computation, imperative model, functional model, logic model; Forward & backward reasoning - chaining, conflict resolution; Control knowledge.

4. References

78-79

Knowledge Representation

Issues, Predicate Logic, Rules

How do we represent what we know ?

- ***Knowledge*** is a general term.

An answer to the question, "*how to represent knowledge*", requires an analysis to distinguish between knowledge "how" and knowledge "that".

- knowing "how to do something".

e.g. "*how to drive a car*" is Procedural knowledge.

- knowing "that something is true or false".

e.g. "*that is the speed limit for a car on a motorway*" is Declarative knowledge.

- ***knowledge and Representation*** are distinct entities that play a central but distinguishable roles in intelligent system.

- Knowledge is a description of the world.

It determines a system's competence by what it knows.

- Representation is the way knowledge is encoded.

It defines the performance of a system in doing something.

- Different types of knowledge require different kinds of representation.

The Knowledge Representation ***models/mechanisms*** are often based on:

◇ *Logic*

◇ *Rules*

◇ *Frames*

◇ *Semantic Net*

- Different types of knowledge require different kinds of ***reasoning***.

1. Introduction

Knowledge is a general term.

Knowledge is a progression that starts with *data* which is of limited utility.

- By organizing or analyzing the data, we understand what the data means, and this becomes *information*.
- The interpretation or evaluation of information yield *knowledge*.
- An understanding of the principles embodied within the knowledge is *wisdom*.

● Knowledge Progression



Fig 1 Knowledge Progression

- **Data** is viewed as collection of : Example : It is raining.
disconnected facts.
- **Information** emerges when : Example : The temperature dropped 15
relationships among facts are established and understood;
Provides answers to "who", "what", "where", and "when".
- **Knowledge** emerges when : Example : If the humidity is very high
relationships among patterns are identified and understood;
Provides answers as "how" .
- **Wisdom** is the pinnacle of : Example : Encompasses understanding
of understanding, uncovers the *principles of relationships that describe patterns.*
Provides answers as "why" .

- **Knowledge Model** (Bellinger 1980)

The model tells, that as the degree of "*connectedness*" and "*understanding*" increase, we progress from *data* through *information* and *knowledge* to *wisdom*.




Fig. Knowledge Model

The model represents *transitions* and *understanding*.

- the *transitions* are from *data*, to *information*, to *knowledge*, and finally to *wisdom*;
- the *understanding* support the transitions from one stage to the next stage.

The distinctions between *data*, *information*, *knowledge*, and *wisdom* are not very discrete. They are more like shades of gray, rather than black and white (Shedroff, 2001).

- *data* and *information* deal with the past; they are based on the gathering of *facts* and adding context.
- *knowledge* deals with the present that enable us to perform.
- *wisdom* deals with the future, acquire vision for what will be, rather than for what is or was.

● Knowledge Type

Knowledge is categorized into two major types: *Tacit* and *Explicit*.

- term "Tacit" corresponds to *informal* or *implicit* type of knowledge,
- term "Explicit" corresponds to *formal* type of knowledge.

Tacit knowledge

- ◇ Exists within a human being; it is embodied.
- ◇ Difficult to articulate formally.
- ◇ Difficult to share/communicate.
- ◇ Hard to steal or copy.
- ◇ Drawn from experience, action, subjective insight.

Explicit knowledge

- ◇ Exists outside a human being; it is embedded.
- ◇ Can be articulated formally.
- ◇ Can be shared, copied, processed and stored.
- ◇ Easy to steal or copy
- ◇ Drawn from artifact of some type as principle, procedure, process, concepts.

[The next slide explains more about tacit and explicit knowledge.]

■ Knowledge typology map

The map shows that, *Tacit knowledge* comes from experience, action, subjective insight and *Explicit knowledge* comes from principle, procedure, process, concepts, via transcribed content or artifact of some type.




Fig. Knowledge Typology Map

- ◇ **Facts** : are data or instance that are specific and unique.
- ◇ **Concepts** : are class of items, words, or ideas that are known by a common name and share common features.
- ◇ **Processes** : are flow of events or activities that describe how things work rather than how to do things.
- ◇ **Procedures** : are series of step-by-step actions and decisions that result in the achievement of a task.
- ◇ **Principles** : are guidelines, rules, and parameters that govern; principles allow to make predictions and draw implications; principles are the basic building blocks of theoretical models (theories).

These artifacts are used in the knowledge creation process to create two types of knowledge: *declarative* and *procedural* explained below.

● Knowledge Type

Cognitive psychologists sort knowledge into *Declarative* and *Procedural* category and some researchers added *Strategic* as a third category.

Procedural knowledge

- ◇ examples : procedures, rules, strategies, agendas, models.
- ◇ focuses on tasks that must be performed to reach a particular objective or goal.
- ◇ Knowledge about "how to do something"; e.g., to determine if Peter or Robert is older, first find their ages.

Declarative knowledge

- ◇ example : concepts, objects, facts, propositions, assertions, semantic nets, logic and descriptive models.
- ◇ refers to representations of objects and events; knowledge about facts and relationships;
- ◇ Knowledge about "that something is true or false". e.g., A car has four tyres; Peter is older than Robert;

Note :

About *procedural knowledge*, there is some disparity in views.

- One view is, that it is close to Tacit knowledge; it manifests itself in the doing of some-thing yet cannot be expressed in words; e.g., we read faces and moods.
- Another view is, that it is close to declarative knowledge; the difference is that a task or method is described instead of facts or things.

All *declarative knowledge* are explicit knowledge; it is knowledge that can be and has been articulated.

The *strategic knowledge* is thought as a subset of declarative knowledge.

● Relationship among knowledge type

The relationship among *explicit*, *implicit*, *tacit*, *declarative* and *procedural knowledge* are illustrated below.




Fig. Relationship among types of knowledge

The Figure shows, declarative knowledge is tied to "describing" and procedural knowledge is tied to "doing."

- The arrows connecting *explicit* with *declarative* and *tacit* with *procedural*, indicate the strong relationships exist among them.
- The arrow connecting *declarative* and *procedural* indicates that we often develop *procedural knowledge* as a result of starting with *declarative knowledge*. i.e., we often "know about" before we "know how".

Therefore, we may view,

- all procedural knowledge as tacit, and
- all declarative knowledge as explicit.

1.1 Framework of Knowledge Representation (Poole 1998)

Computer requires a well-defined problem description to process and also provide well-defined acceptable solution.

To collect fragments of knowledge we need : first to formulate description in our spoken language and then represent it in formal language so that computer can understand. The computer can then use an algorithm to compute an answer. This process is illustrated below.




Fig. Knowledge Representation Framework

The steps are

- The informal formalism of the problem takes place first.
- It is then represented formally and the computer produces an output.
- This output can then be represented in a informally described solution that user understands or checks for consistency.

Note : The Problem solving requires

- formal knowledge representation, and
- conversion of informal (implicit) knowledge to formal (explicit) knowledge.

● Knowledge and Representation

Problem solving requires *large amount of knowledge* and some *mechanism for manipulating that knowledge*.

The Knowledge and the Representation are distinct entities, play a central but distinguishable roles in intelligent system.

- Knowledge is a description of the world;
it determines a *system's competence* by what it knows.
- Representation is the way knowledge is encoded;
it defines the *system's performance* in doing something.

In simple words, we :

- need to know about things we want to represent , and
- need some means by which things we can manipulate.

- | | | |
|-----------------------------------|-------------------------|--------------------------------------|
| ◇ know things to represent | ‡ Objects | - facts about objects in the domain. |
| | ‡ Events | - actions that occur in the domain. |
| | ‡ Performance | - knowledge about how to do things |
| | ‡ Meta-knowledge | - knowledge about what we know |

- | | |
|-----------------------------------|---|
| ◇ need means to manipulate | ‡ Requires some formalism - to what we represent ; |
|-----------------------------------|---|

Thus, knowledge representation can be considered at two levels :

- (a) knowledge level at which facts are described, and
- (b) symbol level at which the representations of the objects, defined in terms of symbols, can be manipulated in the programs.

Note : A good representation enables fast and accurate access to knowledge and understanding of the content.


● Mapping between Facts and Representation

Knowledge is a collection of "facts" from some domain.

We need a representation of *facts* that can be manipulated by a program.
Normal English is insufficient, too hard currently for a computer program to draw inferences in natural languages. Thus some ***symbolic representation is necessary***.

Therefore, we must be able to map "*facts to symbols*" and "*symbols to facts*" using forward and backward representation mapping.

Example : Consider an English sentence



Facts

- ◇ Spot is a dog
- ◇ dog (Spot)
- ◇ $\forall x : \text{dog}(x) \rightarrow \text{hastail}(x)$

Representations

- A fact represented in English sentence
- Using forward mapping function the above fact is represented in logic
- A logical representation of the fact that "all dogs have tails"


Now using **deductive mechanism** we can generate a new representation of object :

- ◇ hastail (Spot)
- ◇ Spot has a tail
- [it is new knowledge]**

- A new object representation
- Using backward mapping function to generate English sentence

■ Forward and Backward representation

The forward and backward representations are elaborated below :



- ‡ The doted line on top indicates the abstract reasoning process that a program is intended to model.
- ‡ The solid lines on bottom indicates the concrete reasoning process that the program performs.

- **KR System Requirements**

A good knowledge representation enables fast and accurate access to knowledge and understanding of the content.

A knowledge representation system should have following *properties*.

- ◇ **Representational Adequacy** The **ability to represent** all kinds of knowledge that are needed in that domain.
- ◇ **Inferential Adequacy** The **ability to manipulate** the representational structures to derive new structure corresponding to new knowledge inferred from old .
- ◇ **Inferential Efficiency** The **ability to incorporate** additional information into the knowledge structure that can be used to focus the attention of the inference mechanisms in the most promising direction.
- ◇ **Acquisitional Efficiency** The **ability to acquire** new knowledge using automatic methods wherever possible rather than reliance on human intervention.

Note : To date no single system can optimizes all of the above properties.

1.2 knowledge Representation schemes

There are four types of Knowledge representation - *Relational, Inheritable, Inferential, and Declarative/Procedural.*

◆ Relational Knowledge :

- provides a framework to compare two objects based on equivalent attributes.
- any instance in which two different objects are compared is a relational type of knowledge.

◆ Inheritable Knowledge

- is obtained from associated objects.
- it prescribes a structure in which new objects are created which may inherit all or a subset of attributes from existing objects.

◆ Inferential Knowledge

- is inferred from objects through relations among objects.
- e.g., a word alone is a simple syntax, but with the help of other words in phrase the reader may infer more from a word; this inference within linguistic is called semantics.

◆ Declarative Knowledge

- a statement in which knowledge is specified, but the use to which that knowledge is to be put is not given.
- e.g. laws, people's name; these are facts which can stand alone, not dependent on other knowledge;

Procedural Knowledge

- a representation in which the control information, to use the knowledge, is embedded in the knowledge itself.
- e.g. computer programs, directions, and recipes; these indicate specific use or implementation;

These KR schemes are detailed below in next few slides

● **Relational knowledge :** associates elements of one domain with another.

Used to associate elements of one domain with the elements of another domain or set of design constraints.

- Relational knowledge is made up of objects consisting of attributes and their corresponding associated values.
- The results of this knowledge type is a mapping of elements among different domains.

The table below shows a simple way to store facts.

- The facts about a set of objects are put systematically in columns.
- This representation provides little opportunity for inference.

Table - Simple Relational Knowledge

<i>Player</i>	<i>Height</i>	<i>Weight</i>	<i>Bats - Throws</i>
Aaron	6-0	180	Right - Right
Mays	5-10	170	Right - Right
Ruth	6-2	215	Left - Left
Williams	6-3	205	Left - Right

- ‡ Given the facts it is not possible to answer simple question such as :
" Who is the heaviest player ? "
- ‡ But if a procedure for finding heaviest player is provided, then these facts will enable that procedure to compute an answer.

- **Inheritable knowledge :** elements inherit attributes from their parents.

The knowledge is embodied in the design hierarchies found in the functional, physical and process domains. Within the hierarchy, elements inherit attributes from their parents, but in many cases, not all attributes of the parent elements be prescribed to the child elements.

- The basic KR needs to be augmented with *inference mechanism*, and
- Inheritance is a powerful form of inference, but not adequate.

The KR in hierarchical structure, shown below, is called "*semantic network*" or a collection of "*frames*" or "*slot-and-filler structure*". It shows property inheritance and way for insertion of additional knowledge.

- Property inheritance : Objects/elements of specific classes inherit attributes and values from more general classes.
- Classes are organized in a generalized hierarchy.

Baseball knowledge

- *isa* : show class inclusion
- *instance* : show class membership




Fig. Inheritable knowledge representation (KR)

- ‡ the directed arrows represent attributes (*isa*, *instance*, and *team*) originating at the object being described and terminating at the object or its value.
- ‡ the box nodes represents objects and values of the attributes.

[Continuing in the next slide]

[Continuing from previous slide – example]

♦ Viewing a node as a frame

Baseball-player

isa : *Adult-Male*
 Bates : *EQUAL handed*
 Height : *6.1*
 Batting-average : *0.252*

♦ Algorithm : Property Inheritance

Retrieve a value **V** for an attribute **A** of an instance object **O**.

Steps to follow:

1. Find object **O** in the knowledge base.
2. If there is a value for the attribute **A** then report that value.
3. Else, see if there is a value for the attribute instance; If not, then fail.
4. Else, move to the node corresponding to that value and look for a value for the attribute **A**; If one is found, report it.
5. Else, do until there is no value for the "**isa**" attribute or until an answer is found :
 - (a) Get the value of the "**isa**" attribute and move to that node.
 - (b) See if there is a value for the attribute **A**; If yes, report it.

This algorithm is simple,

- ‡ It does describe the basic mechanism of inheritance.
- ‡ It does not say what to do if there is more than one value of the instance or "**isa**" attribute.

This can be applied to the example of knowledge base illustrated to derive answers to the following queries :

- team (Pee-Wee-Reese) = Brooklyn–Dodger
- batting-average(Three-Finger-Brown) = 0.106
- height (Pee-Wee-Reese) = 6.1
- bats(Three Finger Brown) = right

[For explanation - refer book on AI by Elaine Rich & Kevin Knight, page 112]

● **Inferential knowledge :** generates new information .

Generates new information from the given information. This new information does not require further data gathering from source, but does require analysis of the given information to generate new knowledge.

- Given a set of relations and values, one may infer other values or relations.
- In addition to algebraic relations, a **predicate logic** (mathematical deduction) is used to infer from a set of attributes.
- Inference through predicate logic uses a set of logical operations to relate individual data. The symbols used for the logic operations are :

**" \rightarrow " (implication), " \neg " (not), " \vee " (or), " \wedge " (and),
 " \forall " (for all), " \exists " (there exists).**

Examples of predicate logic statements :

1. Wonder is a name of a dog : ***dog (wonder)***
2. All dogs belong to the class of animals : ***$\forall x : \text{dog}(x) \rightarrow \text{animal}(x)$***
3. All animals either live on land or in water : ***$\forall x : \text{animal}(x) \rightarrow \text{live}(x, \text{land}) \vee \text{live}(x, \text{water})$***

We can infer from these three statements that :

" Wonder lives either on land or on water."

As more information is made available about these objects and their relations, more knowledge can be inferred.

- **Declarative/Procedural knowledge**

The difference between Declarative/Procedural knowledge is not very clear.

Declarative knowledge :

Here, the knowledge is based on declarative facts about axioms and domains.

- axioms are assumed to be true unless a counter example is found to invalidate them.
- domains represent the physical world and the perceived functionality.
- axiom and domains thus simply exists and serve as declarative statements that can stand alone.

Procedural knowledge:

Here the knowledge is a mapping process between domains that specifies "what to do when" and the representation is of "how to make it" rather than "what it is". The procedural knowledge :

- may have inferential efficiency, but no inferential adequacy and acquisitional efficiency.
- are represented as small programs that know how to do specific things, how to proceed.

Example : a parser in a natural language has the knowledge that a noun phrase may contain articles, adjectives and nouns. It thus accordingly call routines that know how to process articles, adjectives and nouns.

1.3 Issues in Knowledge Representation

The fundamental goal of Knowledge Representation is to facilitate inferencing (conclusions) from knowledge. The issues that arise while using KR techniques are many. Some of these are explained below.

- ◆ Important Attributes : Any attribute of objects so basic that they occur in almost every problem domain ?
- ◆ Relationship among attributes: Any important relationship that exists among object attributes ?
- ◆ Choosing Granularity : At what level of detail should the knowledge be represented ?
- ◆ Set of objects : How sets of objects be represented ?
- ◆ Finding Right structure : Given a large amount of knowledge stored, how can relevant parts be accessed ?

Note : *These issues are briefly explained, referring previous example, Fig. Inheritable KR. For detail readers may refer book on AI by Elaine Rich & Kevin Knight- page 115 – 126.*

- **Important Attributes** : Ref. Example- Fig. Inheritable KR

There are two attributes **"instance"** and **"isa"**, that are of general significance. These attributes are important because they support property inheritance.

- **Relationship among attributes** : Ref. Example- Fig. Inheritable KR

The attributes we use to describe objects are themselves entities that we represent. The relationship between the attributes of an object, independent of specific knowledge they encode, may hold properties like: Inverses , existence in an isa hierarchy , techniques for reasoning about values and single valued attributes.

- ◆ **Inverses :**

This is about consistency check, while a value is added to one attribute. The entities are related to each other in many different ways. The figure shows attributes (*isa*, *instance*, and *team*), each with a directed arrow, originating at the object being described and terminating either at the object or its value. There are two ways of realizing this:

- ✦ first, represent both relationships in a single representation; e.g., a logical representation, *team(Pee-Wee-Reese, Brooklyn-Dodgers)*, that can be interpreted as a statement about Pee-Wee-Reese or Brooklyn-Dodger.
- ✦ second, use attributes that focus on a single entity but use them in pairs, one the inverse of the other; for e.g., one, *team = Brooklyn-Dodgers* , and the other, *team = Pee-Wee-Reese,*

This second approach is followed in semantic net and frame-based systems, accompanied by a knowledge acquisition tool that guarantees the consistency of inverse slot by checking, each time a value is added to one attribute then the corresponding value is added to the inverse.

◆ **Existence in an isa hierarchy :**

This is about generalization-specialization, like, classes of objects and specialized subsets of those classes, there are attributes and specialization of attributes. Example, the attribute *height* is a specialization of general attribute *physical-size* which is, in turn, a specialization of *physical-attribute*. These generalization-specialization relationships are important for attributes because they support inheritance.

◆ **Techniques for reasoning about values :**

This is about reasoning values of attributes not given explicitly. Several kinds of information are used in reasoning, like,

height : must be in a unit of length,

age : of person can not be greater than the age of person's parents.

The values are often specified when a knowledge base is created.

◆ **Single valued attributes :**

This is about a specific attribute that is guaranteed to take a unique value. Example, a baseball player can at time have only a single height and be a member of only one team. KR systems take different approaches to provide support for single valued attributes.

● Choosing Granularity

Regardless of the KR formalism, it is necessary to know :

- At what level should the knowledge be represented and what are the primitives ?."
- Should there be a small number or should there be a large number of low-level primitives or High-level facts.
- High-level facts may not be adequate for inference while Low-level primitives may require a lot of storage.

Example of Granularity :

- Suppose we are interested in following facts:
John spotted Sue.
- This could be represented as
Spotted (agent(John), object (Sue))
- Such a representation would make it easy to answer questions such are :
Who spotted Sue ?
- Suppose we want to know :
Did John see Sue ?
- Given only one fact, we cannot discover that answer.
- We can add other facts, such as
Spotted (x , y) → saw (x , y)
- We can now infer the answer to the question.

● Set of objects

There are certain properties of objects that are true as member of a set but not as individual;

Example : Consider the assertion made in the sentences :

"there are more *sheep* than *people* in Australia", and

"*English* speakers can be found all over the world."

To describe these facts, the only way is to attach assertion to the sets representing *people*, *sheep*, and *English*.

The reason to represent sets of objects is : If a property is true for all or most elements of a set, then it is more efficient to associate it once with the set rather than to associate it explicitly with every elements of the set . This is done,

- in logical representation through the use of universal quantifier, and
- in hierarchical structure where node represent sets and inheritance propagate set level assertion down to individual.

However in doing so, for example: assert *large (elephant)*, remember to make clear distinction between,

- whether we are asserting some property of the set itself, means, *the set of elephants is large*, or
- asserting some property that holds for individual elements of the set , means, *any thing that is an elephant is large*.

There are three ways in which sets may be represented by.

- (a) Name, as in the example – Fig. Inheritable KR, the node - Baseball-Player and the predicates as Ball and Batter in logical representation.
- (b) Extensional definition is to list the numbers, and
- (c) Intensional definition is to provide a rule, that returns true or false depending on whether the object is in the set or not.

[Readers may refer book on AI by Elaine Rich & Kevin Knight- page 122 - 123]

- **Finding Right structure**

This is about access to right structure for describing a particular situation. This requires, selecting an initial structure and then revising the choice. While doing so, it is necessary to solve following problems :

- how to perform an initial selection of the most appropriate structure.
- how to fill in appropriate details from the current situations.
- how to find a better structure if the one chosen initially turns out not to be appropriate.
- what to do if none of the available structures is appropriate.
- when to create and remember a new structure.

There is no good, general purpose method for solving all these problems. Some knowledge representation techniques solve some of them.

[Readers may refer book on AI by Elaine Rich & Kevin Knight- page 124 - 126]

2. KR Using Predicate Logic

In the previous section much has been illustrated about knowledge and KR related issues. This section, illustrates how knowledge may be represented as "*symbol structures*" that characterize bits of knowledge about objects, concepts, facts, rules, strategies;

examples : "*red*" represents *colour red*;
 "*car1*" represents *my car* ;
 "*red(car1)*" represents fact that *my car is red*.

Assumptions about KR :

- Intelligent Behavior can be achieved by manipulation of symbol structures.
- KR languages are designed to facilitate operations over symbol structures, have precise syntax and semantics;
Syntax tells which expression is legal ?,
e.g., red1(car1), red1 car1, car1(red1), red1(car1 & car2) ?; and
Semantic tells what an expression means ?
e.g., property "dark red" applies to my car.
- Make Inferences, draw new conclusions from existing facts.

To satisfy these assumptions about KR, we need *formal notation* that allow automated inference and problem solving. ***One popular choice is use of logic.***

- **Logic**

Logic is concerned with the truth of statements about the world.

Generally each statement is either *TRUE* or *FALSE*.

Logic includes : *Syntax , Semantics and Inference Procedure.*

- ◆ **Syntax :**

Specifies the *symbols* in the language about how they can be combined to form sentences. The facts about the world are represented as sentences in logic.

- ◆ **Semantic :**

Specifies how to assign a truth value to a sentence based on its *meaning* in the world. It Specifies what facts a sentence refers to. A fact is a claim about the world, and it may be *TRUE* or *FALSE*.

- ◆ **Inference Procedure :**

Specifies *methods* for computing new sentences from an existing sentences.

Note :

Facts are claims about the world that are *True* or *False*.

Representation is an expression (sentence), stands for the objects and relations.

Sentences can be encoded in a computer program.

- **Logic as a KR Language**

Logic is a language for reasoning, a collection of rules used while doing logical reasoning. Logic is studied as KR languages in artificial intelligence.

- ◆ **Logic** is a formal system in which the formulas or sentences have true or false values.
- ◆ The problem of designing a **KR language** is a tradeoff between that which is :
 - (a) Expressive enough to represent important objects and relations in a problem domain.
 - (b) Efficient enough in reasoning and answering questions about implicit information in a reasonable amount of time.
- ◆ Logics are of different types : *Propositional logic, Predicate logic, Temporal logic, Modal logic, Description logic* etc;
They represent things and allow more or less efficient inference.
- ◆ **Propositional logic and Predicate logic are fundamental to all logic.**
Propositional Logic is the study of statements and their connectivity.
Predicate Logic is the study of individuals and their properties.

2.1 Logic Representation

The *Facts* are claims about the world that are *True* or *False*.

Logic can be used to represent simple facts.

To build a Logic-based representation :

- ◆ User defines a set of primitive *symbols* and the associated *semantics*.
- ◆ Logic defines ways of putting symbols together so that user can define legal *sentences* in the language that represent *TRUE* facts.
- ◆ Logic defines ways of inferring *new sentences* from existing ones.
- ◆ Sentences - either *TRUE* or *false* but not both are called *propositions*.
- ◆ A declarative sentence expresses a *statement* with a proposition as content; example:

the declarative "*snow is white*" expresses that *snow is white*;

further, "*snow is white*" expresses that *snow is white* is *TRUE*.

In this section, first ***Propositional Logic (PL)*** is briefly explained and then the ***Predicate logic*** is illustrated in detail.

● Propositional Logic (PL)

A proposition is a statement, which in English would be a declarative sentence. Every proposition is either *TRUE* or *FALSE*.

Examples: (a) The sky is blue., (b) Snow is cold. , (c) $12 * 12=144$

‡ propositions are "sentences" , either true or false but not both.

‡ a sentence is smallest unit in propositional logic.

‡ if proposition is true, then truth value is "true" .

if proposition is false, then truth value is "false" .

Example :

Sentence	Truth value	Proposition (Y/N)
"Grass is green"	"true"	Yes
"2 + 5 = 5"	"false"	Yes
"Close the door"	-	No
"Is it hot out side ?"	-	No
"x > 2" where x is variable	-	No (since x is not defined)
"x = x"	-	No

(don't know what is "x" and "=";
 "3 = 3" or "air is equal to air" or
 "Water is equal to water"
 has no meaning)

- *Propositional logic* is fundamental to all logic.
- *Propositional logic is also called Propositional calculus, Sentential calculus, or Boolean algebra.*
- *Propositional logic* tells the ways of joining and/or modifying entire propositions, statements or sentences to form more complicated propositions, statements or sentences, as well as the logical relationships and properties that are derived from the methods of combining or altering statements.

■ Statement, variables and symbols

These and few more related terms, such as, connective, truth value, contingencies, tautologies, contradictions, antecedent, consequent and argument are explained below.

◇ Statement

Simple statements (sentences), *TRUE* or *FALSE*, that does not contain any other statement as a part, are *basic propositions*; lower-case letters, *p*, *q*, *r*, are symbols for simple statements.

Large, compound or complex statement are constructed from basic propositions by combining them with *connectives*.

◇ Connective or Operator

The *connectives* join simple statements into compounds, and joins compounds into larger compounds.

Table below indicates, five basic connectives and their symbols :

- listed in decreasing order of operation priority;
- operations with higher priority is solved first.

Example of a formula : $((((a \wedge \neg b) \vee c \rightarrow d) \leftrightarrow \neg (a \vee c)))$

Connectives and Symbols in decreasing order of operation priority

Connective	Symbols				Read as
assertion	P				"p is true"
negation	$\neg p$	\sim	!	NOT	"p is false"
conjunction	$p \wedge q$	·	&& &	AND	"both p and q are true"
disjunction	$p \vee q$			OR	"either p is true, or q is true, or both "
implication	$p \rightarrow q$	\supset	\Rightarrow	if ..then	"if p is true, then q is true" " p implies q "
equivalence	\leftrightarrow	\equiv	\Leftrightarrow	if and only if	"p and q are either both true or both false"

Note : The propositions and connectives are the basic *elements* of propositional logic.

◇ Truth value

The truth value of a statement is its *TRUTH* or *FALSITY* ,

Example :

- p is either *TRUE* or *FALSE*,
- $\sim p$ is either *TRUE* or *FALSE*,
- $p \vee q$ is either *TRUE* or *FALSE*, and so on.

use " **T** " or " **1** " to mean *TRUE*.

use " **F** " or " **0** " to mean *FALSE*

Truth table defining the basic *connectives* :

p	q	$\neg p$	$\neg q$	$p \wedge q$	$p \vee q$	$p \rightarrow q$	$p \leftrightarrow q$	$q \rightarrow p$
T	T	F	F	T	T	T	T	T
T	F	F	T	F	T	F	F	T
F	T	T	F	F	T	T	F	F
F	F	T	T	F	F	T	T	T

◇ **Tautologies**

A proposition that is always true is called a *tautology*.

e.g., $(P \vee \neg P)$ is always true regardless of the truth value of the proposition P .

◇ **Contradictions**

A proposition that is always false is called a *contradiction*.

e.g., $(P \wedge \neg P)$ is always false regardless of the truth value of the proposition P .

◇ **Contingencies**

A proposition is called a *contingency*, if that proposition is neither a *tautology* nor a *contradiction*

e.g., $(P \vee Q)$ is a contingency.

◇ **Antecedent, Consequent**

In the conditional statements, $p \rightarrow q$, the

1st statement or "if - clause" (here p) is called *antecedent*,

2nd statement or "then - clause" (here q) is called *consequent*.

◇ Argument

Any argument can be expressed as a compound statement.

Take all the premises, conjoin them, and make that conjunction the antecedent of a conditional and make the conclusion the consequent. This implication statement is called the corresponding conditional of the *argument*.

Note :

- Every argument has a corresponding conditional, and every implication statement has a corresponding argument.
- Because the corresponding conditional of an argument is a statement, it is therefore either a tautology, or a contradiction, or a contingency.
- ‡ An argument is *valid* "if and only if" its corresponding conditional is a *tautology*.
- ‡ Two statements are *consistent* "if and only if" their conjunction is not a contradiction.
- ‡ Two statements are *logically equivalent* "if and only if" their truth table columns are identical; "if and only if" the statement of their equivalence using " \equiv " is a tautology.

Note : The truth tables are adequate to test *validity, tautology, contradiction, contingency, consistency, and equivalence*.

● Predicate logic

The **propositional logic, is not powerful** enough for all types of assertions;
 Example : The assertion " $x > 1$ ", where x is a variable, is not a proposition because it is neither true nor false unless value of x is defined.

For $x > 1$ to be a proposition ,

- either we substitute a specific number for x ;
- or change it to something like
 "There is a number x for which $x > 1$ holds";
- or *"For every number x , $x > 1$ holds".*

Consider example :

"All men are mortal.

Socrates is a man.

Then Socrates is mortal" ,

These cannot be expressed in propositional logic as a finite and logically valid argument (formula).

We need languages : that allow us to describe properties (*predicates*) of objects, or a relationship among objects represented by the variables .

Predicate logic satisfies the requirements of a language.

- Predicate logic is powerful enough for expression and reasoning.
- Predicate logic is built upon the ideas of *propositional logic*.

■ **Predicate :**

Every complete *sentence* contains two parts: a *subject* and a *predicate*.

The *subject* is what (or whom) the sentence is about.

The *predicate* tells something about the subject;

Example :

A *sentence* "Judy {runs}".

The *subject* is Judy and the *predicate* is runs .

Predicate, always includes *verb*, tells something about the subject.

Predicate is a verb phrase template that describes a property of objects, or a relation among objects represented by the variables.

Example:

"The car Tom is driving *is blue*" ;

"The sky *is blue*" ;

"The cover of this book *is blue*"

Predicate is "*is blue*" , describes property.

Predicates are given names; Let 'B' is name for predicate "*is_blue*".

Sentence is represented as "*B(x)*" , read as "*x is blue*";

"x" represents an arbitrary *Object* .

■ Predicate logic expressions :

The propositional operators combine predicates, like

$$\text{If } (p(\dots) \ \&\& \ (\ !q(\dots) \ || \ r(\dots)))$$

Examples of logic operators : disjunction (OR) and conjunction (AND).

Consider the expression with the respective logic symbols $||$ and $\&\&$

$$x < y \ || \ (\ y < z \ \&\& \ z < x)$$

Which is $\text{true} \ || \ (\ \text{true} \ \&\& \ \text{true})$;

Applying truth table, found True

Assignment for $<$ are 3, 2, 1 for x, y, z and then

the value can be FALSE or TRUE

$$3 < 2 \ || \ (\ 2 < 1 \ \&\& \ 1 < 3)$$

It is False

■ Predicate Logic Quantifiers

As said before, $x > 1$ is not proposition and why ?

Also said, that for $x > 1$ to be a proposition what is required ?

Generally, a predicate with variables (is called atomic formula) can be made a proposition by applying one of the following two operations to each of its variables :

1. *Assign a value to the variable*; e.g., $x > 1$, if 3 is assigned to x becomes $3 > 1$, and it then becomes a true statement, hence a proposition.
2. *Quantify the variable using a quantifier* on formulas of predicate logic (called wff), such as $x > 1$ or $P(x)$, by using Quantifiers on variables.

Apply Quantifiers on Variables


‡ Variable x

- * $x > 5$ is not a proposition, its truth depends upon the value of variable x
- * to reason such statements, x need to be declared

‡ Declaration $x : a$

- * $x : a$ declares variable x
- * $x : a$ read as " x is an element of set a "

‡ Statement p is a statement about x

- * $Q \ x : a \bullet p$ is quantification of statement

 - statement
 - declaration of variable x as element of set a
 - quantifier

- * Quantifiers are two types :

universal quantifiers , denoted by symbol \forall and
existential quantifiers , denoted by symbol \exists

Note : The next few slide tells more on these two Quantifiers.

■ Universe of Discourse

The universe of discourse, also called domain of discourse or universe.

This indicates :

- a set of entities that the quantifiers deal.
- entities can be set of real numbers, set of integers, set of all cars on a parking lot, the set of all students in a classroom etc.
- universe is thus the domain of the (individual) variables.
- propositions in the predicate logic are statements on objects of a universe.

The universe is often left implicit in practice, but it should be obvious from the context.

Examples:

- About *natural numbers* *forAll* $x, y (x < y \text{ or } x = y \text{ or } x > y)$, there is no need to be more precise and say *forAll* $x, y \text{ in } N$, because N is implicit, being the universe of discourse.
- About *a property that holds for natural numbers but not for real numbers*, it is necessary to qualify what the allowable values of x and y are.

■ **Apply Universal quantifier** \forall "For All "

Universal Quantification allows us to make a statement about a collection of objects.

‡ Universal quantification: $\forall x : a \bullet p$

- * read "for all x in a , p holds "
- * a is universe of discourse
- * x is a member of the domain of discourse.
- * p is a statement about x

‡ In propositional form it is written as : $\forall x P(x)$

- * read "for all x , $P(x)$ holds "
- "for each x , $P(x)$ holds " or
- "for every x , $P(x)$ holds "
- * where $P(x)$ is predicate,
 $\forall x$ means all the objects x in the universe
 $P(x)$ is true for every object x in the universe

‡ Example : English language to Propositional form

- * "All cars have wheels"
- $\forall x : car \bullet x \text{ has wheel}$
- * $x P(x)$
- where $P(x)$ is predicate tells : ' x has wheels'
- x is variable for object ' $cars$ ' that populate universe of discourse

■ **Apply Existential quantifier** \exists " There Exists "

Existential Quantification allows us to state that an object does exist without naming it.

‡ Existential quantification: $\exists x : a \bullet p$

* read " there exists an x such that p holds "

* a is universe of discourse

* x is a member of the domain of discourse.

* p is a statement about x

‡ In propositional form it is written as : $\exists x P(x)$

* read " there exists an x such that $P(x)$ " or

" there exists at least one x such that $P(x)$ "

* Where $P(x)$ is predicate

$\exists x$ means at least one object x in the universe

$P(x)$ is true for least one object x in the universe

‡ Example : English language to Propositional form

* " Someone loves you "

$\exists x : \text{Someone} \bullet x \text{ loves you}$

* $x P(x)$

where $P(x)$ is predicate tells : ' $x \text{ loves you}$ '

x is variable for object ' *someone* ' that populate universe of discourse

■ **Formula :**

In mathematical logic, a formula is a type of abstract object, a token of which is a symbol or string of symbols which may be interpreted as any meaningful unit in a formal language.

‡ **Terms :**

Defined recursively as variables, or constants, or functions like $f(t_1, \dots, t_n)$, where f is an n -ary function symbol, and t_1, \dots, t_n are terms. Applying predicates to terms produce *atomic formulas*.

‡ **Atomic formulas :**

An atomic formula (or simply atom) is a formula with no deeper propositional structure, i.e., a formula that contains no logical connectives or a formula that has no strict sub-formulas.

- *Atoms* are thus the simplest well-formed formulas of the logic.
- *Compound formulas* are formed by combining the atomic formulas using the logical connectives.
- *Well-formed formula* ("wiff") is a symbol or string of symbols (a formula) generated by the formal grammar of a formal language.

An atomic formula is one of the form:

- $t_1 = t_2$, where t_1 and t_2 are terms, or
- $R(t_1, \dots, t_n)$, where R is an n -ary relation symbol, and t_1, \dots, t_n are terms.
- $\neg a$ is a formula when a is a formula.
- $(a \wedge b)$ and $(a \vee b)$ are formula when a and b are formula

‡ **Compound formula :** example

$$(((a \wedge b) \wedge c) \vee ((\neg a \wedge b) \wedge c)) \vee ((a \wedge \neg b) \wedge c))$$

2.2 Representing “IsA” and “Instance” Relationships

Logic statements, containing *subject*, *predicate*, and *object*, were explained. Also stated, two important attributes “*instance*” and “*isa*”, in a hierarchical structure (ref. fig. Inheritable KR). These two attributes support property inheritance and play important role in knowledge representation.

The ways, attributes “*instance*” and “*isa*”, are logically expressed are :

- Example : A simple sentence like “*Joe is a musician*”
 - ◇ Here “*is a*” (called **IsA**) is a way of expressing what logically is called a class-instance relationship between the subjects represented by the terms “*Joe*” and “*musician*”.
 - ◇ “*Joe*” is an instance of the class of things called “*musician*”.
 “*Joe*” plays the role of instance,
 “*musician*” plays the role of class in that sentence.
 - ◇ Note : In such a sentence, while for a human there is no confusion, but for computers each relationship have to be defined explicitly.
 This is specified as: [Joe] **IsA** [Musician]
 i.e., [Instance] **IsA** [Class]

2.3 Computable Functions and Predicates

The objective is to define *class of functions* **C** *computable in terms of* **F**.

This is expressed as **C { F }** is explained below using two examples :

(1) "evaluate factorial n" and (2) "expression for triangular functions".

- Example (1) : A conditional expression to define *factorial n ie n!*

- ◇ Expression

" if p_1 then e_1 else if p_2 then e_2 . . . else if p_n then e_n " .

ie. $(p_1 \rightarrow e_1, p_2 \rightarrow e_2, \dots p_n \rightarrow e_n)$

Here $p_1, p_2, \dots p_n$ are propositional expressions taking the values **T** or **F** for true and false respectively.

- ◇ The value of $(p_1 \rightarrow e_1, p_2 \rightarrow e_2, \dots p_n \rightarrow e_n)$ is the value of the **e** corresponding to the first **p** that has value **T**.

- ◇ The expressions defining $n!$, $n = 5$, recursively are :

$$\begin{aligned} n! &= n \times (n-1)! \text{ for } n \geq 1 \\ 5! &= 1 \times 2 \times 3 \times 4 \times 5 = 120 \\ 0! &= 1 \end{aligned}$$

The above definition incorporates an instance that the product of no numbers ie $0! = 1$, then only, the recursive relation $(n + 1)! = n! \times (n+1)$ works for $n = 0$.

- ◇ Now use conditional expressions

$$n! = (n = 0 \rightarrow 1, n \neq 0 \rightarrow n . (n - 1) !)$$


to define functions recursively.

- ◇ Example: Evaluate $2!$ according to above definition.

$$\begin{aligned} 2! &= (2 = 0 \rightarrow 1, 2 \neq 0 \rightarrow 2 . (2 - 1) !) \\ &= 2 \times 1! \\ &= 2 \times (1 = 0 \rightarrow 1, 1 \neq 0 \rightarrow 1 . (1 - 1) !) \\ &= 2 \times 1 \times 0! \\ &= 2 \times 1 \times (0 = 0 \rightarrow 1, 0 \neq 0 \rightarrow 0 . (0 - 1) !) \\ &= 2 \times 1 \times 1 \\ &= 2 \end{aligned}$$

- Example (2) : A conditional expression for triangular functions

◇ The graph of a well known triangular function is shown below



the conditional expressions for triangular functions are

$$|x| = (x < 0 \rightarrow -x, \quad x \geq 0 \rightarrow x)$$

◇ the triangular function of the above graph is represented by the conditional expression is

$$\text{tri}(x) = (x \leq -1 \rightarrow 0, \quad x \leq 0 \rightarrow -x, \quad x \leq 1 \rightarrow x, \quad x > 1 \rightarrow 0)$$

2.4 Resolution

Resolution is a procedure used in proving that arguments which are expressible in predicate logic are correct.

Resolution is a procedure that produces proofs by refutation or contradiction.

Resolution lead to refute a theorem-proving technique for sentences in propositional logic and first-order logic.

- Resolution is a rule of inference.
- Resolution is a computerized theorem prover.
- Resolution is so far only defined for Propositional Logic. The strategy is that the Resolution techniques of Propositional logic be adopted in Predicate Logic.

3. KR Using Rules

Knowledge representations using predicate logic have been illustrated. The other most popular approach to Knowledge representation is to use **production rules**, sometimes called **IF-THEN rules**. The remaining two other types of KR are *semantic net* and *frames*.

The production rules are simple but powerful forms of knowledge representation providing the flexibility of combining declarative and procedural representation for using them in a unified form.

Examples of production rules :

- IF condition THEN action
- IF premise THEN conclusion
- IF proposition p_1 and proposition p_2 are true THEN proposition p_3 is true

The advantages of production rules :

- they are modular,
- each rule define a small and independent piece of knowledge.
- new rules may be added and old ones deleted
- rules are usually independently of other rules.

The production rules as knowledge representation mechanism are used in the design of many "**Rule-based systems**" also called "**Production systems**".

- **Types of rules**

Three major types of rules used in the Rule-based production systems.

- **Knowledge Declarative Rules :**

These rules state all the facts and relationships about a problem.

e.g., *IF inflation rate declines*

THEN the price of gold goes down.

These rules are a part of the knowledge base.

- **Inference Procedural Rules**

These rules advise on how to solve a problem, while certain facts are known.

e.g., *IF the data needed is not in the system*

THEN request it from the user.

These rules are part of the inference engine.

- **Meta rules**

These are rules for making rules. Meta-rules reason about which rules should be considered for firing.

e.g., *IF the rules which do not mention the current goal in their premise,*

AND there are rules which do mention the current goal in their premise,

THEN the former rule should be used in preference to the latter.

- Meta-rules direct reasoning rather than actually performing reasoning.
- Meta-rules specify which rules should be considered and in which order they should be invoked.

3.1 Procedural versus Declarative Knowledge

These two types of knowledge were defined in earlier slides.

- **Procedural Knowledge** : *knowing 'how to do'*

Includes : Rules, strategies, agendas, procedures, models.

These explains what to do in order to reach a certain conclusion.

e.g., Rule: To determine if Peter or Robert is older, first find their ages.

It is knowledge about how to do something. It manifests itself in the doing of something, e.g., manual or mental skills cannot reduce to words. It is held by individuals in a way which does not allow it to be communicated directly to other individuals.

Accepts a description of the steps of a task or procedure. It Looks similar to declarative knowledge, except that tasks or methods are being described instead of facts or things.

- **Declarative Knowledge** : *knowing 'what', knowing 'that'*

Includes : Concepts, objects, facts, propositions, assertions, models.

It is knowledge about *facts* and *relationships*, *that*

- can be expressed in simple and clear statements,
- can be added and modified without difficulty.

e.g., A car has four tyres; Peter is older than Robert.

Declarative knowledge and explicit knowledge are articulated knowledge and may be treated as synonyms for most practical purposes.

Declarative knowledge is represented in a format that can be manipulated, decomposed and analyzed independent of its content.

■ **Comparison :**

Comparison between Procedural and Declarative Knowledge :

Procedural Knowledge

- Hard to debug
- Black box
- Obscure
- Process oriented
- Extension may effect stability
- Fast , direct execution
- Simple data type can be used
- Representations in the form of sets of rules, organized into routines and subroutines.

Declarative Knowledge

- Easy to validate
- White box
- Explicit
- Data - oriented
- Extension is easy
- Slow (requires interpretation)
- May require high level data type
- Representations in the form of production system, the entire set of rules for executing the task.

■ **Comparison :**

Comparison between Procedural and Declarative Language :

Procedural Language

- Basic, C++, Cobol, etc.
- Most work is done by interpreter of the languages
- For one task many lines of code
- Programmer must be skilled in translating the objective into lines of procedural code
- Requires minimum of management around the actual data
- Programmer understands and has access to each step of the code
- Data exposed to programmer during execution of the code
- More susceptible to failure due to changes in the data structure
- Traditionally faster, but that is changing
- Code of procedure tightly linked to front end
- Code tightly integrated with structure of the data store
- Programmer works with a pointer or cursor
- Knowledge of coding tricks applies only to one language

Declarative Language

- SQL
- Most work done by Data Engine within the DBMS
- For one task one SQL statement
- Programmer must be skilled in clearly stating the objective as a SQL statement
- Relies on SQL-enabled DBMS to hold the data and execute the SQL statement .
- Programmer has no interaction with the execution of the SQL statement
- Programmer receives data at end as an entire set
- More resistant to changes in the data structure
- Originally slower, but now setting speed records
- Same SQL statements will work with most front ends
Code loosely linked to front end.
- Code loosely linked to structure of data; DBMS handles structural issues
- Programmer not concerned with positioning
- Knowledge of SQL tricks applies to any language using SQL

3.2 Logic Programming

Logic programming offers a formalism for specifying a computation in terms of logical relations between entities.

- logic program is a collection of logic statements.
- programmer describes all relevant logical relationships between the various entities.
- computation determines whether or not, a particular conclusion follows from those logical statements.

● characteristics of Logic program

Logic program is characterized by set of relations and inferences.

- the program consists of a set of axioms and a goal statement.
- the Rules of inference determine whether the axioms are sufficient to ensure the truth of the goal statement.
- the execution of a logic program corresponds to the construction of a proof of the goal statement from the axioms.
- the Programmer specify basic logical relationships, does not specify the manner in which inference rules are applied.

Thus Logic + Control = Algorithms

● Examples of Logic Statements

- Statement

A grand-parent is a parent of a parent.

- Statement expressed in more closely related logic terms as

A person is a grand-parent if she/he has a child and that child is a parent.

- Statement expressed in first order logic as

(for all) x : grand-parent(x) \leftarrow (there exist) y, z : parent(x, y) & parent(y, z)

- **Logic programming Language**

A programming language includes :

- the syntax
- the semantics of programs and
- the computational model.

There are many ways of organizing computations.

The most familiar paradigm is **procedural**. The program specifies a computation by saying "how" it is to be performed. **FORTRAN, C,** and object-oriented languages fall under this general approach.

Another paradigm is **declarative**. The program specifies a computation by giving the properties of a correct answer. **Prolog and logic data language (LDL)** are examples of declarative languages, emphasize the logical properties of a computation.

Prolog and LDL are called logic programming languages.


PROLOG is the most popular Logic programming system.

- **Syntax and terminology** (relevant to Prolog programs)

In any language, the formation of components (expressions, statements, etc.), is guided by syntactic rules. The components are divided into two parts: (A) data components and (B) program components.

(A) Data components :

Data components are collection of data objects that follow hierarchy.



Data object of any kind is also called a *term*. A term is a constant, a variable or a compound term.

Simple data object is not decomposable; e.g. atoms, numbers, constants, variables. The syntax distinguishes the data objects, hence no need for declaring them.

Structured data object are made of several components; e.g. general, special structure.

All these data components were mentioned in the earlier slides, are now explained in detail below.

(a) **Data objects** : The data objects of any kind is called a *term*.

◇ **Term** : examples

- ‡ **Constants:** denote elements such as *integers, floating point, atoms*.
- ‡ **Variables:** denote a single but unspecified element; *symbols* for variables begin with an uppercase letter or an underscore.
- ‡ **Compound terms:** comprise a *functor* and sequence of one or more compound terms called *arguments*.
 - **Functor** : is characterized by its name, which is an *atom*, and its *arity* or number of arguments.

$$f/n = f(t_1, t_2, \dots, t_n)$$

where f is name of the *functor* and is of *arity* n

t_i 's are the *arguments*

f/n denotes *functor* f of *arity* n

Functors with the same name but different arities are distinct.

- ‡ **Ground and non-ground:** *Terms* are ground if they contain no variables; otherwise they are non-ground. *Goals* are atoms or compound terms, and are generally non-ground.

(b) **Simple data objects** : *Atoms, Numbers, Variables*

◇ **Atoms**

‡ a *lower-case letter*, possibly followed by other letters (either case), *digits*, and *underscore character*.

e.g. a greaterThan two_B_or_not_2_b

‡ a *string* of special characters such as: + - * / \ = ^ < > : . ~ @ # \$ %

e.g. <> ##&& ::=

‡ a *string* of any characters enclosed within single quotes.

e.g. 'ABC' '1234' 'a<>b'

‡ following are also *atoms* ! ; [] { }

◇ **Numbers**

‡ applications involving heavy numerical calculations are rarely written in Prolog.

‡ *integer* representation: e.g. 0 -16 33 +100

‡ *real numbers* written in standard or scientific notation,

e.g. 0.5 -3.1416 6.23e+23 11.0e-3 -2.6e-2

◇ **Variables**

‡ begins by a capital letter, possibly followed by other letters (either case), digits, and underscore character.

e.g. X25 List Noun_Phrase

(c) **Structured data objects** : *General Structures* , *Special Structures*

◇ **General Structures**

- ‡ a structured term is syntactically formed by a *functor* and a list of *arguments*.
- ‡ *functor* is an *atom*.
- ‡ *list of arguments* appears between parentheses.
- ‡ *arguments* are separated by a comma.
- ‡ *each argument* is a *term* (i.e., any Prolog data object).
- ‡ *the number of arguments* of a structured term is called its *arity*.
- ‡ e.g. `greaterThan(9, 6)` `f(a, g(b, c), h(d))` `plus(2, 3, 5)`

Note : a structure in Prolog is a mechanism for combining terms together, like integers 2, 3, 5 are combined with the functor *plus*.

◇ **Special Structures**

- ‡ In Prolog an *ordered collection of terms* is called a *list* .
- ‡ *Lists* are structured terms and Prolog offers a convenient notation to represent them:
 - * *Empty list* is denoted by the atom `[]`.
 - * *Non-empty list* carries element(s) between square brackets, separating elements by comma.
- e.g. `[bach, bee]` `[apples, oranges, grapes]` `[]`

(B) Program Components

A *Prolog program* is a collection of predicates or rules. A predicate establishes a relationships between objects.

(a) Clause, Predicate, Sentence, Subject

- ‡ *Clause* is a collection of grammatically-related words .
- ‡ *Predicate* is composed of one or more clauses.
- ‡ *Clauses* are the building blocks of *sentences*; every sentence contains one or more clauses.
- ‡ A Complete Sentence has two parts: *subject* and *predicate*.
 - subject is what (or whom) the sentence is about.
 - predicate tells something about the subject.
- ‡ Example 1 : "cows eat grass".

It is a clause, because it contains the *subject* "cows" and the *predicate* "eat grass."
- ‡ Example 2 : "cows eating grass are visible from highway"

This is a complete clause. The *subject* "cows eating grass" and the *predicate* "are visible from the highway" makes complete thought.

(b) Predicates & Clause

Syntactically a predicate is composed of one or more clauses.


‡ The general form of clauses is :

<left-hand-side> :- <right-hand-side>.

where LHS is a single goal called "*goal*" and

RHS is composed of one or more goals, separated by commas, called "*sub-goals*" of the goal on left-hand side.

‡ The structure of a clause in logic program




‡ Example : *grand_parent* (X, Y) :- *parent*(X, Z), *parent*(Z, Y).
parent (X, Y) :- *mother*(X, Y).
parent (X, Y) :- *father*(X, Y).


‡ Interpretation:

* a clause specifies the conditional truth of the goal on the LHS;
i.e., goal on LHS is assumed to be true if the sub-goals on RHS are all true. A predicate is true if at least one of its clauses is true.


* An *individual* "Y" is the *grand-parent of* "X" if a *parent* of that same "X" is "Z" and "Y" is the *parent* of that "Z".



* An *individual* "Y" is a *parent of* "X" if "Y" is the *mother of* "X"



* An *individual* "Y" is a *parent of* "X" if "Y" is the *father of* "X".



(c) Unit Clause - a special Case

Unlike the previous example of conditional truth, one often encounters **unconditional relationships** that hold.

‡ In Prolog the clauses that are unconditionally true are called **unit clause** or **fact**

‡ Example : Unconditionally relationships
say **'Y' is the father of 'X'** is unconditionally true.

This relationship as a Prolog clause is :

father(X, Y) :- true.

Interpreted as relationship of father between **Y** and **X** is always true;
or simply stated as **Y** is father of **X**

‡ Goal true is built-in in Prolog and always holds.

‡ Prolog offers a simpler syntax to express unit clause or fact

father(X, Y)

ie the **:- true** part is simply omitted.

(d) Queries

In Prolog the queries are statements called **directive**. A special case of directives, are called **queries**.

- ‡ Syntactically, directives are clauses with an empty left-hand side.

Example : **? - grandparent(X, W).**

This query is interpreted as : **Who is a grandparent of X ?**

By issuing queries, Prolog tries to establish the validity of specific relationships.

- ‡ The result of executing a query is either **success** or **failure**

Success, means the goals specified in the query holds according to the facts and rules of the program.

Failure, means the goals specified in the query does not hold according to the facts and rules of the program.

- **Programming paradigms : Models of Computation**

A complete description of a programming language includes the *computational model*, *syntax*, *semantics*, and *pragmatic considerations* that shape the language.

Models of Computation :

A *computational model* is a collection of values and operations, while *computation* is the application of a sequence of operations to a value to yield another value. There are three basic computational models : *(a) Imperative*, *(b) Functional*, and *(c) Logic*. In addition to these, there are two programming paradigms (concurrent and object-oriented programming). While, they are not models of computation, they rank in importance with computational models.

(a) Imperative Model :

The Imperative model of computation, consists of a state and an operation of assignment which is used to modify the state. Programs consist of sequences of commands. The computations are changes in the state.

Example 1 : Linear function

A linear function $y = 2x + 3$ can be written as

$$Y := 2 * X + 3$$

The implementation determines the value of X in the state and then create a new state, which differs from the old state. The value of Y in the new state is the value that $2 * X + 3$ had in the old state.

$$\text{Old State: } X = 3, \quad Y = -2,$$

$$Y := 2 * X + 3$$

$$\text{New State: } X = 3, \quad Y = 9,$$

The imperative model is closest to the hardware model on which programs are executed, that makes it most efficient model in terms of execution time.

(b) Functional model :

The Functional model of computation, consists of a set of values, functions, and the operation of functions. The functions may be named and may be composed with other functions. They can take other functions as arguments and return results. The programs consist of definitions of functions. The computations are application of functions to values.

‡ Example 1 : Linear function

A linear function $y = 2x + 3$ can be defined as :

$$f(x) = 2 * x + 3$$

‡ Example 2 : Determine a value for Circumference.

Assigned a value to Radius, that determines a value for Circumference.

$$\text{Circumference} = 2 \times \text{pi} \times \text{radius where pi} = 3.14$$

Generalize Circumference with the variable "radius" ie

$$\text{Circumference}(\text{radius}) = 2 \times \text{pi} \times \text{radius} , \quad \text{where pi} = 3.14$$

Functional models are developed over many years. The notations and methods form the base upon which problem solving methodologies rest.

(c) Logic model :

The logic model of computation is based on relations and logical inference. Programs consist of definitions of relations. Computations are inferences (is a proof).

‡ Example 1 : Linear function

A linear function $y = 2x + 3$ can be represented as :

$$f(X, Y) \text{ if } Y \text{ is } 2 * X + 3.$$

‡ Example 2: Determine a value for Circumference.

The earlier circumference computation can be represented as:

$$\text{Circle}(R, C) \text{ if } \pi = 3.14 \text{ and } C = 2 * \pi * R.$$

The function is represented as a relation between radius R and circumference C .

‡ Example 3: Determine the mortality of Socrates.

The program is to determine the mortality of Socrates.

The fact given that Socrates is human.

The rule is that all humans are mortal, that is

$$\text{for all } X, \text{ if } X \text{ is human then } X \text{ is mortal.}$$

To determine the mortality of Socrates, make the assumption that there are no mortals, that is $\neg \text{mortal}(Y)$

[logic model continued in the next slide]

[logic model continued in the previous slide]

‡ The fact and rule are:

human (Socrates)

mortal (X) if human (X)

‡ To determine the mortality of Socrates, make the assumption that there are no mortals i.e. $\neg mortal(Y)$

‡ Computation (proof) that Socrates is mortal :

1.	<i>human(Socrates)</i>	<i>Fact</i>
2.	<i>mortal(X) if human(X)</i>	<i>Rule</i>
3	<i>$\neg mortal(Y)$</i>	<i>assumption</i>
4.(a)	<i>$X = Y$</i>	<i>from 2 & 3 by unification</i>
4.(b)	<i>$\neg human(Y)$</i>	<i>and modus tollens</i>
5.	<i>$Y = Socrates$</i>	<i>from 1 and 4 by unification</i>
6.	<i>Contradiction</i>	<i>5, 4b, and 1</i>

‡ Explanation :

- * The 1st line is the statement *"Socrates is a man."*
- * The 2nd line is a phrase *"all human are mortal"* into the equivalent *"for all X, if X is a man then X is mortal"*.
- * The 3rd line is added to the set to determine the mortality of Socrates.
- * The 4th line is the deduction from lines 2 and 3. It is justified by the inference rule *modus tollens* which states that if the conclusion of a rule is known to be false, then so is the hypothesis.
- * Variables X and Y are unified because they have same value.
- * By unification, Lines 5, 4b, and 1 produce contradictions and identify Socrates as mortal.
- * Note that, resolution is the an inference rule which looks for a contradiction and it is facilitated by unification which determines if there is a substitution which makes two terms the same.

Logic model formalizes the reasoning process. It is related to relational data bases and expert systems.

3.3 Forward versus Backward Reasoning

Rule-Based system architecture consists a set of rules, a set of facts, and an inference engine. The need is to find what new facts can be derived.

Given a set of rules, there are essentially two ways to generate new knowledge: one, *forward chaining* and the other, *backward chaining*.

- **Forward chaining** : also called data driven.

It starts with the facts, and sees what rules apply.

- **Backward chaining** : also called goal driven.

It starts with something to find out, and looks for rules that will help in answering it.

■ **Example 1 :**

Rule R1 :	IF hot AND smoky	THEN fire
Rule R2 :	IF alarm_beeps	THEN smoky
Rule R3 :	IF fire	THEN switch_on_sprinklers
Fact F1 :	alarm_beeps	[Given]
Fact F2 :	hot	[Given]

■ **Example 2 :**

Rule R1 :	IF hot AND smoky	THEN ADD fire
Rule R2 :	IF alarm_beeps	THEN ADD smoky
Rule R3 :	IF fire	THEN ADD switch_on_sprinklers
Fact F1 :	alarm_beeps	[Given]
Fact F2 :	hot	[Given]

■ **Example 3 : A typical Forward Chaining**

Rule R1 :	IF hot AND smoky	THEN ADD fire
Rule R2 :	IF alarm_beeps	THEN ADD smoky
Rule R3 :	If fire	THEN ADD switch_on_sprinklers
Fact F1 :	alarm_beeps	[Given]
Fact F2 :	hot	[Given]
Fact F4 :	smoky	[from F1 by R2]
Fact F2 :	fire	[from F2, F4 by R1]
Fact F6 :	switch_on_sprinklers	[from F4 by R3]


■ **Example 4 : A typical Backward Chaining**

Rule R1 :	IF hot AND smoky	THEN fire
Rule R2 :	IF alarm_beeps	THEN smoky
Rule R3 :	If _re	THEN switch_on_sprinklers
Fact F1 :	hot	[Given]
Fact F2 :	alarm_beeps	[Given]
Goal :	Should I switch sprinklers on?	

- **Forward chaining**

The Forward chaining system, properties, algorithms, and conflict resolution strategy are illustrated.

- **Forward chaining system**



- ‡ facts are held in a working memory
- ‡ condition-action rules represent actions to be taken when specified facts occur in working memory.
- ‡ typically, actions involve adding or deleting facts from the working memory.

- **Properties of Forward Chaining**

- ‡ all rules which can fire do fire.
- ‡ can be inefficient - lead to spurious rules firing, unfocused problem solving
- ‡ set of rules that can fire known as conflict set.
- ‡ decision about which rule to fire is conflict resolution.

■ Forward chaining algorithm - I

Repeat

- ‡ Collect the rule whose condition matches a fact in WM.
- ‡ Do actions indicated by the rule.
(add facts to WM or delete facts from WM)

Until problem is solved or no condition match

Apply on the Example 2 extended (adding 2 more rules and 1 fact)

Rule R1 :	IF hot AND smoky	THEN ADD fire
Rule R2 :	IF alarm_beeps	THEN ADD smoky
Rule R3 :	If fire	THEN ADD switch_on_sprinklers
Rule R4 :	IF dry	THEN ADD switch_on_humidifier
Rule R5 :	IF sprinklers_on	THEN DELETE dry
Fact F1 :	alarm_beeps	[Given]
Fact F2 :	hot	[Given]
Fact F2 :	Dry	[Given]

Now, two rules can fire (R2 and R4)

- ‡ R4 fires, humidifier is on (then, as before)
- ‡ R2 fires, humidifier is off **A conflict !**

■ Forward chaining algorithm - II

Repeat

- ‡ Collect the rules whose conditions match facts in WM.
- ‡ If more than one rule matches
 - ◊ Use *conflict resolution strategy* to eliminate all but one
- ‡ Do actions indicated by the rules
(add facts to WM or delete facts from WM)

Until problem is solved or no condition match

■ **Conflict Resolution Strategy**

Conflict set is the set of rules that have their conditions satisfied by working memory elements. Conflict resolution normally selects a single rule to fire. The popular conflict resolution mechanisms are *Refractory, Recency, Specificity*.

◇ **Refractory**

- ‡ a rule should not be allowed to fire more than once on the same data.
- ‡ discard executed rules from the conflict set.
- ‡ prevents undesired loops.

◇ **Recency**

- ‡ rank instantiations in terms of the recency of the elements in the premise of the rule.
- ‡ rules which use more recent data are preferred.
- ‡ working memory elements are time-tagged indicating at what cycle each fact was added to working memory.

◇ **Specificity**

- ‡ rules which have a greater number of conditions and are therefore more difficult to satisfy, are preferred to more general rules with fewer conditions.
- ‡ more specific rules are 'better' because they take more of the data into account.

■ **Alternative to Conflict Resolution – Use Meta Knowledge**

Instead of conflict resolution strategies, sometimes we want to use knowledge in deciding which rules to fire. **Meta-rules** reason about which rules should be considered for firing. They direct reasoning rather than actually performing reasoning.

‡ Meta-knowledge : knowledge about knowledge to guide search.

‡ Example of meta-knowledge

```
IF      conflict set contains any rule (c , a) such that
        a = "animal is mammal"
THEN   fire (c , a)
```

‡ This example says meta-knowledge encodes knowledge about how to guide search for solution.

‡ Meta-knowledge, explicitly coded in the form of rules with "object level" knowledge.

● Backward chaining


Backward chaining system and the algorithm are illustrated.

■ Backward chaining system

- ‡ Backward chaining means reasoning from goals back to facts.
The idea is to focus on the search.
- ‡ Rules and facts are processed using backward chaining interpreter.
- ‡ Checks hypothesis, e.g. *"should I switch the sprinklers on?"*

■ Backward chaining algorithm

- ‡ Prove goal G :
If G is in the initial facts , it is proven.
Otherwise, find a rule which can be used to conclude G, and try to prove each of that rule's conditions.



Encoding of rules

Rule R1 :	IF hot AND smoky	THEN fire
Rule R2 :	IF alarm_beeps	THEN smoky
Rule R3 :	If fire	THEN switch_on_sprinklers
Fact F1 :	hot	[Given]
Fact F2 :	alarm_beeps	[Given]
Goal :	Should I switch sprinklers on?	

- **Forward vs Backward Chaining**

- ‡ Depends on problem, and on properties of rule set.
- ‡ If there is clear hypotheses, then backward chaining is likely to be better; e.g., Diagnostic problems or classification problems, Medical expert systems
- ‡ Forward chaining may be better if there is less clear hypothesis and want to see what can be concluded from current situation; e.g., Synthesis systems - design / configuration.

3.4 Control Knowledge

An algorithm consists of : *logic component*, that specifies the knowledge to be used in solving problems, and *control component*, that determines the problem-solving strategies by means of which that knowledge is used. Thus $Algorithm = Logic + Control$. The logic component determines the meaning of the algorithm whereas the control component only affects its efficiency.

An algorithm may be formulated in different ways, producing same behavior. One formulation, may have a clear statement in logic component but employ a sophisticated problem solving strategy in the control component. The other formulation, may have a complicated logic component but employ a simple problem-solving strategy.

The efficiency of an algorithm can often be improved by improving the control component without changing the logic of the algorithm and therefore without changing the meaning of the algorithm.

The trend in databases is towards the separation of logic and control. The programming languages today do not distinguish between them. The programmer specifies both logic and control in a single language. The execution mechanism exercises only the most rudimentary problem-solving capabilities.

Computer programs will be more often correct, more easily improved, and more readily adapted to new problems when programming languages separate logic and control, and when execution mechanisms provide more powerful problem-solving facilities of the kind provided by intelligent theorem-proving systems.

4. References

1. Elaine Rich and Kevin Knight, Carnegie Mellon University, "Artificial Intelligence, 2006
2. Stuart Russell and Peter Norvig, University of California, Artificial Intelligence: A Modern Approach, <http://aima.cs.berkeley.edu/>, <http://www.cs.berkeley.edu/~russell/intro.html>
3. Frans Coenen, University of Liverpool, Artificial Intelligence, 2CS24, <http://www.csc.liv.ac.uk/~frans/OldLectures/2CS24/ai.html#definition>
4. John McCarthy, Stanford University, what is artificial intelligence? <http://www-formal.stanford.edu/jmc/whatisai/whatisai.html>
5. Randall Davis, Howard Shrobe, Peter Szolovits, What is a Knowledge Representation? <http://groups.csail.mit.edu/medq/ftp/psz/k-rep.html#intro>
6. Conversion of data to knowledge, http://atlas.cc.itu.edu.tr/~sonmez/lisans/ai/KNOWLEDGE_REP.pdf
7. Knowledge Management—Emerging Perspectives, <http://www.systems-thinking.org/kmgmt/kmgmt.htm>
8. Knowledge Management , <http://www.nwlink.com/~donclark/knowledge/knowledge.html>
9. Nickols, F. W. (2000), The knowledge in knowledge management, http://home.att.net/~nickols/Knowledge_in_KM.htm
10. Paul Brna, Prolog Programming A First Course, <http://computing.unn.ac.uk/staff/cgpb4/prologbook/book.html>
11. Mike Sharples, David Hogg, Chris Hutchison, Steve Torrance, David Young, A practical Introduction to Artificial Intelligence, <http://www.informatics.susx.ac.uk/books/computers-and-thought/index.html>
12. Alison Cawsey, Databases and Artificial Intelligence 3 Artificial Intelligence Segment, <http://www.macs.hw.ac.uk/~alison/ai3notes/all.html>
13. Milos Hauskrecht , CS2740 Knowledge Representation (ISSP 3712), <http://www.cs.pitt.edu/~milos/courses/cs2740/>
14. Tru Hoang Cao , Knowledge Representation – chapter 4, <http://www.dit.hcmut.edu.vn/~tru/AI/chapter4.ppt>, <http://www.dit.hcmut.edu.vn/~tru/AI/ai.html>
15. Agnar Aamodt, A Knowledge-Intensive, Integrated Approach to Problem Solving and Sustained Learning, <http://www.idi.ntnu.no/grupper/su/publ/phd/aamodt-thesis.pdf>

16. Ronald J. Brachman and Hector J. Levesque, *Knowledge Representation and Reasoning*,
<http://www.cs.toronto.edu/~hector/PublicKRSlides.pdf>.
17. *Stuart C. Shapiro*, *Knowledge Representation*, CSE 4/563
<http://www.cse.buffalo.edu/~shapiro/Courses/CSE563/>
18. Robert M. Keller, *Predicate Logic*
<http://www.cs.hmc.edu/~keller/cs60book/10%20Predicate%20Logic.pdf>
19. Kevin C. Klement, *Propositional Logic*,
<http://www.iep.utm.edu/p/prop-log.htm#top>
20. *Aljoscha Burchardt*, *Stephan Walter*, . . . , *Computational Semantics*
<http://www.coli.uni-saarland.de/projects/milca/courses/comsem/html/index.html>
21. Open To Europe project, *FUNDAMENTALS OF PROPOSITIONAL LOGIC*
<http://www.informatik.htw-dresden.de/~nestleri/main.html>
22. J Lawry, *Propositional Logic Review*,
<http://www.enm.bris.ac.uk/research/aigroup/enjl/logic/>
23. *Al Lehnen*, *An Elementary Introduction to Logic and Set Theory*,
<http://faculty.matcmadison.edu/alehnen/weblogic/logcont.htm>
24. *Jim Woodcock* and *Jim Davies*, *Using Z*, <http://www.uta.edu/cse/levine/fall99/cse5324/z/>
25. *C. R. Dyer*, *Logic* , CS 540 Lecture Notes,
<http://pages.cs.wisc.edu/~dyer/cs540/notes/logic.html>
26. *Peter Suber*, *Symbolic Logic*, , <http://www.earlham.edu/~peters/courses/log/loghome.htm>
27. *John McCarthy*, *A Basis For A Mathematical Theory Of Computation*,
<http://www-formal.stanford.edu/jmc/basis1/basis1.html>
28. *Shunichi Toida*, *CS381 Introduction to Discrete Structures*,
<http://www.cs.odu.edu/~toida/index.html>
29. *Leopoldo Bertossi*, *Knowledge representation* , <http://www.scs.carleton.ca/~bertossi/KR/>
30. *Anthony A. Aaby*, *Introduction to Programming Languages*,
<http://moonbase.wwc.edu/~aabyan/PLBook/book/book.html>
31. *Carl Alphonse*, *CS312 Functional and Logic Programming*,
<http://www.cse.buffalo.edu/faculty/alphonse/.OldPages/CPSC312/CPSC312/Lecture/LectureHTML/CS312.html>
32. *Anthony A. Aaby*, *Introduction to Programming Languages*,
<http://cs.wwc.edu/~aabyan/PLBook/HTML/>

Note : This list is not exhaustive. The quote, paraphrase or summaries, information, ideas, text, data, tables, figures or any other material which originally appeared in someone else's work, I sincerely acknowledge them.