

Contest Duration: 2025-05-10(Sat) 08:00 (<http://www.timeanddate.com/worldclock/fixedtime.html?iso=20250510T2100&p1=248>) - 2025-05-10(Sat) 09:40 (<http://www.timeanddate.com/worldclock/fixedtime.html?iso=20250510T2240&p1=248>) (local time) (100 minutes)

[Back to Home \(/home\)](/home)
[🏠 Top \(/contests/abc405\)](/contests/abc405)
[☰ Tasks \(/contests/abc405/tasks\)](/contests/abc405/tasks)
[❓ Clarifications \(/contests/abc405/clarifications\)](/contests/abc405/clarifications)
[🚀 Submit \(/contests/abc405/submit?taskScreenName=abc405_g\)](/contests/abc405/submit?taskScreenName=abc405_g)
[☰ Results ▼](#)
[🏆 Standings \(/contests/abc405/standings\)](/contests/abc405/standings)
[🏆 Virtual Standings \(/contests/abc405/standings/virtual\)](/contests/abc405/standings/virtual)
[🔧 Custom Test \(/contests/abc405/custom_test\)](/contests/abc405/custom_test)
[📖 Editorial \(/contests/abc405/editorial\)](/contests/abc405/editorial)
[💬 Discuss \(https://codeforces.com/blog/entry/142744\)](https://codeforces.com/blog/entry/142744)


G - Range Shuffle Query

[Editorial \(/contests/abc405/tasks/abc405_g/editorial\)](/contests/abc405/tasks/abc405_g/editorial)


Time Limit: 2 sec / Memory Limit: 1024 MB

Score : 625 points

Problem Statement

You are given a length- N sequence $A = (A_1, A_2, \dots, A_N)$.

Process Q queries.

Each query gives you integers L, R, X and asks you to solve the following.

Let $B = (A_L, A_{L+1}, \dots, A_R)$ be the sequence formed by the L -th through R -th elements of A .

Perform the following procedure exactly once:

- First, remove from B every element whose value is at least X .
- Then, rearrange the remaining elements of B arbitrarily.

How many distinct sequences B can result? Find the count modulo 998244353.

Constraints

- $1 \leq N \leq 2.5 \times 10^5$
- $1 \leq Q \leq 2.5 \times 10^5$

2025-05-10 (Sat)
12:12:04 -04:00

- $1 \leq A_i \leq N$
- $1 \leq L \leq R \leq N$
- $1 \leq X \leq N$
- All input values are integers.

Input

The input is given from Standard Input in the following format, where query_i denotes the i -th query:

```

N Q
A_1 A_2 ... A_N
query_1
query_2
⋮
query_Q

```

Each query is given in the following format:

```

L R X

```

Output

Output Q lines. The i -th line should contain the answer to the i -th query.

Sample Input 1

[Copy](#)

```

5 3
1 2 3 3 1
1 5 3
3 4 1
1 3 4

```

[Copy](#)

Sample Output 1

[Copy](#)

```

3
1
6

```

[Copy](#)

For the first query, there are three possible resulting sequences B : $(1, 1, 2)$, $(1, 2, 1)$, and $(2, 1, 1)$.

For the second query, there is one possible resulting sequence B : the empty sequence $()$.

Sample Input 2

Copy

```
8 6
6 2 4 1 5 1 8 6
5 6 3
1 5 7
1 4 6
4 7 8
4 8 2
5 8 6
```

Copy

Sample Output 2

Copy

```
1
120
6
3
1
2
```

Copy

Language

Python (CPython 3.11.4) ▼

Source Code



Open File



Customize


Toggle Editor

Auto Height

1 |

* at most 512 KiB

* Your source code will be saved as `Main.extension`.



Submit

#telegram)

url=https%3A%2F%2Fatcoder.jp%2Fcontests%2Fabc405%2Ftasks%2Fabc405_g%3Flang%3Den&title=G%20-

[Rule \(/contests/abc405/rules\)](/contests/abc405/rules) [Glossary \(/contests/abc405/glossary\)](/contests/abc405/glossary)

[Terms of service \(/tos\)](/tos) [Privacy Policy \(/privacy\)](/privacy) [Information Protection Policy \(/personal\)](/personal) [Company \(/company\)](/company)

[FAQ \(/faq\)](/faq) [Contact \(/contact\)](/contact)

Copyright Since 2012 ©AtCoder Inc. (<http://atcoder.co.jp>) All rights reserved.

2025-05-10 (Sat)
12:12:04 -04:00