



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Experiment No. 1
Analyze the Boston Housing dataset and apply appropriate Regression Technique
Date of Performance: 24—07—23
Date of Submission: 07—08—23



Vidyavardhini's College of Engineering & Technology


Department of Computer Engineering

Aim: Analyze the Boston Housing dataset and apply appropriate Regression Technique.

Objective: Ability to perform various feature engineering tasks, apply linear regression on the given dataset and minimise the error.

Theory:

Linear Regression is a machine learning algorithm based on supervised learning. It performs a regression task. Regression models a target prediction value based on independent variables. It is mostly used for finding out the relationship between variables and forecasting. Different regression models differ based on – the kind of relationship between dependent and independent variables they are considering, and the number of independent variables getting used.



Linear regression performs the task to predict a dependent variable value (y) based on a given independent variable (x). So, this regression technique finds out a linear relationship between x (input) and y(output). Hence, the name is Linear Regression.

In the figure above, X (input) is the work experience and Y (output) is the salary of a person.

The regression line is the best fit line for our model.



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Dataset:

The Boston Housing Dataset

The Boston Housing Dataset is derived from information collected by the U.S. Census Service concerning housing in the area of Boston MA. The following describes the dataset columns:

CRIM - per capita crime rate by town

ZN - proportion of residential land zoned for lots over 25,000 sq.ft.

INDUS - proportion of non-retail business acres per town.

CHAS - Charles River dummy variable (1 if tract bounds river; 0 otherwise)

NOX - nitric oxides concentration (parts per 10 million)

RM - average number of rooms per dwelling

AGE - proportion of owner-occupied units built prior to 1940

DIS - weighted distances to five Boston employment centres

RAD - index of accessibility to radial highways

TAX - full-value property-tax rate per \$10,000

PTRATIO - pupil-teacher ratio by town

B - $1000(B_k - 0.63)^2$ where B_k is the proportion of blacks by town

LSTAT - % lower status of the population

MEDV - Median value of owner-occupied homes in \$1000's

Code:



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Conclusion:

The selected set of features for estimating house prices includes several attributes that capture various aspects of the towns, which can influence the median home value. These attributes include CRIM, ZN, INDUS, CHAS, NOX, RM, AGE, DIS, RAD, TAX, PTRATIO, B, LSTAT. Crime rate, proportion of residential land, nitric oxide concentration, average number of rooms, accessibility to highways, property-tax rate, etc., these factors influence home prices in different neighborhoods. The target variable, MEDV (Median Home Value), is the central focus of our prediction model these features can predict the median value of homes.

The Mean Squared Error of 0.03112933398095344 indicates the average squared difference between predicted and actual house prices in the model. Comparing this value to the range of actual house prices determines the model's predictions are accurate enough or not

```
import numpy as np
import pandas as pd
from sklearn.metrics import mean_squared_error
from sklearn.linear_model import LinearRegression
from sklearn.model_selection import train_test_split
import matplotlib.pyplot as plt
import seaborn as sns
```

```
data=pd.read_csv('/content/BostonHousing (1).csv')
```

```
pd.read_csv('/content/BostonHousing (1).csv')
```

	crim	zn	indus	chas	nox	rm	age	dis	rad	tax	ptratio	b	lstat
0	0.00632	18.0	2.31	0	0.538	6.575	65.2	4.0900	1	296	15.3	396.90	4.98
1	0.02731	0.0	7.07	0	0.469	6.421	78.9	4.9671	2	242	17.8	396.90	9.14
2	0.02729	0.0	7.07	0	0.469	7.185	61.1	4.9671	2	242	17.8	392.83	4.03
3	0.03237	0.0	2.18	0	0.458	6.998	45.8	6.0622	3	222	18.7	394.63	2.94
4	0.06905	0.0	2.18	0	0.458	7.147	54.2	6.0622	3	222	18.7	396.90	5.33
...
501	0.06263	0.0	11.93	0	0.573	6.593	69.1	2.4786	1	273	21.0	391.99	9.67
502	0.04527	0.0	11.93	0	0.573	6.120	76.7	2.2875	1	273	21.0	396.90	9.08
503	0.06076	0.0	11.93	0	0.573	6.976	91.0	2.1675	1	273	21.0	396.90	5.64
504	0.10959	0.0	11.93	0	0.573	6.794	89.3	2.3889	1	273	21.0	393.45	6.48
505	0.04741	0.0	11.93	0	0.573	6.030	80.8	2.5050	1	273	21.0	396.90	7.88

506 rows × 14 columns

```
column_names = ['CRIM', 'ZN', 'INDUS', 'CHAS', 'NOX', 'RM', 'AGE', 'DIS', 'RAD', 'TAX', 'PTRATIO', 'B', 'LSTAT', 'MEDV']
```

```
print(data.head(5))
```

	crim	zn	indus	chas	nox	rm	age	dis	rad	tax	ptratio	b	lstat	medv
0	0.00632	18.0	2.31	0	0.538	6.575	65.2	4.0900	1	296	15.3	396.90	4.98	24.0
1	0.02731	0.0	7.07	0	0.469	6.421	78.9	4.9671	2	242	17.8	396.90	9.14	21.6
2	0.02729	0.0	7.07	0	0.469	7.185	61.1	4.9671	2	242	17.8	392.83	4.03	34.7
3	0.03237	0.0	2.18	0	0.458	6.998	45.8	6.0622	3	222	18.7	394.63	2.94	33.4
4	0.06905	0.0	2.18	0	0.458	7.147	54.2	6.0622	3	222	18.7	396.90	5.33	36.2

```
print(np.shape(data))
```

(506, 14)

```
print(data.describe())
```

	crim	zn	indus	chas	nox	rm
count	506.000000	506.000000	506.000000	506.000000	506.000000	506.000000
mean	3.613524	11.363636	11.136779	0.069170	0.554695	6.284634
std	8.601545	23.322453	6.860353	0.253994	0.115878	0.702617
min	0.006320	0.000000	0.460000	0.000000	0.385000	3.561000
25%	0.082045	0.000000	5.190000	0.000000	0.449000	5.885500
50%	0.256510	0.000000	9.690000	0.000000	0.538000	6.208500
75%	3.677083	12.500000	18.100000	0.000000	0.624000	6.623500
max	88.976200	100.000000	27.740000	1.000000	0.871000	8.780000

	age	dis	rad	tax	ptratio	b
count	506.000000	506.000000	506.000000	506.000000	506.000000	506.000000
mean	68.574901	3.795043	9.549407	408.237154	18.455534	356.674032
std	28.148861	2.105710	8.707259	168.537116	2.164946	91.294864
min	2.900000	1.129600	1.000000	187.000000	12.600000	0.320000
25%	45.025000	2.100175	4.000000	279.000000	17.400000	375.377500

50%	77.500000	3.207450	5.000000	330.000000	19.050000	391.440000
75%	94.075000	5.188425	24.000000	666.000000	20.200000	396.225000
max	100.000000	12.126500	24.000000	711.000000	22.000000	396.900000

	lstat	medv
count	506.000000	506.000000
mean	12.653063	22.532806
std	7.141062	9.197104
min	1.730000	5.000000
25%	6.950000	17.025000
50%	11.360000	21.200000
75%	16.955000	25.000000
max	37.970000	50.000000

```
data.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 506 entries, 0 to 505
Data columns (total 14 columns):
#   Column      Non-Null Count  Dtype
---  ---
0    crim        506 non-null    float64
1    zn          506 non-null    float64
2    indus       506 non-null    float64
3    chas        506 non-null    int64
4    nox         506 non-null    float64
5    rm          506 non-null    float64
6    age         506 non-null    float64
7    dis         506 non-null    float64
8    rad         506 non-null    int64
9    tax         506 non-null    int64
10   ptratio     506 non-null    float64
11   b           506 non-null    float64
12   lstat       506 non-null    float64
13   medv        506 non-null    float64
dtypes: float64(11), int64(3)
memory usage: 55.5 KB
```

```
linr = LinearRegression()
```

```
data['medv'] = np.log1p(data['medv'])
```

```
X = data.drop(['medv', 'b'], axis=1)
```

```
Y = data['medv']
```

```
print(X)
```

	crim	zn	indus	chas	nox	rm	age	dis	rad	tax	\
0	0.00632	18.0	2.31	0	0.538	6.575	65.2	4.0900	1	296	
1	0.02731	0.0	7.07	0	0.469	6.421	78.9	4.9671	2	242	
2	0.02729	0.0	7.07	0	0.469	7.185	61.1	4.9671	2	242	
3	0.03237	0.0	2.18	0	0.458	6.998	45.8	6.0622	3	222	
4	0.06905	0.0	2.18	0	0.458	7.147	54.2	6.0622	3	222	
..	
501	0.06263	0.0	11.93	0	0.573	6.593	69.1	2.4786	1	273	
502	0.04527	0.0	11.93	0	0.573	6.120	76.7	2.2875	1	273	
503	0.06076	0.0	11.93	0	0.573	6.976	91.0	2.1675	1	273	
504	0.10959	0.0	11.93	0	0.573	6.794	89.3	2.3889	1	273	
505	0.04741	0.0	11.93	0	0.573	6.030	80.8	2.5050	1	273	

	ptratio	lstat
0	15.3	4.98
1	17.8	9.14
2	17.8	4.03
3	18.7	2.94
4	18.7	5.33
..
501	21.0	9.67
502	21.0	9.08
503	21.0	5.64
504	21.0	6.48
505	21.0	7.88

```
[506 rows x 12 columns]
```

```
print(Y)
```

```

0      3.218876
1      3.117950
2      3.575151
3      3.538057
4      3.616309
...
501     3.152736
502     3.072693
503     3.214868
504     3.135494
505     2.557227
Name: medv, Length: 506, dtype: float64

```

```
x_train, x_test, y_train, y_test = train_test_split(X, Y, random_state=42, test_size=0.3)
```

```

print("x_train shape:",x_train.shape)
print("x_test shape:",x_test.shape)
print("y_train shape:",x_train.shape)
print("y_train shape:",x_test.shape)

```

```

x_train shape: (354, 12)
x_test shape: (152, 12)
y_train shape: (354, 12)
y_train shape: (152, 12)

```

```
linr.fit(x_train, y_train)
```

```

LinearRegression
LinearRegression()

```

```
y_pred = linr.predict(x_test)
```

```
print(mean_squared_error(y_test, y_pred))
```

```
0.03112933398095344
```

```

plt.scatter(y_test,y_pred,c='blue')
plt.xlabel("value")
plt.ylabel("Predicted value")
plt.title("True value vs predicted value : Linear Regression")
plt.show()

```

