

CONSUMER SSD

Experience lightning-fast responsiveness and upgrade your everyday computing. Boot up in seconds, load applications instantly, and enjoy a smoother workflow.

MP700G4

- 1 SOLID STATE DEPENDABILITY
- 2 LESS POWER. MORE PLAY.
- 3 IMPROVED POWER EFFICIENCY



INTERFACE

PCIe 4.0 x4



FORM FACTOR

M.2 Series



CAPACITY

256GB - 1 TB





CONSUMER SSD

Experience lightning-fast responsiveness and upgrade your everyday computing. Boot up in seconds, load applications instantly, and enjoy a smoother workflow.

MP700G4

MiPhi MP700G4 PCIe Gen 4 Solid State Drive

- Operating Temperature is from 0 to 70 Celsius
- Provides up to 8TB capacity
- Supports PCIe Gen 4.0 x 4 NVMe 1.4



MP700G4

DATA SHEET CONSUMER SSD

SPECIFICATIONS

	8TB	4TB	2TB	1TB	512GB
MODEL NUMBER					-
	MP5018800T	MP5018400T	MP5018200T	MP5018100T	MP5018512G
INTERFACE	3323331	0010-001	30102001	30101001	30103124
INTERFACE	PCIe 4.0 x4				
	PCIE 4.0 X4	PCIE 4.0 X4	PCIE 4.0 X4	PC16 4.0 X4	PCIE 4.0 X4
NAND Flash					
	3D TLC				
FORM FACTOR					
	M.2 2280				
PERFORMANCE ²					
Sequential Read up to (Mb/s)	7000 MB/s	7200 MB/s	7200 MB/s	7200 MB/s	7000 MB/s
Sequential Write up to (Mb/s)	5900 MB/s	6850 MB/s	6850 MB/s	6000 MB/s	3750MB/s
Random Read	900K IOPS	1150K IOPS	1150K IOPS	1050K IOPS	680K IOPS
Random Write	1000K IOPS	1200K IOPS	1200K IOPS	1200K IOPS	700K IOPS
DWPD					
	0.38	0.38	0.38	0.38	0.38
UBER					
	<10-16 bits				
WARRANTY					
	5 Years				

^{(1) 1} GB = 1,000,000,000 bytes



The data within this specification is subject to change by Miphi without notice. Performance numbers may vary based on system configuration and testing conditions. Copyright © 2024 Miphi Semiconductors Private Limited. All rights reserved.

⁽²⁾ Sequential Performance is based on CrystalDiskMark v8, 1 GB range, command size =1MB, QD=32, Thread=1, and test drive set as secondary Random Performance is based on CrystalDiskMark v8, 1 GB range, ,command size =4KB, QD=32, Thread=16, and test drive set as secondary Numbers are estimated value.