

Python Datastructures are 2 types 1.Inbuid data structures 2.User defined data structures

✓ What is Data structure?

-->Data structures is collection of data types(we can declare more than one value) --
>ex>List,tuple,set,dictionary.

List:

1.we can define list with [] 2.List conatains inbuild methods 3.List allows multile data types.
4.duplicate values are allowed. 5.covered appened(),copy(),reverse(),string indexing()

indexing is 2 types:

forward indexing(left to right) backward indexing(right to left) step indexing

What is Matrix?

-->Collection of Data structures is called matrix.

```
i=5
type(i)
→ int


l=[]
l
→ []

type(l)
→ list

len()
→

→ -----[Type Error]----- Traceback (most recent call last)
<ipython-input-45-adf3103c7c3e> in <cell line: 0>()
----> 1 len()

TypeError: len() takes exactly one argument (0 given)
```



len(l)

→ 0

✓ append(): Adds an element to the end of the list.

```
l.append(10)
l.remove(10)
l
→ []

l
→ []
```

✓ remove(): Removes the first occurrence of a specified element.

```
l.remove(10)
```

```
ValueError
<ipython-input-56-dc80452e70d5> in <cell line: 0>()
----> 1 l.remove(10)

ValueError: list.remove(x): x not in list
```

```
1
[]

l.remove(10)
```

Archana Kapu
Jan 27, 2025

remove method deletes the value present in the first

```
1

l.remove(10)

ValueError
<ipython-input-58-dc80452e70d5> in <cell line: 0>()
----> 1 l.remove(10)

ValueError: list.remove(x): x not in list
```

```
1
[]

l.remove(10)
```

```
1
len(l)

l.append(10,20,30,40)
```

```
l.append(10)
l.append(20)
l.append(30)
l.append(40)

1
```

```
l1=[]
l1

l1.append(70)
l1.append(2.3)
l1.append(True)
l1.append(10+2j)
l1.append([10,20,30])
```

```
l1
[70, 2.3, True, (10+2j), [10, 20, 30]]
```

```
print(l)
print(l1)

[]
```

```
print(id(l))
137788748694784

print(id(l1))
```

Archana Kapu
Jan 27, 2025

append methos takes only 1 argument at time, as we passed 4 arguments, error occured.

Archana Kapu
Jan 28, 2025

in data structures id values are different

 137788747412864

✓ how to find length of list?

```
print(len(l))
print(len(l1))

 0
 5

l1

 [70, 2.3, True, (10+2j), [10, 20, 30]]
```

✓ copy(): Returns a shallow copy of the list.

copying 1 list into another>list with in the another list is called nested list.

```
l2=l1.copy()

l2

 [70, 2.3, True, (10+2j), [10, 20, 30]]
```

Comparing 2 lists using assignment operators

```
l1==l2

 True

l1!=l2

 False

l1

 []
```

```
l1==l2

 False

l1!=l2

 True
```

```
l1==l2

 True

print(l1)
print(l2)

 [70, 2.3, True, (10+2j), [10, 20, 30]]
 [70, 2.3, True, (10+2j), [10, 20, 30]]
```

```
print(id(l1))==print(id(l2))

 137788747412864
 137788747786048
 True
```

```
a=4
b=4
```



Archana Kapu
Jan 28, 2025



in Datastructures of list, address of the list with same values are different, where as in data types address of same data type with same value is same.

```
print(id(a))==print(id(b))
```

```
10750952
10750952
True
```

```
1
```

```
[]
```

```
l.remove()
```

```
10750952
10750952
True
```

```
TypeError
Traceback (most recent call last)
<ipython-input-82-6e57923871b5> in <cell line: 0>()
----> 1 l.remove()

TypeError: list.remove() takes exactly one argument (0 given)
```

```
l.remove(10)
```

```
10750952
10750952
True
```

```
ValueError
Traceback (most recent call last)
<ipython-input-83-dc80452e70d5> in <cell line: 0>()
----> 1 l.remove(10)

ValueError: list.remove(x): x not in list
```

```
1
```

```
[]
```

```
l.remove(10)
1
```

```
10750952
10750952
True
```

```
ValueError
Traceback (most recent call last)
<ipython-input-85-dcd5764900bd> in <cell line: 0>()
----> 1 l.remove(10)
      2 l

ValueError: list.remove(x): x not in list
```

list indexing and slicing

String Indexing:

Forward direction indexing

	0	1	2	3	4	5
String	P	y	t	h	o	n
	-6	-5	-4	-3	-2	-1

Backward direction indexing

```
s7='ArchanaDataScientist'
s7
```

```
10750952
10750952
True
```

```
s7[0]
```

```
10750952
10750952
True
```

```
s7[1]
```



Archana Kapu
Jan 28, 2025



need to pass atleast 1 value in remove method



Archana Kapu
Jan 28, 2025



remove method removes 1st occurrences of specified value in list

```
s7[20]
IndexError
<ipython-input-89-6610ae8d39fa> in <cell line: 0>()
----> 1 s7[20]

IndexError: string index out of range

s7[-1]
s7[-13]
for i in s7:
    print(i)
A
r
c
h
a
n
a
D
a
t
a
s
c
i
e
n
t
i
s
t
```

✓ slicing,in python slicing defines with[:]

slicing are 3 types

forward slicing

backward slicing

step slicing

Forward slicing:

[2:7]--->here 2 is left indexing and 7 is right indexing.

2nd index:(n-1) formula right index(7-1)

output will print as 2th to 6th

backward slicing:

[-7:-1]--->here left indexing is -7:-1-1=-7:-2 p/o:-7,-6,-5,-4,-3,-2

```
s9='nareshit'
s9
```

```
'nareshit'
s9[0:9]
s9
'nnareshit'
s9[1:8]
'nareshit'
```

Archana Kapu

Jan 28, 2025
(edited Jan 28, 2025)

n=n-1

n=-3-1=-4

Archana Kapu

Jan 28, 2025

n=n-1 every time applies to right indexing

```
s9[1:-3]
```

```
s9[1:-4]
```

▼ step slicing

```
step_indexing=[1,2,3,4,5,6,7,8,9,10]
step_indexing[0:10:4]#here this mean print values from 0th to 10th indexing by stepping 4steps
```

```
step_indexing[1:7:2]
```

```
step_indexing
```

```
step_indexing[0:10:5]
```

```
step_indexing
```

```
#empty slice means all elemnets will print
step_indexing[:]
```

```
1
```

```
#reverse method will print values in reverse order of the string
l.reverse()
```

```
1
```

```
t= 5
r = 2
print(t // r)
```

```
1
```

▼ 29th Dec

1.number system 2.list data structure 3.deepseek llm model

```
25
```

▼ Conversion of numeric to binary-->25 to binary conversion)

Handwritten diagram showing the conversion of 25 to binary:

$$\begin{array}{r} 25 \\ \hline 2 | 12-1 \\ 2 | 6-0 \\ 2 | 3-0 \\ \hline 1-1 \end{array}$$

The quotient is 101.

Binary representation: 0b1001

Calculation: $1 \times 16 + 1 \times 8 + 0 \times 4 + 0 \times 2 + 1 \times 1 = 25$

bin(25)

0b1001

int(0b100011)

35

bin(35)

0b100011

numeric to octal conversion

Handwritten diagram showing the conversion of 25 to octal:

$$\begin{array}{r} 25 \\ \hline 3 | 3-1 \\ \hline 2 \end{array}$$

The quotient is 31.

31

$3 \times 8 + 1 \times 1$

$24 + 1 = 25$

oct(25)

0o31

int(0o31)

25

bin(7)

0b111

0000	0	1000	8
0001	1	1001	9
0010	2	1010	A
0011	3	1011	B
0100	4	1100	C
0101	5	1101	D
0110	6	1110	E
0111	7	1111	F

wikiHow

number to hexagonal conversion

$$256 = 16 \times 16 + 0$$

number to hexagonal conversion

hex(1)
0x1
hex(2)
0x2
hex(8)
0x8
hex(10)
0xa
hex(11)
0xb
hex(256)
0x100
hex(1)
0x1
hex(9)
0xa

hex(10)

`0xa`


hex(11)

`0xb`

hex(256)

`0x100`

✓ hexagonal conversion and octal conversion



0x31

`25`

0x19

`25`

0x15

21

Q) how to swap 2 variables in python: a,b=5,6 after swap a=6 b=5

```
#1.using temp variable
a1=5
b1=6
```

```
temp=a1
a1=b1
b1=temp
```

```
print(a1)
print(b1)
```

 6
5

```
#2.swapping variables using sum
a3=5
b3=6
```

```
a3=a3+b3
b3=a3-b3
a3=a3-b3
```

```
print(a3)
print(b3)
```

 6
5

```
bin(5)
```

'0b101'

```
bin(6)
```

'0b110'

```
#3.using binary values we can swap
print(0b101)
print(0b110)
```

 5
6

```
print(0b110)
print(0b101)
```

 6
5

```
#4th way of swapping
d,e=5,6
```

```
e,d=d,e
```

```
print(d)
print(e)
```

 6
5

```
l1
```

[70, 2.3, True, (10+2j), [10, 20, 30]]

```
l2
```

[70, 2.3, True, (10+2j), [10, 20, 30]]

```
12.count(True)
→ 1

12.count(70)
→ 1

12.append(70)

12
→ [70, 2.3, True, (10+2j), [10, 20, 30], 70]
```

```
12.count(70)
→ 2

12[:]
→ [70, 2.3, True, (10+2j), [10, 20, 30], 70]

12[:5]
→ [70, 2.3, True, (10+2j), [10, 20, 30]]
```

```
12[5:]
→ [70]
```

1

```
1.append(40)
→ 1

1.append(50)
```

```
1
→ [40, 50]
```

```
1[1:]
→ [50]
```

```
1[2:]
→ []
```

```
1
→ [40, 50]
```

```
1.append(20)
→ 1

1
→ [40, 50, 20]
```

```
1[:-1]
→ [40, 50]

1[::-1]
→ [40, 50]
```

```
1[::-1]
```



Archana Kapu
Feb 1, 2025



count function provides how many time existed provided arg value in list.

`↳ [20, 50, 40]`

`17=[40,30,20,10,40,30,20]`

`17`

`↳ [40, 30, 20, 10, 40, 30, 20]`

`17[::-1]#adance slicing`

`↳ [20, 30, 40, 10, 20, 30, 40]`

`17`

`↳ [40, 30, 20, 10, 40, 30, 20]`

`17[::-2]`

`↳ [20, 40, 20, 40]`

`17.index(20)`

`↳ 2`

`12`

`↳ [70, 2.3, True, (10+2j), [10, 20, 30], 70]`

`id(12)`

`↳ 137788747786048`

`12.clear()`

`12`

`↳ []`

`id(12)`

`↳ 137788747786048`

`del 12`

`12`

`↳ -----
NameError Traceback (most recent call last)
<ipython-input-171-ea320d2ace30> in <cell line: 0>()
----> 1 12
NameError: name '12' is not defined`

`11`

`↳ [70, 2.3, True, (10+2j), [10, 20, 30]]`

`11.pop()`

`↳ [10, 20, 30]`

`11`

`↳ [70, 2.3, True, (10+2j)]`



Archana Kapu
Feb 1, 2025



prints list of the variables in reverse order



Archana Kapu
Feb 1, 2025



index fun writtens first occurrence of index value of attribute



Archana Kapu
Feb 1, 2025



after clearing the list of varibales also shows same address of the list



Archana Kapu
Feb 1, 2025



deleting the list here.

✓ diff between pop and remove

remove --we need to define value of an element

pop--need to mention index value

1

```
→ [40, 50, 20]
```

l2=l.copy()

12

```
→ [40, 50, 20]
```

l2.remove(50)

12

```
→ [40, 20]
```

l2.pop(-1)

```
→ 20
```

12

```
→ [40]
```

l2.append(10)

12

```
→ [40, 10]
```

l2.append(40)

12

```
→ [40, 10, 40]
```

l2.append(30)

12

```
→ [40, 10, 40, 30]
```

l2.insert(2,25)

12

```
→ [40, 10, 25, 40, 30]
```

1

```
→ [40, 50, 20]
```

1[0]

```
→ 40
```

1[0]=400

1

```
→ [400, 50, 20]
```

- List is mutable
- append()-appended the element/value at te last
- remove()-remove the value from the list and we need pass argument value which we need to remove.
- pop()-pop the element or value by the index(by default last)

Archana Kapu
Feb 1, 2025

in insert we need to pass 2 values 1st one is index and 2nd value as value

- copy()—copy the list
- insert()—insert function requires 2 values at which index we need to insert an element and at what place.ex:(2,25) 1st arg—index position 2nd arg—element of a value
- clear()—clear the elements from the list
- del—we can delete the list using del reverse()—reverse the list.



Archana Kapu
Feb 1, 2025

list is mutable

1

```
↳ [400, 50, 20]
```

11

```
↳ [70, 2.3, True, (10+2j)]
```

len(11)

```
↳ 4
```

12

```
↳ [40, 10, 25, 40, 30]
```

len(12)

```
↳ 5
```

11

```
↳ [70, 2.3, True, (10+2j)]
```

```
for i in l1:  
    print(i)
```

```
↳ 70  
2.3  
True  
(10+2j)
```

```
for i in enumerate (l1):  
    print(i)
```

```
↳ (0, 70)  
(1, 2.3)  
(2, True)  
(3, (10+2j))
```

30Jan

1

```
↳ [400, 50, 20]
```

l.sort()#parameter tuning

1

```
↳ [20, 50, 400]
```

l.sort(reverse=True)#hyper parameter tuning

1

```
↳ [400, 50, 20]
```

l5=['m','a','g']

l5.sort()

15

```
↳ ['a', 'g', 'm']
```

l1

```
↳ [70, 2.3, True, (10+2j)]
```

l1.sort()

```
↳ -----  
TypeError: Traceback (most recent call last)  
<ipython-input-228-b8f5f256bbcf> in <cell line: 0>()  
----> 1 l1.sort()  
  
TypeError: '<' not supported between instances of 'complex' and 'bool'
```

a=2
b=3
a+b

```
↳ 5
```

int.__add__(2,3)

```
↳ 5
```

int.__sub__(2,3)

```
↳ -1
```

int.__mul__(2,3)

```
↳ 6
```

float.__sub__(2.3,3.3)

```
↳ -1.0
```

list is completed



Archana Kapu
Feb 1, 2025



sort applicable for only with in same data type