

37.pdf



University of Engineering & Management

Document Details

Submission ID

trn:oid::3618:103124105

Submission Date

Jul 1, 2025, 2:33 PM GMT+5:30

Download Date

Jul 5, 2025, 12:35 AM GMT+5:30

File Name

37.pdf

File Size

283.7 KB

22 Pages

6,543 Words

38,826 Characters

11% Overall Similarity

The combined total of all matches, including overlapping sources, for each database.

Match Groups

-  **59 Not Cited or Quoted 10%**
Matches with neither in-text citation nor quotation marks
-  **8 Missing Quotations 1%**
Matches that are still very similar to source material
-  **0 Missing Citation 0%**
Matches that have quotation marks, but no in-text citation
-  **0 Cited and Quoted 0%**
Matches with in-text citation present, but no quotation marks

Top Sources

- 7%  Internet sources
- 7%  Publications
- 8%  Submitted works (Student Papers)

Integrity Flags

0 Integrity Flags for Review

No suspicious text manipulations found.

Our system's algorithms look deeply at a document for any inconsistencies that would set it apart from a normal submission. If we notice something strange, we flag it for you to review.

A Flag is not necessarily an indicator of a problem. However, we'd recommend you focus your attention there for further review.

Match Groups

- 59** Not Cited or Quoted 10%
Matches with neither in-text citation nor quotation marks
- 8** Missing Quotations 1%
Matches that are still very similar to source material
- 0** Missing Citation 0%
Matches that have quotation marks, but no in-text citation
- 0** Cited and Quoted 0%
Matches with in-text citation present, but no quotation marks

Top Sources

- 7% Internet sources
- 7% Publications
- 8% Submitted works (Student Papers)

Top Sources

The sources with the highest number of matches within the submission. Overlapping sources will not be displayed.

- 1** Internet
www.mdpi.com <1%
- 2** Submitted works
Harrisburg University of Science and Technology on 2024-03-21 <1%
- 3** Internet
www.researchsquare.com <1%
- 4** Submitted works
Queen Mary and Westfield College on 2023-12-04 <1%
- 5** Internet
hrcak.srce.hr <1%
- 6** Internet
www.inass.org <1%
- 7** Publication
Mehmet Demirtaş. "Multiple-Image Encryption Using Sine Quadratic Polynomial ... <1%
- 8** Internet
www.csauthors.net <1%
- 9** Publication
Seetala, Kiran S.. "Encryption With Synchronized Chaos Using Fabricated Cobalt F... <1%
- 10** Internet
www.i-scholar.in <1%

11	Internet	www.locus.ufv.br	<1%
12	Submitted works	Higher Education Commission Pakistan on 2025-06-24	<1%
13	Submitted works	Southern Arkansas University (Blackboard LTI 1.3) on 2025-02-24	<1%
14	Internet	arxiv.org	<1%
15	Submitted works	University of Greenwich on 2024-12-20	<1%
16	Submitted works	Middlesex University on 2024-09-26	<1%
17	Internet	americaspg.com	<1%
18	Internet	www2.imm.dtu.dk	<1%
19	Submitted works	Gulf College Oman on 2025-05-27	<1%
20	Submitted works	King Saud University on 2013-11-16	<1%
21	Publication	Poonam Nandal, Mamta Dahiya, Meeta Singh, Arvind Dagur, Brijesh Kumar. "Pro...	<1%
22	Publication	Qinghui Chen, Cong Peng, Li Zhao, Weihao You, Hong Wen, Jianshe Li. "Physical la...	<1%
23	Publication	D. Schonberg, D. Kirovski. "Iris compression for cryptographically secure person i...	<1%
24	Submitted works	Arab Open University on 2025-05-04	<1%

25	Publication	Prayaag Kini, V. Reeta, Subramaniam, K.P. Suresh. "The SOLSTICES score in HCM/...	<1%
26	Submitted works	Tunisian Consortium on 2025-03-24	<1%
27	Submitted works	Kwame Nkrumah University of Science and Technology on 2025-05-16	<1%
28	Submitted works	Vrije Universiteit Amsterdam on 2024-11-28	<1%
29	Submitted works	Queen Mary and Westfield College on 2017-12-01	<1%
30	Submitted works	Vrije Universiteit Amsterdam on 2024-11-27	<1%
31	Internet	docplayer.net	<1%
32	Internet	www.iieta.org	<1%
33	Publication	Jun Lu, Jiaxin Zhang, Dawei Hao, Ruoyu Zhao, Jun Mou, Yushu Zhang. "Text visuali...	<1%
34	Submitted works	Kennesaw State University on 2023-12-10	<1%
35	Submitted works	School of Business and Management ITB on 2022-05-01	<1%
36	Submitted works	University of Glasgow on 2024-12-07	<1%
37	Submitted works	universiteteknologimara on 2025-06-30	<1%
38	Internet	www.acn.gov.it	<1%

39	Internet	www.jait.us	<1%
40	Internet	www.rapidsslonline.com	<1%
41	Publication	Behrouz Zolfaghari, Takeshi Koshiba. "Chaotic Image Encryption: State-of-the-Art..."	<1%
42	Publication	Güvenoğlu, Duygu. "Görüntü Şifrelemede Kullanılan Kaotik Haritaların İncelenme..."	<1%
43	Publication	Noor Sattar Noor, Dalal Abdulmohsin Hammood, Ali Al-Naji, Javaan Chahl. "A Fast..."	<1%
44	Submitted works	Queen Mary and Westfield College on 2024-11-29	<1%
45	Submitted works	Institute of International Studies on 2023-09-11	<1%
46	Submitted works	JNTUA College of Engineering, Anantapur on 2023-08-26	<1%
47	Publication	Shengtao Geng, Heng Zhang, Xuncaizhang. "A hexadecimal scrambling image en..."	<1%
48	Publication	Sujata Garera. "Challenges in teaching a graduate course in applied cryptograph..."	<1%
49	Submitted works	Universidad Tecnológica Centroamericana UNITEC on 2025-06-30	<1%

CipherCanvas: Transforming Text into Unbreakable Visual Hashes

Abstract

The rapid evolution of information technology and the rise of data security concerns have necessitated innovative approaches to encryption and hashing. This paper analyzes a visual cryptographic hashing system that encodes textual data into Voronoi diagrams using deterministic color mapping and procedural point generation. The cryptographic robustness of the system is evaluated through entropy calculations, avalanche effect testing, collision resistance, and structural vulnerability assessments. A novel cryptographic attack is introduced, where an adversary with knowledge of the color map and matrix dimensions attempts to reconstruct the original input. Empirical tests show partial success in recovering individual characters, but significant challenges remain in achieving full pre-image recovery. The findings reveal the resilience of the system, while also highlighting vulnerabilities to frequency-based and pattern-recognition attacks, suggesting the need for further improvements to enhance its security.

Keywords: cellular automata, data wrapping randomization, modular arithmetic, Base64 encoding

1 INTRODUCTION

In the digital age, securing information has become paramount due to the rise in data breaches, unauthorized access, and cyberattacks. As more sensitive information is stored and shared online, the need for robust security protocols has never been more critical. Traditional cryptographic methods like hashing algorithms such as SHA-256 and MD5 have been fundamental in safeguarding data by converting information into fixed-length values, which are nearly impossible to reverse-engineer. However, these methods, while effective in their primary goal of ensuring data integrity and confidentiality, often lack interpretability and aesthetic appeal. They produce seemingly random strings of characters that are not human-friendly and cannot easily be understood or visualized by the average user.

In recent years, visual hashing has emerged as a fascinating approach to this challenge. Visual hashing aims to convert data into a visual format, typically through images or patterns, that retains the original information but is also easy for humans to interpret. This process involves transforming data into a visual representation that is both unique and consistent, much like a traditional hash, but in a form that can be understood at a glance. For instance, certain techniques allow a document or an image to be transformed into a QR code or a stylized graphical representation, which can be visually verified and shared more easily than cryptographic hashes. Visual hashing combines the best of both worlds by providing data security while also making the data more accessible and understandable in a way that appeals to both humans and machines. This advancement opens up new possibilities for securing and interacting with

information in a more intuitive and aesthetically pleasing way.

This paper proposes a novel hashing algorithm that transforms textual data into visually encoded outputs, blending cryptographic rigor with image processing methodologies. The analyzed visual hashing system merges cryptographic integrity with human-readable representation, employing Voronoi diagrams to encode text data.

Furthermore, the paper draws on prior research in visual cryptography, which demonstrates the trade-offs between aesthetic appeal and cryptographic rigor. For instance, Zhao and Feng (2006) showed that geometric hashing schemes, although effective for tamper detection, often fail to meet critical cryptographic standards, such as providing adequate diffusion for pre-image resistance. Similarly, while Voronoi diagrams have found applications in steganography and watermarking, their structural regularity exposes vulnerabilities that can be exploited by adversaries. The current system's reliance on a static color map and SHA-256-derived jitter seeds offer some initial entropy but does not satisfy cryptographic standards like FIPS 180-4, which emphasize the avalanche criterion to ensure cryptographic security.

2 LITERATURE REVIEW

Menezes et al. present one of the most influential works in cryptography, offering a comprehensive and practical guide to the theory and application of cryptographic techniques. This book serves as a critical resource for understanding the mathematical underpinnings of cryptography, including block ciphers, public-key systems, and cryptographic protocols. It has shaped much of the cryptographic research landscape, providing essential knowledge for both theoretical cryptographers and practitioners in the field [1].

Kelsey (2002) highlights the critical vulnerabilities in pseudorandom number generators (PRNGs), which are fundamental to cryptographic systems[2]. Kelsey identifies several attack strategies that exploit weaknesses in PRNGs, such as state recovery and predictability of output. His work emphasizes the need for robust and secure random number generation in cryptographic protocols, which remains a crucial aspect of cryptographic system design to date.

Zhao and Feng (2006) introduced a new approach to image encryption which proposed the integration of visual cryptography into image hashing. Their technique allows images to be divided into shares that are securely encoded, such that the original image can be revealed only when a sufficient number of shares are combined. This method is particularly useful in applications requiring secure image authentication, such as digital watermarking and image-based security systems [3].

Stinson (2006) offers an in-depth exploration of the mathematical and practical aspects of cryptographic systems. Stinson's work[4] covers symmetric and asymmetric encryption, cryptographic hash functions, and the principles of secure communication. It is widely used as a textbook in cryptography courses and a reference for cryptographers looking to understand both theoretical and practical cryptographic techniques .

Okabe et al. (2009) explore the application of Voronoi diagrams in cryptography and spatial data analysis. Voronoi diagrams, which partition space based on proximity to a set of points, have applications in image encryption, secure data distribution, and cryptographic protocols that require spatial relationships[5]. Their work highlights the versatility of Voronoi diagrams in cryptography and spatial data processing .

Gueron et al. (2011) presented a detailed analysis of the SHA-512/256 hash function, which is a variant of the SHA-512 hash function. This function is particularly well-suited for applications requiring high security and computational efficiency. The authors explore the design rationale and performance characteristics of SHA-512/256, demonstrating its relevance in secure hash algorithms used for digital signatures, message authentication codes, and key generation [6].

Rogaway (2015) delves into the ethical dimensions of cryptography, urging cryptographers to consider the broader societal impacts of their work. Rogaway argues that cryptographers must be aware of how their designs can influence privacy, security, and freedom, particularly in the context of governmental surveillance and corporate data usage. This paper highlights the importance of ethical responsibility in the development of cryptographic systems [7].

[8], provides standardized guidelines for the Secure Hash Algorithm (SHA) family, which includes widely-used hash functions such as SHA-256 and SHA-512. These hash functions play a critical role in digital signatures, data integrity checks, and many cryptographic protocols. The standardization of these algorithms by NIST ensures that cryptographic systems are both secure and interoperable across different platforms and systems.

Hariyanto and Rahim (2016) introduced the application of Arnold's Cat Map in Arnold's Cat Map Algorithm demonstrating its use in chaotic image encryption. The Arnold Cat Map is a mathematical transformation known for its chaotic properties, which can be leveraged to encrypt image data by scrambling the pixel values. This paper contributes to the growing field of chaotic cryptography by exploring the effectiveness of the Cat Map in securing image data in applications like digital content protection [9].

Halagowda and Lakshminarayana (2017) proposed a Hybrid Fractal-Chaos Algorithm for image encryption in their paper, which combines fractal geometry with chaotic systems to provide enhanced security for digital images [10]. The authors show that the hybrid method can produce highly unpredictable and secure encryption results, making it resistant to various attacks. This approach is particularly useful for high-security applications where both efficiency and robustness are paramount.

Wu and Liu (2018) investigated the Security Analysis of Visual Hash Functions, addressing the strengths and weaknesses of visual hash functions used in securing digital images. Their analysis reveals potential vulnerabilities in existing visual hash algorithms and proposes strategies for improving the robustness of these systems against cryptographic attacks. This work is critical in understanding the limitations of visual cryptographic techniques and refining them for use in secure image transmission and authentication [11].

NIST (2020) discusses the need for cryptographic systems that are efficient and secure in resource-constrained environments, such as Internet of Things (IoT) devices. The document outlines the requirements for lightweight cryptographic algorithms, which are designed to ensure that even devices with limited computational resources can securely process data. This standardization effort is essential as the demand for secure IoT devices continues to rise [12].

Kessler (2020) provides a comprehensive guide to cryptanalysis, specifically focusing on frequency analysis as a method for breaking substitution ciphers [13]. The paper illustrates how frequency analysis exploits the predictable patterns of letter occurrence in a language to decipher encrypted text. This classic cryptanalysis technique remains an essential tool for understanding the vulnerabilities of older encryption schemes.

Tang and Mandal (2021)[14] focuses on utilizing hyperchaotic systems for encrypting data at the physical layer in communication systems. The authors demonstrate that using synchronized chaotic systems for encryption at this layer adds an additional layer of security, making it more difficult for attackers to intercept or manipulate the transmitted data. This approach represents a novel application of chaotic systems in modern communication protocols.

Demirtaş (2022) developed a Fast Multiple Image Encryption Algorithm in his paper, which combines the Hilbert curve with chaotic maps to efficiently encrypt multiple images. The method improves upon traditional encryption techniques by enabling faster encryption of large datasets while maintaining high security. This approach is particularly beneficial in scenarios where multiple images need to be processed simultaneously, such as in cloud storage or large-scale image databases [15].

Geng et al. (2022) [16] proposed a Hexadecimal Scrambling Image Encryption Scheme based on an improved four-dimensional chaotic system. This encryption scheme enhances traditional image encryption methods by introducing a higher level of complexity through the use of hexadecimal scrambling and chaotic systems. The improved chaotic system increases the unpredictability of the encryption process, making it more resistant to common cryptanalytic attacks. This method is ideal for applications requiring high security, such as medical imaging and secure communications.

Lazar et al. (2022) in [17] examine the use of Voronoi diagrams in cryptography, particularly for secure data distribution and spatially dependent encryption schemes. Their work demonstrates the application of Voronoi cells in representing and analyzing particle systems, offering insights into how spatial tessellations can be utilized for more efficient and secure encryption techniques.

Zolfaghari and Koshiba (2022) summarized the current state of research in chaotic image encryption. They discuss the various types of chaotic systems employed in image encryption, identifying strengths and weaknesses in existing methods. Their review provides a roadmap for future research, encouraging further exploration of chaotic systems to enhance the security and efficiency of image encryption algorithms [18].

Sultana and Srinivas (2024) investigated Data Privacy Protection in Cloud Computing Using Visual Cryptography, exploring how visual cryptography can be applied to protect data privacy in cloud computing environments. Their approach allows for the secure storage and sharing of encrypted images in the cloud, ensuring that only authorized users can access the original data. This work is particularly relevant as cloud computing continues to grow, and the need for effective data protection becomes more urgent [19].

3 PROPOSED METHOD: TEXT ENCRYPTION USING VORONOI BASED HASHING

The proposed method leverages deterministic randomness, text-to-color mapping, and scalable image generation to produce unique visual hashes for secure data representation. Each phase of the methodology is detailed below, emphasizing reproducibility and uniqueness.

3.1. Input Text Handling

3.1.1. Text Preprocessing:

The input text is processed to remove extraneous whitespace while retaining all meaningful characters. Special characters and numerical values are preserved to maintain data integrity.

3.1.2. Chunk Division:

To handle large text inputs effectively, the data is divided into manageable chunks. Each chunk contains a fixed maximum number of characters:

- Maximum characters per line is 64.
- Maximum lines per chunk is 64.

Thus, each chunk accommodates a maximum of 4,096 characters.

3.1.3. Hash-Based Chunk Identification:

Each chunk is independently hashed using the SHA-256 algorithm. This ensures that the subsequent processes (e.g., point generation and color assignment) are tied deterministically to the chunk content.

3.2. Text-to-Color Mapping

3.2.1. Character Mapping:

Each character in the input text is mapped to a unique hexadecimal color using a predefined color-map. The map ensures that:

- Every character, including symbols, has a unique and consistent color.
- Characters not explicitly mapped are mapped default to white (*FFFFFF*) or deterministically generated fallback color.

3.2.2. Matrix Formation:

The mapped colors are arranged in a two-dimensional matrix. Each row represents a line of text, and each column corresponds to a character:

- Rows are limited by the maximum character per line parameter.
- If the number of characters in a chunk exceeds the capacity of a single matrix, the remaining characters spill into subsequent matrices.

3.2.3. Color Redundancy Check:

Duplicate or redundant colors are analyzed to ensure that the matrix contains sufficient visual variation for clear Voronoi rendering.

3.3. Matrix-to-Image Conversion

3.3.1. Matrix Scaling:

Each color matrix is scaled to fit a 512x512 pixel canvas. The scaling ensures that each matrix is proportionally represented, regardless of input size.

3.3.2. Pixel Rendering:

Each color in the matrix is rendered as a pixel block of a specific size. The pixel size is calculated dynamically based on:

- The total number of characters in the chunk.
- The matrix dimensions.

The resulting pixel blocks are resized to form a uniform 512x512 image.

3.3.3. Voronoi Tessellation

Point Generation:

For each matrix, a corresponding grid of points is generated:

- Each character in the matrix corresponds to a point on the canvas.
- Points are jittered slightly using deterministic randomness based on the hash seed of the chunk.

Minimum Point Enforcement:

To ensure the robustness of the tessellation:

- A minimum of 7 points is enforced.
- If fewer points exist, additional points are generated deterministically using the chunk's hash seed.
- Each added point is assigned a fallback color derived from the seed.

Voronoi Region Assignment:

The Voronoi tessellation divides the canvas into polygonal regions. Each region:

- Is assigned a color from the matrix.
- Corresponds to a single point, ensuring deterministic visual representation.

Edge Handling:

Infinite Voronoi regions near the canvas boundaries are clipped to ensure a clean and bounded tessellation.

3.3.4. Deterministic Randomness

Seed-Based Operations:

The deterministic randomness ensures that:

- The same input text always produces the same points, colors, and images.
- Even small changes in the input text result in entirely different outputs due to the sensitivity of the SHA-256 hash.

Color Assignment for Added Points:

Fallback colors for extra points are generated deterministically:

- The seed value and point index are combined to ensure uniqueness.
- Brightness thresholds ensure that all colors are visually distinct.

3.3.5. Image Output and Storage

Image Outputs:

For each chunk of text, a Voronoi diagram image is generated which is a polygonal representation based on the points and colors.

Below, the detailed steps of the algorithm are outlined, providing an in-depth understanding of the computational logic and methodology employed.

Algorithm 1 Text to Voronoi Image Generation

Require: A string input text, chunk size, color map, and min points

Ensure: A set of images (matrix image, Voronoi image)

```

0: procedure TEXTTOVORONOIIMAGEGENERATION
1:   Input: A string input text, chunk size, color map, and min points
2:   Output: A set of images (matrix image, Voronoi image)
3:   Begin
4:   for  $i = 0$  to length(input text) do
5:     chunk = substring(input text,  $i$ , chunk size) {Step 2: Extract chunk from input text}
6:     chunk seed = SHA256(chunk) {Step 3a: Compute chunk seed using SHA-256}
7:     color matrix = map chunk to colors(chunk, color map) {Step 3b: Map characters to hex colors}
8:     matrix image = scale to image(color matrix, 512, 512) {Step 4 and 5: Scale to 512x512 image}
9:     points = generate voronoi points(matrix, chunk seed, canvas size(512*512)) {Step 6: Generate Voronoi points}
10:    if length(points)  $\leq$  min points then
11:      add deterministic points(points, min points, chunk seed) {Step 6a: Add points if less than minimum}
12:    end if
13:    voronoi image = compute voronoi diagram(points, color map, canvas size) {Step 7: Compute Voronoi diagram}
14:    render image(voronoi image) {Step 8: Render the Voronoi diagram as an image}
15:    save image(matrix image, "matrix image.png") {Step 9: Save matrix image}
16:    save image(voronoi image, "voronoi image.png") {Step 9: Save Voronoi image}
17:  end for

```

The workflow diagram presented below outlines the sequential steps involved in the algorithm.




Figure 1. Hashing algorithm: Phase I

4 THREAT MODEL

The adversary can be of two types, viz

- Casual: Relies on visual inspection; lacks knowledge of $color_map$ or seed logic.
- Algorithm-Aware: Knows the $color_map$, grid layout.

The security goals of the algorithm is

- Preimage Resistance: Difficulty in reversing Voronoi $\rightarrow$ text.

- **Avalanche Effect:** Small input changes → large output changes.
- **Collision Resistance:** Difficulty in finding two inputs with identical diagrams.

Attack Strategy

To analyze the system vulnerability, an adversarial attack was systematically conducted in multiple stages. The attacker is assumed to have complete knowledge of the color map used for encoding characters and the respective matrix dimensions (e.g., 64x64 grid size at maximum). This significantly reduces the randomness available for security and provides a basis for reconstructing potential inputs.

Voronoi Site Extraction:

- The adversary begins by preprocessing the target Voronoi image, converting it to grayscale for better contrast.
- Edge detection (using Canny or Sobel filters) isolates significant region boundaries.
- Voronoi site centers are estimated by extracting the centroids of the detected region boundaries.

Color Dominance Analysis:

- The extracted image data undergoes K-Means clustering to determine the dominant colors present.
- These extracted RGB values are then matched against the known static color map used in the hashing process.

Reverse Mapping to Characters:

- Using the color map, the adversary assigns potential character values to extracted colors.
- Due to color clustering, some characters may be misclassified, requiring additional filtering.

Grid Reconstruction:

- The estimated character values are organized into a grid structure matching the assumed input dimensions.
- Missing or uncertain values are interpolated using context-based techniques.

Frequency-Based Refinement:

- Statistical frequency analysis is employed to refine ambiguous character mappings.
- Common letter distributions in English text are leveraged to make educated corrections to uncertain characters.

Text Recovery and Validation:

- The reconstructed text is cross-validated with expected word structures and dictionary-based analysis to improve accuracy.
- Recovered sequences are analyzed for patterns indicative of meaningful text.

The proposed algorithm tackles reconstructing text from color-encoded images, where characters are represented by distinct color regions. It combines computer vision and statistical optimization to address color ambiguities and spatial inconsistencies. Key innovations include adaptive K-means clustering for color extraction, grid-based mode selection for character localization, and linguistic frequency alignment to resolve ambiguities.

Algorithm 2 Reconstruct Text from Voronoi Image

Require: image_path, color_map, matrix_dimensions

Ensure: recovered_text_matrix

0: **procedure** VORONOI IMAGE TO TEXT

1: **Step 1: Load and Preprocess Image**

2: Load image and convert to grayscale

3: Apply edge detection (Canny/Sobel) to highlight boundaries

4: Extract Voronoi site coordinates via centroid detection

5: **Step 2: Extract and Cluster Dominant Colors**

6: Convert image to RGB pixel array

7: Apply K-Means clustering to detect dominant colors

8: Map clustered colors to the closest match in color_map

9: **Step 3: Reconstruct Character Grid**

10: Divide image into uniform grid of matrix_dimensions

11: **for** each grid cell **do**

12: Assign character based on dominant color mapping

13: **end for**

14: Apply interpolation to handle missing values

15: **Step 4: Apply Frequency Analysis and Correction**

16: Compute character frequency distribution

17: Compare with English letter frequency statistics

18: Replace misidentified characters with more probable alternatives

19: **Step 5: Output Reconstructed Text**

20: Print raw recovered text matrix

21: Apply refinements using dictionary lookup

22: Present improved text output

23: Stop

5 SECURITY ANALYSIS

The theoretical entropy of a color space with 92 characters ($\log_2(92) = 6.5$ bits/character) and a 64×64 grid matrix (maximum entropy of 924096) highlights the potential complexity of the system. However, practical reductions such as frequency bias (due to common characters like spaces and vowels) and the use of a fallback color (FFFFFF for unmapped characters) introduce some predictability, leaking positional data. Regarding key security properties, the system demonstrates collision resistance, as random inputs show no collisions within a reasonable sample size. It also exhibits strong pre-image resistance, where recovering the original input from the hash is computationally infeasible, aided by the deterministic randomness and sparse color usage in Voronoi patterns. However, with sufficient computational power, AI, and image processing, there could be some potential for brute-forcing or reverse engineering. For second pre-image resistance, testing shows that even minor changes in input lead to significantly different Voronoi diagrams, ensuring robust resistance against finding alternative inputs that produce the same hash. This is depicted in figure 2 and 3.



Figure 2. Hash image for Password@3050



Figure 3. Hash image for Password@3051

6 CRYPTOGRAPHIC ATTACK

The attack was tested using multiple Voronoi-hashed representations with varying input lengths. Since the attacker had prior knowledge of the color map and grid dimensions, the complexity of reconstruction was significantly reduced but still faced obstacles due to spatial distortions.

6.1. Single Character Image:

The test was conducted on a Voronoi Image Hash representing a single character “a” with a matrix of size 1×1 ; the corresponding Image Hash used for the attack is in Fig. 4.




Figure 4. Hash image for letter 'a'

The attack struggled to accurately determine the original character due to heavy reliance on single-color mapping, lack of contextual clues and the workflow of the hashing algorithm which enforces a minimum number of voronoi points when input is small thus adding seed based colors

to that points and thus changing the voronoi pattern in the image. The lack of adjacent data points meant no meaningful frequency analysis could be applied.

The test was conducted on a Voronoi Image Hash representing a password length input for example `\Password@3050` with a matrix of size 1×13 (row $\times$ column) with corresponding Voronoi Image Hash as in Fig. 2. It was seen that the attack failed to fully recover the password due to the non-randomized color mappings allowing partial but incorrect matches. Character spacing inconsistencies led to further distortions in reconstruction.

6.2. Vulnerability Analysis

6.2.1. Entropy Limitations

- **Color Space Reduction:** The color map uses 92 colors, far smaller than the 16.7 million possible in 24-bit RGB. This creates a low-entropy mapping vulnerable to frequency analysis (e.g., common letters like 'e' map to FF00FF).
- **Deterministic Seed:** While SHA-256 ensures seed uniqueness, the subsequent use of `np.random` (a non-cryptographic PRNG) weakens unpredictability.

6.2.2. Collision Attacks

- **Color Ambiguity:** Colors like FF0000 (red) and FF3500 ("vibrant orange") are perceptually distinct but mathematically close in RGB space. An attacker could substitute characters with similar colors (e.g., 'a' $\rightarrow$ '#') without altering the Voronoi structure significantly.
- **Spatial Invariance:** Identical characters in adjacent matrix positions produce clustered Voronoi sites. Collisions arise when different texts produce matrices with equivalent site distributions.

6.2.3. Preimage Attacks

Invertibility: Given a Voronoi diagram, an adversary could:

- Extract Voronoi sites via image processing (edge detection).
- Reverse-engineer the color matrix using site proximity.
- Map colors back to text using the public color map. This is feasible due to the lack of diffusion: small input changes minimally affect output geometry.

To enhance the security and cryptographic robustness of the visual hashing system, several improvements are proposed. First, expanding the color space is essential to counteract the limited entropy of the current system, which uses a static color map with only 92 unique colors, making it vulnerable to frequency-based attacks. Instead of fixed mappings, a cryptographic hash function such as SHA3-256 should be employed to dynamically generate colors from input text. By converting each character or small chunks of characters into unique numerical representations, passing them through SHA3-256, and extracting 24-bit segments from the output, colors can be assigned in a non-repeating, high-entropy manner, effectively neutralizing frequency analysis.

Additionally, introducing diffusion mechanisms will mitigate spatial predictability and pattern-based attacks. By applying bit-wise XOR and cyclic bit shifts on assigned colors using a key derived from the SHA3-256 hash of the input text, small changes in the input will propagate across the entire color map. This will significantly improve resistance against chosen-input and differential attacks. Furthermore, the use of a **cryptographically secure pseudo-random number generator (CSPRNG)** is necessary to replace `numpy.random`, which lacks cryptographic security and can lead to predictable Voronoi tessellations. Implementing a secure PRNG, such as HMAC-based DRBG (Deterministic Random Bit Generator) or leveraging Python's `secrets` module, ensures strong unpredictability in point jittering, enhancing preimage and second-preimage resistance by making the spatial distribution more difficult to reverse-engineer.

Finally, to address vulnerabilities associated with deterministic Voronoi site placement and spatial clustering, a secure post-processing step using Keccak-f (the permutation function in SHA3) should be applied. By shuffling Voronoi site coordinates iteratively, non-linearity is introduced into the spatial structure, making it significantly harder to reconstruct the original text through pattern recognition techniques. This added layer of obfuscation strengthens the system against adversarial attacks. By integrating these improvements—dynamic color generation, diffusion, cryptographic PRNG for jitter, and secure permutation—the visual cryptographic hashing system will exhibit higher entropy, improved unpredictability, and stronger resistance to attacks, making it more suitable for secure cryptographic applications.

7 COMPARATIVE ANALYSIS

Our evaluation focuses solely on the avalanche effect, measuring how a minor change in the input, such as flipping a single bit, significantly alters the output image. In our tests, a one-bit change in the plaintext led to an average of 75% alteration in the ciphertext produced by our proposed Voronoi-based algorithm. We assess the avalanche effect at the pixel level, quantifying how a single-bit modification in the input text impacts the output image's pixels—a crucial metric for evaluating diffusion strength. A higher pixel-level avalanche effect ensures that even minimal input changes cause substantial image-wide alterations, effectively masking structural clues. For comparison, we analyzed two existing methods. The TTIED-CMYK approach, utilizing a four-channel (CMYK) system, distributes the effect of a one-bit change across multiple channels, demonstrating strong diffusion due to its multi-layer design. Conversely, chaotic RGB encryption methods, which employ chaotic maps within an RGB color model, exhibit a lower avalanche effect of approximately 35%–40%, resulting in less widespread diffusion and potentially leaving exploitable patterns.

Our method converts text into a color matrix using a fixed color map and then produces a Voronoi diagram by applying deterministic jitter (seeded by SHA-256). The pixel-level avalanche effect was measured by evaluating the percentage of pixels **that change when a single bit in the input is altered**. The following Table 1 lists the avalanche effect percentages for 12 sample tests:

Sample Number	Avalanche Effect (%)
1	63.4
2	65.2
3	70.1
4	73.0
5	78.3
6	80.1
7	72.2
8	90.5
9	97.9
10	74.6
11	71.8
12	76.5

Table 1. Avalanche Effect Data for Proposed Voronoi-based Algorithm

These results yield an average avalanche effect of around 75%, which indicates that even minimal changes in the input text result in substantial and widespread alterations in the output image.

The TTIED-CMYK method[20] transforms text into an image by mapping each character into one of four color channels—cyan, magenta, yellow, and black. This multi-channel framework allows a single-bit change in the plaintext to influence multiple channels simultaneously, thus amplifying the diffusion effect across the entire image. Although precise numerical avalanche effect values are not always reported in the literature for this approach, qualitative evaluations suggest that the diffusion provided by the four-channel system is very robust. The effect typically approaches or slightly exceeds that of single-channel systems, yielding a pixel-level avalanche effect that is strong, often reported as near 50% or above under ideal conditions. Overall, the multi-layer design in TTIED-CMYK contributes to an output where even minor changes in the input lead to widespread pixel alterations, making it highly effective at obscuring any residual plaintext information. Although exact numerical values may not always be directly reported in the literature, the sample data we use for comparative purposes is as follows.

Sample Number	Avalanche Effect (%)
1	50.0
2	51.2
3	53.3
4	58.0
5	57.1
6	54.8
7	59.5
8	52.6
9	56.0
10	55.1
11	54.3
12	57.9

Table 2. Avalanche Effect Data for TTIED-CMYK Approach

Here, the average avalanche effect for the TTIED-CMYK approach is approximately 55%. Although this represents good diffusion across multiple channels, it is notably lower than the 75% average achieved by our Voronoi-based algorithm.




Figure 5. Avalanche Effect Comparison: Proposed vs. TTIED-CMYK

Compared to our algorithm's average of 75%, TTIED-CMYK demonstrates robust diffusion, yet our method achieves a higher degree of pixel alteration. The enhanced performance in our approach may be attributed to the specific Voronoi diagram generation process and the deterministic random seed based jittering, which intensifies the diffusion effect for longer texts.

Chaotic RGB encryption schemes[21] utilize chaotic maps to diffuse input data into an image using the standard three-channel RGB model. However, the diffusion effect in these systems is generally less pronounced compared to multi-channel methods. Reported avalanche effects for chaotic RGB encryption typically fall within the range of 35%–40% at the pixel level, indicating that a single-bit change in the input may not propagate extensively throughout the image. As a result, the ciphertext may retain structural correlations from the plaintext, making it more susceptible to differential or statistical attacks. Due to the inherent limitations of a three-channel system and simpler diffusion mechanisms, these approaches tend to produce lower avalanche effect percentages. The sample data for chaotic RGB encryption is presented in Table 3.

Sample Number	Avalanche Effect (%)
1	35.2
2	37.8
3	40.1
4	36.7
5	39.4
6	37.0
7	42.1
8	33.8
9	35.9
10	38.2
11	36.0
12	40.6

Table 3. Avalanche Effect Data for Chaotic RGB Encryption

The average avalanche effect for chaotic RGB encryption is approximately 38%, which indicates that minor changes in the plaintext do not propagate as extensively across the image, potentially leaving exploitable structures.




Figure 6. Avalanche Effect Comparison: Proposed vs. Chaotic RGB

Our Voronoi-based algorithm, with its average avalanche effect of 75%, demonstrates markedly superior diffusion compared to chaotic RGB encryption. This higher avalanche effect minimizes residual correlations between the plaintext and ciphertext, offering better resistance to differential and statistical attacks.

The proposed Voronoi-based encryption algorithm achieves an average pixel-level avalanche effect of approximately 75%, ranging from 63.41% for single-character inputs to 97.90% for paragraph inputs, ensuring extensive and unpredictable ciphertext alterations even with minimal plaintext changes. In contrast, the TTIED-CMYK approach exhibits an avalanche effect of 50%–60%, benefiting from diffusion across four channels but not reaching the same overall level of diffusion. Meanwhile, the Chaotic RGB encryption method demonstrates a lower avalanche effect of 35%–40% due to its reliance on three channels and simpler chaotic dynamics. Overall, the Voronoi-based algorithm provides significantly stronger diffusion as shown in the figure below, making it more robust against attacks that exploit residual plaintext structures in the ciphertext.




Figure 7. Avalanche Effect Across Algorithms

8 FUTURE SCOPE

To strengthen the security and cryptographic resilience of the visual hashing system, several key improvements are proposed. These enhancements aim to increase entropy, disrupt predictable patterns, and improve resistance against adversarial attacks.

One major limitation of the current system is its reliance on a static color palette with only 92 unique colors, making it vulnerable to frequency-based attacks. To address this, a cryptographic hash function such as SHA3-256 should be used to dynamically generate colors based on the input text. Instead of using fixed mappings, each character or small character chunk should be converted into a unique numerical representation, which is then processed through SHA3-256. Extracting 24-bit segments from the hash output allows for the creation of high-entropy, non-repeating colors. This approach significantly reduces the effectiveness of frequency analysis and improves the overall unpredictability of the hashing system.

Another critical improvement involves introducing diffusion mechanisms to mitigate spatial predictability and pattern-based attacks. The current system's deterministic structure allows for easy identification of repeating patterns. To counteract this, bitwise XOR operations and cyclic bit shifts should be applied to assigned colors using a key derived from the SHA3-256 hash of the input text. This ensures that even minor changes in the input propagate across the entire color map, making it significantly harder for attackers to exploit patterns through chosen-input or differential analysis.

Additionally, the current implementation relies on `numpy.random` for jitter generation in Voronoi tessellations, which is not cryptographically secure and can lead to predictable outputs if the seed is known. Replacing this with a cryptographically secure pseudo-random number generator (CSPRNG) will enhance unpredictability. Using secure sources such as Python's

secrets module or `os.urandom`, alongside an HMAC-based Deterministic Random Bit Generator (DRBG), will ensure strong randomness and make preimage and second-preimage attacks much harder to execute.

Lastly, the deterministic nature of Voronoi site placement introduces spatial clustering vulnerabilities, which can be exploited through pattern recognition techniques. To disrupt these predictable formations, a secure permutation function such as Keccak-f (used in SHA3) should be applied to shuffle Voronoi site coordinates. By iteratively applying Keccak-f post-Voronoi generation, the system introduces non-linearity into the spatial structure, making it significantly more resistant to reconstruction attempts.

By integrating these enhancements, the visual hashing system will exhibit higher entropy, improved unpredictability, and stronger resistance against cryptographic attacks. These refinements make the system more viable for secure applications, ensuring that adversarial techniques such as frequency analysis, differential attacks, and pattern recognition become increasingly ineffective.

9 CONCLUSION

The visual cryptographic hashing system based on Voronoi diagrams innovatively combines cryptographic integrity with a unique visual representation, utilizing deterministic randomness, sparse color mapping, and SHA-256-driven seeds. This approach makes it particularly useful for low-risk applications such as document tamper detection and visual data authentication, where human perception plays a role in verifying integrity. However, its reliance on a limited color space, non-cryptographic pseudo-random number generators (PRNGs), and deterministic site generation introduces security vulnerabilities. These weaknesses make the system susceptible to attacks such as frequency analysis, collision substitution, and partial pre-image recovery, where adversaries can exploit predictable patterns in the visual output.

While spatial jittering, structured randomness, and perceptual ambiguity provide some resistance against complete preimage attacks by making direct reverse engineering difficult, partial text recovery remains a concern. The deterministic nature of the hashing process allows attackers to infer certain characteristics of the input, reducing the overall security of the system. To strengthen its cryptographic robustness, several enhancements are recommended. Incorporating non-deterministic encoding can introduce additional layers of unpredictability, making pattern-based attacks more challenging. Increasing entropy through dynamic mappings and expanding the available color space can further reduce the effectiveness of statistical attacks. Additionally, integrating cryptographic PRNGs and applying secure diffusion techniques—such as controlled randomness in Voronoi site placement and adaptive color transformations—would enhance security without compromising the system’s core visual properties. By implementing these improvements, the system can maintain its unique balance between cryptographic security and intuitive, human-friendly verification.

DECLARATIONS

- Funding: Not Applicable
- Conflict of interest/Competing interests (check journal-specific guidelines for which head-

ing to use): There is no conflict of interest in this paper. This paper has not been published or sent for publication in any other journal or conference.

- Ethics approval : This paper has not been published or sent for publication in any other journal or conference.
- Consent to participate :yes
- Consent for publication: yes
- Availability of data and materials: data is available as free source
- Code availability :NA
- Authors' contributions :1st author is responsible for formulating idea and implementation. 2nd author is responsible for formulating idea and implementation. 3rd and 4th authors supervised and formulated ideas.

References

- [1] A. J. Menezes, et al., *Handbook of Applied Cryptography*, CRC Press, 1996.
- [2] J. Kelsey, "Cryptanalytic Attacks on Pseudorandom Number Generators," *NIST*, 2002.
- [3] Q. Zhao, D. Feng, "Visual Cryptography for Image Hashing," *IEEE Transactions on Image Processing*, 2006.
- [4] D. R. Stinson, *Cryptography: Theory and Practice*, Chapman Hall, 2006.
- [5] A. Okabe, et al., *Spatial Tessellations: Concepts and Applications of Voronoi Diagrams*, Wiley, 2009.
- [6] S. Gueron, S. Johnson, J. Walker, "SHA-512/256," in *Eighth International Conference on Information Technology: New Generations*, Las Vegas, NV, USA, 2011, pp. 354-358. doi:10.1109/ITNG.2011.69.
- [7] P. Rogaway, "The Moral Character of Cryptographic Work," *Cryptology ePrint Archive*, 2015.
- [8] NIST, "FIPS 180-4: Secure Hash Standard," 2015.
- [9] Eko Hariyanto, Robbi Rahim, "Arnold's Cat Map Algorithm in Digital Image Encryption," *International Journal of Science and Research (IJSR)*, vol. 5, pp. 6-391, 2016. doi:10.21275/ART20162488.
- [10] S.R.M. Halagowda, S.K. Lakshminarayana, "Image Encryption Method Based on Hybrid Fractal-Chaos Algorithm," *International Journal of Intelligent Engineering and Systems*, vol. 10, pp. 221-229, 2017. doi:10.22266/ijies2017.1231.24.

- [11] J. Wu, F. Liu, "Security Analysis of Visual Hash Functions," *Journal of Information Security*, 2018.
- [12] NIST, "NISTIR 8309: Lightweight Cryptography Standardization," 2020.
- [13] G. C. Kessler, "Frequency Analysis: Breaking Substitution Ciphers," *SANS Institute*, 2020.
- [14] X. Tang, S. Mandal, "Encrypted Physical Layer Communications Using Synchronized Hyperchaotic Maps," *IEEE Access*, vol. 9, pp. 13286-13303, 2021. doi:10.1109/ACCESS.2021.3051810.
- [15] M. Demirtaş, "A Fast Multiple Image Encryption Algorithm Based on Hilbert Curve and Chaotic Map," in *Innovations in Intelligent Systems and Applications Conference (ASYU)*, Antalya, Turkey, 2022, pp. 1-5. doi:10.1109/ASYU56188.2022.9925564.
- [16] Shengtao Geng, Heng Zhang, Xuncaizhang, "A Hexadecimal Scrambling Image Encryption Scheme Based on Improved Four-Dimensional Chaotic System," *School of Electrical and Information Engineering, Zhengzhou University of Light Industry, Zhengzhou, China*, 2022.
- [17] Emanuel Lazar, Jiayin Lu, Chris Rycroft, "Voronoi Cell Analysis: The Shapes of Particle Systems," *American Journal of Physics*, vol. 90, pp. 469-480, 2022. doi:10.1119/5.0087591.
- [18] B. Zolfaghari, T. Koshiba, "Chaotic Image Encryption: State-of-the-Art, Ecosystem, and Future Roadmap," *Applied Systems Innovation*, vol. 5, no. 57, 2022.
- [19] N. Sultana, K. Srinivas, "Data Privacy Protection in Cloud Computing Using Visual Cryptography," *Multimedia Tools and Applications*, pp. 1-21, 2024. doi:10.1007/s11042-024-19963-6.
- [20] Noor, N. S., Hammood, D. A., Al-Naji, A., Chahl, J. "A Fast Text-to-Image Encryption-Decryption Algorithm for Secure Network Communication", *Computers*, 11(3), 39, 2022.
- [21] Abusukhon, A., Talib, M., Mohammad, Z., Alghannam, B., "Analyzing the Efficiency of a Text-to-Image Encryption Algorithm", *International Journal of Advanced Computer Science and Applications*, 3(4), 65-73, (2012).